STATE OF THE WATERSHED REPORT

OYSTER BAY/COLD SPRING HARBOR

November 2009







In Association With:

Town of Oyster Bay









State of the Watershed Report Oyster Bay/Cold Spring Harbor

Prepared For:

Friends of the Bay

In Association With:

Town of Oyster Bay

Oyster Bay, New York

November 2009



78 Interstate Drive West Springfield, Massachusetts



Acknowledgements

Funding support for this report was provided by the National Fish and Wildlife Foundation, Long Island Sound Futures Fund, including the Long Island Sound Study, as well as the Town of Oyster Bay, and the Rauch Foundation. We would also like to recognize the Friends of the Bay and the Fuss & O'Neill staff that supported the development of this report.



Executive Summary

Importance of the Estuary Complex

The Oyster Bay/Cold Spring Harbor Complex (which is comprised of Oyster Bay Harbor, Cold Spring Harbor, Mill Neck Creek, and Oyster Bay) is the cleanest estuary in western Long Island Sound and is a vital ecological, economic, and recreational resource. The approximately 6,000-acre estuary, spanning approximately 40 linear miles of shoreline, is the site of one of the most economically-important shellfisheries in the State, contains a National Wildlife Refuge, Statedesignated Significant Coastal Fish and Wildlife Habitats, and has been identified by New York State as an Outstanding Natural Coastal Area. Moreover, the Oyster Bay/Cold Spring Harbor Complex is connected to Long Island Sound, an Estuary of National Significance. Oyster Bay is among the 30plus areas highlighted by the Long Island Sound Study Stewardship Initiative, in New York and Connecticut, for the ecological and/or recreational values that they support.

The harbor complex watershed is an approximately 39 square-mile area located in Nassau and Suffolk Counties. Approximately 80 percent of the watershed is located within the Town of Oyster Bay and its incorporated villages and unincorporated villages and hamlets. A small portion (less than 2 percent) of the watershed is located in Glen Cove, also in Nassau County. The remaining 18 percent of the watershed is within the Town of Huntington and its incorporated villages in Suffolk County. The Oyster Bay/Cold Spring Harbor Complex watershed consists of 14 smaller subwatersheds, from which surface runoff potentially enters the estuary.





Issues Facing the Estuary and Its Watershed

The Oyster Bay/Cold Spring Harbor estuary and its watershed have been facing increasing challenges in recent years. Illegal dumping and polluted stormwater threaten water quality, development pressure is reducing the amount of open space and increasing impervious surfaces in the watershed, and man-made dams and culverts inhibit fish passage along streams. Use impairments to shellfishing, public bathing, fish consumption, habitat/hydrology, aquatic life, and recreation have been identified for parts of the harbor complex. Future uncontrolled development in the watershed will increase the quantity of stormwater runoff to Oyster Bay/Cold Spring Harbor, despite a 2003 New York State Department of Environmental Conservation (NYSDEC) report that highlighted urban runoff as the dominant source of pathogens to the estuary complex (NYSDEC, 2003).

In addition to these findings by the NYSDEC, Defenders of Wildlife announced in October 2005 that the Oyster Bay National Wildlife Refuge (NWR) made their annual list of the ten most endangered Refuges in the country. The Refuges at Risk: America's Ten Most Endangered National Wildlife Refuges 2005 report explains that the Oyster Bay NWR has become threatened by polluted stormwater runoff; habitat destruction; nonsustainable development; and human sewage associated with failing sewer infrastructure, and inadequate on-site septic systems. These humaninduced impacts adversely affect the entire Oyster Bay/Cold Spring Harbor Complex.

Portions of the Oyster Bay/Cold Spring Harbor watershed are located within the Oyster Bay Special Groundwater Protection Area, designated a Critical Environmental Area by the NYSDEC. Long Island's drinking water system was designated as the nation's first Sole Source Aquifer, requiring special protection. The Oyster Bay Special Groundwater Protection Area is one of two such state-designated areas in Nassau County for the purpose of maintaining open space for aquifer recharge. Ongoing development, intensification of land use, and everyday activities within the watershed has the potential to adversely impact groundwater and public drinking water supplies.

The Oyster Bay/Cold Spring Harbor Complex is also the site of one of the most economically-important shellfisheries in the State. The Frank M. Flower & Sons, Inc. shellfish company, along with more than 80 independent commercial baymen, annually harvests up to 90% of New York's oyster crop and up to 33% of the State's hard clam crop from the heart of the National Wildlife Refuge. Most of the waters of Oyster Bay are classified with the highest and best water quality determination for shellfishing – an unusual distinction given its proximity to New York City and the fact that the harbors to the west have been closed for more than 30 years. The detrimental impact of degraded water quality on shellfishing in the estuary complex

Oyster Bay/Cold Spring Harbor is one of the most productive shellfish growing areas in New York State. The Frank M. Flower & Sons, Inc. shellfish company, along with more than 80 independent commercial baymen, annually harvests up to 90% of New York's oyster crop and up to 33% of the State's hard clam crop from the Oyster Bay NWR.

is evident as Oyster Bay Harbor, Mill Neck Creek, and its tidal tributaries are among the 69 water bodies on the New York State list of impaired waters for shellfish harvesting, and the NYSDEC has decertified all shellfish harvesting areas in Mill Neck Creek and some shellfish harvesting areas in Oyster Bay. The harbor complex is also a highly productive area for marine finfish and an important wintering area for a variety of waterfowl (Cashin Associates, P.C., 2002).

Why a State of the Watershed Report?

Friends of the Bay is a leading environmental advocate, committed to the protection of the Oyster Bay/Cold Spring Harbor estuary and its surrounding upland communities. Friends of the Bay is actively involved in water quality protection, watershed and wetlands conservation, land use planning, research, education, and community action and advocacy. Working with the Town of Oyster Bay and other governmental entities, stakeholder groups, and the general public, Friends



of the Bay has prepared this *State of the Watershed Report* with two overall objectives:

- The State of the Watershed Report summarizes existing environmental and land use conditions in the watershed. It is a comprehensive document that integrates many environmental indicators to assess the current health of the watershed and potential future threats. The report provides a baseline assessment of watershed conditions, which can be updated periodically to evaluate changes in the watershed and help direct watershed management planning.
- 2. The State of the Watershed Report is the first step in developing a watershed management plan for the harbor complex, following an approach endorsed by the U.S. Environmental Protection Agency and the NYSDEC for developing watershed-based plans. The State of the Watershed Report will serve as the basis for the development of a subsequent Watershed Action Plan, which will identify prioritized action items to protect and improve the ecological integrity of the estuary and surrounding watershed.

Key Findings

Water Quality

Mill Neck Creek, Cold Spring Harbor, and Oyster Bay Harbor do not meet water quality standards due to elevated levels of pathogenic organisms. Consequently, water quality issues in the harbor complex have focused on elevated pathogen levels, which impact shellfish harvesting in the estuary.

A landmark groundbreaking occurred in April 2009 for long-awaited upgrades to sewer and water infrastructure to connect the homes in the Birches residential subdivision to the Glen Cove sewage treatment plant. This project will eliminate chronic cesspool overflows to Mill Neck Creek.

NYSDEC has developed Total Daily Maximum Loads (TMDL) for pathogens for the impaired waters in the Oyster Bay/Cold Spring Harbor complex. A TMDL determines the maximum amount or load of a pollutant from both point and non-point sources that a water body can receive and continue to meet applicable water quality standards. Several studies and water quality monitoring programs have identified likely sources of pathogens to the estuary, including:

- Wastewater treatment plants
- Domestic waste disposal using cesspools
- Stormwater discharges
- Freshwater streams
- Boats/marinas/mooring areas
- Wildlife and waterfowl

Water quality monitoring data collected by Friends of the Bay and other groups suggests that the water quality in the harbor, particularly in nearshore areas, is strongly influenced by freshwater sources and activities on the land. One location, in particular, has been identified as a significant contributor of pollutants to the harbor complex. This site is located near the outflow of Mill Pond and the Mill River, which supports a substantial population of waterfowl, and Beekman Creek, which flows under West Shore Road and the Beekman Beach parking lot and eventually discharges to the Mill River and Oyster Bay Harbor. It is suspected that the outflow of Mill Pond and the Mill River, including Beekman Creek, is contributing to elevated levels of bacteria and nutrients.

Wetlands

Freshwater and tidal wetlands provide a multitude of functions including flood and stormwater control, pollution reduction, marine food production, wildlife habitat, recreational opportunities, open space, and aesthetic value. Freshwater wetlands comprise less than 2 percent of the harbor complex watershed. The majority of these wetlands are associated with ponds along Beaver Brook, Mill River, Tiffany Creek, and Cold Spring Brook. Approximately 1,000 acres of tidal wetlands exist within the harbor complex. Extensive areas of coastal shoals, bars, and mudflats occur along Mill Neck Creek, the western and southern shoreline of Oyster Bay Harbor, Inner Cold Spring Harbor, and the northeast shoreline of Centre Island. Most of the shoreline in the harbor complex is fringed by vegetated tidal wetlands of



varying width, interrupted by man-made waterfront structures.

Climate Change

Changes in climate are anticipated to occur over the next century. The magnitude of changes in temperature, sea level, and the timing and intensity of rainfall will depend upon future emissions of carbon dioxide and other greenhouse gases driving climate change. Climate change in the Northeastern U.S. is anticipated to result in an increase in the extent and frequency of coastal flooding, a rise in the frequency of severe storms and related damages, and sea level rise of 2-6 feet (Frumhoff et al., 2007). Increases in sea level and frequency of severe storms will result in more inundation of coastal areas, and subsequent increases in shoreline erosion and wetland loss. Inundation of low-lying areas will result in the potential for saltwater to infiltrate into freshwater surface waters and aquifers. Increased flooding and erosion has the potential to negatively impact transportation infrastructure and sewage and septic systems.

Information on the impact of climate change on Long Island is being developed through a collaborative effort led by The Nature Conservancy (TNC). The TNC Coastal Resilience project is intended to provide planners and other decision-makers with tools to assess reasonable future impacts of flooding from sea level rise and storms.

Coastal wetlands are vulnerable to the effects of sea-level rise, increasing water temperatures, and increased nutrients. If accretion of river-borne sediment and organic matter is unable to keep pace with the combined affects of sea-level rise and land subsidence, coastal marshes will be reduced or disappear. This will impact the ecological services provided by these areas including

buffering coastal areas from waves and erosion, filtering nutrients and pollutants, providing wildlife habitat, and providing nursery areas for fisheries. Because hard-clams and oysters depend on wetland-based food chains, impacts to coastal wetlands are anticipated to impact those fisheries (Frumhoff et al., 2007).

Fish and Wildlife

Portions of the Oyster Bay/Cold Spring Harbor Complex and its watershed provide abundant and significant habitat that supports a variety of fish and wildlife. The presence of diverse fish and wildlife habitats and species is indicative of the capacity of the harbor complex and its watershed to support these natural resources, despite the developed suburban landscape that makes up a large percentage of the watershed.

Various estuarine, palustrine, riverine, and upland areas provide habitat to finfish, shellfish, mammals, amphibians, reptiles and birds. The most notable tracts of protected or preserved land (including submerged or tidal areas) within the estuary and watershed include:

- Oyster Bay National Wildlife Refuge
- Charles T. Church/Shu Swamp Nature Preserve
- Sagamore Hill National Historic Site
- Planting Fields Arboretum
- Muttontown Preserve
- Bailey Arboretum
- Stillwell Woods Park
- Tiffany Creek Preserve

Due to the importance of these habitats, the State of New York has designated some of them as Significant Coastal Fish and Wildlife Habitats (SCFWH), which provide living and feeding areas for animals and are also economically important. Three NYSDEC-designated SCFWH areas exist in the watershed: Mill Neck Creek, Cold Spring Harbor, and Oyster Bay Harbor.

The Oyster Bay National Wildlife Refuge (NWR) is a 3,200-acre refuge that is the largest in the Long Island National Wildlife Refuge Complex. Oyster Bay NWR includes the northern three-quarters of Oyster Bay Harbor, the northwestern quadrant of Cold Spring Harbor (approximately 1,000 acres), and all of Mill Neck Creek. The Oyster Bay NWR is well-sheltered from Long Island Sound and, as such, provides excellent winter habitat for a variety of water fowl and shorebirds. It also provides



significant nursery and feeding habitat for finfish and substrate for shellfish (USFWS, 2009).

Water Supply

Groundwater aquifers supply drinking water to all of Long Island. Long Island's drinking water system was designated as the nation's first Sole Source Aquifer. To protect these groundwater aquifers, the state designated nine Special Groundwater Protection Areas (SGPAs), as defined in Article 55 of the NYS Environmental Conservation Law. The Oyster Bay SGPA is one of two such statedesignated aquifer recharge areas in Nassau County. The Town of Oyster Bay has an Aquifer Protection Overlay District (APO) in addition to the SGPA, adopted in 2004, which affords added protection to groundwater resources.

The Town of Huntington contains portions of two SPGAs, only one of which (West Hills/Melville in the western part of the Town) is located within the Oyster Bay/Cold Spring Harbor Complex watershed. Most of the Town of Huntington's public water supply wells are located outside of SPGAs. Unlike the Town of Oyster Bay, Huntington has not enacted aquifer protection overlay district regulations.

Wastewater

Oyster Bay Hamlet and portions of the Unincorporated Villages of Upper Brookville are served by sanitary sewers that transport sanitary waste to the Oyster Bay District Sewage Treatment Plant (OBDSTP). The treatment plant is located in Oyster Bay Hamlet and discharges treated effluent to Oyster Bay Harbor east of the Mill River outlet.

The OBDSTP has been in service since 1926 and has been upgraded several times. The most recent upgrade occurred in 2006 to provide advanced treatment for nitrogen removal. Nitrogen has been identified as the primary pollutant causing low dissolved oxygen conditions, or hypoxia, occurring throughout much of Long Island Sound's bottom waters each summer. To address this water quality problem, NYSDEC imposed limits to reduce nitrogen discharged from the 12 municipal treatment plants located on the north shore of Long Island. NYSDEC issued a revised discharge permit that required the OBDSTP to reduce nitrogen discharged to Oyster Bay from the treatment plant by 63.8 percent in three 5-year increments by August 2014. The OBDSTP advanced treatment facility is achieving the 2014 nitrogen limits

imposed by NYSDEC permit, and the upgrade has reduced the daily nitrogen discharged by as much as 75%.

Much of the harbor watershed is served by individual on-site sewage disposal systems, including cesspools and septic tank systems. Cesspools were the most common method of onsite sewage disposal until about 1973, when the local development regulations were modified to require the use of sanitary sewers.

In October 2008, the Oyster Bay/Cold Spring Harbor Complex was declared a federal No-Discharge Zone for vessel sewage, regulated under Section 312 of the Clean Water Act. The designation prohibits the discharge of sewage from vessels, providing an additional level of protection to address water quality issues associated with sewage contamination in marine waters.

Cesspools and septic systems are a potential source of pollution, including nitrogen, pathogens, and other contaminants, to surface waters and groundwater as a result of system failure (inadequately treating sewage or by creating potential for direct or indirect contact between sewage and the public) or malfunction (typically a slow loss of function that is difficult to detect). Since a large portion of the watershed was developed prior to 1973, failure or malfunction of cesspools and septic systems is believed to be a significant source of pollution to surface water and groundwater.

Stormwater

The stormwater collection and drainage system within the harbor complex watershed consists of drainage infrastructure operated and maintained by the watershed municipalities, including the Town of Oyster Bay, the Town of Huntington, the associated villages, and Nassau and Suffolk Counties. All of



these municipal entities are regulated small Municipal Separate Storm Sewer Systems (MS4s) under the NYSDEC State Pollution Discharge Elimination System Phase II stormwater program.

Stormwater within the watershed is discharged to surface waters and to groundwater. A large portion of the watershed drains to surrounding surface waters through numerous outfalls and as overland flow.

Artificial infiltration of stormwater runoff by use of basins or sumps has been practiced on Long Island since the 1930s to recharge collected stormwater back to the groundwater system. In the 1950s, Nassau and Suffolk Counties adopted regulations requiring stormwater to be retained and infiltrated onsite. Subsequently, the use of drywells, recharge basins, and drainage reserve areas became common practice to retain and infiltrate stormwater runoff from roadways in residential, commercial, and industrial areas. Recharge basins are most prevalent in eastern Nassau County and western Suffolk County. Most of these facilities have overflow structures that direct stormwater resulting from extreme rainfall events to either other recharge basins or to drainage facilities that ultimately discharge to surface waters.

Since much of the watershed was developed prior to the adoption of stormwater quality regulatory requirements, most of the existing drainage infrastructure that does not discharge to recharge basins consists of traditional storm drains/catch basin and storm pipes that discharge directly to surface waters without treatment, other than detention to maintain peak rates of discharge. Uncontrolled stormwater runoff from impervious surfaces is a significant source of potential impacts to surface waters within the harbor complex watershed, groundwater supplies, and the water quality of the harbor complex itself.

Through their Phase II stormwater management programs and other planning initiatives, the watershed municipal entities, including Nassau and Suffolk Counties, have developed and implemented a variety of Best Management Practices to address stormwater quality and quantity issues associated with land development and redevelopment projects. The municipalities have also begun to address historical development and nonpoint source pollution impacts in the watershed by identifying potential sites for stormwater retrofits.

However, stormwater runoff continues to be a significant threat to the water quality and overall health of the Oyster Bay/Cold Spring Harbor Complex and its watershed.

Impervious Cover

Impervious cover has emerged as a measurable, integrating concept used to assess the overall condition of a watershed. Numerous studies have documented the cumulative effects of urbanization on stream and watershed ecology. Research has also demonstrated similar effects of urbanization and watershed impervious cover on downstream receiving waters such as lakes, reservoirs, estuaries, and coastal areas.

The correlation between watershed impervious cover and stream indicators is due to the relationship between impervious cover and stormwater runoff, since streams and receiving water bodies are directly influenced by stormwater quantity and quality. Although well-defined imperviousness thresholds are difficult to recommend, research has generally shown that when impervious cover in a watershed reaches between 10 and 25 percent, ecological stress becomes clearly apparent. Between 25 and 60 percent, stream stability is reduced, habitat is lost, water quality becomes degraded, and biological diversity decreases. Watershed imperviousness in excess of 60 percent is generally indicative of watersheds with significant urban drainage. These research findings have been integrated into a general watershed planning model known as the Impervious Cover Model (ICM) (CWP, 2003).

Based on a GIS impervious cover analysis, the overall imperviousness of the harbor complex watershed is estimated at approximately 12.3%, which slightly exceeds the 10% threshold in the ICM where ecological stress and stream impacts become apparent. Impervious cover is generally highest (30% to 70%) in the urbanized areas of Oyster Bay Hamlet and the Villages of Glen Cove, Bayville, Locust Valley, West Hills and the southern portion of Woodbury. Impervious cover in most of the residential areas of the watershed generally ranges from less than 10 percent up to 30%.

Most of the subwatersheds fall into the "impacted" category (impervious cover between 10 and 25%) according to the ICM. Several of the subwatersheds have significantly less than 10% impervious cover, including the Bailey Arboretum and Lloyd Neck



subwatersheds. The White's Creek subwatershed has the highest impervious cover (43.3%), which is consistent with the high-density development in Oyster Bay Hamlet and indicative of degraded stream conditions according to the ICM.

Under a watershed buildout scenario, the impervious cover in the overall harbor complex watershed is predicted to increase from 12.3% to 13.6%, but remain well below the ICM nonsupporting threshold of 25%. The Cold Spring Harbor and Tiffany Creek subwatersheds are predicted to increase from slightly less than 10% impervious cover to meet or slightly exceed the 10% threshold where ecological impacts become apparent. The largest relative change in impervious cover is predicted in the Oyster Bay Harbor subwatershed, where imperviousness could increase from approximately 14.1% to 17.6%.

Pollutant Loads

A pollutant loading model was used to compare existing nonpoint source pollutant loads from the watershed to projected future pollutant loads that would occur under a watershed buildout scenario.

Several of the subwatersheds are predicted to experience significantly higher increases in pollutant loads and loading rates under a watershed buildout scenario, including the Tiffany Creek, Mill River, Oyster Bay Harbor, and Kentuck Brook subwatersheds. The buildout conditions of the Mill River and Oyster Bay Harbor subwatersheds are projected to result in greater than 5% increase in pollutant loading rates for nitrogen, phosphorus and sediment loads. The projected increase in future pollutant loads is relatively small across the watershed because much of the watershed is already developed or consists of protected open space.

Restoration Potential

A comparative subwatershed analysis was performed for the Oyster Bay/Cold Spring Harbor subwatersheds to identify the subwatersheds with the greatest restoration potential. Subsequent field assessments were performed in priority subwatersheds to evaluate potential pollutant sources and environmental problems, as well as possible locations where restoration opportunities and mitigation measures can be implemented. The findings of these and other recent assessments identified a number of key findings and common issues throughout the watershed, including:

- Overall in-stream habitat in the assessed reaches was mixed, although many of the stream reaches assessed appear to be either supporting biological communities (fish, frogs, birds, etc.) or sufficient to support such communities.
- Many potential barriers to fish passage were observed throughout the watershed. The impacts of these obstructions on fish passage and the feasibility of fish barrier removal efforts in the harbor complex watershed are currently being investigated through a study led by the Long Island Chapter of Trout Unlimited, Environmental Defense, and Friends of the Bay.
- Segments of some streams in the watershed are buried in underground conduits, providing potential opportunities for daylighting and stream restoration to enhance aquatic and wildlife habitat, improve aesthetics, and provide educational opportunities.
- Stream buffer encroachments are prevalent along stream corridors in or near areas of residential, commercial, and industrial development and roads. Education, signage, stream buffer regulations, and stream cleanups are potential approaches for improving buffer management.
- Residential roofs appear to contribute significant quantities of stormwater runoff to the storm drainage system. Opportunities exist to disconnect residential rooftop runoff from the storm drainage system through the use of rain barrels or rain gardens.
- Lawn-care maintenance practices in residential areas are typically high. Opportunities exist to educate the public about the impacts of lawn care practices on the water quality of the harbor complex and to encourage the use of residential lawn care best management practices.
- Most of the development in the watershed employs traditional curb and gutter storm drainage collection systems with little, if any, stormwater management beyond water quality inlets and detention basins for peak flow control. Parking lots associated with existing



commercial development, municipal and institutional land uses, and commuter parking areas are potential candidates for stormwater retrofits to reduce site runoff and improve water quality through the use Low Impact Development (LID) and green infrastructure retrofits.

- Opportunities exist for stormwater retrofits at roadway stormwater outfalls throughout the watershed. Opportunities also exist for incorporating LID practices into existing roadway upgrades and retrofit projects (i.e., "green streets") to promote stormwater infiltration, streetscape improvements, and traffic calming.
- Relatively isolated areas of moderate to severe streambank erosion were observed along Beaver Brook, Mill River, Cold Spring Brook, Tiffany Brook, and White's Creek, providing opportunities for bank stabilization projects.
- Hotspot land uses and facilities, including several commercial shopping centers, the Town of Oyster Bay highway yard, the LIRR Maintenance Yard, Commander Oil Terminal, and municipal parking lots, discharge stormwater directly to receiving waters with no treatment or attenuation. Opportunities exist for improved pollution prevention and source controls at these facilities.

Looking Ahead

Over the next several months, Friends of the Bay will build upon the findings of the *State of the Watershed Report* to begin the next phase of the watershed planning process, which is to develop a *Watershed Action Plan* for the Oyster Bay/Cold Spring Harbor estuary. Specific tasks include:

- Form a steering committee to guide the development of the *Watershed Action Plan*.
- Work with the steering committee to reach consensus on the specific goals and objectives of the Watershed Action Plan.
- Identify and evaluate alternative strategies to address the watershed management goals and objectives, including source controls, public education, regulatory controls, and structural controls.

Develop a Watershed Action Plan for the harbor complex. The plan will be developed consistent with EPA and NYSDEC guidance for the development of watershed-based plans, which includes nine key elements that establish the structure of the plan. These nine elements include specific goals, objectives, and strategies to protect and restore water quality; methods to build and strengthen working partnerships; a dual focus on addressing existing problems and preventing new ones; a strategy for implementing the plan; and a feedback loop to evaluate progress and revise the plan as necessary. Following this approach will enable implementation projects under this plan to be considered for funding under Section 319 of the Clean Water Act.

References

Cashin Associates, P.C. (2002). Oyster Bay/Cold Spring Harbor Complex Harbor Management Plan.

Center for Watershed Protection. (2003). Impacts of Impervious Cover on Aquatic Systems. March 2003.

Frumhoff, P.C., J.J. McCarthy, J.M. Melillo, S.C. Moser, and D.J. Wuebbles. (2007). Confronting Climate Change in the U.S. Northeast: Science, Impacts, and Solutions. Synthesis report of the Northeast Climate Impacts Assessment (NECIA). Cambridge, MA: Union of Concerned Scientists (UCS).

New York State Department of Environmental Conservation (NYSDEC). (2003). Pathogen Total Maximum Daily Loads for Shellfish Waters in Oyster Bay Harbor and Mill Neck Creek. September 2003.

U.S. Fish & Wildlife Service. (2009). Oyster Bay National Wildlife Refuge: Wildlife and Habitat. U.S. Department of the Interior, Fish and Wildlife Service.



State of the Watershed Report Oyster Bay/Cold Spring Harbor

EXECUTIVE SUMMARY

1	Intro	oduction	1	
	1.1	Background		
	1.2	Development of the Report	2	
	1.3	Prior Watershed Studies and Planning Documents	3	
	1.4	Ongoing Watershed Conservation and Restoration Efforts	4	
2	Stud	dy Area Description		
	2.1	Municipal Jurisdictions		
	2.2	Estuary	10	
	2.3	Watershed	10	
3		orical and Social Perspective		
	3.1	History of the Watershed		
	3.2	Population and Demographics		
	3.3	Recreation and Community Resources	17	
4	Natu	ıral Resources		
	4.1	Geology and Soil		
	4.2	Topography		
	4.3	Surface Hydrology		
	4.4	Flood Hazard Areas	22	
	4.5	Climate	24	
		4.5.1 Climate Change Impacts	25	
	4.6	Wetlands	26	
	4.7	Fish and Wildlife Resources	29	
		4.7.1 Estuarine Habitats	31	
		4.7.2 Riverine and Palustrine Habitats	35	
		4.7.3 Threatened and Endangered Species	38	
5	Wate	er Quality	39	
	5.1	Water Quality Classifications, Standards, and Impairments		
	5.2	History of Water Quality Issues	43	
	5.3	Friends of the Bay Water Quality Monitoring Program		
		5.3.1 Open Water Body Monitoring		
		5.3.2 Stream and Outfall Monitoring		
		5.3.3 Water Quality Trends		
	5.4	Other Water Quality Monitoring		
		5.4.1 Long Island Sound Study – Sound Health 2008		
		5.4.2 Shellfish Growing Area Sanitary Surveys		
		, ,		



State of the Watershed Report Oyster Bay/Cold Spring Harbor

		5.4.3 Nassau County Department of Public Health Beach Monito	ring51
		5.4.4 Nassau County Groundwater Monitoring	53
		5.4.5 Subwatershed Illicit Discharge Detection and Hot Spot Invo	estigations 54
6	Wate	ershed Modifications	58
	6.1	Dams and Impoundments	58
	6.2	Water Supply	58
	6.3	Wastewater	61
	6.3	Stormwater Infrastructure	65
	6.4	Other Regulated Sites	66
7	Land	d Use and Land Cover	69
	7.1	Current Conditions	69
		7.1.1 Land Use	69
		7.1.2 Zoning	71
		7.1.3 Land Cover	71
		7.1.4 Impervious Cover	78
		7.1.5 Open Space	82
	7.2	Future Conditions	85
		7.2.1 Watershed Buildout Analysis	85
8	Pollu	utant Loading	90
9	Com	nparative Subwatershed Analysis	93
	9.1	Analysis Methods and Results	
	9.2	Subwatersheds Recommended for Field Assessments	96
10	Wate	ershed Field Assessments	99
	10.1	Summary of Findings	100
	10.2	Stream Corridor Assessment	
		10.2.1 2009 Stream Assessments	104
		10.2.2 2007 Stream Assessments	112
	10.3	Upland Assessments	117
	10.4	Neighborhood Source Assessment	117
	10.5	Hotspot Site Investigation	
	10.6	Streets and Storm Drain Assessment	127
11	Land	d Use Regulatory Controls	
	11.1	Introduction	
	11.2	Summary of Regulatory Jurisdictions	130
		11.2.1 Federal	
		11.2.2 State	130



State of the Watershed Report Oyster Bay/Cold Spring Harbor

	11.2.3 County	13
	11.2.4 Municipal	
	11.3 Land Use Regulatory Survey	134
	11.3.1 Wetland Resources	
	11.3.2 Site Development	
	11.3.3 Open Space	
	11.3.4 Stormwater Management	
	11.3.5 On-Site Wastewater Disposal	
	11.3.6 Aquifer Protection	14
12	References	142
Tabl	les	Page
2-1	Political Jurisdictions Within the Watershed	-
2-2	Profile of the Oyster Bay/Cold Spring Harbor Complex Watershed	Ç
2-3	Oyster Bay Subwatersheds	12
4-1	Tidal Wetland Categories	27
4-2	Freshwater and Tidal Wetland Coverage in the Oyster Bay/Cold Spring	
	Harbor Complex	29
4-3	Shellfish Production in Oyster Bay	32
5-1	Selected Surface Water Quality Classifications	39
5-2	Narrative Water Quality Standards	41
5-3	Numeric Water Quality Standards	41
5-4	Sampling Stations and Pollution Sources in Oyster Bay Harbor, SGA #47	54
5-5	Sampling Stations and Pollution Sources in Cold Spring Harbor, SGA #48	50
6-1	Facilities in the Oyster Bay Watershed with SPDES Permits	63
6-2	Regulated Sites	60
7-1	Watershed Land Use	69
7-2	Watershed Land Cover	75
7-3	Forest Cover – Oyster Bay Watershed	77
7-4	Developed Land Cover by Subwatershed	77
7-5	Existing Subwatershed Impervious Cover	79
7-6	Potential Developable Land	87
7-7	Percent Impervious Cover – Existing and Future Conditions	87
7-8	Existing Impervious Cover/Riparian Zone Metric	88
8-1	Existing Pollutant Loads and Loading Rates	91
8-2	Projected Future Pollutant Loading Rates and Load Increases	92



State of the Watershed Report Oyster Bay/Cold Spring Harbor

rabi	es	Page
9-1	Comparative Subwatershed Analysis Restoration Potential Metrics	94
9-2	Results of Comparative Subwatershed Analysis	95
10-1	Field Inventory Nomenclature	99
10-2	Number of Reach Level Assessments Performed and Impact	
	Conditions Identified	104
10-3	Cold Spring Brook Overall Stream Reach Scores	104
10-4	2007 Stream Assessment Results Summary	112
10-5	Neighborhood Source Assessments Conducted in the	
	Oyster Bay/Cold Spring Harbor Complex Watershed	118
10-6	Hotspot Site Investigation Summary	123
10-7	Streets and Storm Drain Assessment Photographs	128
11-1	Land Use Departments and Commissions within the	
	Oyster Bay/Cold Spring Harbor Watershed	134
11-2	Municipal Land Use Regulations	135
11-3	Municipal Zoning Lot Specifications	136
11-4	Open Space Plans	138
11-5	Open Space Regulations	139
11-6	Municipal Stormwater Management Regulations	140
11-7	Aquifer/Groundwater Protection Regulations	141
		-
Figu		Page
2-1	Oyster Bay/Cold Spring Harbor Watershed	8
2-2	Subwatersheds	11
3-1	Population Trends in Nassau County	17
4-1	Hydrogeologic Cross Section of Long Island Near the Nassau-Suffolk	4.0
4.0	County Border (McClymonds and Franke, 1972)	19
4-2	Shaded Relief Map	21
4-3	Mean Monthly Streamflow of Mill Neck Creek and Cold Spring Brook	22
4-4	Flood Zones	23
4-5	Coastal Vulnerability Index (CVI) for the Northeastern U.S.	25
4-6	Tidal and Freshwater Wetlands	28
5-1	Surface Water Quality Classifications	40
5-2	Oyster Bay Harbor and Mill Neck Creek Shellfish Closure Areas	44
5-3	Cold Spring Harbor Shellfish Closure Areas	44
5-4 5-5	Water Quality Monitoring Locations	47
5-5 5-6	Indicator Bacteria Concentrations	49 52
5-6	Regulated Shellfishing Areas	52 50
6-1	Watershed Dams	59 60
6-2	Water Supply Wells	60



State of the Watershed Report Oyster Bay/Cold Spring Harbor

Figures		Page
6-3	Sewer Service Areas and Treatment Plants	62
6-4	Stormwater Discharges and Recharge Basins	64
6-5	Regulated Sites	67
7-1	Land Use	70
7-2	Zoning	72
7-3	Residential Zoning Minimum Allowable Lot Size	73
7-4	Land Cover	74
7-5	Conceptual Model Illustrating Relationship Between Watershed Impervious	
	Cover and Stream Quality	78
7-6	Watershed Impervious Cover	80
7-7	Impervious Cover by Subwatershed	81
7-8	Protected Open Space	83
7-9	Potentially Developable Land	86
9-1	Subwatersheds Recommended for Field Assessment	97
10-1	Photographs of Cold Spring Brook Stream Reaches	105

Appendices End of Report

- A Pollutant Loading Documentation
- B Watershed Field Inventory Documentation





1 Introduction

Friends of the Bay has retained Fuss & O'Neill, Inc. to prepare a watershed management plan for the Oyster Bay/Cold Spring Harbor estuary and surrounding watershed. The watershed management plan is being developed in cooperation with Friends of the Bay, the Town of Oyster Bay, and other governmental entities, stakeholder groups, and the general public. The watershed management plan for Oyster Bay/Cold Spring Harbor will be developed in two phases – a State of the Watershed Report and a Watershed Action Plan – following an approach endorsed by the U.S. Environmental Protection Agency for developing watershed-based plans. The State of the Watershed Report, which is the subject of this document, summarizes existing environmental and land use conditions in the watershed. The subsequent Watershed Action Plan will identify prioritized action items to protect and improve the ecological integrity of the estuary and surrounding watershed.

1.1 Background

The Oyster Bay/Cold Spring Harbor Complex (which is comprised of Oyster Bay Harbor, Cold Spring Harbor, Mill Neck Creek, and Oyster Bay) is the cleanest estuary in western Long Island Sound and is a vital ecological, economic, and recreational resource. The approximately 6,000-acre estuary is the site of one of the most economically-important shellfisheries in the State, contains a National Wildlife Refuge, State-designated Significant Coastal Fish and Wildlife Habitats, and has been identified by New York State as an Outstanding Natural Coastal Area. Moreover, the Oyster Bay/Cold Spring Harbor Complex is connected to Long Island Sound, an Estuary of National Significance. Oyster Bay is among the 30-plus areas highlighted by the Long Island Sound Study Stewardship Initiative, in New York and Connecticut, for the ecological and/or recreational values that they support.

Despite its close proximity to New York City and the more densely developed surrounding areas of western Long Island, much of the Oyster Bay/Cold Spring Harbor Complex watershed consists of low density residential development, recreational facilities, and open space. The Village of Bayville and the hamlets of Oyster Bay, East Norwich, and Cold Spring Harbor have areas of higher density residential development, while commercial and industrial facilities are concentrated in Oyster Bay hamlet, Bayville, and on the eastern shore of Cold Spring Harbor. Waterfront land uses include existing and former operations of the Jakobsen Shipyard, the Oyster Bay Sewage Treatment Plant, and the Commander and Mobil Oil terminals, as well as public recreational facilities and residential waterfront properties (Cashin Associates, P.C., 2002).

The Oyster Bay/Cold Spring Harbor watershed has been facing increasing challenges in recent years. Illegal dumping and polluted stormwater threaten water quality, development pressure is reducing the amount of open space and increasing impervious surfaces in the watershed, and man-made dams and culverts inhibit fish passage along streams. Use impairments to shellfishing, public bathing, fish consumption, habitat/hydrology, aquatic life, and recreation have been identified for parts of the harbor complex. Future uncontrolled development in the watershed will increase the quantity of stormwater runoff to Oyster Bay/Cold Spring Harbor, despite a 2003 New York State Department of Environmental Conservation (NYSDEC) report





that highlighted urban runoff as the dominant source of pathogens to the estuary complex (Pathogen Total Maximum Daily Loads for Shellfish Waters in Oyster Bay Harbor and Mill Neck Creek, Nassau County, New York, September 2003).

In addition to these findings by the NYSDEC, Defenders of Wildlife announced in October 2005 that the Oyster Bay National Wildlife Refuge (NWR) made their annual list of the ten most endangered Refuges in the country. The Refuges at Risk: America's Ten Most Endangered National Wildlife Refuges 2005 report explains that the Oyster Bay NWR has become threatened by polluted stormwater runoff; habitat destruction; non-sustainable development; and human sewage associated with failing sewer infrastructure, and inadequate on-site septic systems. These human-induced impacts adversely affect the entire Oyster Bay/Cold Spring Harbor Complex.

Portions of the Oyster Bay/Cold Spring Harbor watershed are located within the Oyster Bay Special Groundwater Protection Area, designated a Critical Environmental Area by NYSDEC. Long Island's drinking water system was designated as the nation's first Sole Source Aquifer, requiring special protection. The Oyster Bay Special Groundwater Protection Area is one of two such state-designated areas in Nassau County for the purpose of maintaining open space for aquifer recharge. Ongoing development, intensification of land use, and everyday activities within the watershed has the potential to adversely impact groundwater and public drinking water supplies.

The Oyster Bay/Cold Spring Harbor Complex is also the site of one of the most economically-important shellfisheries in the State. The Frank M. Flower & Sons, Inc. shellfish company, along with more than 80 independent commercial baymen, annually harvests up to 90% of New York's oyster crop and up to 33% of the State's hard clam crop from the heart of the National Wildlife Refuge. Most of the waters of Oyster Bay are classified SA, the highest and best water quality determination for shellfishing – an unusual distinction given its proximity to New York City and the fact that the harbors to the west have been closed for more than 30 years. The detrimental impact of degraded water quality on shellfishing in the estuary complex is evident as Oyster Bay Harbor, Mill Neck Creek, and its tidal tributaries are among the 69 water bodies on the New York State list of impaired waters for shellfish harvesting, and the NYSDEC has decertified all shellfish harvesting areas in Mill Neck Creek and some shellfish harvesting areas in Oyster Bay. The harbor complex is also a highly productive area for marine finfish and an important wintering area for a variety of waterfowl (Cashin Associates, P.C., 2002).

1.2 Development of the Report

The following tasks were completed in developing this *State of the Watershed Report* for the Oyster Bay/Cold Spring Harbor Complex:

- Reviewed existing data, studies, and reports on the Oyster Bay/Cold Spring Harbor Complex and its watershed.
- Compiled and analyzed available Geographic Information System (GIS) data.
- Consulted with the Friends of the Bay, the Town of Oyster Bay and Town of Huntington, local villages and hamlets, and state agencies regarding available land use information, mapping, and land use planning regulations.





- Identified and delineated subwatersheds within the overall harbor complex watershed.
- Conducted a comparative subwatershed analysis to prioritize watershed field inventories and management plan recommendations.
- Reviewed existing land use regulatory controls.

This report documents current watershed conditions for the following topics:

- Historical and social perspective (Section 3).
- Natural resources including geology and soils, topography, hydrology, wetlands and watercourses, and fish and wildlife resources (Section 4).
- Water quality including classifications and trends based on available monitoring data (Section 5).
- Watershed modifications including dams, water supply, wastewater discharges, and regulated sites (Section 6).
- Land use and land cover (Section 7).
- Pollutant loading (Section 8).

In addition, the results of a comparative subwatershed analysis (Section 9), watershed field inventories (Section 10), and land use regulatory review (Section 11) are also presented.

1.3 Prior Watershed Studies and Planning Documents

The Oyster Bay/Cold Spring Harbor Complex has long been recognized as a unique and highly valued ecological, economic, and recreational resource by the local residents, visitors, and all levels of government. As a result, a large number of prior watershed studies and related land use planning efforts have been undertaken by the watershed municipalities, Nassau County, NYSDEC, Friends of the Bay, and other agencies and stakeholder groups. This State of the Watershed Report incorporates and builds upon the extensive information available from these previous studies and reports to document current conditions and trends in the Oyster Bay/Cold Spring Harbor Complex. The following watershed-related studies have been completed for the harbor complex.

- Oyster Bay Mill Pond Dam Fish Passage Assessment Project, Oyster Bay-Cold Spring Harbor Watershed (Gomez and Sullivan Engineers, P.C., undated);
- Water Quality Data Evaluation, Oyster Bay/Cold Spring Harbor, 2000 2006 (Fuss & O'Neill, Inc., January 2009);
- Annual Water Quality Monitoring Program Reports, 1999 2008 (Friends of the Bay);
- Mill River Watershed Study and Public Stewardship Program (Cashin Associates, P.C., December 2007);
- Bailey Arboretum Subwatershed, Stormwater Runoff Impact Analysis and Candidate Site Assessment Report (Cashin Associates, P.C., October 1, 2007);
- Francis Pond Subwatershed, Stormwater Runoff Impact Analysis and Candidate Site Assessment Report (Cashin Associates, P.C., October 1, 2007);





- Kentuck Brook Subwatershed, Stormwater Runoff Impact Analysis and Candidate Site Assessment Report (Cashin Associates, P.C., October 1, 2007);
- Mill River Subwatershed, Stormwater Runoff Impact Analysis and Candidate Site Assessment Report (Cashin Associates, P.C., October 1, 2007);
- Tiffany Brook Subwatershed, Stormwater Runoff Impact Analysis and Candidate Site Assessment Report (Cashin Associates, P.C., October 1, 2007);
- White's Creek Subwatershed, Stormwater Runoff Impact Analysis and Candidate Site Assessment Report (Cashin Associates, P.C., October 1, 2007);
- Build-Out and Cumulative Impact: Oyster Bay Hamlet (Cashin Associates, July 2007);
- Pathogen Total Maximum Daily Loads for Shellfish Waters in Oyster Bay Harbor and Mill Neck Creek (NYSDEC, September 2003);
- Oyster Bay/Cold Spring Harbor Complex Harbor Management Plan (Cashin Associates, P.C., June 2002);
- Mill Pond Outflow Study Water Quality Testing Program (Cashin Associates, P.C., 2001);
- Local Waterfront Revitalization Program for Huntington Harbor, Town of Huntington (Cashin Associates, P.C., April 2000);
- Mill River Watershed Study Sampling and Water Quality Testing (Cashin Associates, P.C.);
- Oyster Bay/Cold Spring Harbor Complex Stormwater Management/Coastal Water Quality Improvement Program Report (Town of Oyster Bay, 1995).

1.4 Ongoing Watershed Conservation and Restoration Efforts

There are a number of ongoing and recently completed efforts to maintain the existing high-quality natural resources of the harbor complex and its watershed, as well as to restore or improve the condition of other degraded resources. Many of these efforts are described in the studies and reports identified in the previous section. Notable ongoing or recently completed watershed conservation and restoration efforts are summarized below.

Friends of the Bay continues to be a leading environmental advocate, committed to the protection of the Oyster Bay/Cold Spring Harbor estuary and its surrounding upland communities. Friends of the Bay is actively involved in water quality protection, watershed and wetlands conservation, land use planning, research, education, and community action and advocacy.

Friends of the Bay has been monitoring the water quality within the Oyster Bay/Cold Spring Harbor Complex since 1999. Today, Friends of the Bay conducts weekly monitoring at 19 locations, from April through October, within Oyster Bay, Mill Neck Creek, and Cold Spring Harbor, as well as additional monitoring at selected streams and outfalls to the estuary. The volunteer water quality monitoring program provides high quality data to continue the dissolved oxygen-testing baseline established by Nassau County's Department of Health in 1972, screens for water quality impairments, supports the Total Maximum Daily Load (TMDL) for pathogens





that has been established for Oyster Bay and Mill Neck Creek, evaluates long-term water quality trends, documents the effects of water quality improvement programs, and educates and involves citizens and public officials about water quality protection.

In partnership with the Town of Oyster Bay and Nassau County, Friends of the Bay has been working to improve the water quality of Mill Neck Creek. The shellfish beds in this water body have been closed since 1983. The long-term goal is to reopen all 300 acres. To achieve this goal Friends of the Bay and its municipal partners have worked to obtain funding to improve wastewater treatment and stormwater runoff. A landmark groundbreaking occurred in April 2009 for long-awaited upgrades to sewer and water infrastructure to connect the homes in the Birches residential subdivision, located on the west side of Oak Neck Creek in the Locust Valley area, to the Glen Cove sewage treatment plant. This project will eliminate chronic cesspool overflows to Mill Neck Creek. Friends of the Bay has also been providing outreach to residents regarding the importance of conducting routine maintenance of their onsite wastewater treatment systems.

The Town of Oyster Bay, in partnership with Friends of the Bay, has been working to restore, enhance, and protect the Mill River, which is a major tributary to the Oyster Bay/Cold Spring Harbor Complex. The Town of Oyster Bay completed a watershed study and public stewardship plan in December 2007 to characterize the natural resources of the Mill River watershed, develop strategies to mitigate stormwater quality impacts to the Mill River and the harbor complex, and develop a public outreach/education materials and program. Nassau County has also completed subwatershed stormwater studies for a number of the harbor complex subwatersheds, including Mill River, White's Creek, Tiffany Creek, and others. These studies identify specific stormwater improvement projects that can be implemented in each subwatershed to restore and protect water quality within the estuary and its tributaries.

In July 2009, Oyster Bay was named the second case study location for the National Fish and Wildlife Federation Long Island Futures Fund project entitled "Watershed Trading to Improve the LIS Water Quality" (pilot case study is of the Saugatuck River Watershed in Connecticut). It is believed that the introduction of pollutant trading can reduce the overall cost to meet the reduction goal (e.g., 10% of non-point source Total Nitrogen, TN) as well as serve as a solution to the conflict between economic development and environmental protection and connect stakeholders (municipalities, agriculture, industry, etc.) in a watershed approach. The goal of this project is to assist involved entities including states, municipalities, and watershed groups, overcome the multitude of barriers to implementing a successful water pollution control program while accelerating the water quality improvement in the LIS. This project will build on watershed management initiatives, such as this one, to create a baseline for current watershed planning efforts. A guidance manual will be produced at the conclusion of this project, the LIS Trading Guidance Manual, which will serve as a guide for all LIS watershed entities on the technical, policy, regulatory, and administrative issues involved in pollutant trading and the "lessons learned" in the pilot watersheds.

A number of efforts are underway to restore diadromous fish (sea-run brook trout and other species) to the Mill River and other areas of the harbor complex. The Long Island Chapter of Trout Unlimited, Environmental Defense, and Friends of the Bay recently recently completed a





fish passage feasibility study for the Oyster Bay/Cold Spring Harbor Complex, and specifically for the Mill River. Results of these feasibility evaluations will guide the next steps relative to specific fish passage restoration projects and design alternatives.

Friends of the Bay, in cooperation with the Town of Oyster Bay and Nassau County, using Town and County funds (e.g., SEA Fund and other bond funds) successfully acquired the Mill Pond Overlook property for \$4.5 million in 2006. The purchase of this 3.6-acre site prevented the adverse affects development of this parcel would have had on the Mill Pond, the National Oyster Bay Wildlife Preserve, and Oyster Bay. The Town is currently in the process of securing \$59,000 in grant funding which the Town will match to develop a restoration plan to return the property to its natural state. The site is fenced and not currently open to the public. Under prior ownership, the Mill Pond site had been poorly maintained and an illegal dumping site for the prior owners asphalt business.

The U.S. Fish and Wildlife Service, NYSDEC, and other state and local government agencies, as well as Friends of the Bay, have been working to protect and restore tidal wetlands and coastal habitat within the estuary. One such project, the Centre Island tide gate project, was designed to restore approximately 20 acres of degraded tidal wetland located in the "Eastover Marsh", which had been dissected by a road that restricted the tidal flow to a large section of the marsh. This reduction caused water to stagnate, and Phragmites and other less desirable plant species dominated much of the marsh for years. To increase tidal flow and restore the marsh, two culverts were installed with a self regulating tide gate on one and a traditional flap tide gate on the other, which was the first time a self-regulating tide gate was installed in New York State.

The Oyster Bay/Cold Spring Harbor Complex was declared a federal No-Discharge Zone (NDZ) for vessel sewage, regulated under Section 312 of the Clean Water Act. The designation prohibits the discharge of sewage (whether treated or untreated) from vessels, providing an additional level of protection to address water quality issues associated with sewage contamination in marine waters.

There are also multiple efforts underway at the local, county, and state level to acquire open space within the harbor complex watershed to protect water quality and provide other environmental, recreational, and quality-of-life benefits. The State of New York, Nassau and Suffolk Counties, and the Town of Oyster Bay and the Town of Huntington have identified properties in the watershed for open space acquisition. In February 2008, the Nassau County Legislature acquired most of the 31-acre Smithers Estate in Mill Neck for open space preservation. This important acquisition creates a continuous preserve all the way to the Oyster Bay National Wildlife Refuge, helping to protect water quality and the health of the Oyster Bay/Cold Spring Harbor estuary system.

Other ongoing watershed protection/restoration and related land use planning activities include planning for Oyster Bay's Western waterfront (formerly Jacobson's Shipyard) and eastern waterfront, smart growth initiatives, and other site-specific development proposals.





2 Study Area Description

2.1 Municipal Jurisdictions

The Oyster Bay/Cold Spring Harbor Complex watershed is an approximately 39 square-mile watershed located in Nassau and Suffolk Counties on Long Island (*Figure 2-1*). As shown in *Table 2-1*, approximately 80 percent of the watershed is located within the Town of Oyster Bay and its incorporated villages and unincorporated villages and hamlets. A small portion (less than 2 percent) of the watershed is located in Glen Cove, also in Nassau County. The remaining 18 percent of the watershed is within the Town of Huntington and its incorporated villages in Suffolk County.


Table 2-1. Political Jurisdictions Within the Watershed


County	Town	Village/Hamlet	Area in Watershed (sq. miles)	% of Watershed
Nassau			31.97	81.9%
	Glen Cove		0.70	1.8%
		Glen Cove	0.70	1.8%
	Oyster Bay		31.28	80.2%
		Old Brookville	0.57	1.5%
		Lattingtown	1.11	2.8%
		Laurel Hollow	2.95	7.6%
		Woodbury	2.73	7.0%
		Hamlet of Oyster Bay	<i>1.27</i>	3.3%
		Cove Neck	1.32	3.4%
		Muttontown	2.94	7.5%
		Syosset	0.68	1.7%
		Bayville	<i>0.73</i>	1.9%
		Locust Valley	0.91	2.3%
		Upper Brookville	<i>3.58</i>	9.2%
		Bayville (Unincorporated)	0.12	0.3%
		Mill Neck	2.70	6.9%
		Oyster Bay Cove	<i>3.79</i>	9.7%
		Centre Island	<i>1.04</i>	2.7%
		Glen Head	0.33	0.9%
		Matinecock	2.66	6.8%
		Brookville	0.81	2.1%
		East Norwich	1.04	2.7%
Suffolk			7.04	18.1%
	Huntington		7.04	18.1%
		Lloyd Harbor	2.22	5.7%
		Cold Spring Harbor	2.50	6.4%
		West Hills	2.19	5.6%
1		Huntington	0.14	0.4%

Within the watershed, the primary jurisdiction lies with the Town of Oyster Bay and the Town of Huntington, each of which has authority to regulate land use and the underwater lands within its boundary and within unincorporated villages and hamlets. The Towns also have authority to regulate over-water use of coastal waters within its boundaries, but which lie outside of the 1,500-foot area of over-water jurisdiction of the incorporated villages. Each town also has a proprietary authority to control the placement of structures on underwater lands within their respective ownerships, including areas within the incorporated villages'











1,500-foot area of over-water jurisdiction. The incorporated villages have authority to regulate land use activities and the use of underwater lands within their respective boundaries, as well as authority to regulate the over-water use of coastal waters within 1,500 feet of their corporate boundaries. For the towns, incorporated and unincorporated villages, there are certain restrictions regarding the use of underwater lands within the Oyster Bay National Wildlife Refuge, which is owned and regulated by the U.S. Fish and Wildlife Service (Cashin Associates, P.C., 2002).

A basic profile of the watershed is provided in *Table 2-2*. Later sections of this document provide more detailed information on these watershed characteristics.

Table 2-2. Profile of the Oyster Bay/Cold Spring Harbor Complex Watershed

	1 00 0 11 /07 /00		
Area	39.3 square miles (25,136 acres)		
Stream Length	Approximately 7.9 miles		
Subwatersheds	14 subwatersheds defined for this study		
	2 Counties (Nassau and Suffolk)		
Jurisdictions	3 Towns		
	24 Villages/Hamlets		
	Identified impairments for Mill Neck Creek and its tidal		
Water Quality	tributaries, Cold Spring Harbor and its tidal tributaries,		
	and Oyster Bay Harbor.		
Current Impervious Cover	12.3%		
	Mill Neck Creek		
Subwatersheds with the	Bailey Arboretum		
Highest Restoration	Mill River		
Potential (Section 9)	Cold Spring Brook		
,	White's Creek		
	Jericho Turnpike (State Route 25)		
Major Transportation	Northern Boulevard/N. Hempstead Turnpike (State		
Major Transportation	Route 25A)		
Routes	Pine Hollow Road (State Route 106)		
	Harbor Road (State Route 108)		
	Caumsett State Park		
	Cold Spring Harbor State Park		
	Sagamore Hill National Historic Site in Cove Neck		
	Tiffany Creek Preserve		
	Stillwell Woods		
	Muttontown Preserve		
	Roosevelt Memorial Park		
	Charles T. Church/ Shu Swamp Nature Sanctuary		
Significant Natural and	Village Woods Park		
Historic Features	Mill Neck Preserve		
	Centre Island Town Park		
	Beekman Beaches		
	Theodore Roosevelt Audubon Sanctuary		
	Planting Fields Arboretum		
	Bailey Arboretum		
	Cold Spring Harbor Laboratory		
	Cold Spring Harbor Fish Hatchery		
	Raynham Hall		



2.2 Estuary

The Oyster Bay/Cold Spring Harbor estuary is located on the north shore of Long Island, spanning approximately 40 linear miles of shoreline and covering approximately 10 square miles (6,400 acres) of open water and intertidal area (Cashin Associates, P.C., 2002). The waterbodies that comprise the estuary are:

- Oyster Bay Harbor the approximately 2,500 acres between the Bayville Bridge and Plum Point on Centre Island. The mapped embayments associated with Oyster Bay Harbor include Beekman Beach, Oyster Bay Harbor proper, and Oyster Bay Cove.
- *Mill Neck Creek* a tributary to Oyster Bay Harbor, located west of the Bayville Bridge, with an approximately 300-acre watershed.
- Cold Spring Harbor the approximately 1,360 acres located south of a line between Cooper's Bluff in Cove Neck and West Neck Beach in the Village of Lloyd Harbor, including approximately 275 acres within the Town of Huntington. The embayments that are associated with Cold Spring Harbor include Inner Harbor and Cold Spring Brook.
- Oyster Bay the approximately 2,240 acres between Centre Island and the Lloyd Neck peninsula, which connects Oyster Bay Harbor and Cold Spring Harbor to Long Island Sound.

2.3 Watershed

For the purpose of this report, the Oyster Bay/Cold Spring Harbor Complex watershed is divided into 14 subwatersheds, from which surface runoff potentially enters the estuary. The subwatershed delineations are based on information from a variety of sources including previous watershed studies, municipal infrastructure mapping and GIS data, USGS topographic mapping, GIS data provided by Nassau County, and the EPA/USGS National Hydrology Dataset Plus. Subwatersheds were also delineated to facilitate assessment and development of watershed management plan recommendations. The subwatersheds include the area tributary to stormwater recharge basins. *Figure 2-2* depicts the subwatersheds identified in this report, and *Table 2-3* summarizes basic characteristics of the subwatersheds. Brief descriptions of the subwatersheds follow *Table 2-3*.










Table 2-3. Oyster Bay Subwatersheds

Subwatershed Name	Area (acres)	Area (square miles)	% of OB/CSH Watershed	Watershed Acronym
Bailey Arboretum	526	0.82	2.1%	BAI
Beaver Brook	4,793	7.49	19.1%	BEA
Centre Island	802	1.25	3.2%	CTR
Cold Spring Brook	4,810	7.52	19.1%	CSB
Cold Spring Harbor	3,004	4.69	12.0%	CSH
Kentuck Brook	1,516	2.37	6.0%	KBR
Lloyd Neck	893	1.40	3.6%	LNK
Mill Neck Creek	1,010	1.58	4.0%	MNC
Mill River	2,159	3.37	8.6%	MRV
Oyster Bay Harbor	1,679	2.62	6.7%	OBH
Tiffany Creek	1,894	2.96	7.5%	TFY
Upper Kentuck Brook	451	0.71	1.8%	UKB
Upper White's Creek	1,310	2.05	5.2%	UWC
White's Creek	289	0.45	1.1%	WCR
Harbor Complex Watershed	25,136	39.3		

The Centre Island subwatershed (CTR) contains all but the northern edge of the Centre Island peninsula and extends along the southern edge of the land connecting Centre Island to Oak Neck. CTR contains the entire village of Centre Island and the unincorporated village of Bayville. The 802 acre subwatershed is approximately 3.2% of the total watershed area of the harbor complex. The northeastern portions of the watershed discharge to Oyster Bay, while the southern and western portions drain to Oyster Bay Harbor.

The Mill Neck Creek subwatershed (MNC) wraps around Mill Neck Creek, extending from approximately the Bayville Bridge west to the large pond southwest of Factory Pond Lane, and from that pond east to the northern tip of Mill Neck. The subwatershed is located in the villages of Bayville, Locust Valley, Lattingtown, and Mill Neck. The subwatershed is relatively small in area (1,010 acres), but is downstream of approximately 29% of the watershed area contributing to the Oyster Bay/Cold Spring Harbor Complex. Oak Neck Creek is tributary to Mill Neck Creek on the north; the Beaver Lake and Kentuck and Upper Kentuck Brook subwatersheds discharge to Mill Neck Creek on the southern side of the subwatershed; and Bailey Arboretum discharges to the western side of Mill Neck Creek through the large pond southwest of Factory Pond Lane.

The Kentuck Brook (KBR) subwatershed is located within the Town of Oyster Bay and the City of Glen Cove, at the western edge of the watershed contributing to the Oyster Bay/Cold Spring Harbor Complex. Kentuck Brook is a freshwater stream that flows from Glen Cove northeast to the southwest corner of Beaver Lake. This subwatershed is approximately 1,516 acres or 6% of the total watershed area of the harbor complex.

The Upper Kentuck Brook (UKB) subwatershed is located primarily within the Village of Old Brookville in the southwestern corner of the watershed, with the northwest corner of the watershed located in Glen Cove. This southern limit of this 451-acre subwatershed runs approximately parallel to Pound Hollow Road and perpendicular to Brookville Lane and is bounded by Piping Rock Road to the East. This subwatershed discharges to the Kentuck Brook subwatershed near Frost Pond Road.





The Beaver Lake (BEA) subwatershed is located within the Town of Oyster Bay and the Villages of Brookville, Muttontown, Upper Brookville, Matinecock, and Mill Neck. The approximately 4,793-acre subwatershed is nearly 2 miles in length, extending from Cedar Swamp Road (Route 107) in the south to Mill Neck Creek. The downstream portion of the watershed consists of a series of freshwater ponds and wetlands connected by stream segments. The upstream waterbody is Upper Francis Pond, located near the intersections of Oyster Bay road and Mill Hill Road, which discharges to Lower Francis Pond, Shu Swamp, and finally into Beaver Lake. Beaver Lake receives discharge from Kentuck Brook before discharging into Mill Neck Creek.

The Mill River (MRV) subwatershed is located within the Town of Oyster Bay and the Villages of Muttontown, East Norwich, Upper Brookville and Mill Neck and the Hamlet of Oyster Bay in the northeastern portion of Nassau County. The approximately 2,159-acre watershed extends from wetlands in the Muttontown Preserve north under North Hempstead Turnpike (State Route 25A) to Mill Pond, a large pond located between Oyster Bay-Glen Cove Road and West Main Street. The pond also receives drainage from multiple stormwater outfalls and sluices from the encircling roads and outflows under Main Street, discharging through the tidal segment of Mill River into Oyster Bay Harbor (Cashin Associates, P.C., 2007).

The Upper White's Creek (UWC) subwatershed is an approximately 1,310-acre watershed located within the Town and Hamlet of Oyster Bay and the villages of upper Brookville, East Norwich, Muttontown, Syosset, and Oyster Bay Cove. The creek is centered along Route 106, which becomes South Street in the downstream White's Creek (WCR) subwatershed. According to a recent analysis of stormwater runoff in the watershed, the area of the entire White's Creek watershed has been reduced significantly in size by the installation of recharge basins and other drainage infrastructure that contain storm runoff volume from roads, subdivision developments, and commercial and industrial sites. Consequently, the Upper White's Creek subwatershed should provide little or no stormwater runoff (Cashin Associates, P.C., 2007).

White's Creek (WCR) is located downstream of the Upper White's Creek subwatershed and consists of a short section of tidal creek and a narrow segment of freshwater creek. According to the recent stormwater analysis of the subwatershed (Cashin Associates, P.C., 2007), the tidal creek receives drainage from stormwater outfalls located at the northerly end of South Street. Runoff from the majority of the subwatershed, carried in street gutters and a network of underground piping, discharges at these outfalls. The report states that the freshwater segment is a channelized stream located between South Street and White Street that carries runoff from the drainage infrastructure in municipal parking lots and surrounding roadways. The area contributing runoff is approximately 289 acres and is located primarily within the Hamlet of Oyster Bay.

The Tiffany Creek (TFY) subwatershed is an approximately 1,894-acre subwatershed located within the Town of Oyster Bay, within the villages of Oyster Bay Cove, Laurel Hollow, and Cove Neck. Tiffany Creek extends from its headwaters near the intersection of Cove Road and Yellow Cote Road to the outflow into Oyster Bay Cove. According to a recent analysis of stormwater runoff in the Tiffany Creek subwatershed (Cashin Associates, P.C., 2007), the brook is comprised of a short tidal segment and a longer freshwater segment. The tidal segment is





influenced by the Oyster Bay Cove tidal changes and receives stormwater runoff from areas northeast of Tiffany Road. The freshwater segment is a partially channelized stream located between Cove Neck Road and Yellow Cote Road and receives surface runoff from adjacent residential properties and nearby roads. At the downstream end of the freshwater segment, there is a small pond located just south of Cove Neck Road.

The Oyster Bay Harbor (OBH) subwatershed consists of the 1,679 acres, extending from the Bayville Bridge in the west to Cove Neck peninsula in the east, that discharge directly to Oyster Bay Harbor. This subwatershed is located in the Town of Oyster Bay and the Villages of Mill Neck, Oyster Bay Cove, Cove Neck, and the Hamlet of Oyster Bay. There are no significant streams in the watershed; Spring Lake in the western portion of the watershed off of Cleft Road is the largest water feature within the subwatershed.

The eastern side of the Cold Spring Brook (CSB) subwatershed is located in the Town of Oyster Bay and the Villages of Syosset, Woodbury, and Laurel Hollow in Nassau County, and the western side of the subwatershed is located in the Town of Huntington and the Villages of Cold Spring Harbor and West Hills in Suffolk County. The subwatershed is approximately 4,810 acres, making it and the Beaver Lake subwatershed the largest in the harbor complex watershed, each comprising roughly 19% of the total watershed area. The headwaters of Cold Spring Brook are located south of Jericho Turnpike. The brook is parallel to Harbor Road before discharging to Cold Spring Harbor downstream of Route 25A (Lawrence Hill Road).

The Cold Spring Harbor (CSH) subwatershed is approximately 3,004 acres, extending from Cove Neck peninsula in the west to Lloyd Harbor in the east, that drain directly into Cold Spring Harbor. The western side of the subwatershed is located in Nassau County in the Town of Oyster Bay and the Villages of Cove Neck, Oyster Bay Cove and Laurel Hollow. The eastern side of the subwatershed is located in the Suffolk County Town of Huntington and the Villages of Huntington and Cold Spring Harbor. Several small streams, running approximately parallel to the shoreline, drain the subwatershed.

Lloyd Neck subwatershed (LNK) is located on the western portion of Lloyd Neck, north of Lloyd Harbor in the Village of Lloyd Harbor in the Town of Huntington. The subwatershed is approximately 3.6% of the watershed area contributing to the harbor complex. While there are no large streams in the watershed, there is a freshwater pond south of Whitewood Point with two mapped tributaries, which drains directly to Oyster Bay.






3 Historical and Social Perspective

3.1 History of the Watershed

The area including the Oyster Bay/Cold Spring Harbor Complex watershed was purchased by colonists from the Native Americans in 1653, with the exception of Lloyd Neck and Centre Island, which were not purchased until 1664 and 1665, respectively. The Oyster Bay/Cold Spring Harbor waterways have attracted merchants and colonization throughout the centuries. During the 17th century, common occupations were related to maritime activities, such as boat builders, carpenters, innkeepers, shipwrights and surveyors. The clay deposits on Centre Island began to be used for brickmaking. Commerce and populations increased through the 18th century. By



the mid-19th century and the invention of the steamboat, Long Island Sound became a popular summer vacation resort destination (McGee, 1997).

Scientific exploration of Cold Spring Harbor and Oyster Bay began in the early 20th century with the development of a biological laboratory to study the freshwater rivers, springs, tidal flats, and saltwater harbor. The Cold Spring Harbor Laboratory of Quantitative Biology is still in operation more than 100 years later, conducting world-renowned research. The laboratory boasts seven Nobel Prize winners (McGee, 1997).

In the time following World War II, prominent people continued to commute to Oyster Bay from New York City. Business and shopping increased in the area. Current waterfront commerce and activities include: Petro-Commander Oil Corporation, Oyster Bay Marine Center, Frank M. Flower and Sons, three yacht clubs (Seawanhaka Corinthian, Sagamore, and Oak Cliff), and various beaches and a sport club. Commercial oystering remains a prominent industry in Oyster Bay which began in the second half of the 19th century, with underwater shellfish lands leased by the Town of Oyster Bay. The harbor bottom and Mill Neck Creek are important oystering grounds. Prior to World War II, the shellfish in Oyster Bay were plentiful and supported four major oyster harvesting companies and independent baymen. By 1960, the oyster populations began to dwindle and the Flower and Sons Company began a shellfish hatchery to replenish the harbor stock. Today, the Frank M. Flower & Sons, Inc. shellfish company, along with more than 80 independent commercial baymen, annually harvests up to 90% of New York's oyster crop and up to 33% of hard clams from the Oyster Bay/Cold Spring Harbor estuary. The continued success of commercial shellfishing in Oyster Bay remains a concern for town and village government due to threatened water quality from development and other activities in the harbor and its watershed (McGee, 1997).





3.2 Population and Demographics

The population and demographics of the Oyster Bay/Cold Spring Harbor Complex watershed reflect the trends within the Town of Oyster Bay and Nassau County, since the Town of Oyster Bay comprises approximately 80% of the total watershed area. Information on the population and demographics of the watershed are based on information from the Nassau County Master Plan, the U. S. Census Bureau, the Long Island Power Authority, and the Long Island Index Report.

According to the 2008 Nassau County Master Plan Update (Nassau County, April 2009), the County has experienced two periods of major population growth over the past 100 years (*Figure 3-1*). The first occurred in the 1920s as part of the New York area's initial suburban expansion and the second occurred during the 1950s following the passing of the Servicemen's Readjustment Act ("G.I. Bill") and the end of World War II, both of which led to a dramatic increase in single home ownership for returning veterans and their families.

According to data from the U.S. Census Bureau's 2006 American Community Survey, the Town of Oyster Bay population is approximately 299,635. The population is 48.5% male and 51.5% female, with 47.3% of the population between the ages of 25 and 59. Approximately 32.0% of Oyster Bay's population is below age 25, with 20.7% age 59 or older.

The Nassau County population trend from 1900 through 2006 provided by the U.S. Census Bureau depicts two drastic periods of growth on Long Island, in the 1920s and again in the 1950s (*Figure 3-1*). According to a Long Island population study conducted by the Long Island Regional Planning Board, the population of Long Island by 2010 is expected to remain at the present level of 1.3 million people. The population within the harbor complex watershed is also anticipated to remain relatively stable, as there is little remaining developable land in the watershed.

According to the 2000 U.S. Census, the Town of Oyster Bay racial and ethnic characteristics are 86.5% white, 1.8% Black or African American, 7.6% Asian, 0.1% American Indian and Alaska Native, and 6.6% Hispanic or Latino of any race. The Town of Oyster Bay population has a higher percentage of white residents compared to the U.S. population average of 73.9%, and has a notably lower Black or African American and Hispanic or Latino population compared to the U.S. averages of 12.4% and 14.8%, respectively. There is a higher population of Asian residents in Oyster Bay, with a percentage of 7.6%, as compared to the national average of 4.4%.

The average household and family sizes in Oyster Bay are similar to the average U.S. population at 3.0 and 3.4 people, respectively. The median value of single-family owner-occupied homes in Oyster Bay is \$556,800, which is considerably higher than the U.S. median \$185,200. The median household income is \$97,934 (in 2006 dollars) which is more than twice the U.S. median of \$48,451. The percentage of families and individuals below the poverty level are less than the U.S. average; 2.4% of families are below the poverty level, compared with 9.8% in the U.S., and similarly 4.1% of individuals as compared to 13.3% in the U.S. are below the poverty level.








Figure 3-1. Population Trends in Nassau County

The Long Island Index 2008 Report provides an annual review of the goals of government and residents of Long Island to direct regional planning efforts. The 2007 report highlights the need for more affordable housing for young professionals, empty-nesters and retirees. The report found that a majority of current home-owners on Long Island could not afford to purchase a home in today's market. This project was and continues to be funded by the Rauch Foundation.

3.3 Recreation and Community Resources

The Oyster Bay/Cold Spring Harbor Complex provides many opportunities for recreational activities, such as fishing, swimming, and boating. The National Wildlife Refuge and North Shore Wildlife Sanctuary provide significant opportunities for nature observation. Recreational boating is an important activity in the harbor complex, with a 750-vessel mooring area in Oyster Bay Harbor managed by the Town of Oyster Bay. Freshwater fishing is popular in Mill Pond. There are also many public parks, preserves and beaches within the Oyster Bay/Cold Spring Harbor Complex, including:

- Caumsett State Park,
- Cold Spring Harbor State Park,
- Sagamore Hill National Historic site in Cove Neck,
- Tiffany Creek Preserve,
- Stillwell Woods,





- Muttontown Preserve,
- Roosevelt Memorial Park,
- Charles T. Church/Shu Swamp Nature Sanctuary,
- Village Woods Park,
- Mill Neck Preserve,
- Centre Island Town Park,
- Beekman Beach.

A number of country clubs and golf courses exist in the watershed including the Cold Spring Harbor Country Club, Pine Hollow Country Club, Muttontown Golf and Country Club, Mill River Country Club, Brookville Country Club, Piping Rock Country Club, and Nassau Country Club.





4 Natural Resources

4.1 Geology and Soil

Long Island is formed largely of two spines of glacial moraine. Oyster Bay/Cold Spring Harbor is on the northern moraine, which directly abuts the North Shore of Long Island at points and is known as the Harbor Hill moraine. The moraine consists of gravel and loose rock left behind during the two most recent pulses of Wisconsin glaciation around 19,000 BC. The glaciers melted and receded to the north, resulting in the difference between the North Shore beaches and the South Shore beaches. The North Shore beaches are rocky from the remaining glacial debris, while the South Shore's are crisp, clear, outwash sand (Mills, 1974).

The underlying bedrock is composed of the Monmouth Group, Matawan Group and Magothy Formation of the Coastal Plain Deposits. The surficial geology in the watershed is composed of till and till moraine along the coast, which can be of variable texture (boulders to silt) and permeability. Outwash sand and gravel is present inland from the till deposits composed of coarse to fine gravel with sand. Patches of Kame deposits are present in the watershed, consisting of coarse to fine gravel and/or sand (NYS Museum, 2000).




Figure 4-1. Hydrogeologic Cross Section of Long Island Near the Nassau-Suffolk County Border (McClymonds and Franke, 1972)





The regional surficial sediment distribution in Long Island Sound exhibits textural trends which are related to sea-floor geology, bathymetry, and the effects of currents. In general, gravelly sediments are dominant in easternmost Long Island Sound, where tidal currents are strong, and in areas characterized by glacial tills. Sand occurs across the east-central Sound and along most of the nearshore margins. Sand-silt-clay is predominant in Oyster Bay/Cold Spring Harbor (USGS, 2007).

The unconfined groundwater aquifer in the harbor complex watershed is the Upper Glacial Aquifer which extends from Long Island Sound south to the Atlantic Ocean (*Figure 4-1*). The unconfined aquifer is underlain in the Oyster Bay area by several deeper freshwater aquifers. Beneath the Upper Glacial Aquifer, the North Shore Aquifer is confined by the North Shore confining Raritan clay unit. The Lloyd aquifer is confined between the Raritan clay unit and the bedrock formation (Nassau DPW, 2005). Monitoring in the Oyster Bay area has detected significant saltwater intrusion into the Upper Glacial Aquifer and less extensive intrusion into the deeper confined Lloyd Aquifer (USGS, 2004).

4.2 Topography

The topography of the area within the Oyster Bay/Cold Spring Harbor Complex watershed is generally characterized by long, narrow stream valleys surrounded by gentle (1-2%) to steeply (25% or more) sloping hills that transition into broader areas of gently sloping topography (Figure 4-2). Based on U.S. Geological Survey topographic mapping of the area, elevations in the southernmost, upper, portions of the watersheds are typically 200 feet above mean sea level (MSL) with some elevations as high as approximately 350 feet MSL in the Cold Spring Harbor watershed near High Hill in Huntington. Elevations near the watershed's outlets to the estuary are typically less than 10 feet MSL, with some sandy rocky bluffs of 20 to 80 feet MSL elevation adjacent to narrow beach areas (NYDEC, 2003).


4.3 Surface Hydrology

Surface hydrology on Long Island is primarily limited to small streams since the land area is relatively small, and fresh water runoff reaches the ocean without forming large rivers (Mills, 1974). This is also true of the Oyster Bay/Cold Spring Harbor Complex watershed, where the surficial hydrology is dominated by smaller headwater streams and associated impoundments.

The small streams and creeks on Long Island are primarily fed by base flow or groundwater. The distribution and timing of flows is therefore relatively stable year-round. *Figure 4-3* shows the seasonal pattern of mean monthly streamflow in Mill Neck Creek (USGS Stream Gage 01303000, at Beaver Lake 30 feet upstream from Cleft Road in Mill Neck) and Cold Spring Brook (USGS Stream Gage 01303500, at Cold Spring Fish Hatchery 270 feet upstream from State Highway 25A) for the period of record. Normalized by drainage area, the streamflow data in *Figure 4-3* are presented in units of cubic feet per second per square mile (CFSM). The highest streamflow generally occurs during March and April, while seasonal low-flows typically occur during late summer or early fall.













Figure 4-3. Mean Monthly Streamflow of Mill Neck Creek and Cold Spring Brook

As described in Section 2.3, the major surface hydrologic features within the harbor complex watershed are Cold Spring Brook, which feeds Cold Spring Harbor, Tiffany Creek and Mill River, which discharge to Oyster Bay Harbor, and Beaver and Kentuck Brooks, which combine at Beaver Lake before discharging into Mill Neck Creek.

4.4 Flood Hazard Areas

Floodplains, which are areas that would be impacted by floodwaters of some depth, are delineated by the Federal Emergency Management Agency 100-year and 500-year flood zones (FEMA, 1979). Much of the watershed's coastline is subject to inundation and flooding due to wave action (*Figure 4-4*). The 100-year flood zone is typically within 500 feet of the coast and includes residential areas in Bayville and the estuarine complex on the eastern side of Centre Island. Most areas of the watershed lie outside the 500-year flood zone. Portions of Beaver Brook, Mill Pond, Tiffany Creek and St. John's Pond have designated 100-year and 500-year flood zones.







4.5 Climate

Climate in the Oyster Bay/Cold Spring Harbor Complex watershed is similar to other coastal areas in the Northeast, with warm humid summers and cold winters. Climate on Long Island is influenced strongly by the ocean, which results in a relatively mild winter season compared to inland areas and helps to alleviate heat in the summer months. According to the National Oceanic and Atmospheric Administration, there are an average of 7 days between June and September when the afternoon temperature on Long Island exceeds 90 degrees, while farther inland there are 10 to 15 such days. The winter season is relatively mild, with below zero temperatures reported on only one or two days in about half the winters. Temperatures of 10 degrees below zero or colder are extremely rare and there are often extended periods during the winter when no snow cover is present. The freeze-free season is typically from late April/early May to mid- to late-October.

The area typically receives 45-50 inches of precipitation on an annual basis. The seasonal snowfall averages about 30 inches. Almost all of this snow falls between December and March. Coastal low pressure systems, Northeasters, are the principle source of this snow. These weather systems will occasionally produce a heavy snowfall. It is uncommon for the eye of a tropical storm to pass directly over Long Island. Tropical weather systems moving along the Atlantic Coast, however, are capable of producing episodes of heavy rain and strong winds in the late summer or fall.

Changes in climate are anticipated to occur over the next century. The magnitude of changes in temperature, sea level, and the timing and intensity of rainfall will depend upon future emissions of carbon dioxide and other greenhouse gases driving climate change. However, using different emissions scenarios, climate modelers have predicted the following changes to the climate in the Northeast United States as summarized below (Ashton et al., 2007; Fogarty et al., 2007; Frumhoff et al., 2007; Hayhoe et al., 2008; Kirshen et al., 2008).

Over the next several decades, temperatures are anticipated to rise 2.5-4°F in winter and 1.5-3.5°F in summer. By the end of the century, winter temperatures are predicted to rise 5-12°F and summer temperatures 3-14°F compared to current conditions. As a result, days over 90°F will be more frequent, there will be a longer growing season, less winter precipitation falling as snow and more as rain, a reduced snowpack, and an earlier spring snowmelt. In addition, regional sea surface temperatures are expected to rise 4-8°F by 2100.

The Northeast is anticipated to experience an increase in total precipitation of about 10% or 4 inches on an annual basis by the end of the century. Seasonally, winter precipitation is predicted to increase 20-30%, while summer precipitation amounts will remain relatively unchanged. In addition to increased precipitation amounts, more extreme precipitation is expected. Current model predictions include an increase in the precipitation intensity, i.e., the average amount of rain falling on a rainy day, and the number of heavy precipitation events. Precipitation intensity is predicted to increase 8-9% by mid-century and 10-15% by the end of the century. An 8% increase in the number of heavy precipitation events is expected by mid-century, with a 12-13% increase by the end of the century. The resulting hydrologic response will be higher winter and lower summer streamflow.





4.5.1 Climate Change Impacts

Climate change in the Northeastern U.S. is anticipated to result in an increase in the extent and frequency of coastal flooding, a rise in the frequency of severe storms and related damages, and sea level rise of 2-6 feet (Frumhoff et al., 2007). Increases in sea level and frequency of severe storms will result in more inundation of coastal areas, and subsequent increases in shoreline erosion and wetland loss. Inundation of low-lying areas will result in the potential for saltwater to infiltrate into freshwater surface waters and aquifers. Increased flooding and erosion has the potential to negatively impact transportation infrastructure and sewage and septic systems.

Areas of coastline most vulnerable to sea-level rise impacts have been identified by the U.S. Geological Survey (USGS) (Hammar-Klose and Thieler, 1999) through the calculation of a coastal vulnerability index (CVI). Calculation of the CVI depends on past changes in shoreline position, typical wave climates, tidal range, coastal geomorphology and sea-level history. Each region is assigned a CVI from 1 (low-risk) to 5 (high-risk). The assessment indicates a low CVI of 1 for the north shore of Long Island, in contrast to a CVI of 2 or higher for large segments of the south shore of Long Island and other coastal areas of the Northeastern U.S. (*Figure 4-5*). However, it is important to keep in mind that the CVI does not predict future shoreline location or take into account large events such as hurricanes.




Figure 4-5. Coastal Vulnerability Index (CVI) for the Northeastern U.S.





Coastal wetlands are vulnerable to the effects of sea-level rise, increasing water temperatures, and increased nutrients. If accretion of river-borne sediment and organic matter is unable to keep pace with the combined affects of sea-level rise and land subsidence, coastal marshes will be reduced or disappear. This will impact the ecological services provided by these areas including buffering coastal areas from waves and erosion, filtering nutrients and pollutants, providing wildlife habitat, and providing nursery areas for fisheries. Because hard-clams and oysters depend on wetland-based food chains, impacts to coastal wetlands are anticipated to impact those fisheries (Frumhoff et al., 2007).

It is difficult to predict the ways in which warming of water temperatures will influence other factors that affect marine ecosystems, including nutrient dynamics, ocean circulation, and plankton production. However, commercial fish and shellfish have water temperature thresholds that define conditions suitable for reproduction, growth, and survival. Increased water temperatures over the last decade have already led to declines in lobster landings in Long Island Sound (Fogarty et al. 2007). In addition, warmer water temperatures also appear to facilitate the spread of shellfish disease, the frequency and intensity of harmful algal blooms, and the ability of invasive species to reproduce and spread (Frumhoff et al., 2007).

More geographically-specific information on the impact of climate change on Long Island is currently being developed through a collaboration of The Nature Conservancy (TNC), the National Oceanic and Atmospheric Administration (NOAA), the NASA Goddard Institute for Space Studies, Pace Law School, the University of Southern Mississippi, and the Association of State Floodplain Managers. The TNC Coastal Resilience project is intended to provide planners and other decision-makers with tools to assess reasonable future impacts of flooding from sea level rise and storms. The mapping tool developed for the project is an interactive decision support tool that explores future flooding scenarios and is available at http://maps4.msi.ucsb.edu/. Currently the online tool is only operational for the south shore of Long Island, although plans to include the north shore of Long Island are included in the project.

4.6 Wetlands

Generally, wetlands are lands where saturation with water is the dominant factor determining the nature of soil development and the types of plant and animal communities living in the soil and on its surface. Wetlands vary widely because of regional and local differences in soils, topography, climate, hydrology, water chemistry, vegetation, and other factors, including human disturbance.

Wetlands are classified by NYSDEC as either freshwater or tidal, depending on the vegetation they support, which is a function of water salinity and inundation. Freshwater and tidal wetlands provide a multitude of functions including flood and stormwater control, pollution reduction, marine food production, wildlife habitat, recreational opportunities, open space, and aesthetic value.





In New York State, freshwater wetlands are regulated under the Freshwater Wetlands Act (under Article 24 of the Environmental Conservation Law) and are defined and mapped by NYSDEC. Freshwater wetlands are those areas of land and water that support a preponderance of characteristic wetlands plants that out-compete upland plants because of the presence of wetlands hydrology (such as prolonged flooding) or hydric (wet) soils. Freshwater wetlands commonly include marshes, swamps, bogs and fens. *Figure 4-6* depicts the extent and distribution of freshwater wetlands in the Oyster Bay/Cold Spring Harbor Complex watershed. Freshwater wetlands comprise less than 2 percent of the harbor complex watershed. The majority of these wetlands are associated with ponds along Beaver Brook, Mill River, Tiffany Creek, and Cold Spring Brook.

Tidal wetlands are regulated in New York State under the Tidal Wetland Act of 1973. Tidal wetlands are the coastal areas periodically flooded by seawater during high or spring tides or are affected by the changes in water levels caused by the tidal cycle. Salt marshes and mud flats are common types of tidal wetlands found along New York's marine shoreline. Tidal wetlands are classified by the amount of inundation during high and low tides and the type of vegetation. *Table 4-1* summarizes the categories of tidal wetlands, as designated by NYSDEC, which exist within the Oyster Bay/Cold Spring Harbor Complex.

Table 4-1. Tidal Wetland Categories


Category	Description
Coastal Shoals, Bars and Mudflats (SM)	The tidal wetland zone that at high tide is covered by saline or fresh tidal waters, and at low tide is exposed or is covered by water to a maximum depth of approximately one foot, and is not vegetated.
Littoral Zone (LZ)	The tidal wetland zone that includes all lands under tidal waters which are not included in any other category. There shall be no LZ under waters deeper than six feet at mean low water.
Formerly Connected (FC)	The tidal wetlands zone in which normal tidal flow is restricted by man-made causes. Phragmites sp. is the dominant vegetation.
Fresh Marsh (FM)	The tidal wetland zone found primarily in the upper tidal limits of the riverine systems where significant fresh water inflow dominates the tidal zone. Species normally associated with this zone include narrow leaved cattail, Typha angustifolia; the tall brackish water cordgrass, Spartina pectinata and/or S. cynosuroides; and the more typically emergent fresh water species such as arrow arum, Peltandra; pickerel weed, Pondederia; and cutgrass, Leersia.
High Marsh (HM)	The normal upper most tidal wetland zone usually dominated by salt meadow grass, Spartina patens; and spike grass, Distichlis spicata. This zone is periodically flooded by spring and storm tides and is often vegetated by low vigor, Spartina alterniflora and Seaside lavender, Limonium carolinianum. Upper limits of this zone often include black grass, Juncus Gerardi; chairmaker's rush, Scirpus sp; marsh elder, Iva frutescens; and groundsel bush, Baccharis halimifolia.
Intertidal Marsh (IM)	The vegetated tidal wetland zone lying generally between average high and low tidal elevations in saline waters. The predominant vegetation in this zone is low marsh cordgrass, Spartina alterniflora.
Dredged Spoil (DS)	All areas of fill material.

Source: http://www.dec.ny.gov/lands/5120.html

Figure 4-6 depicts the extent and distribution of tidal wetlands in the Oyster Bay/Cold Spring Harbor Complex watershed. Approximately 1,000 acres of tidal wetlands exist within the harbor complex. Extensive areas of coastal shoals, bars, and mudflats occur along Mill Neck Creek, the western and southern shoreline of Oyster Bay Harbor, Inner Cold Spring Harbor,









and the northeast shoreline of Centre Island. Most of the shoreline in the harbor complex is fringed by vegetated (IM and HM) tidal wetlands of varying width, interrupted by man-made waterfront structures. Some of the larger areas of vegetated tidal wetlands in the harbor complex are (Cashin Associates, P.C., 2002):

- Marshes along most of the shoreline in Mill Neck Creek,
- Oak Neck Creek, a northwesterly tributary of Mill Neck Creek, which is characterized by NYSDEC as one of the largest undeveloped salt marshes remaining on the north shore of Long Island,
- The Town of Oyster Bay-owned marsh at Goose Point in Bayville,
- Centre Island Marsh, which connects to Oyster Bay,
- Marsh along the entire length of West Shore Road on Oyster Bay Harbor,
- St. John's Marsh at the head of Cold Spring Harbor.

Table 4-2 summarizes the distribution and extent of freshwater and tidal wetlands in the harbor complex subwatersheds. Freshwater wetlands account for approximately 1.7 percent of the harbor complex watershed area, with the majority of these located in the Beaver Brook, Cold Spring Brook, and Mill River subwatersheds. Tidal wetlands account for approximately 1,000 acres within the harbor complex subwatersheds and estuary. Approximately half of the acreage of tidal wetlands is within the estuary, outside of the subwatershed boundaries.

Table 4-2. Freshwater and Tidal Wetlands in the Oyster Bay/Cold Spring Harbor Complex

Subwatershed Name	Freshwater Wetland Acreage (Percent of Watershed)	Tidal Wetland Acreage	Total Wetland Acreage
Bailey Arboretum	22.8 (5.5%)	6.1	28.9
Beaver Brook	168 (3.5%)	0	168
Centre Island	0 (0%)	329.4	329.4
Cold Spring Brook	86.2 (1.8%)	0	86.2
Cold Spring Harbor	10.8 (0.4%)	169.9	180.7
Kentuck Brook	15.3 (1.0%)	0	15.3
Lloyd Neck	6.7 (0.8%)	62.6	69.3
Mill Neck Creek	0 (0.0%)	335.2	335.2
Mill River	108 (5.0%)	0	108
Oyster Bay Harbor	0 (0.0%)	169.4	169.4
Tiffany Creek	16.1 (0.9%)	0	16.1
Upper Kentuck Brook	0 (0%)	0	0
Upper White's Creek	0 (0%)	0	0
White's Creek	0 (0%)	0	0
Harbor Complex Watershed	433.9 (1.7%)	1,072.6	1,506.5

4.7 Fish and Wildlife Resources

Portions of the Oyster Bay/Cold Spring Harbor Complex and its watershed provide abundant and significant habitat that supports a variety of fish and wildlife. Various estuarine, palustrine, riverine, and upland areas provide habitat to finfish, shellfish, mammals, amphibians, reptiles and birds.





The most notable tracts of protected or preserved land (including submerged or tidal areas) within the estuary and watershed include:

- Oyster Bay National Wildlife Refuge,
- Charles T. Church/Shu Swamp Nature Preserve,
- Sagamore Hill National Historic Site,
- Planting Fields Arboretum,
- Muttontown Preserve,
- Bailey Arboretum,
- Stillwell Woods Park,
- Tiffany Creek Preserve.

These tracts of privately and publicly owned land provide valuable habitat or unique natural resources in an otherwise developed residential watershed. Due to the importance of these habitats, the State of New York has designated some of them as Significant Coastal Fish and Wildlife Habitats (SCFWH). According to NYSDEC, SCFWH include marshes, wetlands, mud and sandflats, beaches, rocky shores, riverine wetlands and riparian corridors, stream, bay and harbor bottoms, submerged aquatic vegetation beds, dunes, old fields, grasslands and woodlands and forests. These coastal habitats provide living and feeding areas for animals and are also economically important. Three NYSDEC-designated SCFWH areas exist in the watershed: Mill Neck Creek, Cold Spring Harbor, and Oyster Bay Harbor.

Oyster Bay Harbor and Cold Spring Harbor are hydrogeomorphically different from Mill Neck Creek, being predominantly composed of deep water estuarine habitats. Mill Neck Creek, in contrast, is predominantly composed of a tidal creek and marsh estuarine habitats. Each estuarine habitat provides unique resources for the fish and wildlife that use them. All or portions of these areas make up the majority of the Oyster Bay National Wildlife Refuge.

The Oyster Bay National Wildlife Refuge (NWR) is a 3,200-acre refuge that is the largest in the Long Island National Wildlife Refuge Complex. Oyster Bay NWR includes the northern three-quarters of Oyster Bay Harbor, the northwestern quadrant of Cold Spring Harbor (approximately 1,000 acres), and all of Mill Neck Creek. The refuge consists of bay bottom, saltmarsh, and freshwater wetlands systems. Bay bottom is the largest proportion of habitat owned and managed by the USFWS (78%). The remaining 22% consists of saltmarsh (low and high), estuarine stream bed, and unconsolidated shore habitats (10%, 9% and 3% respectively). The refuge also includes Mill Pond and its associated freshwater wetlands. The Oyster Bay NWR is well-sheltered from Long Island Sound and, as such, provides excellent winter habitat for a variety of water fowl and shorebirds. It also provides significant nursery and feeding habitat for finfish and substrate for shellfish (USFWS, 2009).

The following sections describe representative habitats and protected lands to illustrate the diverse and rich ecological communities that exist within the Oyster Bay/Cold Spring Harbor Complex and its watershed. The presence of diverse fish and wildlife habitats and species is indicative of the capacity of the harbor complex and its watershed to support these natural resources, despite the developed suburban landscape that makes up a large percentage of the watershed.





4.7.1 Estuarine Habitats

Oyster Bay/Cold Spring Harbor

The NYSDEC-designated SCFWH in Oyster Bay consists of approximately 2,500 acres of open tidal waters, mud flats, salt marshes, tidal creeks and sand islands. Depth of water at mean low tide ranges from 6 feet to 30 feet with some areas greater than 50 feet (USFWS, 2009; NYSDOS, 2005).

The designated SCFWH in Cold Spring Harbor consists of approximately 2,500 acres of open tidal waters, mud flats, salt marshes, tidal creeks and sand islands. Depth of water at mean low tide ranges from 6 feet to 20 feet with some areas as deep as 70 feet. Only a few areas of undeveloped salt marsh remain, including St. John's Marsh located at the southern end of the harbor and unnamed tidal marshes on the west shore associated with the Sagamore Hill National Historic Site (NYSDOS, 1987).

Finfish

Oyster Bay/Cold Spring Harbor and its associated lagoons, smaller embayments and tidal marshes serve as nursery and feeding habitat for various marine fish species including scup (Stenotomus chrysops), striped bass (Morone saxatilis), bluefish (Pomatomus saltatrix), Atlantic silverside (Menidia menidia), Atlantic menhaden (Brevoortia tyrannus), winter flounder (Pseudopleuronectes americanus), and blackfish (Tautoga onitis). This area is also known as one of a few spawning runs for smelt (Osmerus mordax) on Long Island (NYSDOS, 1987).

Attempts in recent years have been made to open up fish passage throughout the watershed to anadromous fish (which spend most of their adult lives in coastal marine waters) such as river herring (Alosa sapidissim), sea lamprey (Petromyzon marinus) and sea-run brook trout and catadromous fish (which live in freshwater but spawn at sea) such as American eel (Anguilla rostrata). (NYSDOS, 2005; Gomez & Sullivan, undated). A fish ladder has been constructed at the downstream end of Beaver Lake to open passage to sea run trout and potentially other anadromous and catadromous fish (NYSDOS, 2005).

Fish passage feasibility studies have also been completed by the Long Island Chapter of Trout Unlimited, Environmental Defense, and Friends of the Bay to evaluate restoration of diadromous fish (which travel between salt and freshwater and include both anadromous and catadromous fish) to the Mill River and other areas of the harbor complex watershed. According to an evaluation conducted by NYSDEC, Region 1 Fisheries Bureau (Kozlowski, 2001), the fishery in the Oyster Bay/Mill River system is unusual for Nassau County (Gomez & Sullivan, undated) due to the documented presence of brown trout and brook trout.

The NYSDEC conducted electrofishing of Mill River above the pond near Glen Cove Road in December 1993 and discovered that Mill River, upstream of Mill Pond, has a naturally reproducing brown trout population. It is one of three known reproducing brown trout populations on Long Island. The NYSDEC believes this population became established from stockings of brown trout in Mill Pond, as annual stocking has occurred since 1978. NYSDEC continues to stock brown trout in Mill Pond.





The presence of brook trout in Beekman Creek is one of only two known spawning populations in Nassau County. The other exists in the Beaver Brook subwatershed, in Shu Swamp Preserve. In February 2008, for the first time, natural reproduction of brook trout in Beaver Brook was documented by NYSDEC and Long Island Trout Unlimited (Gomez & Sullivan, undated).

Brook trout are also believed to be using Mill River during various times of their life cycle. From the Mill River confluence, Beekman Creek runs upstream under the Beekman Beach parking lot and West Shore Avenue where it runs exposed for approximately 75 yards before passing beneath the LIRR Bridge. In December 1995, ten brook trout were captured in Beekman Creek ranging in size from 3.4 to 10.2 inches with at least three size classes. Brook trout have never been stocked in Beekman Creek; however, they were stocked in Mill Pond until 1977 by the NYSDEC. Brook trout were stocked in Mill River upstream of the dam in 1996 and 1997 by the Cold Spring Harbor Fish Hatchery (Gomez & Sullivan, undated).

Shellfish

Oyster Bay/Cold Spring Harbor is one of the most productive shellfish growing areas in New York State. The Frank M. Flower & Sons, Inc. shellfish company, along with more than 80 independent commercial baymen, annually harvests up to 90% of New York's oyster crop from the Oyster Bay NWR. In addition to oysters, Oyster Bay/Cold Spring Harbor produces a substantial crop of other commercial shellfish including soft clams (*Mya arenaria*), mussels, Conch (*Strombus* sp.), Razor clam (*Ensis directus*), and most notably hard clams (*Mercenaria mercenaria*).

Landing data from the NYSDEC Shellfish Division illustrates the abundant commercial value of the shellfish population in Oyster Bay/Cold Spring Harbor. The average annual landing of oysters between 2005 and 2007 was more than 25,000 bushels worth an estimated annual average of \$1.6 million. By comparison, the average hard clam production from Oyster Bay/Cold Spring Harbor between 2005 and 2007 was over 61,000 bushels worth an estimated annual average of \$5.5 million. *Table 4-3* summarizes annual shellfish landing data from the NYSDEC Shellfish Division from 2005, 2006 and 2007 for Oyster Bay (NYSDEC Shellfish Harvest Area NS2) (NYSDEC, 2008).

0	2005 Bushels Value*		2006		2007	
Shellfish			Bushels	Value*	Bushels	Value*
Hard Clams	53,744	\$5,062	58,040	\$5,201	72,492	\$6,489
Soft Clams	65	\$5.2	169	\$15	69	\$6.2
Oysters	27,010	\$1,812	14,879	\$964	33,415	\$2,239
Mussels				-	180	\$1.8
Conch	147	\$3.9	447	\$8.6	855	\$16.4
Razor Clams			32	\$1.3		

Table 4-3. Shellfish Production in Oyster Bay

Overharvesting, habitat destruction, pollution, and disease reduced native oyster populations in Oyster Bay and Cold Spring Harbor to 1 to 2 percent of historic populations by the early 1960's. Wild oyster reefs have been gone so long that there is no record of where they were. To compensate for the decline of oyster populations, the only remaining commercial oyster



^{*} in thousands of dollars



company, Frank M. Flower & Sons, raises oysters in a hatchery and uses them to seed the underwater beds which they lease from the Town of Oyster Bay. The oyster population has been restored to the abundant levels seen in the past, and up to 90% of NY's oyster harvest comes from Oyster Bay. Construction of artificial reefs can be used to boost the commercial wild harvest of oysters by the local independent baymen as well. Those reefs could be populated with larvae generated by the annual spawning of the large number of broodstock size oysters now present in the bay.

Birds

The sheltered nature of Oyster Bay/Cold Spring Harbor provides excellent winter and breeding habitat for a variety of avian species including waterfowl; shorebirds; gulls, terns and allied species; song birds; and raptors. Over 110 species of birds have been documented in the Oyster Bay NWR and other coastal areas, (USFWS, 2006, 2009; NYDOS, 1987, 2005; Edinger et al., 2002, Conolly, 1991).

- Waterfowl Numerous waterfowl use the Oyster Bay/Cold Spring Harbor area as overwinter habitat. Mid-winter aerial surveys of the embayment have documented an abundance of waterfowl, in some cases more than 20,000 individuals per survey, during peak usage. Common species include American black duck (Anas rubripes), Canada goose (Branta canadensis), mallard (Anas platyrhynchos), greater scaup (Aythya marila), lesser scaup (Aythya affinis), canvasback (Aythya valisineria), bufflehead (Bucephala albeola), common goldeneye (Bucephala clangula), American widgeon (Anas Americana), mergansers (common (Mergus merganser), red-breasted (Mergus serrator) and hooded (Lophodytes cucullatus)) long-tail duck (Clangula hyemalis), gadwall (Anas strepera), green-winged teal (Anas carolinensis), and mute swan (Cygnus olor) (NYDOS, 1987, 2005; USFWS, 2006). It is estimated that 85% of all the duck species using the embayment as over-winter habitat are greater scaup, bufflehead and black duck. (USFWS, 2006).
- Shorebirds, Gulls, Terns and Allied Species The category of shorebirds includes cormorants, gulls, terns egrets, grebes, plovers and the like. The most common of these species in Oyster Bay/Cold Spring Harbor are double-crested cormorant (*Phalacrocorax auritus*) and gulls. The double-crested cormorant is a year-round resident, with populations peaking during breeding season (between April and October). Great cormorants also inhabit Oyster Bay/Cold Spring Harbor, however, not typically as a breeding species but as an over-winter species (USFWS, 2006, Conolly, 1991).
- Gulls As in most northeastern coastal areas, gulls are very common. Most common of these include herring gull (Larus argentatus), great black-backed gull (Larus marinus), ring-billed gull (Larus delawarensis), laughing gull (Leucophaeus atricilla) and Bonaparte's gull (Chroicocephalus philadelphia) (SCFWH CSH/MNC; Oyster Bay NWR). An estimated 1,500 gulls, mostly herring and great black-backed gulls, use the Oyster Bay NWR over winter. However some, such as the laughing gulls, use the NWR in the summer (USFWS, 2006; Conolly, 1991)





- Passerine Birds Variable coastal habitats support a wide assemblage of passerine birds (song birds). These birds may make use of any number of habitats from beaches to tidal marshes to upland forests and will move among different habitats depending on the time of year, availability of food, and breeding status. Common passerine birds that have been observed throughout the area include, but are not limited to, mourning dove (Zenaida macroura), gray catbird (Dumetella carolinensi), northern mockingbird (Mimus polyglottos), northern flicker (Colaptes auratus), eastern kingbird (Tyrannus tyrannus), American robin (Turdus migratorius), barn swallow (Hirundo rustica), red-winged blackbird (Agelaius phoeniceus), house sparrow (Passer domesticus), sharp-tailed sparrow (Ammodramus caudacutus), and fish crow (Corvus ossifragus) (NPS, 2009, Conolly, 1991).
- Raptors Numerous raptors have been observed in Oyster Bay/Cold Spring Harbor.
 These include piscivorous (i.e., fish-eating) species like wintering populations of bald
 eagle (Haliaeetus leucocephalus) and breeding populations of osprey (Pandion haliaetus);
 carnivorous species like the red-tailed hawk (Buteo jamaicensis) and northern harrier
 (Circus cyaneus); and scavenger species like the turkey vulture (Cathartes aura) (USFWS,
 2006; NPS, 2009; Conolly, 1991).
- Other Common Bird Species Other common shorebird, migrants and residents, have been observed in the NWR at various times of the year. These species include common loon (Gavia immer), red-throated loon (Gavia stellata), horned grebe (Podiceps auritus), pie-billed grebe (Podilymbus podiceps), American coot (Fulica americana), belted kingfisher (Megaceryle alcyon), great blue heron (Ardea herodias), black-crowned night heron (Nycticorax nycticorax), yellow-crowned night heron (Nycticorax violaceus), green heron (Butorides virescens), great egret (Ardea alba), snowy egret (Egretta thula), least bittern (Ixobrychus exilis), black-bellied plover (Pluvialis squatarola), dunlin (Calidris alpina), greater yellow legs (Tringa melanoleuca), lesser yellowlegs (Tringa flavipes), least sand piper (Calidris minutilla), spotted sandpiper (Actitis macularia) (USFWS, 2006; Conolly, 1991).

Mill Neck Creek

The NYSDEC-designated SCFWH in Mill Neck Creek consists of approximately 700 acres of open tidal waters, tidal marshes and creeks, mudflats and wooded freshwater swamps. The fish and wildlife habitat areas that are associated with Mill Neck Creek include Oak Neck Creek, Bayville Brook, and Beaver Brook.

The network of tidal creeks and salt marshes that make up much of Mill Neck Creek provide a unique and valuable habitat to a variety of species. This area is composed of a combination of high salt marsh, low salt marsh, intertidal mudflat communities and sub-tidal areas. Each of these communities is a part of the larger coastal marsh ecosystem – one transitioning to another – forming a mosaic with adjacent communities.

The low salt marsh community is characterized by regular flooding of semidiurnal tides. The vegetation of the low salt marsh is a nearly monospecific stand of cordgrass (*Spartina alterniflora*). A few species of marine algae can form dense mats on the surface sediments between the cordgrass stems, including knotted wrack (*Ascophyllum nodosum*), and rockweed (*Fucus vesiculosus*). Sea lettuce (*Ulva* spp.), and hollow green weeds (*Enteromorpha* spp.) can be abundant, especially





in early summer. Other plants that are present in very low numbers include glasswort (*Salicornia europaea*), salt marsh sand-spurry (*Spergularia marina*), and lesser sea blite (*Suaeda maritima*) (Edinger et al., 2002).

Animals common to these low salt marsh communities include clapper rail (Rallus longirostris), willet (Catoptrophorus semipalmatus), marsh wren (Cistothorus palustris), seaside sparrow (Ammodramus maritimus), fiddler crabs (Uca pugilator and U. pugnax) nesting along creek banks, ribbed mussel (Geukensia dimissa), and at high tide mummichog (Fundulus heteroclitus), sheepshead minnow (Cyprinodon variegatus), and several other small fishes that live in the tidal creeks at low tide (Edinger et al., 2002).

The high salt marsh community is characterized by less frequent flooding compared to low salt marsh communities. Typically, flooding occurs only at the spring tide; however, semidiurnal tidal fluctuations maintain regular, saturated conditions in the soil. The vegetation of the high salt marsh is dominated in many areas by either salt-meadow grass (*Spartina patens*) or a dwarf form of cordgrass (*Spartina alterniflora*); also common are large areas dominated by spikegrass (*Distichlis spicata*), black-grass (*Juncus gerardii*), and glassworts (*Salicornia* spp.) (Edinger et al., 2002).

Characteristic species of the upper high marsh (the area that grades into salt shrub or is topographically slightly higher than its surroundings) are blackgrass, switchgrass (*Panicum virgatum*), sea-lavender (*Limonium carolinianum*), seaside gerardia (*Agalinus maritima*), seaside goldenrod (*Solidago sempervirens*), and slender saltmarsh aster (*Aster tenuifolius*) (Edinger et al., 2002).

Animals characteristic to the high salt marsh include salt marsh mosquitoes (Aedes spp.), greenhead flies (Tabanidae), coffeebean snail (Melampus bidentatus), sharp-tailed sparrow (Ammodramus caudacutus), marsh wren (Cistothorus palustris), eastern meadowlark (Sturnella magna), clapper rail (Rallus longirostris), and American black duck (Anas rubripes).

4.7.2 Riverine and Palustrine Habitats

Representative areas of riverine and palustrine habitats in the Oyster Bay/Cold Spring Harbor Complex are described below.

Charles T. Church/Shu Swamp Nature Preserve

The Charles T. Church/Shu Swamp Nature Preserve (Shu Swamp) is located in the Beaver Brook subwatershed immediately upstream of Beaver Lake. This 60-acre preserve is dominated by a forested wetland system set in the heavy clay soils of the Mill Neck Creek valley. The wetland system is dominated by trees, specifically red maple (Acer rubrum), tulip tree (Liriodendron tulipifera) and black tupelo (Nyssa sylvatica) and an understory of primarily sweet pepperbush.

Red maple-black gum swamps are hardwood swamps that occur in poorly drained depressions. Hummock-hollow microtopography is usually evident in these wetlands. Other characteristic shrubs of this wetland type are highbush blueberry (*Vaccinium corymbosum*), swamp azalea (*Rhododendron viscosum*), fetterbush (*Leucothoe racemosa*), dangleberry (*Gaylussacia frondosa*), and on





the Atlantic coastal plain inkberry (*Ilex glabra*). Vines such as greenbrier (*Smilax rotundifolia*), sawbrier (*Smilax glauca*), Virginia creeper (*Parthenocissus quinquefolia*), and poison ivy (*Toxicodendron radicans*) are present at low amounts in the understory. The herbaceous layer is not particularly diverse, characterized by cinnamon fern (*Osmunda cinnamomea*), skunk cabbage (*Symplocarpus foetidus*). The nonvascular layer may include some *Sphagnum* species (Edinger et al., 2002).

Given the hummock-hollow microtopography of the swamp, small pockets of breeding amphibian pools provide habitat for species such as wood frog (*Rana sylvatica*), spring peeper (*Pseudacris crucifer*), northern red-back salamander (*Plethodon glutinosa*) and possibly spotted salamander (*Ambystoma maculatum*).

Common bird species that may inhabit Shu Swamp include American robin *Turdus migratorius*, hermit thrush (*Catharus guttatus*), veery *Catharus fuscescens*, grey catbird (*Dumetella carolinensis*), and wood duck (*Aix sponsa*). Common mammals may include Virginia opossum (*Didelphis virginiana*), short-tailed shrew (*Blarina brevicauda*), little brown myotis (*Myotis lucifugus*), eastern cottontail (*Sylvilagus floridanus*), beaver (*Castor canadensis*), muskrat (*Ondatra zibethicus*), mink (*Neovison vison*)/ Recent observations indicate that river otter (*Lontra canadensis*) may also have begun populating local waterbodies such as Shu Swamp (Rather, 2008).

Muttontown Preserve

Muttontown preserve is a 550-are parcel located in the upper reaches of the Mill River subwatershed. Nassau County's largest nature preserve, this tract of land consists of fields, moist woodlands, and kettle-hole ponds.

The dominant vegetation community type in Muttontown Preserve is a coastal oak-hickory forest. These types of forests are co-dominated by several species of oaks (*Quercus* spp.) and hickory (*Carya* spp.) and are typically found in dry well-drained, loamy sand of knolls, upper slopes, or slopes of glacial moraines. The forest is usually co-dominated by two or more species of oaks, usually white oak (*Q. alba*), black oak (*Quercus velutina*) and chestnut oak (*Q. montana*). Scarlet oak (*Quercus coccinea*) is also a common associate. Mixed with the oaks, usually at moderate densities, are one or more of the following hickories: pignut (*Carya glabra*), mockernut (*C. tomentosa*), and sweet pignut (*C. ovalis*) (Edinger et al., 2002).

Characteristic animals include eastern towhee (*Pipilo erythrophthalamus*), vireos (*Vireo* spp.), woodpeckers (Edinger et al., 2002). Muttontown Preserve is also notable for having several kettle-hole ponds. In addition, there are an estimated eight to ten vernal pools. These habitats offer both breeding and refuge for several common species of amphibians including green frog (*Rana clamitans*), American toad (*Bufo americanus*) wood frog, spring peepers, and spotted salamanders. Tiger salamanders (*Ambystoma tigrinum*) have also been documented at the site; however, the local populations appears to have been locally extirpated.

Sagamore Hill National Historic Site

Sagamore Hill National Historic Site is located on the western shore of Cold Spring Harbor. One of Sagamore Hill's greatest natural resource values lies in the high number of varied habitat types located in close proximity to each other. From oak-tulip forests, to open fields, to ponds,





to salt marshes, the park offers a wide variety of habitat types that support a diverse assemblage of plants and animal species. The following account was provided by the National Park Service for the Sagamore Hill National Historic Site.

Birds

Though a small park, Sagamore Hill contains a range of vegetation types and habitats that support a wider variety of bird species. Most notably, mature forest, salt marsh, and beach habitats on the eastern portion of the site offer excellent natural habitat. Notable species found here include the winter wren (*Troglodytes troglodytes*), great crested flycatcher (*Myiarchus crinitus*), yellow-billed cuckoo (*Coccyzus americanus*), and ruby-crowned kinglet (*Regulus calendula*).

Reptiles & Amphibians

Reptiles and amphibians can be found in nearly all of Sagamore Hill's vegetative communities, from dry upland forests to salt marshes. Many of the amphibian and reptile species of the park exhibit complex life-cycles that require complex habitat mosaics for reproduction and overwintering. Species such as wood frogs and spotted salamanders (a locally uncommon species) spend only a short time within the park's ponds during the breeding season and utilize adjacent forested upland for the remainder of the year. Aquatic species, such as painted and snapping turtles, likewise depend upon well-drained upland forests and fields for nesting.

Terrestrial species such as the eastern red-backed salamander, common garter snake, and box turtle extensively utilize Sagamore Hill's mixed deciduous forests, with the box turtle in particular depending upon large, roadless patches. Heron and Woodpile ponds constitute the only freshwater wetland sites within the park, but they exhibit the highest species diversity of amphibians and reptiles. These sites are critical for obligate vernal-pool breeders, such as wood frogs, spotted salamanders, spring peepers, and grey treefrogs.

The northern diamondback terrapin, though the most abundant reptile at Sagamore Hill, is found exclusively within the park's estuarine habitats. These turtles are found primarily in Eel Creek and Cold Spring Harbor and nest on the adjacent beach. Though small, the maritime complex at Sagamore Hill is a vital part of the larger harbor complex, which supports one of the larger diamondback terrapin populations in the state.

Insects, Spiders, Centipedes, Millipedes

According to a recent odonate survey of Sagamore Hill, the site hosts at least twenty-one species of dragonflies and damselflies, which utilize a variety of habitats within the park.

Heron Pond, located in the eastern forest, had one of the highest species diversities for odonates in the entire park, with six species of dragonflies and two species of damselflies recorded at the site. These species included the park's only recorded Twelve-spotted skimmer and Slender spread-wings. Three dragonflies and one damselfly were also recorded at the Woodpile Pond just north of the parking area. Two fields within the park also displayed high species abundance, with at least 10 species being found in each. These included one rare species, the Comet Darner (*Anax Longipes*).





Five species of dragonflies have also been recorded within the estuarine complex at the eastern edge of the park. These include the only Seaside dragonlet recorded at Sagamore Hill, as well as Wandering and Spot-winged gliders.

4.7.3 Threatened and Endangered Species

The NYSDEC Natural Heritage Program was consulted regarding rare or state-listed animals and plants, significant communities and other significant habitats within the Oyster Bay/Cold Spring Harbor Complex watershed. A query of the Natural Heritage Program database was generated on January 27, 2009 and a response, dated February 6, 2009, was received from NYSDEC Natural Heritage Program listing rare species and ecological communities.

The NYSDEC Natural Heritage Program database shows, based on recent observation and documentation (1980 to present), that there are 6 rare or state-listed animal species and 16 rare or state-listed plant species within (in whole or in part) the Oyster Bay/Cold Spring Harbor Complex watershed. Animal species include one species of amphibian, four species of birds and one species of butterfly. In addition, six significant natural communities were identified within the watershed.

The NYSDEC Natural Heritage Program database also provided historic records of plants and animals, located in the vicinity of the watershed, which have not been documented since 1979. One rare or state-listed animal species and eight rare or state-listed plant species have historically been identified within the harbor complex watershed.

The location of these species and the information provided by the NYSDEC Natural Heritage Program is considered sensitive. It is strongly recommended that the information provided should not be disseminated to the public without permission from the Natural Heritage Program. For this reason, details regarding the exact species and communities have not been appended to this report.





5 Water Quality

5.1 Water Quality Classifications, Standards, and Impairments

All waters in New York State are assigned a classification indicating their best uses including drinking water source, swimming, boating, fishing and shellfishing. Letter classes such as A, B, C, and D are assigned to fresh waters and two-letter classifications beginning with S are assigned to saline (marine) waters. Water quality classifications for New York surface waters are found at 6 NYCRR Part 701, and classifications for surface waters in the Oyster Bay/Cold Spring Harbor Complex are summarized in *Table 5-1*.

Table 5-1. Selected Surface Water Quality Classifications

Classification	Description
А	The best usages of Class A waters are: a source of water supply for drinking, culinary or food processing purposes; primary and secondary contact recreation; and fishing. The waters shall be suitable for fish, shellfish, and wildlife propagation and survival.
В	The best usages of Class B waters are primary and secondary contact recreation and fishing. These waters shall be suitable for fish, shellfish, and wildlife propagation and survival.
С	The best usage of Class C waters is fishing. These waters shall be suitable for fish, shellfish, and wildlife propagation and survival. The water quality shall be suitable for primary and secondary contact recreation, although other factors may limit the use for these purposes.
SA	The best usages of Class SA waters are shellfishing for market purposes, primary and secondary contact recreation and fishing. These waters shall be suitable for fish, shellfish, and wildlife propagation and survival.
SB	The best usages of Class SB waters are primary and secondary contact recreation and fishing. These waters shall be suitable for fish, shellfish, and wildlife propagation and survival.
SC	The best usage of Class SC waters is fishing. These waters shall be suitable for fish, shellfish, and wildlife propagation and survival. The water quality shall be suitable for primary and secondary contact recreation, although other factors may limit the use for these purposes.

Note: Complete description of classifications at http://www.dec.ny.gov/chemical/23853.html.

Figure 5-1 shows the water quality classifications assigned to fresh and marine waters in the Oyster Bay/Cold Spring Harbor Complex and its watershed. All freshwaters in the watershed are Class C. Class SA, SB, and SC marine waters are located in the Oyster Bay/Cold Spring Harbor Complex, with SA designations assigned to the open water areas and many nearshore areas. Exceptions are the Frost Creek, Mill Pond, Beaver Brook, and Fresh Pond areas where saline waters have an SC classification (Figure 5-1).

Numeric and narrative water quality standards for New York waters are found at 6 NYCRR Part 703. The narrative standards for surface water classifications A, B, C, SA, SB, and SC are shown in *Table 5-2*. Numeric standards for these surface water classifications for pH, dissolved oxygen (DO), dissolved solids, total coliform, and fecal coliform are provided in *Table 5-3*.










Table 5-2. Narrative Water Quality Standards

Parameter	Classes	Standard
Taste-, color-, and odor-producing, toxic and other deleterious substances	A, B, C, SA, SB, SC	None in amounts that will adversely affect the taste, color or odor thereof, or impair the waters for their best usages.
Turbidity	A, B, C, SA, SB, SC	No increase that will cause a substantial visible contrast to natural conditions.
Suspended, colloidal and settleable solids	A, B, C, SA, SB, SC	None from sewage, industrial wastes or other wastes that will cause deposition or impair the waters for their best usages.
Oil and floating substances	AA, A, B, C,SA, SB, SC	No residue attributable to sewage, industrial wastes or other wastes, nor visible oil film nor globules of grease.
Garbage, cinders, ashes, oils, sludge and other refuse	SA, SB, SC	None in any amounts.
Phosphorus and nitrogen	A, B, C,SA, SB, SC	None in amounts that will result in growths of algae, weeds and slimes that will impair the waters for their best usages.
Thermal discharges	AA, A, B, C, SA, SB, SC	Details in 6 NYCRR Part 704.
Flow	A, B, C	No alteration that will impair the waters for their best usages.

Table 5-3. Numeric Water Quality Standards

Parameter	Classes	Standard	
pH	A, B, C	Shall not be less than 6.5 nor more than 8.5.	
	SA, SB, SC	The normal range shall not be extended by more than one-tenth (0.1) of a pH unit.	
Dissolved oxygen (DO)	A, B, C	For trout spawning waters (TS), the DO concentration shall not be less than 7.0 mg/L from other than natural conditions. For trout waters (T), the minimum daily average shall not be less than 6.0 mg/L, and at no time shall the concentration be less than 5.0 mg/L. For nontrout waters, the minimum daily average shall not be less than 5.0 mg/L, and at no time shall the DO concentration be less than 4.0 mg/L.	
	SA, SB, SC	Chronic: Shall not be less than a daily average of 4.8 mg/L* Remark: "The DO concentration may fall below 4.8 mg/L for a limited number of days, as defined by the formula: $DO_1 = \frac{13.0}{2.80 + 1.84e^{-0.11}} \qquad \text{where } DO_i = DO$ concentration in mg/L between 3.0 - 4.8 mg/L and $t = \text{time in days}$. This equation is applied by dividing the DO range of 3.0 - 4.8 mg/L into a number of equal intervals. D_i is the lower bound of each interval (i) and t_i is the allowable number of days that the DO concentration can be within that interval. The actual number of days that the measured DO concentration falls within each interval (i) is divided by the allowable number of days that the DO can fall within interval (ii). The sum of the quotients of all intervals (iiin) cannot exceed 1.0: i.e., $\sum_{i=1}^n \frac{t_i(actual)}{t_i(allowed)} < 1.0$ The DO concentration shall not fall below the acute standard of 3.0 mg/L at any time.	



Table 5-3. Numeric Water Quality Standards

Parameter	Classes	Standard	
	SA, SB, SC	Acute: Shall not be less than 3.0 mg/L at any time.	
Dissolved Solids	A, B, C	Shall be kept as low as practicable to maintain the best usage of waters but in no case shall it exceed 500 mg/L.	
		The monthly median value and more than 20 percent of the samples, from a minimum of five examinations, shall not exceed 2,400 and 5,000, respectively.	
100 mij	SA	The median most probable number (MPN) value in any series of representative samples shall not be in excess of 70.	
Fecal Coliforms (number per 100 ml)	A, B, C, SB, SC	The monthly geometric mean, from a minimum of five examinations, shall not exceed 200	

Assessments of water quality are typically based on comparisons with numeric and narrative criteria for various pollutants or water characteristics (e.g., color or dissolved oxygen) and determination of impairment. Waters that are unable to support the uses for which they are designated (e.g., primary or secondary contact recreation, fishing, water supply, habitat, etc.) are said to be impaired. Section 303(d) of the Clean Water Act (CWA) as amended by the Water Quality Act of 1987, Public Law 100-4 and regulations for Water Quality Planning and Management found at 40 CFR 130 require each state to identify waters not meeting water quality standards for any given pollutant applicable to the water's designated uses, i.e., classification. The NYSDEC develops the 303(d) list for New York waters.

The 2008 303(d) list references Mill Neck Creek and its tidal tributaries, Cold Spring Harbor and its tidal tributaries, and Oyster Bay Harbor as impaired due to pathogens from urban and stormwater runoff and, in the case of Mill Neck Creek, municipal discharges are also identified as a source of impairment. As reflected by these impairments, water quality issues in the Oyster Bay/Cold Spring Harbor Complex have focused on elevated pathogen levels, which impact shellfish harvesting in the estuary. Shellfish, such as oysters and clams, are filter feeders, meaning they filter the water around them to feed on microscopic organisms. If the water column contains pathogenic bacteria and viruses, they can be retained in the shellfish and pose a health threat if the oysters or clams are eaten raw or partially cooked.

Although identified as impaired, these waters are no longer on the 303(d) list because, in response to these impairments, the NYSDEC has developed Total Daily Maximum Loads (TMDL) for pathogens for the impaired waters in the Oyster Bay/Cold Spring Harbor complex. A TMDL is required for each pollutant violating or causing a violation of water quality standards for each impaired water body. A TMDL determines the maximum amount or load of a pollutant from both point and non-point sources that a water body can receive and





continue to meet applicable water quality standards. In 2003, a TMDL for Oyster Bay Harbor and Mill Neck Creek and its tidal tributaries was developed (NYSDEC et al., 2003). In 2007, Cold Spring Harbor was included in the New York Shellfish Pathogen TMDL (NYSDEC et al., 2007).

5.2 History of Water Quality Issues

The TMDL for Oyster Bay Harbor and Mill Neck Creek (NYSDEC, 2003) summarized the water quality issues and identified potential sources of pathogens by conducting a shoreline survey and investigation of point and non-point sources of pollutants. The following were identified as pathogen sources:


- Centralized wastewater discharges (Oyster Bay wastewater treatment plant, Seawanhaka Corinthian Yacht Club, The Birches),
- Domestic waste disposal using cesspools,
- Stormwater discharges,
- Freshwater streams,
- Boats/marinas/mooring areas,
- Wildlife and waterfowl.

The impact of these point and non-point sources varies spatially throughout the harbor complex. Figures 5-2 and 5-3 show the areas in the harbor complex subject to shellfish harvesting closures. Uncertified areas are those that fail to meet the water quality standards for shellfishing listed in Table 5-3. Conditionally certified harvesting areas are those that marginally fail to meet the certified shellfish harvesting area criteria and may be operated during certain times of the year under certain rainfall conditions. Areas around the wastewater treatment plant outfalls, marinas, and boat mooring areas are subject to administrative closures for shellfishing. Although these areas may meet the water quality standard for coliform, the administrative closures are necessary in the event of a wastewater treatment plant malfunction, and they provide a buffer between pathogen sources and nearby certified shellfish harvesting areas.

The New York Shellfish Pathogen TMDL (NYSDEC et al., 2007) provided a generic identification of pollution sources likely to affect pathogen concentrations in Cold Spring Harbor. These included agricultural sources, marine vessels/marinas, urban/residential sources including pet waste, waterfowl, beach wrack, and marine sediment resuspension.








Source: http://www.dec.ny.gov/regs/4014.html

Figure 5-2. Oyster Bay Harbor and Mill Neck Creek Shellfish Closure Areas



Source: http://www.dec.ny.gov/regs/4014.html

Figure 5-3. Cold Spring Harbor Shellfish Closure Areas





In addition to these broader analyses of water quality, there have been specific studies of water quality in locations in the estuary complex where chronic water quality problems exist. Over the past several years, the Friends of the Bay water quality monitoring program (See Section 5.1.3) has identified elevated concentrations of pathogens and nutrients in the area near Beekman Beach. This area is near the discharge of the Mill River to Oyster Bay Harbor. In 2007, the Town of Oyster Bay's Mill River Watershed Study and Public Stewardship Program report summarized the nearly 30 years of investigations into water quality in the Mill River watershed. Beginning with a 1977 study, high coliform levels were noted in the Mill River outflow and the need for reduced dumping and dog wastes and sediment removal from Mill Pond were identified as measures to improve water quality. The 1995 Oyster Bay/Cold Spring Harbor Complex Stormwater Management/Coastal Water Qualty Improvement Program (SM/WQIP) Report identified stormwater outfalls along the shoreline and recommended general measures to improve stormwater quality. A study of the Mill Pond outflow in 2001 (Cashin Associates, P.C., 2001) identified the need to address wet-weather flows from the pond to reduce pathogen loading to Oyster Bay Harbor and suggested dredging or drawdown in anticipation of significant rainfall events to reduce loading from Mill Pond.

In 2004-2005, three rounds of dry-weather sampling at three locations in the Mill River watershed were conducted and are presented in the Mill River Watershed Study and Public Stewardship Program report. Based on the three samples, the report concluded that:

- Fecal and total coliform levels were consistent with typical results for similar waters under dry weather conditions.
- Elevated nitrate levels found on the South Side of Glen Cove Road are likely due to leachate from on-site wastewater disposal systems.
- Elevated phosphate levels and total dissolved solids from samples collected at a tributary near the Town Highway Yard may be due to runoff from the Yard.
- Despite the presence of golf course lands, arboretum grounds and cultivated areas, the samples did not exceed the detection limit for the herbicide atrazine, indicating it is unlikely to be a concern in the Mill River watershed.

5.3 Friends of the Bay Water Quality Monitoring Program

Friends of the Bay's ongoing water quality monitoring program in the Oyster Bay/Cold Spring Harbor Complex was developed in cooperation with the U.S. Fish and Wildlife Service, the U.S. Environmental Protection Agency, the NYSDEC, local governments, and other volunteer monitoring groups around Long Island Sound. Under the ongoing monitoring program, every Monday morning from April through October, data is collected on water quality and ambient conditions at 19 sites throughout the harbor complex. Since 2007, Friends of the Bay has also collected quarterly water quality data at 10 stream and outfall monitoring locations within the watershed. Sampling in the estuary and the watershed is conducted consistent with the Standard Operating Procedures and Quality Assurance Project Plans (QAPPs) that were approved by the EPA in 2006 and 2007 for the open water and stream and outfall monitoring, respectively.





5.3.1 Open Water Body Monitoring

Figure 5-4 shows the 19 monitoring locations in the Oyster Bay/Cold Spring Harbor Complex. During the 28-week annual monitoring season, the parameters measured by Friends of the Bay including:

- Bacteria fecal coliform (since 2000) and enterococci (since 2004),
- Nutrients ammonia, nitrate/nitrite, total Kjeldahl nitrogen, total phosphorus,
- Salinity,
- Water clarity Secchi disk depth.

In addition to sample collection for these parameter, several environmental conditions are noted including the time the sample was collected; qualitative description of rainfall in the previous 24 hours; tidal stage on a scale of 1-4; air temperature; wind direction and speed; wave height (subjective, on a scale of 0-5); weather conditions (on a predetermined 1-6 scale); water color (subjective color, e.g. yellow-brown); cloud cover (0-5 scale); and any unusual conditions (i.e., odors, fish kills, debris).

5.3.2 Stream and Outfall Monitoring

In 2007, Friends of the Bay began collecting stream and outfall data from 10 major discharges into the estuary four times a year to complement the open water body monitoring program. The objectives of the stream and outfall monitoring program are to establish current baseline water quality conditions in the watershed, identify water quality impacts from potential point and non-point pollution sources, develop a water quality database to guide environmental decision-making, and measure the progress toward meeting water quality goals in the watershed.


The monitoring locations (*Figure 5-4*) include streams, ponds, an untreated sewage discharge, and a 'rotating' outfall that changes in an effort to identify other pollutant sources, based on a set of standard criteria. Samples are collected four times per year, with two of these monitoring events to occur following a period without precipitation ("dry weather" events), and the remaining two during precipitation events ("wet weather" events). The dry weather events are used to characterize background constituent inputs and potential dry weather issues such as illicit discharges, while the wet weather events provide information on pollutant concentrations and loadings associated with precipitation runoff.

Samples are analyzed for a variety of biological, chemical, and physical parameters including:

- Bacteria fecal coliform and escherichia coli (E. coli),
- Nutrients ammonia, nitrate/nitrite, total Kjeldahl nitrogen, total phosphorus,
- Chemical oxygen demand,
- Turbidity,
- Dissolved oxygen and temperature,
- Hardness,
- pH,
- Metals lead, copper, zinc.









5.3.3 Water Quality Trends

Results of the Friends of the Bay water quality monitoring from 1999 to 2008 have been documented in a series of annual reports. A 2008 summary report (Fuss & O'Neill, 2008) evaluated spatial and temporal trends in the water quality data generated through the 2006 monitoring season. The goals of the comprehensive analysis were to identify how water quality in the Oyster Bay/Cold Spring Harbor Complex has changed and the progress that is being made as a result of management efforts to address water quality problems in the estuary. The evaluation consisted of graphical and statistical analysis of the data, including non-parametric tests for trends in the bacteria and nutrient data collected from 2000 to 2006.


Based on the results of this evaluation, fecal coliform concentrations appear to be decreasing at many locations, and there is no indication of an increasing trend in fecal coliform concentrations at any of the 19 monitoring locations. These findings were made through visual analysis of the boxplots and confirmed by the trend analysis. Only two years of enterococci data were available for the analysis. Two key observations that emerged are: (1) in some locations the two indicator organisms sampled appeared to trend in different directions, with decreases in fecal coliform and increases in enterococci observed at the same monitoring locations (e.g., FB-13 and FB-15), and (2) where trends were present, there was an increase in enterococci. Given, that the enterococci data set is of limited duration compared to the fecal coliform data period of record, the identification of a trend in the enterococci concentrations at some locations should be viewed with caution and should be revisited with additional years of data. This result supports the need for on-going enterococci monitoring. Use of this indicator organism is encouraged because it is found exclusively in the intestinal tracts of warm-blooded animals, while coliform bacteria can originate from other sources including plant material, and because it is typically considered a more reliable indicator of health risk for contact recreation in marine waters (USEPA, 1986).


There are also spatial trends in microbial water quality. Generally, monitoring locations in the southern part of Oyster Bay Harbor (FB-7, FB-8, FB-10), the southern part of Cold Spring Harbor (FB-1 and FB-2), and landward in Mill Neck Creek (FB-15 and FB-17) exhibit consistently higher bacteria values, as shown in the boxplots in *Figure 5-5*, which summarize the data at each station for the entire period of record evaluated. In these locations, point and non-point sources are likely contributors to in-harbor water quality. This finding is also supported by the observed relationships with rainfall and tides. At many of the monitoring locations, there is a correlation between bacteria concentrations and/or nitrogen species concentrations and precipitation on the day of or day prior to sampling. Examination of indicator organism concentrations at various phases of the tidal cycle shows the influence of landside sources on water quality. In both Cold Spring Harbor and Oyster Bay Harbor, there are higher concentrations of bacteria at low tide, when there is less dilution from the incoming tide and inharbor water quality is more strongly influenced by inputs from runoff and streams discharging to the estuary.







Cold Spring Harbor






Oyster Bay Harbor





Mill Neck Creek






Figure 5-5. Indicator Bacteria Concentrations





The results of multi-year monitoring shows that in the Oyster Bay/Cold Spring Harbor Complex (1) there are correlations between nutrients and precipitation and (2) while the concentrations of ammonia show no trends or are decreasing, TKN and therefore organic nitrogen levels are increasing at some locations in the estuary. For example, in Oyster Bay Harbor, at FB-5, FB-6, FB-7, and FB-9, there is a decline in ammonia over the period of record, but there is an increasing trend in TKN, the result of increased organic nitrogen. This may reflect the input of organic nitrogen from sources such as runoff or atmospheric deposition or from sources within the estuary such as phytoplankton. Bronk et al. (1994) report that an estimated 25-41% of inorganic nitrogen (i.e., ammonia and nitrate/nitrite) taken up by phytoplankton is released and dissolved organic nitrogen. Since phytoplankton utilize ammonia, the decreased ammonia and increased TKN may reflect increased phytoplankton within the estuary system. In addition, sediment can act as both a source and sink of organic nitrogen.

The influence of the tides and precipitation should be considered in any temporal comparison of monitoring stations, as a direct comparison under different tidal/precipitation conditions requires adjustment of the data for these influences. Additional understanding of in-harbor water quality and the factors that influence water quality could be gained from targeted monitoring under clearly defined wet or dry weather conditions. Such sampling would both provide a snapshot of water quality under specific conditions and could be added to the long term water quality database.

The statistical analysis generally indicates that monitoring locations near the shore show higher concentrations of nutrients and bacteria, which suggests the influence of freshwater sources. Location FB-10 consistently exhibited lower water quality compared with other locations in the estuary. This has been noted in prior annual water quality reports, and the multi-year analysis demonstrates that this location is clearly impacted by a localized pollution source. This site is located near the outflow of Mill Pond and the Mill River, which supports a substantial population of waterfowl, and Beekman Creek, which flows under West Shore Road and the Beekman Beach parking lot and eventually discharges to the Mill River and Oyster Bay Harbor. It is suspected that the outflow of Mill Pond and the Mill River, including Beekman Creek, is contributing to elevated levels of bacteria and nutrients at FB-10.

5.4 Other Water Quality Monitoring

5.4.1 Long Island Sound Study – Sound Health 2008

The Long Island Sound Study (LISS) is a cooperative effort involving researchers, regulators, user groups and other concerned organizations and individuals. The LISS report *Sound Health 2008* provides information on water quality, the abundance of animal and plant life in the Sound, and trends in land use along the shore. The LISS divides Long Island sound into three (3) basins: Western, Central, and Eastern. The Oyster Bay/Cold Spring Harbor Complex





discharges to the Western Basin. The *Sound Health 2008* report uses three indices to rate basin conditions: water quality, sediment quality, and benthic quality. The Western Basin, with greater population density and weaker currents, is the most stressed of the three basins (LISS, 2008)

5.4.2 Shellfish Growing Area Sanitary Surveys

The NYSDEC conducts shoreline surveys of shellfish growing areas (SGAs) at least every 10 years to identify pollution sources that may be affecting SGAs. The Oyster Bay/Cold Spring Harbor Complex is divided into two SGAs, one consisting of Mill Neck Creek and Oyster Bay Harbor (SGA #47) and the other consisting of Cold Spring Harbor (SGA #48).

SGA #47 is approximately 5,040 acres. Of that area, approximately 785 acres are uncertified for shellfish harvesting and an additional 75 acres are seasonally certified (*Figure 5-6*). There are approximately 17 miles of shoreline within SGA #47, and NYSDEC maintains 42 sampling stations within the SGA. Thirty-eight (36) are located in Oyster Bay Harbor and seven (7) are located in Mill Neck Creek. A shoreline survey was completed in May 2002 and updated in 2003. *Table 5-4* summarizes the findings of the survey. The survey concluded that water quality is primarily affected by nonpoint source runoff. Waterfowl, wastewater treatment plant discharges, and improperly treated septic wastes from recreational vessels were identified as secondary pollution sources.


The total area of SGA #48 (Cold Spring Harbor) is approximately 4,640 acres with an uncertified area of approximately 190 acres located at the southern end of the harbor (*Figure 5-6*). Twenty (20) sampling stations are monitored by NYSDEC in SGA #48 (*Figure 5-6*). The shoreline in SGA #48 is over 9 miles, and surveys of the shoreline for potential pollution sources were conducted in 1988 and 2001. *Table 5-5* summarizes the findings of the survey. The sanitary survey found that the primary source of bacterial loading in Cold Spring Harbor is non-point source runoff and that this source is primarily concentrated a the southern end of the Harbor near the intersection of Routes 25A and 108 and from the stormwater drainage system serving the Village of Cold Spring Harbor. Waterfowl and discharges from recreational vessels were determined to be insignificant.

5.4.3 Nassau County Department of Public Health Beach Monitoring

Each beach season, samples for bacteria testing are collected by the Nassau County Department of Health (NCDH) with assistance from the Town of Oyster Bay at four active beaches in the Oyster Bay/Cold Spring Harbor Complex: Laurel Hollow Beach, Theodore Roosevelt Beach, West Harbor Beach, and Centre Island Bay Beach (Wendolovske, pers. comm., 2009). Samples are also collected at Beekman Beach, although the beach is no longer an approved public bathing beach. On average, samples are collected twice a week with additional sampling conducted in the event of a closure. These bacteria samples are analyzed at the NCDH laboratory, currently for fecal coliform and enterococci, in conformance with beach closure standards that were implemented in 2004. In addition to beach closings based on









bacteria sample results, NCDH instituted pre-emptive or administrative beach closings following rain events that exceed a threshold level and duration of precipitation. During the 2008 beach season, that threshold was ½ inch of rain or more. In 2008, the beaches in the harbor complex were closed pre-emptively for nine days due to rain events. The beach closings occurred on 6/15, 7/24, 7/28, 8/6, 8/8, 8/12, 8/15, 8/16, and 8/31, based on a threshold of ½-inch of precipitation over a 24-hour period (Wendolevske, pers. comm., 2009).

5.4.4 Nassau County Groundwater Monitoring

The Nassau County Department of Public Works has been monitoring groundwater quality and quantity in the County since the 1930s. Currently, the County monitors a network of 5,000 monitoring wells for groundwater quality, water elevations, and potentiometric head in the deeper aquifers (Nassau County DPW, 2005). There are several monitoring wells located in the Oyster Bay/Cold Spring Harbor Complex watershed used to monitor water levels in the Upper Glacial, Lloyd, and Magothy aquifers as well as volatile organic compounds (VOCs), pesticides, perchlorate, the gasoline additive methyl tertiary butyl ether (MBTE), and pharmaceuticals.

The 2005 report entitled Nassau County Groundwater Monitoring Program 2000-2003 With Historical Information (Nassua County DPW, 2005) concluded that raw groundwater quality throughout the County is improving due to the installation of sanitary sewers and the implementation and enforcement of regulatory programs governing the use, storage and disposal of hazardous substances and that annual water demand has been increasing in recent years. Saltwater intrusion is present in the watershed, as the monitoring wells illustrate saltwater intrusion has occurred at localized areas in Bayville and in Centre Island. As a result of the saltwater intrusion, portions of the Lloyd, North Shore, and Upper Glacial aquifers have become unusable for public water supply purposes. Saltwater intrusion along the north shore of Long Island is driven by groundwater withdrawal from public supply wells located near the shoreline.

MTBE was detected at levels of 2 to 10 parts per billion (ppb) in a monitoring well in the Upper Glacial aquifer located in the Mill Neck Creek watershed during the period 1995-1999. It was not detected at monitoring wells within the watershed during 2000-2003. This is consistent with the larger finding by the Nassau County DPW that there is not widespread MBTE contamination in the County's groundwater. There were no detectable levels of pesticides or perchlorate in monitoring wells within the watershed sampled in 2001-2003, and no detectable levels of pharmaceuticals in monitoring wells within the watershed sampled in 2002-2003. Although VOCs were detected at levels of >5 to 10 ppb in 1985-1987 in monitoring wells located in Cove Neck in the Oyster Bay Harbor subwatershed, concentrations of Total VOCs in monitoring wells in the Upper Glacial, Lloyd, and North Shore Aquifers within the watershed during 2000-2003 were at concentrations ranging from below detection limit to 5 ppb. This finding is consistent with the general conclusion that raw water quality in Nassau County is improving with respect to VOCs (Nassau County DPW, 2005).





5.4.5 Subwatershed Illicit Discharge Detection and Hot Spot Investigations

As part of their compliance with the National Pollution Discharge Elimination System (NPDES) Phase II requirements and as part of a stormwater runoff impact analysis, Nassau County initiated illicit discharge detection and elimination surveys in the Oyster Bay/Cold Spring Harbor Complex watershed in 2006, and six have been completed to date (Bailey Arboretum, Francis Pond, Kentuck Brook, Mill River, Tiffany Creek, Whites Creek). One goal of the investigations was to identify "hot spots" or illicit discharges. Hot spots are land uses that are known to have a high potential for pollutant discharge. Illicit discharges are locations were unpermitted discharges outfall into the stream. The investigations found potential hot spots and/or illicit discharges in the Mill River and Whites Creek subwatersheds. In the Mill River subwatershed, the Town of Oyster Bay Highway Yard on Lake Avenue, a golf course along Mill River Road, and commercial businesses on State Route 25a were identified as having the potential to be hot spots or illicit discharges (Cashin Associates, P.C., 2007). Numerous potential hot spots were also identified in the Whites Creek subwatershed. These included a petroleum bulk station, railroad car terminal/storage yard, multiple auto repair and service stations, boat storage and repair shops, gas stations, and parking lots (Cashin Associates, P.C., 2007).

Table 5-4. Sampling Stations and Pollution Sources in Oyster Bay Harbor, SGA #47

Station Number	Location & Pollution Source(s) Monitored A = Actual P = Potential	Type(s) of Pollution Source(s) PT = Point NP = Non-Point
1	On closure line, near buoy C "19" in channel to boat ramp. Effects of runoff from boat ramp and outflow from Mill Pond at Beekman Beach A & P	Indirect, NP
1A	Near shore (Beekman Beach) effect of outflow from Mill Pond, west of former Jakobsen Shipyard A & P	Direct, PT (Mill Pond outflow) Indirect, NP (runoff to/waterfowl in Mill Pond)
2	Near buoy C "15" off Brickyard Point, general water quality in certified area SW section of OB Hbr. P	Indirect, NP
3	Near shore, outflow from unnamed cove, north of Brickyard Point; runoff from residential property P	Indirect, NP
4	Near shore, off long dock at just north of Cleft Road. Effect of non-point runoff from West Shore Road P	Indirect, NP (runoff)
5	Near shore, effects of non-point runoff from West Shore Road P	Indirect, NP
6	Off shore, mid-harbor. General water quality in the certified area of West Harbor P	Indirect, NP
7	Near shore, off the NW point of Centre Island peninsula, runoff from residential property P	Indirect, NP
8	Off shore, mid-harbor. General water quality in the certified area of West Harbor P	Indirect, NP
9	On south end of seasonal closure line outside Mill Neck Creek. Effects of outflow from M N Crk A & P	Direct, PT (Mill Neck Creek mouth)/ Indirect, NP (runoff into M N Creek)
10	In seasonal closure, effects of drainage from wetlands south of West Harbor Road and effects of outflow from Mill Neck Creek A & P	Direct PT (wetlands runoff & Mill Neck Creek)/ Indirect, NP (runoff into wetlands & Mill Neck Creek)
11	Off shore, effects of outflow from Mill Neck Creek and potential effects of cesspool at Mill Neck Rod & Gun Club P	Indirect, NP



Table 5-4. Sampling Stations and Pollution Sources in Oyster Bay Harbor, SGA #47

Station Number	Location & Pollution Source(s) Monitored A = Actual P = Potential	Type(s) of Pollution Source(s) PT = Point NP = Non-Point
12	Off shore, mid-harbor. General water quality in the certified area of West Harbor. Potential effects of large # of occupied boats summer weekends	Direct, NP (summer boat discharges) Indirect, NP (rest of the year)
13	Near shore, off Town of Oyster Bay Centre Island Beach. <u>Potential</u> effects of bathers, runoff; and, large number of occupied boats summer weekends P	Indirect, NP
13A	Near shore, north end of West Harbor at mouth of private canal on Centre Island. Potential effects of large # of occupied boats summer weekends P	Indirect, NP Direct, NP (summer boat discharges)
14	Near shore, off long dock for a residence on Centre Island. Potential effects of large # of occupied boats summer weekends P	Direct, NP (summer boat discharges) Indirect, NP (rest of year)
15	Near shore, near "split rock" on beach. Potential effects of large # of occupied boats summer weekends	Direct, NP (summer boat discharges) Indirect, NP (rest of year)
16	Near buoy N Red "12" south of Brickyard Point, middle of east-west boat channel and just north of closed area around STP outfall & boat moorings P	Indirect, NP
17	Off shore, in uncertified area around closed area around STP outfall & boat moorings (summer) A & P	Indirect, PT (STP outfall) and NP (runoff from Oyster Bay village)
18	Near buoy N Red "8" south of Brickyard Point, middle of east-west boat channel and just north of closed area around STP outfall & boat moorings P	Indirect, PT (STP outfall) and NP (runoff from Oyster Bay village)
19	Near buoy Red N "6" southeast of Moses Point P	Indirect, NP
20	Near buoy JB "B" south of Moses Point, just north of closed area around STP outfall & boat moorings A&P	Indirect, PT (STP outfall) and NP (runoff from Oyster Bay village)
21	Near buoy Red N "4" in commercial channel to fuel depot & marinas. Within the uncertified area around STP outfall & boat moorings A & P	Direct, PT (STP outfall) and Indirect, NP runoff from village
22	Near shore, near buoy C "7" in commercial channel to fuel depot & marinas. Within the uncertified area around STP outfall & boat moorings A & P	Direct, PT (STP outfall) and Indirect, NP runoff from village
	Near shore at STP outfall site. Effects of STP outfall and stormwater runoff from Whites Creek and village business district, end of South Street A & P	Direct, PT (STP outfall) and Indirect, NP runoff from village
23	Near shore, off long fixed dock at a residence east of Steamboat Landing Road. Within uncertified area around STP outfall & boat moorings. Potential effects of runoff from road end. P	Indirect, NP (runoff from road end)
24	Off shore, along closure line at east side of the uncertified area around STP outfall & moorings. Potential effects of discharges from occupied boats in summer weekend anchoring area P	Indirect, NP & Direct, NP (boat discharges, summer months)
25	Off Roosevelt Breakwater (stone jetty) northeast side of Oyster Bay Cove. Along the seasonal closure line. Potential effects of discharges from occupied boats (summer months) & runoff into OB Cove A & P	Indirect, NP & Direct, NP (boat discharges)
26	Near shore, off small boat house on Cove Neck P	Indirect, NP
27	Near shore, off large estate property on Cove Neck P	Indirect, NP
28	Near shore, at Cove Point. General water quality in the certified area. P	Indirect, NP



Table 5-4. Sampling Stations and Pollution Sources in Oyster Bay Harbor, SGA #47

Station Number	Location & Pollution Source(s) Monitored A = Actual P = Potential	Type(s) of Pollution Source(s) PT = Point NP = Non-Point
29	Off shore, near buoy Green "5" between Cove Point and Plum Point. General water quality in the certified area.	Indirect, NP
30	Near shore, at buoy Red N "4" east of Plum Point. General water quality in outer Oyster Bay Harbor P	Indirect, NP
31	Off long dock at Sewanhaka-Corinthian YC, on closure line for sewage outfall from YC. A & P	Direct, PT (sewage outfall) & Indirect (boats in S-C YC mooring area)
32	Near shore off long dock for residences on Centre Island. Potential effects of discharges from occupied yacht/sailboats in S-C YC anchorage P	Indirect, NP (boats in YC mooring area)
33	Near shore, off small group of residences along shoreline (Morgan Place & Roosevelt Drive). Potential effects of cesspools & road runoff P	Indirect, NP
C-1	Near shore at Weeks Point, along west end of seasonal closure line. Potential effects of runoff to Oyster Bay Cove & discharges from occupied boats in/outside OB Cove. (summer months) P	Indirect, NP
	Same as Sta. #25. Sampled as C-2 when evaluating w/q in Oyster Bay Cove for Conditional program P	Indirect, NP & Direct, NP (boat discharges)
C-3	Near shore in seasonally (November - April) certified area in Oyster Bay Cove. Potential effects of runoff from Cove Neck Road. P	Indirect, NP (runoff)
C-4	Near shore in the uncertified portion of Oyster Bay Cove, quite shallow. Potential effects of road runoff and discharge from Tiffany Creek. A & P	Indirect, NP (runoff)
C-5	Tiffany Creek at Cove Neck Road. Assess w/q in Tiffany Crk. when establishing conditional programs in OB Cove. Station not used in many yrs. A & P	Direct, PT (NP runoff into Creek)

Table 5-5. Sampling Stations and Pollution Sources in Cold Spring Harbor, SGA #48

Station Number	Location & Pollution Source(s) Monitored A = Actual P = Potential	Type(s) of Pollution Source(s) PT = Point NP = Non-Point
1	Near shore, at Cooper Bluff; general water quality in outer harbor area, land runoff below bluff P	Indirect, NP
2	Off shore, mid-harbor; general water quality in outer harbor area P	Indirect
3	Near shore, off West Neck Beach pavilion; potential effects of septic systems serving beaches, bathers P	Indirect, NP
3.1	Outflow from Smugglers Cove, runoff into Cove P	Indirect, PT (outflow from Cove)/NP land runoff into cove
4	Off shore, mid-harbor; general water quality in outer harbor area P	Indirect
5	Mouth of unnamed inlet at private residence P	Direct from inlet, NP
6	Off shore, mid-harbor; general water quality in outer harbor area P	Indirect
7	Near shore, runoff P	Indirect, NP
8	Near shore, near rock jetty, runoff P	Indirect, NP
9	Off shore, mid-harbor; general water quality in souther portion or Cold Spring Harbor P	Indirect





Table 5-5. Sampling Stations and Pollution Sources in Cold Spring Harbor, SGA #48

Station Number	Location & Pollution Source(s) Monitored A = Actual P = Potential	Type(s) of Pollution Source(s) PT = Point NP = Non-Point
10	General water quality near Harbor mouth P	Indirect, NP
11	Near mouth of marina boat basin, in uncertified area potential effects of boats & outflow from inner Cold Spring Harbor uncertified area A & P	Indirect, NP; Direct (boats) NP
12	Just east of south end of closure line, in uncertified area. Off white house on CSH Labs property. Potential effects of outflow from inner CSH uncertified area A & P	Indirect, NP
13	Off eastern tip of sand spit, north of boat ramp. Effects of runoff from ramp and Route 25A, boats and marina in inner harbor uncertified area A&P	Direct, NP
13.1	In uncertified cove north of station 13, effects of outflow from ponds at Spring Road and runoff from Cold Spring Harbor village roads A & P	Direct, PT (pond outflow); NP (runoff from roads)
14	West of Town fishing dock, within boat mooring area potential effects of runoff, marina and boats A&P	Direct, PT (boats); Indirect, NP (runoff)
15	Near shore, former discharge from small STP serving CSH Labs. Discharge ceased 1992. Station monitors w/q effects of runoff and freshwater inflow from ponds south of Route 25A, near hatchery	Indirect, NP (runoff)
21	Near fixed navigation aid , general water quality in outer harbor area P	Indirect
22	Near buoy Red N "2", general water quality in outer harbor area P	Indirect
23	Near buoy Gong "1", general water quality in outer harbor area, near boundary with SGA #34, P	Indirect



6 Watershed Modifications

6.1 Dams and Impoundments

There are several small dams and impoundments in the Oyster Bay/Cold Spring Harbor Complex watershed, which are used primarily for recreational purposes. According to the NYSDEC Dam Safety Regulations, a dam's hazard classification is based on the height of the dam, its maximum impoundment capacity, physical characteristics of the dam site, and location of downstream facilities. *Figure 6-1* shows the location and hazard classification of each of the eight dams within the watershed; all dams are a rated a low hazard. Mill Pond Dam is owned by the Nassau County Department of Public Works and the others are privately owned. Mill Pond Dam creates an approximately 6-acre impoundment. The lands beneath the impoundment are part of the Oyster Bay National Wildlife Refuge.

In addition to recreational opportunities, these impoundments also provide aquatic and wildlife habitat. Some of the dams, as well as culverts and other obstructions, are potential barriers to fish passage. As described in Section 4.7 of this report, the Long Island Chapter of Trout Unlimited, Environmental Defense, and Friends of the Bay recently completed fish passage feasibility studies to evaluate restoration of diadromous fish to the Mill River and other areas of the harbor complex watershed by installing fish ladders or removing Mill Pond Dam and other obstructions.

6.2 Water Supply


Groundwater aquifers supply drinking water to all of Long Island. Long Island's drinking water system was designated as the nation's first Sole Source Aquifer. To protect these groundwater aquifers, the state designated nine Special Groundwater Protection Areas (SGPAs), as defined in Article 55 of the NYS Environmental Conservation Law. The Oyster Bay SGPA is one of two such state-designated aquifer recharge areas in Nassau County. The Town of Oyster Bay has an Aquifer Protection Overlay District (APO) in addition to the SGPA, adopted in 2004, which affords added protection to groundwater resources.

The Town of Huntington contains portions of two SPGAs, only one of which (West Hills/Melville in the western part of the Town) is located within the Oyster Bay/Cold Spring Harbor Complex watershed. Most of the Town of Huntington's public water supply wells are located outside of SPGAs. Unlike the Town of Oyster Bay, Huntington has not enacted aquifer protection overlay district regulations.

Public water is supplied within the Oyster Bay/Cold Spring Harbor Complex watershed by the Jericho Water District, Village of Bayville, City of Glen Cove, Oyster Bay Water District, Locust Valley Water District and several private wells on Cove Neck and Centre Island. In Suffolk County, there are eleven wells that service the watershed within the Village of Lloyd Harbor, West Hills, Cold Spring Harbor and Huntington. *Figure 6-2* shows the locations of public water supply wells and the approximate limits of SGPAs within the watershed.








0.5

Miles







6.3 Wastewater

Oyster Bay Hamlet and portions of the Unincorporated Villages of Upper Brookville are served by sanitary sewers that transport sanitary waste to the Oyster Bay District Sewage Treatment Plant (OBDSTP). The treatment plant is located in Oyster Bay Hamlet and discharges treated effluent to Oyster Bay Harbor east of the Mill River outlet. The treatment plant operates under a State Pollution Discharge Elimination System permit with a maximum treatment capacity of 1.8 million gallons per day (MGD). The plant currently averages 1.25 MGD. The OBDSTP serves an area (*Figure 6-3*) of approximately 975 acres, with approximately 20 miles of sewer lines and 2,000 individual service connections (Ryan & Ryan PR, Inc., 1999). All facilities within the sewer service area must be connected to public sanitary sewers, and existing on-site sewage disposal systems, such as septic tanks or cesspools, must be properly abandoned according to the Nassau County Department of Public Works and Department of Health guidelines (Cashin Associates, P.C., 2007).

The OBDSTP has been in service since 1926 and has been upgraded several times. The most recent upgrade occurred in 2006 to provide advanced treatment for nitrogen removal. Nitrogen has been identified as the primary pollutant causing low dissolved oxygen conditions, or hypoxia, occurring throughout much of Long Island Sound's bottom waters each summer. Wastewater treatment plants that discharge directly to the Sound or into inland surface waters that reach the Sound are a significant contributor of nitrogen. To address this water quality problem, NYSDEC imposed limits to reduce nitrogen discharged from the 12 municipal treatment plants located on the north shore of Long Island. NYSDEC issued a revised discharge permit that required the OBDSTP to reduce nitrogen discharged to Oyster Bay from the treatment plant by 63.8 percent in three 5-year increments by August 2014. According to the Friends of the Bay 2007 and 2008 Annual Water Quality Report, the OBDSTP's new advanced treatment facility is already achieving the 2014 nitrogen limits imposed by NYSDEC permit. The upgrade has reduced the daily nitrogen discharged by as much as 75%.

Sanitary sewers in the southeastern portion of the watershed collect and convey waste to wastewater treatment plants on the South Shore of Long Island operated by the Nassau County Department of Public Works.

A second wastewater treatment plant in the harbor complex watershed is located west of Plum Point on Centre Island. This privately-owned plant, Seawanhaka STP, operates primarily in the summer months to process waste during the boating season. *Table 6-1* identifies the OBDSTP and the Seawanhaka STP, as well as other facilities with NYSDEC State Pollution Discharge Elimination System (SPDES) permits in the Oyster Bay/Cold Spring Harbor Complex watershed. *Figure 6-4* also depicts the locations of these facilities within the watershed.










Table 6-1. Facilities in the Oyster Bay Watershed with SPDES Permits

Facility	Town	Facility Type
Commander Terminal	Oyster Bay	Petroleum Bulk Station and Terminal
Mill-Max Manufacturing Corp.	Oyster Bay	Electronic Connector Manufacturing
MTA LIRR Oyster Bay Yard	Oyster Bay	Railroad
Oyster Bay Water Pollution Control Plant	Oyster Bay	Sewerage System
Seawanhaka-Corinthian Yacht Club Property	Oyster Bay (Centre Island)	Sports and Recreation Club
County Parkland	Huntington	
Cold Spring Harbor Terminal*	Cold Spring Harbor	Petroleum Bulk Station and Terminal

Source: EPA Water Permit Compliance System (PCS) database and NYSDEC. SPDES: New York State Pollutant Discharge Elimination System


The Birches (also known as Continental Villas) is a residential subdivision located on the west side of Oak Neck Creek, in the Locust Valley area. This subdivision historically operated its own sewage treatment system, which suffered chronic problems due to cesspool overflows and inadequate treatment of waste, impacting low-lying wetlands and the adjacent creek. In an attempt to address these issues, a contact chlorine treatment system was installed which disinfects the wastewater by adding chlorine prior to discharging to Oak Neck Creek. The treatment system did not fully address the problem, as elevated coliform bacteria concentrations in the harbor persisted near this location. Failing and/or low-functioning individual on-site sewage disposal systems located in this area are also believed to have contributed to these chronic problems. A groundbreaking occurred in April 2009 for long-awaited upgrades to sewer and water infrastructure to connect the homes in the Birches residential subdivision to the Glen Cove sewage treatment plant. This project will eliminate chronic cesspool overflows to Mill Neck Creek.

In October 2008, the Oyster Bay/Cold Spring Harbor Complex was declared a federal No-Discharge Zone (NDZ) for vessel sewage, regulated under Section 312 of the Clean Water Act. The designation prohibits the discharge of sewage (whether treated or untreated) from vessels, providing an additional level of protection to address water quality issues associated with sewage contamination in marine waters.

The remainder of the Oyster Bay/Cold Spring Harbor Complex watershed is served by individual on-site sewage disposal systems, including cesspools and septic tank systems. Cesspools were the most common method of on-site sewage disposal until about 1973, when the local development regulations were modified to require the use of sanitary sewers. Cesspools are essentially underground chambers with perforated walls through which wastewater leaches into the soil. Cesspools receive untreated sanitary waste, including both liquid and solid materials, and are therefore are susceptible to clogging. Septic tanks are typically

^{*} Although still listed in the database, the Cold Spring Harbor Terminal bulk storage tanks have been removed.







installed prior to a cesspool in order to settle out the heavier solids before entering the leaching system and prolong the life of the system. Further treatment of wastewater occurs in the soil below the leaching system, the effectiveness of which is strongly influenced by groundwater and soil conditions.

Cesspools and septic systems are a potential source of pollution, including nitrogen, pathogens, and other contaminants, to surface waters and groundwater as a result of system failure (inadequately treating sewage or by creating potential for direct or indirect contact between sewage and the public) or malfunction (typically a slow loss of function that is difficult to detect). Since a large portion of the watershed was developed prior to 1973, failure or malfunction of cesspools and septic systems is believed to be a significant source of pollution to surface water and groundwater.

6.3 Stormwater Infrastructure

The stormwater collection and drainage system within the harbor complex watershed consists of drainage infrastructure operated and maintained by the watershed municipalities, including the Town of Oyster Bay, the Town of Huntington, the associated villages, and Nassau and Suffolk Counties. Nassau and Suffolk County are responsible for the drainage infrastructure associated with county roadways. All of these municipal entities are regulated small Municipal Separate Storm Sewer Systems (MS4s) under the NYSDEC State Pollution Discharge Elimination System Phase II stormwater program.

Stormwater within the watershed is discharged to surface waters and to groundwater. A large portion of the watershed drains to surrounding surface waters. The stormwater drainage systems in selected areas of the watershed are described in the stormwater runoff impact analysis subwatershed reports prepared on behalf of Nassau County (Cashin Associates, P.C., October 2007) and in the Stormwater Management/Coastal Water Quality Improvement component of the Oyster Bay/Cold Spring Harbor Complex Harbor Management Plan (Cashin Associates, P.C., 2002). Outfall surveys performed by Nassau County and the Town of Oyster Bay to meet Phase II stormwater program requirements identified stormwater outfalls throughout the watershed, including numerous stormwater outfalls that discharge directly to the harbor complex (*Figure 6-4*). Note that information regarding stormwater outfalls was unavailable from the Town of Huntington as of the preparation of this report.

Artificial infiltration of stormwater runoff by use of basins or sumps has been practiced on Long Island since the 1930s to recharge collected stormwater back to the groundwater system. In the 1950s, Nassau and Suffolk Counties adopted regulations requiring stormwater to be retained and infiltrated onsite. Subsequently, the use of drywells, recharge basins, and drainage reserve areas became common practice to retain and infiltrate stormwater runoff from roadways in residential, commercial, and industrial areas. Recharge basins are most prevalent in eastern Nassau County and western Suffolk County. Most of these facilities have overflow structures that direct stormwater resulting from extreme rainfall events to either other recharge basins or to drainage facilities that ultimately discharge to surface waters. Figure 6-4 shows the existing recharge basins within the Nassau County portion of the harbor complex watershed (note that information regarding recharge basins in the portion of the watershed within Suffolk County was unavailable as of the preparation of this report). Overall, there are approximately 70





recharge basins in the watershed in Nassau County. According to the Nassau County Storm Water Management Program, nearly half of the land area of Nassau County is serviced by recharge basins (Nassau County DPW, 2003).

Since much of the watershed was developed prior to the adoption of stormwater quality regulatory requirements, most of the existing drainage infrastructure that does not discharge to recharge basins consists of traditional storm drains/catch basin and storm pipes that discharge directly to surface waters without treatment, other than detention to maintain peak rates of discharge. As described in Section 7.1.4, uncontrolled stormwater runoff from impervious surfaces is a significant source of potential impacts to surface waters within the harbor complex watershed, groundwater supplies, and the water quality of the harbor complex itself. Through their Phase II stormwater management programs and other planning initiatives, the watershed municipal entities, including Nassau and Suffolk Counties, have developed and implemented a variety of Best Management Practices to address stormwater quality and quantity issues associated with land development and redevelopment projects. The municipalities have also begun to address historical development and nonpoint source pollution impacts in the watershed by identifying potential sites for stormwater retrofits. However, stormwater runoff continues to be a significant threat to the water quality and overall health of the Oyster Bay/Cold Spring Harbor Complex and its watershed.

6.4 Other Regulated Sites

Historical and current industrial and commercial activities within the harbor complex watershed pose a potential threat to surface waters and groundwater supplies. Illegal waste disposal, improper use and disposal of chemicals such as used oil, pesticides, and herbicides, and chemical spills are potential sources of contaminants from industrial and commercial facilities. As summarized in *Table 6-2* and shown in *Figure 6-5*, several hazardous waste generators and other regulated sites are located within the watershed. These facilities are generally located in the more densely developed commercial and industrial areas of the Towns of Oyster Bay and Huntington, primarily in the central and southeastern portions of the watershed.

Table 6-2. Regulated Sites


O: -	Number of Sites in OB/CSH Watershed			
Site Types	Oyster Bay	Huntington	Glen Cove	
Hazardous Waste Generators	94	27	0	
Air Emissions	19	4	0	
Remediation Sites	3	0	0	

Source: EPA RCRAInfo (EPA and State Treatment, Storage, Disposal facilities), Air Facility System (AFS), and Superfund National Priorities List (NPL).

There are three NYSDEC-regulated remediation sites located within the watershed, all within the Town of Oyster Bay. The Bayville Village Cleaners, located in the western portion of the watershed, is being remediated under the NYSDEC Voluntary Cleanup Program.









The Mill Neck Marina located on Mill Neck Creek (northern portion of the watershed). The site is designated by the NYSDEC as a Class 2 site, meaning that the disposal of hazardous waste has been confirmed and the presence of such hazardous waste or its components or breakdown products represent a significant threat to the environment.

The third site is the former Jakobsen Shipyard, which is a six-acre site bordered on the north by Oyster Bay Harbor and in close proximity to Beekman Beach and Theodore Roosevelt Memorial Park on the west and east respectively. This State Superfund site was once highly contaminated with metals and other pollutants, but has been remediated and has been partially redeveloped as a passive waterfront park owned jointly by the Town and the State.





7 Land Use and Land Cover

The type and distribution of land use and land cover within a watershed has a direct impact on nonpoint sources of pollution and water quality. This section describes the current and potential future land use and land cover patterns in the harbor complex watershed, and the implications for water quality.

7.1 Current Conditions

7.1.1 Land Use

Figure 7-1 depicts general land use patterns in the Oyster Bay/Cold Spring Harbor Complex watershed. The land use information in Figure 7-1 is a combination of parcel-based land use GIS data provided by the Town of Oyster Bay and land use derived from the Town of Huntington's Comprehensive Plan July 2008 Draft (Town of Huntington, 2008). Land use categories and associated acreage within the watershed are provided in Table 7-1.

The watershed's predominant land use (approximately 64%) is low-density residential. Approximately 10.3% of the watershed is considered open space, including conservation land and public parks. Land classifies as "open space" in the Town of Huntington consists of both undeveloped land and recreational parks. Land classified as "vacant" by the Town of Oyster Bay accounts for approximately 4.8% of the watershed area. The vacant land in Oyster Bay is a mixture of undeveloped parcels and forested areas. Transportation land use, including local and county roads and highways, comprises approximately 7% of the watershed land area.

Table 7-1. Watershed Land Use


Land Use Category	Acres	Percent of Watershed
Agriculture	96	0.4%
Commercial	368	1.5%
Industrial	16	0.1%
Residential	15949	63.9%
Transportation (3, 4)	1756	7.0%
Public Services (1)	131	0.5%
Recreation And Entertainment (1)	964	3.9%
Vacant Land (1,5)	1206	4.8%
Wild, Conservation Lands and Public Parks (1)	1490	6.0%
Community Services (1)	1911	7.7%
Institutional (2)	5	0.0%
Open Space (2)	1064	4.3%
Utilities (2)	9	0.0%
Water (2)	12	0.0%

Notes: (1) Category for Town of Oyster Bay land use only.

- (2) Category for Town of Huntington land use only.
- (3) Transportation land use for in the Town of Huntington was estimated by buffering roads included in the Census 2000 Tiger Road file.
- (4) Transportation land use in the Town of Oyster Bay was estimated as the area between parcels bordered by roads.
- (5) Some parcels in the Town of Oyster Bay were unclassified and determined to be vacant land based on aerial orthophotography.









Commercial land use accounts for less than 2% of the watershed area, with the majority of the commercial areas concentrated in Oyster Bay Hamlet and along the Route 106/Pine Hollow Road/South Street corridor. Other isolated commercial areas are located along Forest Avenue in Locust Valley, in Laurel Hollow near the head of Cold Spring Harbor, along Main Street in Cold Spring Harbor, and along Jericho Turnpike in Woodbury and West Hills. Current and former industrial land use account for a small percentage of the watershed area (0.1%) and are located primarily along the Oyster Bay waterfront and Oyster Bay Hamlet.

7.1.2 Zoning


Figure 7-2 depicts the generalized existing zoning in the Oyster Bay/Cold Spring Harbor Complex watershed, which is based on a compilation of zoning districts and designations established by the various municipal entities in the watershed. The specific zoning districts across the watershed are highly variable because they are defined at the village or town level. For this reason, the village-defined zoning designations were grouped into the generalized zoning designations shown in Figure 7-2, including business, recreation, industrial, office, multifamily residential, and single-family residential. The pattern of existing zoning largely reflects the existing pattern of residential, commercial, office, and industrial uses. The majority of the harbor complex watershed is zoned single-family residential. Figure 7-3 depicts the minimum lot size required in each residential zoning district based on the village-specific zoning. Minimum residential lot sizes vary from less than a quarter acre to over 5 acres.

7.1.3 Land Cover


Figure 7-4 depicts the generalized land cover in the harbor complex watershed. The data shown in Figure 7-4 are land cover types derived from 2002 Landsat satellite imagery with ground resolution of 30 meters. The land cover data in the watershed are summarized into eleven categories (*Table 7-2*). These ten categories are those used in the Connecticut Land Cover Map Series and are described following the table (University of Connecticut Center for Land Use Education and Research).




















Table 7-2. Watershed Land Cover

		1985	2	002	Relative Change in	Relative
Land Cover Type	Acres	Percent of Watershed	Acres	Percent of Watershed	Percent of Watershed (%) ¹	Change in Acreage (%) ²
Deciduous Forest	9,500	39.0	9,068	37.2	-1.8	-5
Developed	7,175	29.5	7,455	30.6	1.1	4
Turf/Grass	3,439	14.1	3,661	15.0	0.9	6
Coniferous Forest	2,039	8.4	1,999	8.2	-0.2	-2
Other Grasses	561	2.3	683	2.8	0.5	22
Agriculture	559	2.3	524	2.2	-0.1	-6
Water	450	1.8	465	1.9	0.1	3
Barren	274	1.1	142	0.6	-0.5	-48
Tidal Wetland	250	1.0	247	1.0	0.0	-1
Forested Wetland	101	0.4	102	0.4	0.0	2
Non-forested Wetland	8	< 1	10	< 1		

¹Calculation = % land cover 2002 - % land cover 1985

- Barren Mostly non-agricultural areas free from vegetation, such as sand, sand and
 gravel operations, bare exposed rock, mines, and quarries. Also includes some
 urban areas where the composition of construction materials spectrally resembles
 more natural materials. Also includes some bare soil agricultural fields.
- Coniferous Forest Includes Southern New England mixed softwood forests. May include isolated low density residential areas.
- Deciduous Forest Includes Southern New England mixed hardwood forests. Also includes scrub areas characterized by patches of dense woody vegetation. May include isolated low density residential areas.
- Developed High density built-up areas typically associated with commercial, industrial and residential activities and transportation routes. These areas contain a significant amount of impervious surfaces, roofs, roads, and other concrete and asphalt surfaces.
- Forested Wetland Includes areas depicted as wetland, but with forested cover. Also includes some small watercourses due to spectral characteristics of mixed pixels that include both water and vegetation.
- Non-forested Wetland Includes areas that predominantly are wet throughout most
 of the year and that have a detectable vegetative cover (therefore not open water).
 Also includes some small watercourses due to spectral characteristics of mixed
 pixels that include both water and vegetation.



²Calculation = (acres land cover 2002 - acres land cover 1985) / acres land cover 1985 Source: University of Connecticut's Center for Land Use Education and Research (CLEAR)



- Other Grasses and Agriculture Includes non-maintained grassy areas commonly found along transportation routes and other developed areas and also agricultural fields used for both crop production and pasture.
- Turf & Grass A compound category of undifferentiated maintained grasses associated mostly with developed areas. This class contains cultivated lawns typical of residential neighborhoods, parks, cemeteries, golf courses, turf farms, and other maintained grassy areas. Also includes some agricultural fields due to similar spectral reflectance properties.
- Utility Includes utility rights-of-way. This category was manually digitized onscreen from rights-of-way visible in the Landsat satellite imagery. The class was digitized within the deciduous and coniferous categories only.
- Water Open water bodies and watercourses with relatively deep water.

A comparison of watershed land cover data between 1985 and 2002 (*Table 7-2*) shows a minor increase in watershed development during this period (4% increase in developed cover types) and a corresponding loss of coniferous (2% decrease) and deciduous forest (5% decrease). There was a significant percentage loss of barren land cover and percentage increase in other grasses; however these land cover categories comprise a very small percentage of the watershed area and could reflect construction or agricultural activity at the time the satellite data was obtained.

The harbor complex watershed is characterized by roughly equal amounts of forested land cover and developed land cover. These land cover types are described below.

Forest Cover

Approximately 45% of the watershed consists of deciduous and coniferous forest cover, which is associated with open space and wooded portions of low-density residential properties. *Table 7-3* compares the total acres and percent forest cover by subwatershed. The percent forest cover in each subwatershed ranges from approximately 15% in the White's Creek subwatershed to approximately 65% in the Tiffany Creek subwatershed.

Based on literature threshold values documented in several studies (CLEAR, 2007), watershed forest cover of 65% or greater is typically associated with a healthy aquatic invertebrate community. Only one of the fourteen subwatersheds, Tiffany Creek, meets or exceeds this threshold value of 65%. Based on a recommendation of the American Forests organization, 40% forest cover is a reasonable threshold goal for urban areas. Although the harbor complex watershed, as a whole, is above this threshold value, several of the subwatersheds, Centre Island (31%), Cold Spring Brook (37%), Kentuck Brook (39%), Mill Neck Creek (30%), and Upper White's Creek (33%), are below this threshold, with White's Creek significantly below the threshold at approximately 15%.





Table 7-3. Forest Cover – Oyster Bay Watershed

Subwatershed Name	Forest Cover in Subwatershed (acres)	Percent Forest Cover in Subwatershed	Developable Forest Cover in Subwatershed (acres)	Percent of Forest Cover that is Developable
Bailey Arboretum	310	61%	25	8%
Beaver Brook	2,157	46%	97	4%
Centre Island	243	31%	39	16%
Cold Spring Brook	1,745	37%	122	7%
Cold Spring Harbor	1,460	50%	25	2%
Kentuck Brook	567	39%	40	7%
Lloyd Neck	463	54%	0	0%
Mill Neck Creek	295	30%	9	3%
Mill River	1,207	58%	141	12%
Oyster Bay Harbor	777	48%	128	16%
Tiffany Creek	1,189	65%	77	6%
Upper Kentuck Brook	188	43%	0	0%
Upper White's Creek	424	33%	4	1%
White's Creek	42	15%	8	19%
Harbor Complex Watershed	11,067	45%	25	8%

Developed Areas

Developed land cover, characterized by significant amounts of impervious surfaces such as roofs, roads, and other concrete and asphalt surfaces, accounts for approximately 30% of the harbor complex watershed. When considered together with the turf/grass land cover category (primarily cultivated lawns typical of residential neighborhoods, parks, cemeteries, golf courses, turf farms, and other maintained grassy areas), approximately 46% of the watershed area consists of developed land cover types. The percentage of developed land cover (not including turf/grass) in each subwatershed ranges from approximately 17% in the Lloyd Neck and Bailey Arboretum subwatersheds to approximately 66% in the White's Creek subwatershed.

Table 7-4. Developed Land Cover by Subwatershed

Subwatershed Name	Developed Land Cover in Subwatershed (acres)	Percent Developed Land Cover in Subwatershed (%)
Bailey Arboretum	85	17
Beaver Brook	1,064	23
Centre Island	198	25
Cold Spring Brook	1,815	39
Cold Spring Harbor	797	27
Kentuck Brook	598	41
Lloyd Neck	144	17
Mill Neck Creek	407	42
Mill River	541	26
Oyster Bay Harbor	515	32
Tiffany Creek	464	25
Upper Kentuck Brook	148	34
Upper White's Creek	496	39
White's Creek	184	66
Harbor Complex Watershed	7,455	30



7.1.4 Impervious Cover

Impervious cover has emerged as a measurable, integrating concept used to assess the overall condition of a watershed. Numerous studies have documented the cumulative effects of urbanization on stream and watershed ecology (Center for Watershed Protection, 2003; Schueler et al., 1992; Schueler, 1994; Schueler, 1995; Booth and Reinelt, 1993, Arnold and Gibbons, 1996; Brant, 1999; Shaver and Maxted, 1996). Research has also demonstrated similar effects of urbanization and watershed impervious cover on downstream receiving waters such as lakes, reservoirs, estuaries, and coastal areas.

The correlation between watershed impervious cover and stream indicators is due to the relationship between impervious cover and stormwater runoff, since streams and receiving water bodies are directly influenced by stormwater quantity and quality. Although well-defined imperviousness thresholds are difficult to recommend, research has generally shown that when impervious cover in a watershed reaches between 10 and 25 percent, ecological stress becomes clearly apparent. Between 25 and 60 percent, stream stability is reduced, habitat is lost, water quality becomes degraded, and biological diversity decreases (NRDC, 1999). Watershed imperviousness in excess of 60 percent is generally indicative of watersheds with significant urban drainage. *Figure 7-5* illustrates this effect. These research findings have been integrated into a general watershed planning model known as the Impervious Cover Model (ICM) (CWP, 2003).

Figure 7-5 also demonstrates the wide variability in stream response found in less-urban watersheds at lower levels of impervious cover (generally less than 10 percent). Stream quality at lower range of impervious cover is generally influenced more by other watershed metrics, such as forest cover, road density, extent of riparian vegetative cover, and cropping practices. Less variability exists in the stream quality at higher levels of impervious cover because most streams in highly impervious, urban watersheds exhibit fair or poor stream health conditions, regardless of other conditions (CWP, 2008).




Figure 7-5. Conceptual Model Illustrating Relationship Between Watershed Impervious Cover and Stream Quality





A GIS-based impervious cover analysis was performed for the harbor complex watershed, with assistance from the Center for Landuse Education and Research (CLEAR) at the University of Connecticut (Wilson, 2008). The satellite-derived land cover data described previously were used in the analysis. The sub-pixel classification method extracts impervious surface data directly from 2002 Landsat imagery to estimate the amount of impervious surface within each 30 meter pixel. The percent imperviousness by basin was calculated using the subwatershed GIS layer described previously. *Figure 7-6* graphically summarizes the results of this analysis.

The overall imperviousness of the harbor complex watershed is estimated at approximately 12.3% (*Table 7-5*), which slightly exceeds the 10% threshold in the ICM where ecological stress and stream impacts become apparent. As shown in *Figure 7-6*, impervious cover is generally highest (30% to 70%) in the urbanized areas of Oyster Bay Hamlet and the Villages of Glen Cove, Bayville, Locust Valley, West Hills and the southern portion of Woodbury. Impervious cover in most of the residential areas of the watershed generally ranges from less than 10 percent up to 30%.

Figure 7-7 and Table 7-5 summarize estimates of impervious cover by subwatershed. Most of the subwatersheds fall into the "impacted" category (impervious cover between 10 and 25%) according to the ICM. Several of the subwatersheds have significantly less than 10% impervious cover, including the Bailey Arboretum and Lloyd Neck subwatersheds. The White's Creek subwatershed has the highest impervious cover (43.3%), which is consistent with the high-density development in Oyster Bay Hamlet and indicative of degraded stream conditions according to the ICM.


Table 7-5. Existing Subwatershed Impervious Cover

Subwatershed	Percent Impervious Cover
Bailey Arboretum	4.6%
Beaver Brook	8.0%
Centre Island	10.0%
Cold Spring Brook	16.4%
Cold Spring Harbor	9.6%
Kentuck Brook	18.5%
Lloyd Neck	4.4%
Mill Neck Creek	19.1%
Mill River	10.5%
Oyster Bay Harbor	14.1%
Tiffany Creek	8.6%
Upper Kentuck Brook	11.9%
Upper White's Creek	15.8%
White's Creek	43.3%
Harbor Complex Watershed	12.3%


The results of this analysis provide an initial diagnosis of potential stream and receiving water quality within the watershed study area. The analysis method and ICM are based on several assumptions and caveats, which limits its application to screening-level evaluations. Some of the assumptions of the ICM include:
















- Requires accurate estimates of percent impervious cover, which is defined as the
 total amount of impervious cover over a subwatershed area. The resolution of the
 land cover data used in the evaluation is relatively coarse, although sufficient for
 screening analysis.
- Predicts potential rather than actual stream quality.
- Does not predict the precise score of an individual stream quality indicator but rather predicts the average behavior of a group of indicators over a range of impervious cover.
- The 10 and 25 % thresholds are approximate transitions rather than sharp breakpoints.
- Does not currently predict the impact of watershed best management practices (treatment or non-structural controls).
- Does not consider the geographic distribution of the impervious cover relative to the streams and receiving waters. Effective impervious cover (impervious cover that is hydraulically connected to the drainage system) has been recommended as a better metric, although determining effective impervious cover requires extensive and often subjective judgment as to whether it is connected or not.
- Impervious cover is a more robust and reliable indicator of overall stream quality beyond the 10 percent threshold. The influence of impervious cover on stream quality is relatively weak compared to other potential watershed factors such as percent forest cover, riparian community, historical land use, soils, agriculture, etc. for impervious cover less than 10 percent.


7.1.5 Open Space

Open space areas were identified based on a review of land use information provided by the Town of Oyster Bay and Town of Huntington, review of aerial photographs, and through coordination with Friends of the Bay. Approximately 10% of the harbor complex watershed consists of protected open space that is primarily conservation land and public parks (*Figure 7-8*). This land is protected against future development. In addition, recreational open space (golf courses, beaches, and private institutional open space) accounts for another 5% to 10% of the watershed area (*Figure 7-1*). Future development of these parcels is unlikely, unless their continued use becomes threatened. Additional privately held natural open space exists on already subdivided parcels and large estates.

Nassau County has identified open space, parks, stormwater systems and brownfields that are recommended for acquisition or restoration funding in the report *The 2006 Nassau County Environmental Program*: Recommended Properties and Projects (Nassau County, 2006). The open space acquisition recommendations total 52 acres in the harbor complex watershed and include the Humes Property and Smithers Property in Mill Neck, the Held Property and Schwab Property in Oyster Bay Cove, and Woodbury Hills in Woodbury.









In February 2008, the Nassau County Legislature acquired most of the 31-acre Smithers Estate in Mill Neck for open space preservation. This important acquisition creates a continuous preserve all the way to the Oyster Bay National Wildlife Refuge, helping to protect water quality and the health of the Oyster Bay/Cold Spring Harbor estuary system. The Smithers Estate is within a state-designated Special Groundwater Protection Area (SGPA) and contains two ponds, as well as many of the fresh-water springs that supply Shu Swamp, Beaver Dam, Mill Neck Creek and Oyster Bay. The NYSDEC has documented 74 species of birds breeding in the area, including migratory birds. It also provides critical habitat for numerous fish species, such as Brook Trout and the American Brook Lamprey.

The NYSDEC 2006 New York State Open Space Conservation Plan identifies several properties in the Oyster Bay/Cold Spring Harbor Complex watershed that are priorities for future acquisition to protect water quality, fish and wildlife habitat, and water-based industry, and provide increased opportunities for public access to Long Island Sound. The DRAFT 2009 New York State Open Space Conservation Plan updates the 2006 priority list and includes:

- Sagamore Hill Additions 19 parcels totaling 358 acres, flanking Sagamore Hill National Park on the Cove Neck peninsula in the Town of Oyster Bay. Most parcels front either Oyster Bay or Cold Spring Harbor.
- Shu Swamp Natural Area 9 parcels totaling 80 acres on either side of Shu Swamp Preserve in the Town of Oyster Bay. The area is a Class I freshwater wetland within the Oyster Bay SGPA. Home to endangered brook trout, brook lamprey and water otter as well as several unusual or regionally rare plant species.
- Oyster Bay Mill Pond Area One 6-acre parcel fronting Oyster Bay Mill Pond, an 8-acre stream-fed pond within the boundaries of the Oyster Bay National Wildlife Refuge that flows directly into Oyster Bay Harbor.
- Oyster Bay Harbor Area 36 parcels totaling 294 acres surrounding Oyster Bay Harbor, home to New York State's largest oyster fishing area. This popular area provides outstanding recreational opportunities and includes a large concentration of both saltwater and freshwater wetlands.

The DRAFT 2009 New York State Open Space Conservation Plan also identifies acquisition of parcels along trail corridors and greenways associated with the Long Island Trail & Greenway System to provide non-motorized travel corridors for people and wildlife, and to link recreational, natural and cultural attractions. In the Oyster Bay/Cold Spring Harbor Complex watershed, the primary trail and greenway acquisition priorities include:

 Muttontown Preserve Trail System – 11 parcels totaling 295 acres adjoining the Muttontown Preserve. This popular horse and foot trail system is heavily used and is threatened with fragmentation. It is located in the Oyster Bay SGPA and contains rare plants, tiger salamanders, and glacial kettle-hole ponds.





Finally, the DRAFT 2009 New York State Open Space Conservation Plan identifies acquisition of vacant land within SGPAs identified in the 1992 Long Island Comprehensive Special Groundwater Protection Area Plan. The protection of land within SGPA boundaries is directly linked to the long term health of Long Island's drinking water supply. In the Oyster Bay/Cold Spring Harbor Complex watershed, the primary acquisition priorities include:

- Route 25A Heritage Area 16 parcels totaling 231 acres along Route 25A in the Statedesignated Long Island North Shore Heritage Area and the Oyster Bay SGPA. Parcels will preserve the history of Long Island's rural past while protecting drinking water for its future.
- Planting Fields Arboretum Additions 21 parcels totaling 606 acres near or adjoining Planting Fields Arboretum State Historic Park in the Oyster Bay SGPA.
- Tiffany Creek Preserve 18 parcels totaling 221 acres in the Oyster Bay SGPA. Two water district wells are located in project area, as well as spring fed ponds and streams, old growth woods, migratory songbirds, several turtle species and tiger salamanders.

7.2 Future Conditions

7.2.1 Watershed Buildout Analysis

A watershed buildout analysis was conducted to estimate future potential land use and impervious cover conditions in the watershed as a result of maximum development allowed by current zoning.

Land Use

Existing undeveloped land that could be developed in the future (i.e. "developable" land) is shown in *Figure 7-9*. Land designated as "Potential New Development" in *Figure 7-9* includes parcels in the Town of Oyster Bay that are designated as "Vacant Land." There is little vacant land remaining in the Town of Huntington, and no significant vacant parcels in the Huntington portion of the watershed. Areas identified as protected open space, as well as areas identified as having "Recreation and Entertainment" land use, were excluded from the analysis. Isolated fragments of land or parcels less than ½-acre in size were also excluded. Potentially developable parcels were verified by Friends of the Bay using local knowledge of parcels that are unlikely to be developed and land designated as protected open space. The developable land in the watershed is primarily forested.

As indicated in *Table 7-6*, the harbor complex watershed is largely built-out. There are relatively few vacant, undeveloped parcels that are not either protected open space or recreational open space that is likely to be developed in the future. Overall, less than 3% of the watershed area has the potential for new development. The actual amount of land in the watershed that is subject to future development is likely even less since development on these parcels would be restricted by wetlands, steep slopes, and other physical factors, as well as maximum lot coverage, setbacks, and other zoning constraints. Most significant future development will most likely occur as infill or redevelopment.










Table 7-6. Potential Developable Land

Subwatershed Name	Potential New Development (acres)	New Development Percent of Subwatershed
Bailey Arboretum	25	4.8%
Beaver Brook	97	2.0%
Centre Island	39	5.1%
Cold Spring Brook	3	0.0%
Cold Spring Harbor	25	0.8%
Kentuck Brook	40	2.6%
Lloyd Neck	0	0.0%
Mill Neck Creek	9	0.9%
Mill River	141	6.5%
Oyster Bay Harbor	128	7.9%
Tiffany Creek	77	4.0%
Upper Kentuck Brook	0	0.0%
Upper White's Creek	4	0.3%
White's Creek	8	2.7%
Harbor Complex Watershed	596	2.4%

Impervious Cover

The watershed buildout analysis was used in conjunction with the existing conditions impervious cover analysis (Section 7.1.4) to estimate future impervious cover in the harbor complex watershed. For this analysis, impervious cover was included as a parameter in the pollutant loading model described in Section 8.1. Each urban land use type was assigned an impervious cover coefficient based on literature values (see Table 2 in *Appendix A*). Land use data for both existing and buildout conditions were then entered into the model to determine the change in impervious cover for each subwatershed. The predicted change in impervious cover was then added to the existing impervious cover estimates described in Section 7.1.3 to estimate future impervious cover.

Table 7-7 presents estimates of existing and future impervious cover by subwatershed. The shaded cells in the table highlight the subwatersheds in which future impervious cover is predicted to approach or exceed the "impacted" (10%) threshold value as described by the Impervious Cover Model.

Table 7-7. Percent Impervious Cover – Existing and Future Conditions

Subwatershed	Existing Percent Impervious Cover	Future Percent Impervious Cover	Percent Change (IC ^{future} -IC ^{existing})
Bailey Arboretum	4.6%	6.9%	2.3%
Beaver Brook	8.0%	8.7%	0.7%
Centre Island	10.0%	12.1%	2.1%
Cold Spring Brook	16.4%	16.4%	0.0%
Cold Spring Harbor	9.6%	10.0%	0.4%
Kentuck Brook	18.5%	20.0%	1.5%
Lloyd Neck	4.4%	4.4%	0.0%
Mill Neck Creek	19.1%	19.6%	0.5%
Mill River	10.5%	13.4%	2.9%
Oyster Bay Harbor	14.1%	17.6%	3.5%
Tiffany Creek	8.6%	10.4%	1.8%
Upper Kentuck Brook	11.9%	11.9%	0.0%
Upper White's Creek	15.8%	16.0%	0.2%





Table 7-7. Percent Impervious Cover – Existing and Future Conditions

White's Creek	43.3%	45.3%	2.0%
Harbor Complex Watershed	12.3%	13.6%	1.3%

Based on this analysis, the impervious cover in the overall harbor complex watershed is predicted to increase from 12.3% to 13.6%, but remain well below the ICM non-supporting threshold of 25%. The Cold Spring Harbor and Tiffany Creek subwatersheds are predicted to increase from slightly less than 10% impervious cover to meet or slightly exceed the 10% threshold where ecological impacts become apparent (see *Figure 7-5*). The largest relative change in impervious cover is predicted in the Oyster Bay Harbor subwatershed, where imperviousness could increase from approximately 14.1% to 17.6%.

Another useful metric was developed by Goetz et al. (2003) for the Chesapeake Bay region, which combines subwatershed impervious cover and tree cover within the 100-foot riparian area along streams and other watercourses. The harbor complex subwatersheds were analyzed with regard to the combined impervious cover/riparian zone metric, which is summarized in the following matrix by Goetz et al. (2003).

Stream Health	% Watershed Impervious Cover	% Natural Vegetation in 100- ft Riparian Zone
Excellent	< = 6%	>=65%
Good	6-10%	60-65%
Fair	10-25%	40-60%
Poor	> 25%	<40%

Natural vegetation was determined using the CLEAR land cover data and included the deciduous forest, coniferous forest, forested wetland, and non-forested wetland categories. A 100-foot riparian area was considered on both sides of mapped streams and around Beaver Pond, Mill Pond, and St. John's Pond. The following table presents the results from the combined impervious cover/riparian zone metric. Centre Island, Cold Spring Harbor, Lloyd Neck, Mill Neck Creek, Oyster Bay Harbor, Upper Kentuck Brook, and Upper White's Creek are not included in the table since these subwatersheds do not contain well-defined, mapped streams.

Table 7-8. Existing Impervious Cover/Riparian Zone Metric

Subwatershed	% Watershed Impervious Cover	% Natural Vegetation in 100-ft Riparian Zone		
Bailey Arboretum	4.6%	63%		
Beaver Brook	8.0%	61%		
Cold Spring Brook	16.4%	82%		
Kentuck Brook	18.5%	62%		
Mill River	10.5%	62%		
Tiffany Creek	8.6%	71%		
White's Creek	43.3%	30%		





Overall, most of the harbor complex subwatersheds evaluated are currently categorized as "good" to "excellent" based on the riparian zone metric published by Goetz et al. (2003). White's Creek falls into the "poor" category, with approximately 30% natural vegetation in the 100-foot stream buffer. The segment of the stream in the subwatershed is approximately 360 feet long and the Oyster Bay Sewage Treatment Plant is on the western bank of the stream, with a forested area along the western bank. Future conditions were not evaluated since there is no significant undeveloped land within the 100-foot riparian zone.





8 Pollutant Loading

A pollutant loading model was developed using the land use/land cover data described in Section 7.0. The model was used to compare existing nonpoint source (NPS) pollutant loads from the watershed to projected future pollutant loads that would occur under a watershed buildout scenario. It is important to note that the results of this screening-level analysis are intended for the purposes of comparing existing and future conditions and not to predict future water quality. This section summarizes the methods and results of the analysis, which are presented in greater detail in *Appendix A*.

The Spreadsheet Tool for the Estimation of Pollutant Load (STEPL), Version 4.0, was used for this analysis. This model was developed for US EPA by Tetra Tech in EPA Region 5 and has since been modified for use in other areas. The model calculates watershed pollutant loads for sediment and nutrients based on land use-related pollutant sources, including urban runoff, septic system failures, stream bank erosion, and agricultural activities. The model also allows simulation of best management practices (BMPs) and Low Impact Development (LID) techniques to reduce pollutant loads.

Data obtained as part of the Land Use/Land Cover analysis presented in Section 7.0 were used to generate model inputs. Several other model parameters were specified for each pollutant and subwatershed, including:

- Event Mean Concentrations (EMCs), which are literature values for the mean concentration of a pollutant in stormwater runoff for each land use, and
- Curve Number (CN), which is a measure of the runoff potential of the land surface and is a function of soil type, cover condition, and slope.

The model was applied to each subwatershed to estimate annual pollutant loads under existing and future land use scenarios, as described in Section 7.0. The existing and future pollutant loads were compared to assess anticipated changes in loads for each subwatershed. The area draining to existing recharge basins (see *Figure 6-4* for areas in the watershed that currently drain to a recharge basin) was excluded from the pollutant loading analysis since the recharge basins effectively infiltrate and provide treatment for the water quality volume, thereby eliminating pollutant loads to surface waters. The recharge basin drainage areas were determined based on mapping available from the Nassau County subwatershed stormwater management reports, where available, and the Nassau County Department of Public Works.

Because the study subwatersheds vary in size, pollutant loads were also evaluated in terms of loading rates (i.e., pollutant loads per acre of land area, as shown in *Table 8-1*). A higher loading rate indicates relatively greater pollutant sources per unit area, which suggests that implementation of best management practices (BMPs) in these areas would be more effective in reducing pollutant loads. The results in *Table 8-1* indicate that pollutant loading rates are relatively uniform across many of the subwatersheds. The highest loading rates for nitrogen, phosphorus and sediment are associated with the White's Creek, Mill Neck Creek, Centre Island, and Cold Spring Harbor subwatersheds.





As discussed previously, pollutant loads and loading rates are also correlated with the amount of area within a subwatershed that is served by recharge basins. For example, the Kentuck Brook and Tiffany Creek subwatersheds are characterized by high density residential, commercial, and institutional land use, but a large percentage of the stormwater runoff from these subwatersheds is captured and infiltrated in recharge basins (65% and 31% respectively). Consequently, these subwatersheds have lower pollutant loading rates than the Mill Neck Creek and Cold Spring Harbor subwatersheds, for example, in which little or none of the drainage area is currently served by recharge basins.

% Area to Ρ Ρ Ν Sediment Ν Sediment Subwatershed Recharge lb/yr lb/yr ton/yr lb/ac-yr lb/ac-yr ton/ac-yr **Basins** 3,113 Cold Spring Brook (4,851 ac) 17,479 324 3.6 0.6 0.07 39% 16,476 2,834 314 Cold Spring Harbor (2,953 ac) 5.6 1.0 0.11 0% 269 14,789 2,677 3.0 0.6 0.06 Beaver Brook (4,862 ac) 31% Oyster Bay Harbor (1,612 ac) 2% 8,769 1,494 173 5.4 0.9 0.11 1,765 132 Mill Neck Creek (968 ac) 5% 8,491 8.8 1.8 0.14 7,796 1,494 140 3.6 0.7 0.06 Mill River (2,175 ac) 17% Tiffany Creek (1,923 ac) 31% 7.670 1.386 137 4.0 0.7 0.07 Kentuck Brook (1,538 ac) 65% 5,942 1,483 71 3.9 1.0 0.05 Centre Island (762 ac) 0% 4,307 799 78 5.7 1.0 0.10 697 Lloyd Neck (894 ac) 0% 3,661 69 4.1 8.0 80.0 Bailey Arboretum (527 ac) 5% 2,929 504 53 5.6 1.0 0.10 White's Creek (292 ac) 0% 2,814 436 61 9.6 1.5 0.21 Upper White's Creek (1,317 ac) 100% 1,155 452 0 0.9 0.3 0.00 0 Upper Kentuck Brook (451 ac) 100% 295 115 0.7 0.3 0.00

Table 8-1. Existing Pollutant Loads and Loading Rates

- White's Creek Although the White's Creek subwatersheds is the smallest in the study area, it is characterized by the dense residential and highest percent composition of commercial (18.4%) and industrial (2.2%) land uses in the watershed. For comparison, the next highest percentage of commercial land use is Cold Spring Brook with only 3.8% of the total subwatershed area. Transportation and other land uses are in comparable proportions to other subwatersheds in Oyster Bay. White's Creek does not contain any recharge basins, and is therefore characterized by high pollutant loading rates.
- Mill Neck Creek Mill Neck Creek is characterized by both relatively high total pollutant loads and pollutant loading rates due to a high proportion of dense residential land use (42.8%). Other land uses are similar to other subwatershed areas. A major factor contributing the high pollutant loading rates in this subwatershed is that only 2 recharge basins are present in the watershed, with only 5% of the total area treated through recharge basins.
- Centre Island Centre Island is characterized by rural residential land uses and no recharge basins within the subwatershed. The high loading rates for nitrogen and phosphorus are due to the septic systems.





• Cold Spring Harbor and Oyster Bay Harbor – Cold Spring Harbor and Oyster Bay Harbor are moderately-sized subwatersheds in which stormwater is conveyed to the harbor complex through stormwater collection systems and overland flow. These coastal areas are heavily developed, and only very small portions of these subwatersheds are served by recharge basins. Consequently, existing pollutant loads and loading rates for these subwatersheds are relatively high.

Table 8-2 presents the results of the future pollutant loading analysis under the watershed buildout scenario described in Section 7. Results are shown in terms of increase in pollutant loading rate (the mass of pollutants discharged per contributing acre of land on an annual basis) and percent increase in pollutant load (based on the total pollutant discharge from each of the subwatersheds).

Table 8-2. Projected Future Pollutant Loading Rates and Load Increases

	Projected Future Loading Rate			Projected Load Increase		
Subwatershed	N	Р	Sediment	N	Р	Sediment
	lb/ac-yr	lb/ac-yr	lb/ac-yr	lb/yr	lb/yr	ton/yr
Bailey Arboretum (527 ac)	5.8	0.99	0.107	5%	4%	6%
Beaver Brook (4,862 ac)	3.1	0.56	0.057	3%	2%	3%
Centre Island (762 ac)	5.9	1.09	0.109	5%	4%	6%
Cold Spring Brook 4,851 ac)	3.6	0.64	0.067	0%	0%	0%
Cold Spring Harbor (2,953 ac)	5.6	0.97	0.107	1%	1%	1%
Kentuck Brook (1,538 ac)	4.1	0.99	0.051	5%	3%	9%
Lloyd Neck (894 ac)	4.1	0.78	0.077	0%	0%	0%
Mill Neck Creek (968 ac)	8.8	1.83	0.137	1%	0%	1%
Mill River (2,175 ac)	3.9	0.73	0.072	10%	7%	11%
Oyster Bay Harbor (1,612 ac)	5.9	0.99	0.117	8%	7%	9%
Tiffany Creek (1,923 ac)	4.2	0.75	0.076	6%	4%	7%
Upper Kentuck Brook (451 ac)	0.7	0.26	0.000	0%	0%	0%
Upper White's Creek (1,317 ac)	0.9	0.34	0.000	0%	0%	0%
White's Creek (292 ac)	9.9	1.53	0.214	3%	3%	3%

Several of the subwatersheds are predicted to experience significantly higher increases in pollutant loads and loading rates under a watershed buildout scenario. These include Tiffany Creek, Mill River, Oyster Bay Harbor, and Kentuck Brook watersheds. The build-out conditions of the Mill River and Oyster Bay Harbor subwatersheds are projected to result in greater than 5% increase in pollutant loading rates for nitrogen, phosphorus and sediment loads. The increase in urban land use with a corresponding decrease in forest, with a proportion of the new urban land is likely to consist of new residential and industrial development. The increase in pollutant loads is the future is relatively small across the watershed because there is little opportunity for redevelopment in existing residential areas and for development in forested or vacant areas.



9 Comparative Subwatershed Analysis

A Comparative Subwatershed Analysis was performed for the Oyster Bay/Cold Spring Harbor subwatersheds to identify the subwatersheds with the greatest restoration potential. Subwatershed "metrics" were used to conduct this analysis. Metrics are numeric values that characterize the relative restoration potential of a subwatershed. The results of this analysis are used to prioritize field assessment efforts in future phases of this study and to guide plan recommendations.

The analysis involves a screening level evaluation of selected subwatershed metrics that are derived by analyzing available GIS layers and other subwatershed data sources. The basic approach used to conduct the Comparative Subwatershed Analysis consisted of:

- 1. Delineation of subwatershed boundaries and review of available metric data.
- 2. Selection and calculation of metrics that best describe subwatershed restoration potential.
- 3. Developing weighting and scoring rules to assign points to each metric.
- Computing aggregate scores and developing initial subwatershed rankings.

Subwatersheds with higher aggregate "restoration potential" scores are more likely to have been impacted and have greater potential for restoration to improve upon existing conditions. This approach enables watershed planners to allocate limited resources on subwatershed where restoration and conservation efforts have the greatest chances of success. The subwatersheds used in this analysis are those identified in Section 5.1 of this document.

9.1 Analysis Methods and Results

The metrics for the Comparative Subwatershed Analysis are presented in *Table 9-1*. Ten metrics were evaluated for each subwatershed and points were assigned for the relative restoration potential indicated by the metric. All metrics were scored between 1 and 10, with 1 indicating the lowest potential for restoration and 10 indicating the highest potential for restoration. The scores for each of the 10 metrics were then added to arrive at a composite score for each subwatershed. The total number of points possible for each subwatershed is 100.

The results of the Comparative Subwatershed Analysis are summarized in *Table 9-2*. The restoration potential scores ranged from 20 to 54 points out of a possible 100. The highlighting identifies subwatersheds with high (orange), moderate (yellow), and low (green) restoration potential in the harbor complex watershed.





Table 9-1. Comparative Subwatershed Analysis Restoration Potential Metrics

Subwatershed Metric	How Metric is Measured	Indicates Higher Restoration Potential When	Metric Points
Existing Impervious Cover	% impervious cover in subwatershed	Current impervious cover is low, suggesting range of possible sites for storage retrofits and stream repairs	<10% = 10pts; 10 to 25% = 7 pts; 26 to 40 = 5 pts; 41 to 60% = 3 pts; > 60% = 1 pts
2. Forest Cover	% forest cover in subwatershed	Forest cover is low, suggesting potential for upland and riparian reforestation	<20% = 10 pts; 21 to 30% = 7 pts; 31 to 40% = 5 pts 41 to 60% = 3 pts, >60 % = 1 pt
3. Recharge Basin Drainage Area	% drainage area	Recharge basin drainage area is low, subwatersheds with smaller proportion of area served by recharge basins are better candidates for stormwater retrofits	One pt for each 10% below 100%
4. Publicly- owned land	% of subwatershed that is publicly owned	Public land ownership is high, providing range of potential sites for restoration practices	Award 1 pt for each 2.5% of subwatershed in public ownership (up to 10 pts)
5. Residential Land	% of subwatershed residential land use	residential land is high, suggests strong feasibility for neighborhood source control, on-site retrofits and upland forestry	Award 1 pt for each 10% residential land use
6. Industrial & Commercial Land	% of subwatershed that is industrial or commercial land	Industrial/Commercial land is high, suggesting potential for source controls, discharge prevention, and on-site retrofits	Award 1 pt for each 2% of subwatershed classified as industrial or commercial
7. Wetland Area	% of subwatershed that is tidal or freshwater wetlands	Wetland cover is high, suggesting potential for wetland and riparian restoration	Award 1 pt for each 4% of subwatershed area
8. Stream Density	Stream miles / square mile	Stream density is high, suggesting greater feasibility of stream corridor restoration practices	Award 1 pt for each 0.1- mile of stream/sq mi (up to 10 pts)
9 Regulated Site Density	Regulated sites / sq mi. (incl. RCRA, AFS, CERCLIS)	Regulated site density is high, suggests strong potential to implement source controls, discharge prevention and on-site retrofits	0 to 1 sites/sq. mi. = 1 pt; 1 to 2 = 3 pts; 2 to 5 = 5 pts; 5 to 10 = 7 pts; > 10 = 10 pts
10. Developed Areas with Septic	Density (septic systems/acre)	Density of septic systems is high, suggesting greater potential for improvements through septic system upgrades or new sewers	Award 1 pt for each 0.2 septic system per acre in subwatershed



Table 9-2. Results of Comparative Subwatershed Analysis

Subwatershed	1. Current Impervious Cover	2. Forest Cover	3. Recharge Basin Collection Area	4. Publicly-Owned Land	5. Residential Land	6. Industrial & Commercial Land	7. Wetland Area	8. Stream Density	9. Regulated Sites Density	10. Developed Areas Served by Septic	Total
Mill Neck Creek	7	7	10	3	7	0	8	0	3	9	54
Bailey Arboretum	10	1	10	4	7	0	1	10	5	2	50
Mill River	7	3	8	10	5	1	1	8	5	2	50
Cold Spring Brook	7	5	6	10	5	2	1	3	7	3	49
White's Creek	3	10	10	1	4	10	0	1	10	0	49
Centre Island	7	5	10	5	6	0	10	0	1	2	46
Cold Spring Harbor	10	3	10	6	5	1	2	0	5	2	43
Lloyd Neck	10	3	10	9	7	0	2	0	0	2	43
Oyster Bay Harbor	7	3	10	3	6	1	3	0	7	1	41
Kentuck Brook	7	5	3	4	6	1	0	3	5	6	40
Beaver Brook	10	3	6	3	6	0	1	3	1	1	34
Tiffany Creek	10	1	6	5	6	0	0	4	0	1	33
Upper White's Creek	7	5	0	4	6	1	0	0	5	3	31
Upper Kentuck Brook	7	3	0	0	8	0	0	0	0	2	20

As shown in *Table 9-2*, the following subwatersheds have the highest restoration potential based on the Comparative Subwatershed Analysis scoring system:

- Mill Neck Creek The Mill Neck Creek subwatershed is ranked highest for the wetland
 and septic system-related metrics. The area of Bayville is densely developed and
 contains a significant number of on-site septic systems, offering ample opportunities for
 residential-related retrofits and restoration projects to address pollutant sources. The
 Mill Neck Creek subwatershed also has a high proportion of tidal wetlands, which
 provides opportunities for wetland restoration/preservation.
- Bailey Arboretum_— The Bailey Arboretum subwatershed drains to Mill Neck Creek
 through a small tributary. The subwatershed is characterized by high impervious cover
 and residential development. Only 5% of the subwatershed area is served by existing
 recharge basins, providing opportunities for new stormwater controls.





- Mill River The Mill River subwatershed contains a relatively high percentage of
 publicly-owned land, including large portions of the Muttontown Preserve and Planting
 Fields. The Mill River also has a relatively high stream density, suggesting greater
 feasibility for stream corridor restoration practices.
- Cold Spring Brook The Cold Spring Brook subwatershed ranked favorably for
 restoration potential in terms of recharge basin density, publicly-owned land, existing
 impervious cover, and regulated sites. This subwatershed has a relatively low impervious
 cover, indicating a greater range of potential restoration sites for stormwater retrofits,
 stream repairs, reforestation, and source control practices. The relatively high density of
 regulated sites in this watershed, including permitted stormwater dischargers, provides
 opportunities for source controls, discharge prevention, and on-site retrofits.
- White's Creek The White's Creek subwatershed is a small drainage area characterized by high density residential development, as well as commercial and industrial uses with low forest cover. The subwatershed has a relatively high density of regulated sites, primarily located along South Street. White's Creek is, in effect, hydraulically separated from Upper White's Creek, as Upper White's Creek is almost entirely served by recharge basins. Unlike Upper White's Creek, the White's Creek subwatershed does not contain existing recharge basins, and therefore offers good potential for future stormwater retrofits.

9.2 Subwatersheds Recommended for Field Assessments


The Comparative Subwatershed Analysis results suggest that the subwatersheds identified in the previous section should be the focus of subsequent field assessments. However, a number of previous studies and stream/outfall assessments have already been performed by Nassau County in several of these priority subwatersheds, including Bailey Arboretum, Mill River, and White's Creek, in addition to subwatersheds with lower restoration potential including Beaver Brook (also named Francis Pond), Kentuck Brook, and Tiffany Creek. Subsequent field assessments should focus on those priority subwatersheds where previous studies and field assessments have not yet been performed, thereby providing new information and avoiding duplication of previous work. The results of the field assessments conducted in support of this watershed planning study will be combined with the findings of previous stream/outfall assessments to guide the overall watershed management plan recommendations.

The following subwatersheds are therefore recommended for detailed field assessments (Figure 9-1), potentially including stream corridor assessments and restoration inventories (for those areas where a defined stream channel exists), neighborhood source assessments, hotspot site investigations, and street and storm drain assessments:

- Cold Spring Brook,
- Cold Spring Harbor,
- Oyster Bay Harbor,









- Mill Neck Creek,
- Centre Island,
- Lloyd Neck.

Limited upland assessments focusing on neighborhoods, hotspots, and streets/storm drains (rather than the stream corridor and stormwater outfalls along the stream corridor) are also recommended in selected areas of those subwatersheds that were previously studied by Nassau County. Detailed field assessments are not recommended for the Upper White's Creek or Upper Kentuck Brook subwatersheds since these areas are self-contained (i.e., the areas drain to existing recharge basins).





10 Watershed Field Assessments

Field inventories were performed by Fuss & O'Neill during summer 2009 to further assess existing watershed conditions and potential sources of pollution. The field inventories are a screening level tool for locating potential pollutant sources and environmental problems in a watershed along with possible locations where restoration opportunities and mitigation measures can be implemented. Similar field inventories were conducted by Cashin Associates in 2007 as part of a series of stormwater investigation reports developed for Nassau County in the Bailey Arboretum, Kentuck Brook, Francis Pond (Beaver Brook), Mill River, White's Creek, and Tiffany Creek subwatersheds. The 2007 field inventories primarily focused on the stream corridors and did not include upland assessments. However, retrofit opportunities were identified in the subwatersheds where field inventories were conducted. The field inventories conducted by Fuss & O'Neill during the summer of 2009 focused on subwatersheds that were not previously investigated, and were prioritized based on the Comparative Subwatershed Analysis presented in Section 9 of this report. This section integrates the findings of both the 2007 and 2009 subwatershed field assessments.

The stream corridor assessment procedure used in this study is adapted from the U.S. EPA Rapid Bioassessment (RBA) protocol (EPA, 1999) and the Center for Watershed Protection's Unified Stream Assessment (USA) method (CWP, 2005). Upland areas and activities that may impact stream quality were also assessed using methods adapted from the Center for Watershed Protection's Unified Subwatershed and Site Reconnaissance (USSR) techniques (CWP, 2005). The upland assessments included inventories of selected representative residential neighborhoods, streets and storm drainage systems, and land uses with higher potential pollutant loads (i.e., "hotspot" land uses). Field assessment efforts were targeted on stream segments and upland areas with the greatest potential for direct impacts to streams and the harbor complex. These areas were identified through aerial and land use mapping. To the extent possible, efforts were also focused on publicly-owned land, which typically offers greater opportunities for retrofits and mitigation projects as opposed to privately-owned land. Potential retrofit opportunities were identified during the upland assessments, and preliminary sketches of structural retrofits were documented for use in the Watershed Action Plan.

During the field inventories, crews assessed approximately 1.2 miles of stream corridors, eight potential hotspot locations, nine representative residential neighborhoods, and a number of streets and storm drainage systems associated with the residential neighborhoods and hotspot land uses. Field inventory nomenclature used throughout this report is summarized in *Table 10-1*. Copies of completed field assessment forms are provided in *Appendix B*. Photographs of specific or representative pollutant sources and problem areas are included throughout this document for illustrative purposes. All of the photographs taken during the field inventories are included on a CD in *Appendix B*.

Table 10-1. Field Inventory Nomenclature

Bailey Arboretum	BAI
Beaver Brook	BEA
Centre Island	CTR
Cold Spring Brook	CSB
Cold Spring Harbor	CSH





Table 10-1. Field Inventory Nomenclature

Kentuck Brook	KBR
Lloyd Neck	LNK
Mill Neck Creek	MNC
Mill River	MRV
Oyster Bay Harbor	OBH
Tiffany Creek	TFY
White's Creek	WCR
Reach Level Assessment	RCH
Channel Modification	CM
Severe Bank Erosion	ER
Impacted Buffer	IB
Stormwater Outfall	OT
Stream Crossing	SC
Trash & Debris	TB
Utilities	UT
Hotspot Investigation	HSI
Neighborhood Site Assessment	NSA
Streets and Storm Drains	SSD
Retrofit Reconnaissance Inventory	RRI

10.1 Summary of Findings

A variety of conditions and issues were identified during the 2007 and 2009 subwatershed field assessments. Key findings, including some common issues throughout the watershed, are described below. These findings, along with other information presented in this baseline assessment report, will help guide the recommendations of the watershed management plan for the harbor complex.

- Overall in-stream habitat in the assessed reaches was mixed. Some of the assessed reaches have high quality habitat, with riparian cover, good floodplain connection, varied substrate, and significant stream shading (e.g., Bailey Arboretum, Kentuck Brook, and the middle segments of Cold Spring Brook). In other segments, even within the same subwatershed, in-stream habitat is marginal to poor due to bank erosion, buffer encroachment, trash and debris, lack of shading, and in-stream sedimentation (much of White's Creek, portions of Mill River, and the lower reach of Cold Spring Brook). However, many of the stream reaches assessed appear to be either supporting biological communities (fish, frogs, birds, etc.) or sufficient to support such communities.
- Many potential barriers to fish passage were observed throughout the watershed, including perched culverts, culverts with very shallow flow, and natural and manmade dams. The impacts of these obstructions on fish passage and the feasibility of fish barrier removal efforts in the harbor complex watershed are currently being investigated through a study led by the Long Island Chapter of Trout Unlimited, Environmental Defense, and Friends of the Bay.
- Segments of some streams in the watershed are buried in underground conduits, resulting from historical development and past storm drainage practices. These stream reaches offer potential opportunities for daylighting and stream restoration to enhance





aquatic and wildlife habitat, improve aesthetics, and provide educational opportunities. Potential candidates for daylighting include segments of White's Creek and Beekman Creek.

- Stream buffer encroachments are prevalent along stream corridors in or near areas of
 residential, commercial, and industrial development and roads. Residential lawns and
 some commercial lawns extend down to the banks of the stream in many areas,
 particularly in residential back yards. Yard waste such as grass clippings, leaves, and
 brush and waste materials were also common occurrences in and near these areas where
 easy access exists to the streams. Education, signage, stream buffer regulations, and
 stream cleanups are potential approaches for improving buffer management.
- Residential roofs appear to contribute significant quantities of stormwater runoff to the storm drainage system, particularly in residential neighborhoods with smaller yards and lots with a high percentage of impervious cover. Opportunities exist to disconnect residential rooftop runoff from the storm drainage system and reduce the quantity of runoff by redirecting the runoff to pervious areas or through the use of rain barrels or rain gardens.
- Lawn-care maintenance practices in residential areas are typically high. Manicured lawns are common in residential areas, suggesting the prevalent use of fertilizer and other lawn care products, as well as permanent irrigation systems. Opportunities exist to educate the public about the impacts of lawn care practices on the water quality of the harbor complex and to encourage the use of residential lawn care best management practices, with the objective of reducing excess fertilizer runoff and the overall quantity of runoff from residential lawns.
- Parking lots associated with existing commercial development, municipal and
 institutional land uses, and commuter parking areas are potential candidates for
 stormwater retrofits to reduce site runoff and improve water quality through the use of
 bioretention, water quality swales, buffer strips/level spreaders, and other small-scale
 Low Impact Development (LID) and green infrastructure approaches. Candidate
 stormwater retrofit sites exist in virtually all of the assessed subwatersheds but are most
 prevalent in Mill River, Tiffany Creek, White's Creek, Mill Neck Creek, and Oyster Bay
 Harbor.
- The field assessments identified many areas in the watershed where storm drains are stenciled or watershed stewardship signage exists. Storm drain stenciling and/or stewardship signage could be expanded to other areas of the watershed, targeting commercial areas such as the Pine Hollow Shopping Complex and additional residential subdivisions including those along Harbor Road in Huntington and along Hernan Avenue in Bayville. Interpretive educational signage is also recommended in key public areas of the watershed.





- Stormwater recharge basins are prevalent in many areas of the watershed. Recharge basins are designed to capture and infiltrate stormwater, thereby replenishing groundwater aquifers and reducing the quantity of runoff that is discharged directly to surface receiving waters. Drainage areas that are served by existing recharge basin are believed to be self-contained by infiltrating their entire design volume. However, several of the basins maintained by Nassau County and the Town of Oyster Bay are overgrown and have a large amount of accumulated sediment and/or standing water, and a few are completely full. Their performance may be compromised as a result of the accumulated sediment and reduced storage volume and infiltration capacity. Routine sediment removal and other maintenance measures are recommended for the recharge basins.
- Most of the developed areas surveyed have inadequate stormwater quality controls.
 Many of the residential developments were constructed prior to the advent of modern stormwater quality regulations and design requirements. Therefore, most of the development observed in the watershed employs traditional curb and gutter storm drainage collection systems with little, if any, stormwater management beyond water quality inlets and detention basins for peak flow control.
- Stormwater runoff from areas that are not served by recharge basins generally receives
 little or no treatment prior to discharge. Such discharges are a source of sediment,
 pathogens, nutrients, and other pollutants to the receiving streams and the harbor
 complex. Opportunities exist for stormwater retrofits at roadway stormwater outfalls
 throughout the watershed. A number of roadway outfall retrofit candidates were
 identified in the Bailey Arboretum, Beaver Brook, Kentuck Brook, Mill River, and
 White's Creek.
- Roosevelt Memorial Park is one of the few areas in the watershed where Low Impact Development (LID) design practices were observed. The stormwater management features that were incorporated into this redevelopment project exemplify the type of stormwater controls that could be promoted throughout the watershed. Local LID demonstration sites are a valuable tool for public education and promoting the widespread use of such practices. The incorporation of LID into town and county projects, parks, and municipal buildings can also serve as a proactive model for private development. Opportunities also exist for incorporating LID practices into existing roadway upgrades and retrofit projects (i.e., "green streets") to promote stormwater infiltration, streetscape improvements, and traffic calming.
- Relatively isolated areas of moderate to severe streambank erosion were observed along Beaver Brook, Mill River, Cold Spring Brook, Tiffany Brook, and White's Creek. Most of these areas are located at or downstream of stormwater outfalls in developed areas of the watershed. Access to some of these areas is limited; therefore, potential candidate sites for bank stabilization projects should be evaluated further for overall feasibility.
- Hotspot land uses and facilities were observed throughout the watershed, including several commercial shopping centers, the Town of Oyster Bay highway yard, the LIRR Maintenance Yard, Commander Oil Terminal, and municipal parking lots. Many of





these facilities discharge stormwater directly to receiving waters with no treatment or attenuation. Pollution prevention and source controls are often lacking or nonexistent at these facilities.

The following sections present a more detailed discussion of the stream corridor and upland assessment methods and findings.

10.2 Stream Corridor Assessment

Stream corridors along Cold Spring Brook were assessed by Fuss & O'Neill during August 24 through 27, 2009 using methods adapted from the U.S. EPA Rapid Bioassessment (RBA) protocol (EPA, 1999) and the Center for Watershed Protection's Unified Stream Assessment (USA) (CWP, 2005). Stream assessments were not performed on other priority subwatersheds since similar assessments were recently performed in these subwatersheds in 2007.

The method used for the 2009 stream assessments is a continuous stream walk method that identifies and evaluates the following impact conditions:

- Outfalls (OT), including stormwater and other manmade point discharges;
- Severe Bank Erosion (ER), such as bank sloughing, active widening, and incision;
- Impacted Buffer (IB), which is a narrowing or lack of natural vegetation;
- Utilities in the stream corridor (UT), such as leaking or exposed pipes;
- Trash and Debris (TR), such as drums, yard waste, and other illegal dumping;
- Stream Crossings (SC), which are hard objects, whether natural or artificial, that restrict or constrain the flow of water. These may include bridges, culverts, dams, and falls;
- Channel Modification (CM), where the stream bottom, banks, or direction have been modified;
- Miscellaneous (MI), other impacts or features not otherwise covered; and
- Reach Level Assessment (RCH), the average characteristics of each reach.

The stream assessment method also includes a semi-quantitative scoring system as part of the reach level assessment to evaluate the overall condition of the stream, riparian buffer, and floodplain, based on a consideration of in-stream habitat, vegetative protection, bank erosion, floodplain connection, vegetated buffer width, floodplain vegetation and habitat, and floodplain encroachment.

Stream assessments were performed by Cashin Associates in 2007 for the Nassau County Stormwater Management Program for the Bailey Arboretum, Francis Pond (Beaver Brook), Kentuck Brook, Mill River, Tiffany Creek and White's Creek subwatersheds. These subwatershed stormwater runoff impact investigations were performed to assess subwatershed conditions and identify stormwater retrofit opportunities to improve water quality. The 2007 stream assessments were performed using the Center for Watershed Protection's USA methods.





Six stream reaches were evaluated by Fuss & O'Neill in 2009 and 14 as part of the Nassau County subwatershed stormwater runoff impact investigations in 2007. *Table 10-2* summarizes the number of reach level assessments that were performed and the number of impact conditions that were identified. Stream assessments were not performed along Upper Kentuck Brook and Upper White's Creek since these subwatersheds drain to existing recharge basins.

Table 10-2. Number of Reach Level Assessments Performed and Impact Conditions Identified

Subwatershed 1	RCH	СМ	ER	MI	IB	OT	SC	TR	UT
Bailey Arboretum	1	-	-	-	-	5	-	-	-
Beaver Brook	3	-	-	1	-	16	-	-	-
Cold Spring Brook ²	6	3	-	-	1	7	10	3	-
Kentuck Brook	1	-	-	1	-	13	-	-	-
Mill River	5	1	1	3	1	21	13	-	1
Tiffany Creek	2	-	-	2	-	7	-	-	-
White's Creek	2	1	-	-	2	6	4	1	-

¹Subwatersheds without a well-defined stream are not included in the table.

10.2.1 2009 Stream Assessments

The primary objective of the 2009 stream assessments of Cold Spring Brook was to quantify the overall condition of stream corridors in Cold Spring Brook and identify opportunities for stream restoration, stormwater retrofits, land preservation, and other stewardship recommendations.

Reach level assessment scores were assigned by field crews based upon the overall condition of the stream, stream buffer, and floodplain. A subjective determination of eight criteria is assessed on a scale of 0 to 20; 0 relating to poor conditions and 20 being optimal conditions. The total of these scores provides a quantitative index of overall stream health and condition. The maximum possible number of points that would be assigned for a fully optimal stream reach is 160 points. *Table 10-3* summarizes the total scores and associated ranks for the assessed stream reaches along Cold Spring Brook.

Table 10-3. Cold Spring Brook Overall Stream Reach Scores

Reach	Instream Habitat Score	Buffer Zone and Floodplain Score	Total Score	Rank
CSB-01	54	38	92	4
CSB-02	68	67	135	1
CSB-03	70	72	142	2
CSB-04	46	48	94	3
CSB-05	38	20	58	6
CSB-06	42	43	85	5



²Field surveys conducted by Fuss & O'Neill in 2009; streams associated with the other subwatersheds listed in the table were conducted in 2007 by Nassau County.



As depicted in the photographs in *Figure 10-1*, CSB-03 is the highest rated stream reach due to a wide vegetative buffer, adequate riparian cover, and good instream habitat. In contrast, CSB-05 has the lowest total score due to channel modification along the entire reach, the lack of canopy cover, poor instream habitat due to uniform channel properties, and limited stream buffer due to the proximity of Harbor Road.



Figure 10-1. Photographs of Cold Spring Brook Stream Reaches

The following sections summarize the major issues identified during the 2009 stream assessment of Cold Spring Brook. Specific locations are identified according to the stream reach and impact condition IDs described previously. Identification of "right" and "left" stream banks is from the observer's perspective facing downstream. Stream reaches were assigned a subwatershed abbreviation followed by a two-digit numerical identifier. Reaches were generally numbered sequentially from downstream to upstream. A reach was considered to be a stream segment with relatively consistent geomorphology and surrounding land use, and generally less than one-half mile in length. Features noted at reach junctions (e.g., culvert crossings) were associated with the downstream reach. Impact conditions within each reach were numbered sequentially with an abbreviation followed by a two-digit number. For example, the second stream crossing in a reach would have the identifier SC-02.

Cold Spring Brook

Cold Spring Brook originates in a forested area northeast of the Cold Spring Harbor MTA commuter train station parking lot and flows in a northerly direction generally parallel to Harbor Road, eventually discharging downstream of the Route 25A overpass into Cold Spring Harbor. Franklin Pond and St. John's Pond are large ponds inline with the stream channel created by man-made impoundments. Cold Spring Brook is divided into six stream reaches, labeled CSB-01 through CSB-06 (*Figure 1; Appendix B*). All six reaches were assessed on August 24, 2009. The reaches are described beginning at the mouth of the stream and moving upstream to the headwaters.





CSB-01

Stream reach CSB-01 begins in a tidal marsh at the mouth of Cold Spring Brook and continues upstream under Route 25A, past the Cold Spring Harbor Fish Hatchery, and ends at the St. John's Pond dam.

- RCH The overall stream conditions are suboptimal due to a lack of stable in-stream habitat, protective vegetation and some evidence of non-native vegetation in the upland areas. There is suboptimal connection to the floodplain in the upper portion of the reach due to the area of impacted buffer caused by a deck, a large pool downstream of the St. John's Pond dam spillway, and other impacts on the fish hatchery property. The overall buffer and floodplain condition is marginal due to a narrow vegetated buffer of approximately 15 feet on the left bank and slightly wider on the right bank, possibly 40 feet or greater. The floodplain is highly impacted in the vicinity of the Route 25A overpass. The floodplain vegetation is dominated by shrub and wetland plants. The tidal wetlands downstream of the Route 25A stream crossing are minimally impacted.
- OT There are six outfalls along this reach. The first, OT-01, is a circular, 24-inch diameter concrete pipe embedded in the concrete abutment wall associated with the St. John's Pond dam. The pipe had a small dry-weather flow and some orange staining, although is likely caused by iron in the groundwater and is therefore not recommended for further investigation or retrofit. OT-02 and OT-03 are twin 6-inch metal pipes on the left bank, possibly associated with stormwater drainage from the fish hatchery property. The pipes are in fair condition, with some chips and cracking. OT-04 is a 14-inch circular clay pipe on the left bank discharging water from the fish hatchery, with moderate dry-weather flow. The discharge is clear and does not have a detectable odor. OT-05 and OT-06 are 18-inch concrete pipes located near the Route 25A overpass, one on the left bank and the other on the right bank, and are associated with stormwater outfalls from the roadway. A substantial dry-weather discharge was observed. However, the source could not be determined in the field and further investigation should be conducted to determine the source.
- SC There are three stream crossings along the reach. SC-01 is the St. John's Pond dam at the upstream end of the reach. This dam is approximately 15 feet wide and 20 feet high and is a physical barrier to fish passage. Downstream of the dam is a plunge pool that collects and slows the water from the dam spillway. A concrete broad-crested weir approximately 2 feet in height (SC-02) was constructed approximately 25 feet downstream of the spillway to create the plunge pool. SC-03 is a twin box culvert beneath the Route 25A overpass. Each culvert is approximately 12 feet wide, 6 feet deep, and has a concrete bottom. The flow in both culverts was shallow (approximately 3 inches deep), which may impede fish passage under low-flow conditions.





SC-03 is a twin box culvert beneath Route 25A along reach CSB-01.

• IB – One area of impacted buffer is present on the left bank where a deck of approximately 15 feet in length was installed on the fish hatchery property. The deck was constructed to overhang the stream by approximately 2 to 4 feet.



Impacted buffer along reach CBS-01 near the Cold Spring Fish Hatchery property.

CSB-02

Stream reach CSB-02 begins at the outlet structure of the Franklin Pond dam and continues downstream to the inlet to St. John's Pond. A portion of the reach is within the Nature Conservancy's Franklin Pond Preserve, and the remaining portions are on private lands.

• RCH – The stream reach is of high quality and is characterized by wide stream buffers, a connected floodplain as evidenced by a large adjacent are of wetland seeps, and extensive canopy cover. The stream reach has optimal instream habitat characterized by submerged logs, shaded areas, large woody debris in the channel, and over 90% of the streambank shaded by native trees. The vegetated buffer width exceeds 50 feet along the main stream channel with little evidence of human impacts. The floodplain area is characterized by a mixture of wetland species and mature forest species.







Reach CSB-02 is a high quality segment, characterized by optimal instream habitat, vegetated buffer, and floodplain connectivity.

• SC – The Franklin Pond dam is the only stream crossing along this reach. The dam is approximately 15 feet wide and the spillway cascades approximately 15 feet from the pond elevation to a downstream pool prior to entering the main stream channel. The dam is a physical barrier to fish passage, although it is an unlikely candidate for removal due to the presence of the St. John's Pond dam downstream and the recreational benefits that Franklin Pond provides.

CSB-03

Stream reach CSB-03 begins at a footbridge that crosses the stream connecting a walking trail adjacent to Harbor Road to the downstream area at the inlet to Franklin Pond, which is primarily a braided channel that flows through a wetland complex.

- RCH The stream reach flows adjacent to Harbor Road and is generally of optimal quality, with sand and gravel channel substrate and a mostly-shaded stream canopy. There is some evidence of stream widening and sediment deposition, which is consistent with the upstream development. The overall stream conditions are optimal with the exception of instream habitat, which is suboptimal due to lack of woody debris, undercut banks, or non-uniform channel substrate. The streambanks are stable and there is adequate floodplain connectivity along this reach. The vegetated buffer width is greater than 50 feet and there is little evidence of human impacts.
- SC There are two stream crossings along this reach. SC-01 is a private driveway crossing at 428 Harbor Road constructed of wood beams, concrete and a paved surface. The crossing does not impact potential fish passage or have a large impact on the channel dynamics since the crossing has an open bottom and a natural substrate. The second stream crossing, SC-02, is located at the upstream end of the reach and is a footbridge associated with a trail system through the adjacent wooded area. Consistent with the construction of SC-01, the bottom substrate was left intact, and the footbridge has minimal impact on fish passage.





• TR – Although the reach habitat, stream buffers and floodplain are in optimal condition, the reach is characterized by areas of trash (bottles, cups, and various other household trash) in the stream and on the banks. The relatively minor amount of trash observed could be collected by volunteers with trash bags. This reach is a potential candidate for s stream cleanup.



Evidence of household trash and debris, which was typical along CSB-03.

CSB-04

Stream reach CSB-04 begins at the footbridge stream crossing and continues upstream to a gabion wall constructed across the stream channel for stabilization. The stream channel divides into two channels for approximately 100 feet, although the characteristics of the two channels are similar and are therefore considered part of the same reach.

- RCH The reach is characterized by sand and gravel substrate, some floating aquatic plants, approximately 50% stream shading, and evidence of active channel dynamics, including downcutting, headcutting, sediment deposition and channelization. The overall instream habitat and buffer and floodplain characteristics are lower compared to stream reaches downstream (CSB-03, CSB-02, and CSB-01). The instream habitat ranges from marginal to suboptimal due to limited vegetative protection, non-native and invasive vegetation growing over the stream channel, and active bank erosion and stream channel dynamics. The vegetative buffer is wider on the left bank and narrower on the right bank. The floodplain habitat is marginal due to a lack of plant species diversity on the streambanks.
- SC There is one stream crossing along reach SC-01, consisting of a gabion wall constructed across the stream channel at the upstream end of the reach. The gabion wall is approximately 2 feet tall, 6 feet long and 20 feet wide and spans the entire stream channel and banks. The gabion wall appears to have been constructed to prevent active headcutting at the location. Although the headcutting is no longer occurring, a pool exists downstream of the wall and shows signs of active downcutting.





Gabion wall along reach CSB-04

• TR – There are two areas of trash in the stream channel and on the streambanks along this reach. TR-01 is a fallen wire fence that was previously a property marker which is approximately 4 to 5 feet tall and greater than 200 feet long. The second is a trash dumping area (TR-02) consisting of traffic cones and household trash.

CSB-05

This reach is almost entirely channelized and flows from the base of the Cold Spring Harbor MTA parking lot, beneath Woodbury Road and continues along Harbor Road in a channelized roadside ditch, ending at the gabion wall structure, which marks the downstream end of a channelized stream segment.

- RCH This reach is characterized by cobble and gravel channel substrate reinforced by wire mesh, creating a channelized stream bottom. The channel is a uniform 6 foot width with 4 foot vertical bank walls. Due to the uniform properties of the channel and the roadside location, the instream habitat and vegetative protection are marginal. There is little evidence of bank erosion since gabion walls are securing the banks. There is an approximately 15-foot buffer between the roadway and the channel. The channel has been disconnected from the floodplain by creating vertical retaining walls that serve as the banks of the stream, and the floodplain characteristics are generally marginal to poor.
- CM The entire channel reach has been modified and can be subdivided into three distinct channel segments, CM-01, CM-02, and CM-03. CM-01 extends from the gabion wall on the downstream end of the reach to an upstream culvert. This segment is approximately 200 feet long, and wire mesh has been placed on the bottom of the stream channel and approximately 10 feet up both banks for stabilization. The bottom width of the stream at this location is approximately 6 feet. CM-02 is a stream segment that is entirely contained in an underground concrete box culvert that conveys the stream beneath Harbor Road. The culvert is approximately 3 feet tall, with an approximately 12-feet wide concrete bottom. CM-03 begins at the upstream end of the culvert where the stream is daylighted and runs to the upstream end of the stream reach, across Woodbury Road. CM-03 is also characterized by a modified channel, with wire





mesh used for stabilizing the channel bottom and vertical gabion walls for bank stabilization. The stream channel along this segment is approximately 8 feet wide and is greater than 500 feet long, flowing adjacent to Harbor Road.



Reach CSB-05(CM-03) consists of a modified stream channel with gabion wall banks.

• OT – One outfall, OT-01, is present along this reach, which conveys flow from a mulched area and discharges inside the culvert along CM-02. Although the outfall is approximately 8 feet in diameter, no dry weather flow was observed.



This arched culvert, OT-01, discharges to the box culvert that conveys Cold Spring Brook beneath Harbor Road.

SC – There are three stream crossings along this reach. SC-01 and SC-02 are box culvert
driveway crossings providing access to residences at 511 and 523 Harbor Road. SC-03 is
a diagonal road crossing beneath Woodbury Road. At the intersection of Harbor Road
and Woodbury Road, the stream flows from a catch basin on the west side of the street





with an outlet pipe heading east. The pipe is believed to be connected to the inlet pipe on the opposite side of Woodbury Road, although the connection could not be field verified.

CSB-06

Stream reach CBS-06 is located at the headwaters of Cold Spring Brook. The brook originates in a forested wetland northeast of the MTA railway tracks and parking lot. The stream flows from its headwaters to the inlet structure adjacent to Woodbury Road.

 RCH – The reach is characterized by a sand substrate with some sediment deposition observed. The instream habitat, buffer and floodplain are generally suboptimal to marginal due to the small channel width and impacts from the railway tracks and nearby parking lot.

10.2.2 2007 Stream Assessments

The following sections briefly summarize the findings of the 2007 stream assessments performed by Cashin Associates for the Nassau County Stormwater Management Program. Stream assessments were performed for Bailey Arboretum, Francis Pond (Beaver Brook), Kentuck Brook, Mill River, Tiffany Creek, and White's Creek. The details of these assessments are provided in the Stormwater Runoff Impact Analysis and Candidate Site Assessment Reports that are cited in Section 1.3 of this report.

The 2007 stream assessment results presented in the Stormwater Runoff Impact Analysis and Candidate Site Assessment Reports were compared based on the number of outfalls, hotspot locations, road crossings, inadequate buffers, trash accumulation locations, etc. in each subwatershed. *Table 10-4* presents an overall score for each subwatershed based upon the quantitative results from the 2007 stream assessments. The subwatersheds in *Table 10-4* are listed in order of decreasing pollution potential (relative high pollution ranking to low pollution ranking). It is important to note that the 2007 stream assessment results should not be compared directly with the 2009 stream assessment results for Cold Spring Brook due to differences in the assessment methods and field personnel used in each study. However, the scores presented in *Table 10-4* are useful for comparing the relative pollution potential of the subwatersheds that were assessed in 2007.

Table 10-4. 2007 Stream Assessment Results Summary

Subwatershed	Pollution Potential Score ¹
White's Creek	86
Mill River	51
Tiffany Creek	35
Beaver Brook	26
Kentuck Brook	25
Bailey Arboretum	18

Pollution potential score calculated from the quantitative stream assessment results presented in the 2007 Stormwater Runoff Impact Analysis and Candidate Site Assessment Report for each subwatershed.





Bailey Arboretum

The overall stream condition was assessed to fall in the suboptimal to optimal range due to the inadequate vegetated buffers in the arboretum. The overall buffer and floodplain condition was assessed as being within the suboptimal to optimal range due to minor floodplain encroachment and a narrow vegetated buffer width (Cashin Associates, P.C., 2007).

The Bailey Arboretum subwatershed is in optimal condition for most of the subwatershed but the drainage infrastructure system carries road runoff directly into the creek and the buffer impacts within the Bailey Arboretum property offer opportunities to improve the subwatershed further. A number of stormwater retrofits were recommended to address pollutant loads associated with the existing drainage system in the Bailey Arboretum subwatershed. In addition, the 2007 study report recommended non-structural measures including increased street sweeping, public education on garden fertilizer and chemical use and disposal, public education on the importance of buffers between cultivated lawns and waterbodies, and public education on the importance of vegetative cover to prevent soil erosion (Cashin Associates, P.C., 2007).

Beaver Brook (Francis Pond)

Three reaches were assessed in the Beaver Brook (Francis Pond) subwatershed. The first reach (103-1) encompasses all of Beaver Lake. The second reach (103-2) extends from Beaver Lake south to the intersection of Frost Mill Road and Beaverbrook Road. The third reach (103-3) extends south from Frost Mill Road and to the headwaters in the vicinity of Valley Road, including Lower Francis Pond, Upper Francis Pond, and two small branches extending south and southwest from Upper Francis Pond (Cashin Associates, P.C., 2007).

The overall stream condition for reach 103-1 was assessed to be within the suboptimal to optimal range because of its favorable in-stream habitat and floodplain connection. The overall buffer and floodplain condition was assessed to be within the poor to marginal range due to significant floodplain encroachment and inadequate floodplain vegetation due to various land development such as cultivated residential yards, roadways, horse grazing and an ice skating facility (Cashin Associates, P.C., 2007).

The overall stream condition for reach 103-2 was assessed to be within the optimal range due to the well maintained area in Shu Swamp Preserve and ideal vegetative protection. The overall buffer and floodplain condition was assessed to be within the optimal range due to little or no floodplain encroachment and adequate vegetated buffer width (Cashin Associates, P.C., 2007).

The overall stream condition for reach 103-3 was assessed in the optimal range due to ideal instream habitats and vegetative protection. The overall buffer and floodplain condition was assessed in the optimal range also due to little or no floodplain encroachment and ideal floodplain vegetation (Cashin Associates, P.C., 2007).

The area of the subwatershed that actually contributes surface runoff to waterbodies has been reduced by the installation of upgradient recharge basins and other drainage infrastructure that contain the storm runoff volume from roads and subdivisions. The drainage systems that discharge to waterbodies include two piped drainage systems that outfall to the west side of Shu Swamp and numerous individual catch basins and leaching structures located along the subwatershed roads, several of which have outfalls to waterbodies. Stormwater retrofits were





recommended at several outfalls at the ice skating facility at the eastern end of Kaintuck Lane, an outfall located on the west side of Shu Swamp, concrete swales that contribute runoff to Upper Francis Pond, and catch basin inserts in several catch basin systems located on Chicken Valley Road, Glen Cove Oyster Bay Road, and Oyster Bay Road that outfall to Upper Francis Pond. The 2007 study report also recommends implementing non-structural measures similar to those recommended for the Bailey Arboretum subwatershed (Cashin Associates, P.C., 2007).

Kentuck Brook

The overall stream condition was assessed as being within the optimal range due to its ideal instream habitat and vegetative protection. The overall buffer and floodplain condition was assessed as being within the suboptimal to optimal range due to some buffer and floodplain encroachment from man-made structures (Cashin Associates, P.C., 2007).

The Kentuck Brook subwatershed is in optimal condition for most of the subwatershed but at the lower limit there are limited areas of buffer and floodplain encroachment and several outfalls that contribute road runoff to the brook (Cashin Associates, P.C., 2007).

The area of the subwatershed that actually contributes surface runoff to waterbodies has been reduced by the installation of upgradient recharge basins and other drainage infrastructure that contain the storm runoff volume from roads and subdivisions. The main areas of the subwatershed that contribute runoff to Kentuck Brook include the residential area in the northeastern section of the subwatershed and area roads including Oyster Bay Road and adjacent residential roads. Stormwater retrofits were recommended for a swale that carries road runoff from Kaintuck Lane, at outfalls associated with the high-density residential neighborhood located north of the railroad tracks including Valley Avenue and Maple Avenue, and at selected outfalls along Oyster Bay Road. Similar non-structural measures were also recommended for this subwatershed (Cashin Associates, P.C., 2007).

Mill River

The following stream reaches were assessed in the Mill River subwatershed:

- Reach 101-1: Muttontown Preserve to NYS Route 25A
- Reach 101-2: NYS Route 25A north to north side of small ponds
- Reach 101-3: Ponds north to Remsen Lane pipe and roadside channel
- Reach 101-4: Remsen Lane north to Mohawk Drive roadside channel
- Reach 101-5: Mohawk Drive north to Main Street -natural river channel and Mill Pond

Reach 101-1 has optimal overall stream conditions and optimal overall buffer and floodplain conditions. The overall stream condition for reach 101-2 was assessed to be in the optimal range with a suboptimal vegetative protection assessment of the right bank due to the adjacent roadway. Consequently, the overall buffer and floodplain conditions were assessed to be in the optimal range, although a suboptimal assessment of the right bank's vegetated buffer width was noted (Cashin Associates, P.C., 2007).





The overall stream condition of reach 101-3 was assessed to be in the marginal to suboptimal range due to inadequate in-stream habitat availability, little vegetative protection, and moderate levels of bank erosion, especially along the roadway. The overall buffer and floodplain condition was assessed in the poor to marginal range due to a small buffer zone width, inadequate floodplain vegetation, significant floodplain encroachment, and an uneven mix of wetland and non-wetland habitats (Cashin Associates, P.C., 2007).

The overall stream condition of reach 101-4 was assessed to be in the poor to suboptimal range due to poor vegetative protection, severe bank erosion areas, and inadequate floodplain connection. The overall buffer and floodplain condition was assessed to be in the marginal to poor range due to the lack of buffer zone and high levels of floodplain encroachment (Cashin Associates, P.C., 2007).

The overall stream condition of reach 101-5 was assessed to be in the suboptimal to optimal range because of a stable in-stream habitat, good vegetative protection, and very good floodplain connection. The overall buffer and floodplain condition was assessed to be in the suboptimal to optimal range due to a wide buffer zone and an even mix of wetland and non-wetland habitats (Cashin Associates, P.C., 2007).

Based on the conditions identified during the field assessment, a large segment of Mill River is in marginal condition and has been impacted by the surrounding land use and channelized stream banks. A number of candidate stormwater retrofit sites were identified based on the 2007 study, including:

- Town of Oyster Bay Highway Yard located on Lake Avenue
- Outfalls located in the vicinity of Glen Cove Road and Mill River Road Intersection
- Outfalls located along Lake Avenue
- Stabilization of the stream channel along Mill River Road
- Modification of the recharge basin #130 located on NYS Route 25A east of the Mill River

Similar non-structural measures were also recommended for this subwatershed (Cashin Associates, P.C., 2007).

Tiffany Creek

Two reaches were assessed in the Tiffany Creek subwatershed. The first reach (102-1) extends from Oyster Bay Cove south to a small pond located on private property. The overall buffer and floodplain condition in this reach was assessed to be in the poor to marginal range because of a small vegetated buffer zone, cultivated lawn floodplain vegetation, and a significant amount of floodplain encroachment. However, the floodplain habitat does provide an adequate mix of wetland and non-wetland habitats (Cashin Associates, P.C., 2007).

The second reach (102-2) extends from the south side of the pond in Reach 102-1 to Yellow Cote Road. The overall stream condition was assessed to be in the optimal range due to ideal instream habitat and vegetative protection. The overall buffer and floodplain condition was also assessed to be in the optimal range due to a wide, vegetated buffer with little or no floodplain encroachment (Cashin Associates, P.C., 2007).





The area of the subwatershed that actually contributes surface runoff to waterbodies has been reduced by the installation of upgradient recharge basins and other drainage infrastructure. Most of the development south of Route 25A appears to have recharge basins and/or drainage structures in place to contain the water quality volume. There are two recharge basins located north of Route 25A that appear to contain the water quality volume (at a minimum) and are assumed to be self-contained. An additional two basins located in close proximity to Tiffany Creek may have overflows that allow pollutants to reach the creek. The 2007 stream assessment study recommended further evaluation of these basins to determine if water quality modifications are warranted. Other candidate stormwater retrofit sites that were identified in the 2007 study report include a parcel located on the south corner of Cove Road and Shutter Lane and a number of vacant parcels located along roads close to Tiffany Creek. Similar non-structural measures were also recommended for this subwatershed (Cashin Associates, P.C., 2007).

White's Creek

Two reaches were assessed in the White's Creek subwatershed. Reach 100-1 is the tidal segment and Reach 100-2 is the freshwater segment.

The overall stream condition in reach 100-1 was assessed to be in the suboptimal range, with the east bank ranking higher because of the vegetated, stable bank and buffer width. The west bank was rated lower because of channelization and lack of vegetation. The overall buffer and floodplain condition was assessed to be in the marginal to suboptimal range because of the lack of buffer zone and floodplain encroachment along the west bank. It should be noted that although the open water segment of White's Creek is limited, an extensive upgradient drainage infrastructure system outfalls through OT-1. The system has been determined to be undersized for the flow, creating an upstream flooding condition during rainfalls events. Prior studies have been conducted to identify measures to mitigate the flooding conditions, but no solution has been implemented to date. Additional studies may be necessary to develop a solution to the flooding, which may also be able to address some of the water quality issues at this location (Cashin Associates, P.C., 2007).

Reach 100-2 is a small segment of the creek that extends south along the west side of White Street. The creek has been channelized through this section and carries storm flows from upgradient drainage infrastructure. There does not appear to be any aquatic habitat remaining in this reach. In several locations, the shoreline has been hardened by the installation of granite blocks. The reach has a commercial parking lot on the east side. On the west side, the northern segment is adjacent to a small open grass lot and the southern segment runs behind several residences. The overall stream condition was assessed to be in the suboptimal to marginal range because of disruption in vegetation and an area of bank erosion caused by high flows. The overall buffer and floodplain condition was assessed to be in the marginal to poor range because of the lack of buffer zone and floodplain encroachment (Cashin Associates, P.C., 2007).

The 2007 study report, which also cites recommendations from the Whites Creek Watershed Analysis & Stormwater Mitigation Plan dated March 1998, recommends removal of accumulated sediment and modification of NYSDOT recharge basin #15 and stormwater





retrofits at outfalls that drain portions of White Street, East Main Street, and South Street. Similar non-structural measures were also recommended for this subwatershed (Cashin Associates, P.C., 2007).

10.3 Upland Assessments

Fuss and O'Neill conducted upland assessments in the harbor complex watershed on August 24 through 27, 2009. The field observations assist in identifying pollution prevention and potential restoration opportunities at hotspot land uses and residential neighborhoods in the watershed. Factors that were considered when determining which hotspots and neighborhood areas to prioritize for assessment include:

- Stream condition (assessed during stream corridor inventory)
- Site proximity to the stream and harbor complex
- Land use type and development density
- Land ownership
- Restoration potential

The assessment framework was adapted from the Unified Subwatershed and Site Reconnaissance (USSR) method developed by the Center for Watershed Protection. USSR is a "windshield survey" evaluation method in which field crews drive and walk through areas of the watershed to quickly identify pollution prevention and restoration opportunities. The three major components to the upland assessments conducted in the harbor complex watershed are: hotspots, residential neighborhoods, and streets and storm drains. All of the harbor complex subwatersheds were considered for the upland assessments, with the exception of Upper Kentuck Brook and Upper White's Creek since these subwatersheds are self-contained by existing recharge basins. Field data forms that were completed during the upland assessments are provided in *Appendix B*.

10.4 Neighborhood Source Assessment

Stormwater runoff from existing residential neighborhoods is an important consideration for this study, since residential land use is the predominant land use in the Oyster Bay/Cold Spring Harbor Complex watershed. Neighborhood source assessments were conducted to evaluate pollution source areas, stewardship behaviors, and residential restoration opportunities within individual residential neighborhoods throughout the watershed. The residential behaviors that contribute to stormwater quality were assessed by considering the following source areas for "representative" neighborhoods throughout the subwatershed:

- Yards and lawns
- Driveways, sidewalks, and curbs
- Rooftops
- Common areas





Neighborhoods were selected for assessment based on their proximity to stream corridors and the harbor complex and their overall potential to contribute pollutants to the receiving waters. The selected neighborhoods include a variety of residential types, including low- and high-density single-family residential and multi-family residential (apartments). One field sheet was completed for each neighborhood assessed. The selected neighborhoods are located in the Bailey Arboretum, Cold Spring Harbor, Centre Island, Mill Neck Creek, Mill River, Oyster Bay Harbor, and White's Creek subwatersheds, as summarized in *Table 10-5*.

Each neighborhood was assigned a score for pollution severity and restoration potential. Pollution severity is a measure of how much nonpoint source pollution a neighborhood is likely generating based on readily observable features such as lawn care practices, drainage patterns, pavement staining, etc. Restoration potential is a measure of the feasibility of on-site retrofits or behavior changes based on available space, number of opportunities, presence of a strong homeowners association, and other factors.

Table 10-5. Neighborhood Source Assessments Conducted in the Oyster Bay/Cold Spring Harbor Complex Watershed

Neighborhood/ Subdivision Name	Subwatershed	Residential Type	Pollution Severity	Restoration Potential
Matinecock Lane	Bailey Arboretum	Medium to high- density single family	Moderate	Low
Harbor Road, Huntington	Cold Spring Harbor	Medium-density, single-family	Moderate	Low
Centre Island	Centre Island	Low-density/ estate, single-family	None - poor access	Unknown- poor access
Bayview Avenue	Mill Neck Creek	High-density, single- family	Moderate	Moderate
Hernan Avenue	Mill Neck Creek	High-density, single- family	Moderate	Moderate
Oyster Bay Gardens	Mill River	Multifamily Townhouses	Moderate- high	Low
Ships Point Lane	Oyster Bay Harbor	High-density single- family	Moderate	Moderate
Maxwell Avenue	Oyster Bay Harbor	Multifamilty apartments	Moderate	Low
Singworth Street	White's Creek	High-density single family	Moderate	Moderate

Matinecock Lane

This medium to high-density single family neighborhood is approximately 6.6 acres in size. The neighborhood consists of three streets with residences of similar age, density, and other characteristics, including Egypt Lane, Matinecock Lane, and Cherrywood Lane south of Horse Hollow Road and east of Bayville Road. The assessment was performed on Matinecock Lane and Egypt Lane, although the characteristics of Cherrywood Lane are generally similar. The neighborhood is adjacent to a small pond that is tributary to Factory Hollow Pond.

The lots in the neighborhood vary in size from approximately 1/8 acre to 1/3 acre in size. Overall impervious cover is estimated at approximately 30 percent. The majority of lots include intensively maintained laws (approximately 35% of lot coverage) and many include significant landscaping consisting of mulched garden beds, shrubs, trees, and hedgerows. The





neighborhood forest canopy cover is significant (approximately 50%). The streets in the neighborhood are unusually narrow with a typical width of approximately 15 feet. Residents appear to park on the street on a regular basis. No sidewalks are present. Roadway drainage appears to discharge to the small pond via overland flow (curb, gutter, and piped drainage are not present). A significant proportion of the existing driveways (25% estimated) are gravel or other pervious material.

The overall pollution severity of this neighborhood is rated as moderate due to potential nutrient loads. Although it is a moderate to densely-developed neighborhood, the quantity of impervious surface is relatively low since the streets are narrow, no sidewalks are present, not all driveways are paved, and few, if any, downspouts appeared to be connected directly to impervious surface. However, the coverage by well-maintained lawns and garden beds suggest a high level of fertilizer use.

This neighborhood has low restoration potential. The majority of potential retrofits would need to occur at the lot level, such as installing rain gardens to promote stormwater infiltration and provide treatment. A small quantity of undeveloped land may be available south of the end of Egypt Lane where stormwater treatment could be implemented on a larger scale, although the ownership status is unknown.





Views of Matinecock Lane showing intensively-landscaped lawns and planting beds adjacent to the relatively narrow road (left) and a typical residential lot (right).

Harbor Road

This neighborhood consists of single-family houses as well as multifamily residences in older woodframe structures that line Harbor Road in Huntington. Lots in this neighborhood are varied, although the lots to the north (approaching Terrance Place) are generally smaller (approximately ½ acre) and tend to contain multi-family structures, while many of the lots to the south are larger than an acre. The residences appear to vary significantly in age and condition. Harbor Road is drained via curbs, gutters, and catch basins. Many of the downspouts discharge to lawns, although the topography slopes generally downward to Harbor Road such that lot runoff would discharge to the roadway drainage system during larger storm events. The yard of at least one multi-family residence appears to be used for parking, and evidence of irrigation water running off impervious surfaces was also observed in several cases.





The pollution severity index of this neighborhood was moderate, with the potential for sediment discharge from the more densely developed areas and potential for lawn chemical discharge from the less densely developed lots. Additionally, the roadway itself is likely a significant pollutant source.

The neighborhood restoration opportunity index for this neighborhood is generally low, since the sites are constrained by slopes, the location of the roadway, and little land is available between the roadway and the harbor. A notable exception is the Cold Spring Harbor State Park parking area, located at the southern end of this neighborhood, which is likely to be a significant sediment source and has reasonable restoration potential (see *Section 10.7*).





Views of Harbor Road residences, including potential sediment source (left) and lawn irrigation runoff (right).

Centre Island

Centre Island Village consists primarily of residential land use located in the Center of Oyster Bay and connected to Bayville via a narrow isthmus. The majority of residences are large estates with well-landscaped grounds and manicured lawns. A Neighborhood Source Assessment was not completed in this area since field staff were asked to leave the area by private security personnel.

Bayview Avenue

This neighborhood is located in the Mill Neck Creek subwatershed in the Village of Bayville and includes homes on the streets bounded by Ellison Lane, Mountain Avenue and Bayview Avenue. The neighborhood consists of single family detached homes on 1/8 acre lots. Mountain Avenue and Ellison Street are paved, and Bayview Avenue has gravel cover. The majority of the drainage from the subdivision is collected in a curb and gutter system which is conveyed directly to Mill Neck Creek via an outfall at the end of Mountain Avenue.

Approximately 80 percent of the homes have roof leaders that are directed to impervious areas such as a walkway or driveway to be conveyed to the street drainage system. Due to the small lot size, approximately 60 percent of the lots consist of impervious cover. The majority of the lots in the subdivision are miticulously maintained, with the exception of some overgrown lawns with various debris along Bayview Avenue. There is little open space in the vicinity of this neighborhood.





The pollution severity of the watershed is moderate due to the unpaved roadway and debris and lack of maintenace on Bayview Avenue. The restoration opportunity in this neighborhood is low since there is little available open space to implement a structural stormwater retrofit. However, some area is available on many lots downgradient of roof leaders for the installation of a rain garden.

Hernan Avenue

The Hernan Avenue neighborhood is located in the Mill Neck Creek subwatershed in the Village of Locust Valley. The neighborhood includes lots on both sides of Hernan Avenue, which extends from Bayville Road to a dead end at Oak Neck Creek (an arm of Mill Neck Creek), encompassing an area of approximately 8.2 acres. The storm drainage system consists of a curb and gutter system that conveys stormwater to an outfall at the end of Hernan Avenue into Oak Neck Creek.

The houses in this neighborhood are single family detached homes on ½ to ¼-acre lots. The properties have uniformly high management status, with a high percentage of the lot covered with landscaping, although the lots typically have less than 5% canopy cover. A majority (80%) of the roof leaders discharge to a pervious areas such as lawn or mulched areas. The neighborhood contains an approximately 2.4-acre wetland that is believed to provide treatment of stormwater from the neighborhood prior to discharging to Oak Neck Creek. A follow-up investigation is recommended to assess the performance of this wetland and the drainage system connectivity.

Oyster Bay Gardens

The Oyster Bay Gardens housing complex is a multi-family public housing building managed by the Oyster Bay Housing Authority. The complex is located in the Mill River subwatershed on Glen Cove Road. The grounds are generally well maintained and consist of landscaped and turf grass areas. Approximately half of the roof leaders drain to pervious areas such as the mulched areas around the buildings. Sidewalks are present along one side of the roadway.

Potential pollution sources at this location are associated with the impervious parking areas. The parking lot pavement is deteriorating in some places, and there is a significant amount of oil staining on the pavement in the parking spaces. The area for on-street parking near the building contains a significant quantity of accumulated sediment. One location on the roadway had accumulated approximately 3 inches of sediment. The cause of the sediment is believed to be a combination of inoperable vehicles being stored along the road which prevents street cleaning and the area of roadway is the low point in the road, with no catch basin for drainage.

Potential retrofit candidates for this site include a parking lot retrofit that incorporates permeable pavement and bioretention or other form of stormwater infiltration system to collect and infiltrate stormwater runoff from the parking lot.

Ships Point Lane

The Ships Point Lane neighborhood is in Oyster Bay Hamlet in the Oyster Bay Harbor subwatershed and includes single-family residences along Ships Point Lane, Melbourne Street, Sidney Street and Florence Avenue. The lots are typically ½ acre in size with intensively-managed lawn areas, believed to include significant fertilizer use and irrigation practices.





This neighborhood is a good candidate for "green streets" retrofits. The typical street width in this neighborhood is 28 feet and had low utilization of on-street parking observed mid-morning on a weekday. A potential restoration candidate for this location includes stormwater curb extensions that can be easily retrofitted alongside the existing curb. Runoff from the street could be conveyed to these landscaped infiltration areas and would overflow into the existing drain inlets during larger storms. Since this street has a lot of unused on-street parking, the addition of curb extensions would not adversely impact existing parking. The curb extensions could provide stormwater infiltration, a more aesthetically pleasing roadway, and traffic calming.



Views of Ships Point Lane residences, which is a potential candidate for a green streets retrofit.

Maxwell Street

Maxwell Street is located in downtown Oyster Bay in the Oyster Bay Harbor subwatershed and is a mixed single family and multifamily neighborhood with lot sizes less than ¼ acre. The area is serviced by sanitary sewer. There are no catch basins located along the street and stormwater is conveyed by a curb system toward a large catch basin inlet on Shore Avenue. The lots have a high percentage of impervious cover since the buildings comprise in excess of 80 percent of the lot area, and some lots have cement walkways around the perimeter of the house to the edge of the lot making it 100 percent impervious. Several of the driveways on this street consist of a pervious material. There is a low potential for restoration in this neighborhood due to the narrow street width and small lot size, which do not typically have sufficient space for surface stormwater retrofits such as rain gardens, or landscaped areas that would benefit from irrigation from a rain barrel connected to the roof leaders.

Singworth Street

The Singworth Street neighborhood consists of the block bounded by Singworth Street, and Summers Street off of Berry Hill Road in Oyster Bay. The neighborhood subdivision has narrow, long lots approximately ½ acre is size with well-maintained lawns. Some areas of the neighborhood have a mature tree canopy, covering upwards of 25 percent. However, there is evidence of infill and redevelopment occurring with new construction in progress. The lots in





this neighborhood have potential for rain barrel implementation since the majority of the lawns are highly landscaped. Encouraging rain gardens may also be well-received in this neighborhood, and future educational efforts should target this and similar residential subdivisions.

10.5 Hotspot Site Investigation

Hotspot site investigations were conducted for representative sites with a high potential to contribute polluted stormwater runoff to the storm drainage system or receiving waters. The purpose of the investigation was to qualitatively assess the potential for stormwater pollution from previously identified commercial, industrial, municipal or transportation-related sites. The hotspot investigation was limited in scope to representative hotspot facilities in order to evaluate and illustrate common issues. The investigation was not intended to be an exhaustive review of all potential hotspot facilities in the entire watershed nor a detailed inspection or audit of each facility, which are beyond the scope of this study.

The hotspots examined in the field were located within the Bailey Arboretum, Cold Spring Harbor, Centre Island, Mill River, Oyster Bay Harbor, and White's Creek subwatersheds. Representative priority hotspots were selected to cover a range of watersheds and land uses, including transportation-related (highway/railroad/boat maintenance facilities and parking lots), commercial, industrial, and state/municipal sites. Sites are identified by the watershed abbreviation, followed by "HSI" and a numeric identifier. *Table 10-6* summarizes the selected hotspots that were evaluated. Several of the sites that were investigated are privately-owned, and field crews were unable to gain full access to the sites to closely evaluate the storm drainage and other site characteristics.

Table 10-6. Hotspot Site Investigation Summary

Site ID (Watershed)	Land Use Category	Description of Site Operations
BAI-HSI-01 (Bailey Arboretum)	State/Municipal	Locust Valley Intermediate School & Bus Maintenance Facility
CSH-HSI-01 (Cold Spring Harbor)	Transportation	Municipal Parking Lot, Main Street, Huntington
CTR-HSI-01 (Centre Island)	Transportation	Seawanhaka Yacht Club
MRV-HSI-01 (Mill River)	Municipal	Highway Maintenance Facility
OBH-HSI-01 (Oyster Bay Harbor)	3H-HSI-01 (Oyster Bay Harbor) Transportation	
OBH-HSI-02 (Oyster Bay Harbor)	State/Municipal	Oyster Bay High School
WCR-HSI-01 (White's Creek)	Industrial	Commander Oil Terminal
WCR-HSI-02 (White's Creek)	Commercial	Pine Hollow Shopping Center

Locust Valley Intermediate School & Bus Maintenance Facility

The Locus Valley Intermediate School is located in the Bailey Arboretum subwatershed on Ryefield Road. The property consists of a school and a regional bus storage and maintenance facility in the rear of the school. Approximately 15 school buses and 10 other vehicles are stored outdoors at the site. A small garage is located on site for the repair and maintenance of the vehicles. An uncovered outdoor fueling area is located in the center of the parking area,





which is believed to be indirectly connected to the storm drainage system. The facility stores waste oil outdoors (within secondary containment) as well as miscellaneous used parts and garbage dumpsters.

The pavement and gravel areas where buses are stored were in good condition with some evidence of oil staining. A follow-up inspection or future education effort is recommended to examine the used equipment stored along the fence on Ryefield Road and in the rear of the facility along the wooded area. The outdoor storage of waste equipment is a potential source of oil pollution into the storm drainage system. It is recommended that the outdoor fueling station be covered to decrease the potential for gasoline discharges to be conveyed to the storm drainage system. This site may be a higher



Covering the outdoor fueling station at the bus maintenance facility would decrease the stormwater pollution potential of the fueling activities.

priority for follow-up since the stormwater appears to drain from the maintenance facility toward the school playground.

Municipal Parking Lot, Main Street, Huntington

The municipal parking lot in the commercial district along Main Street in Huntington is approximately 35,000 square feet, with approximately 95 parking spaces. This potential hotspot was assessed mid-morning on a weekday and the lot was approximately one-third full. The parking lot was not determined to be a hotspot for pollution sources, although the area is a potential stormwater retrofit candidate since the parking lot drains to two curb inlets along Main Street. There is a small grass island between the parking area and Main Street that has approximately 10 trees planted in a brick and concrete surface.

Seawanhaka Yacht Club

The Seawanhaka Yacht Club is located on Centre Island on Seawanhaka Road. The club provides members with boat storage and launching. The facility is regulated under the state and federal NPDES program. Access to the site for further investigation was denied, and a follow-up interview or inspection is recommended.

Highway Maintenance Facility

The Town of Oyster Bay highway maintenance facility is located in the Mill River subwatershed on Lake Avenue. Stormwater discharge from the facility drains directly to the Mill River via a series of outfalls. The facility is used for the maintenance, fueling, washing and storage of fleet vehicles. Vehicles and the fueling station are located outdoors with no cover. The maintenance and repair of vehicles occurs in a covered garage. Sand and salt storage and loading operations are located outdoors and uncovered. Garbage dumpsters on-site were observed to be uncovered and overflowing with garbage.







Uncovered materials storage

Uncovered and overflowing dumpster

This facility was also identified during the 2007 stream assessments conducted on behalf of Nassau County as a candidate site for significant retrofits and operational improvements. The 2007 study report recommended that the entire yard be redeveloped to contain all storm runoff onsite and to bring the facilities into conformance with current hazardous materials regulations (Cashin Associates, P.C., October 1, 2007).

A follow-up on-site investigation is recommended to further assess the pollution potential from the salt and sand stockpile, the fueling station, outdoor vehicle storage, the sand and salt loading operation, and any current stormwater controls that may exist at the facility. Recommended best management practices include construction of containment berms and/or a covered structure for the sand and salt stockpile, the addition of a canopy over the fueling station, and installing structural controls such as oil/water separators and stormwater management controls for site runoff. This site is a high priority for follow-up since stormwater from the facility discharges directly to the Mill River.

LIRR Maintenance Yard

The Long Island Railroad Maintenance Yard is located in the White's Creek subwatershed in Oyster Bay Hamlet. The yard contains many electrical boxes and has seven divided tracks for the temporary storage and maintenance of railway cars. No confirmed sources of pollution were observed from outside the fence of the property. Potential pollution sources include motor oil and lubricating oil associated with railcar maintenance. A follow-up inspection of this facility is recommended.

Oyster Bay High School

Oyster Bay High School is located on Main Street in Oyster Bay and includes the school building, administration building and associated parking lots. There were no observed sources of pollution at the site, other than the parking areas and maintained lawn. There are large areas of turf grass adjacent to the parking areas that can be seen from Main Street, which could be an ideal location for a high-visibility structural stormwater retrofit that could also have educational benefits. An infiltration basin on the property could collect runoff from the parking area associated with the administration building.

Commander Oil Terminal

The Commander Oil Terminal is a bulk oil receiving and storage facility located at the end of South Street in the White's Creek subwatershed. The facility is regulated under the National Pollutant Discharge Elimination System (NPDES) permit program and is registered with the





NYSDEC under the Oil Spill Prevention, Control and Compensation Act for Major Oil Storage Facilities. Under these and federal oil pollution prevention regulations, the facility must implement a Spill Prevention, Control and Countermeasure Plan and potentially a facility response plan in the event of an oil spill to navigable waters.

Pine Hollow Shopping Center

A hotspot site investigation was conducted at the commercial stores at the Pine Hollow Shopping Center located on Pine Hollow Road (Route 106) in the White's Creek subwatershed. The focus of the investigation was the Stop & Shop located at the south end of the shopping complex and the Rite Aid, which is located one building north of the Stop & Shop. Stormwater from the rooftops and paved areas, including the parking lot, discharges to the drainage system along Pine Hollow Road.








Outdoor storage of materials

Many stormwater pollutant sources were observed on this site. Vehicles, pallets, cardboard, and various bakery racks and store shelving are being stored outdoors uncovered in the rear of the buildings. The waste is not managed properly, and dumpsters were left uncovered with overflowing trash left in trash bags on the ground next to the dumpster. The parking lot and paved area behind the building is stained with oil and has a buildup of sediment.

The Pine Hollow Shopping Center is a confirmed hotspot. A follow-up inspection should be conducted. This and similar commercial retail centers should be included as targets for future education and outreach efforts. This site is also a good candidate for structural stormwater retrofits since the stormwater is conveyed toward the drainage system along Pine Hollow Road. Potential retrofits include parking lot bioretention, particularly along the perimeter of the parking lot adjacent to Pine Hollow Road.



Pine Hollow Shopping Center along Pine Hollow Road





10.6 Streets and Storm Drain Assessment

Urban streets and storm drains can be a source of stormwater pollutants if not maintained on a regular basis. The condition of the local road and storm drain infrastructure can be assessed to determine if existing maintenance practice could reduce pollutant accumulation. Selected streets and storm drains were assessed during the upland field inventories conducted the week of August 3, 2009. Most of the streets and storm drains that were assessed are located in or near hotspot or neighborhood source assessment locations. Findings of the street and storm drain assessment are summarized below. Photographs of the storm drains and the street conditions evaluated are provided as *Table 10-7*.

Approximately half of the streets and storm drains evaluated were clean, free of sediment and debris, and in good condition. The other half had varying degrees of sediment and organic matter accumulated on top of the catch basin grates, either partially or fully prohibiting stormwater from entering the drainage system and sediment accumulation on the street. Many of the inspected catch basins had varying degrees of sediment accumulation and nearly all could benefit from increased clean-out and street sweeping. Many of the storm drains observed during the field assessments were stenciled. However, other areas of the watershed could benefit from storm drain stenciling and similar watershed stewardship signage, particularly along Harbor Road in Huntington, the Pine Hollow Shopping Complex in Oyster Bay, along Hernan Avenue, and other residential and commercial locations throughout the watershed.





Table 10-7. Streets and Storm Drain Assessment Photographs

Location	Storm Dr	rains	Comments
Harbor Road, Huntington (Cold Spring Harbor)			
Mountain Road, Bayville (Mill Neck Creek			Catch basin grates are clean; however sediment accumulation is present on the roadway.
Hernan Avenue, Locust Valley (Mill Neck Creek)			Catch basin grates are partially or completely covered by accumulated organic material
Ships Point Lane, Oyster Bay (Oyster Bay Harbor)			
Pine Hollow Shopping Center, Oyster Bay (White's Creek)		CLEASES & RAIDES NAIL & S	The parking lot pavement is cracked around some of the catch basins located in the parking lot.



11 Land Use Regulatory Controls

11.1 Introduction

Municipal land use plans and regulations help shape the development patterns within a watershed and can play a significant role in protecting water quality and other natural resources at the watershed scale. These commonly include municipal comprehensive plans, zoning regulations, subdivision regulations, and stormwater regulations, all of which influence the type and density of development that can occur within a watershed. Local land use regulations often vary by municipality within a watershed, and regulations are periodically revised in response to development pressure, shifts in attitude toward natural resource protection, and political and socioeconomic factors.

In addition to municipalities, other governmental agencies also have jurisdiction over lands and activities within the harbor complex watershed. The regulatory programs and policies of these agencies also play an important role in addressing land use, water quality, and natural resource issues facing the watershed.

A key element in the development of a watershed management plan is to identify potential land use regulatory and planning mechanisms (i.e., new or modified land use regulations and planning approaches) that can be implemented by the watershed municipalities and other governmental entities to strengthen existing land use controls and better protect natural resources within the watershed. Communities in urbanized areas are also faced with a mandate to meet State and Federal Phase II stormwater permit requirements under the National Pollutant Discharge Elimination System (NPDES) program, as well as addressing local concerns about the damaging effects of increased impervious cover and uncontrolled stormwater runoff from land development and suburban sprawl.

An opportunity exists for the watershed municipalities to strengthen existing regulatory mechanisms and satisfy Phase II stormwater requirements, while also updating and improving upon existing land use regulations and land use planning strategies to help protect and restore water quality and other valuable natural resources in the Oyster Bay/Cold Spring Harbor complex and its watershed.

This section summarizes the various governmental entities with jurisdiction over land use or resources within the watershed boundaries, including existing land use regulatory and planning mechanisms. The information presented in this section is based on responses obtained from a land use questionnaire distributed by Friends of the Bay in 2008, as well as existing regulatory and planning documents made available by the watershed municipalities and other government entities (Town of Oyster Bay, Town of Huntington, City of Glen Cove, and their incorporated villages, and Nassau and Suffolk Counties).





11.2 Summary of Regulatory Jurisdictions

This section describes the various land use regulatory jurisdictions within the Oyster Bay/Cold Spring Harbor Complex watershed. Information in this section is summarized from the Oyster Bay/Cold Spring Harbor Complex Harbor Management Plan (Cashin Associates, 2002), the Mill River Watershed Study and Public Stewardship Program (Cashin Associates, 2007), and information provided by local, county, state, and federal government entities with jurisdiction over land use or resources in the watershed.

11.2.1 Federal

United States Fish and Wildlife Service

The United States Fish and Wildlife Service (USFWS) is responsible for the regulation, management, and preservation of the Oyster Bay National Wildlife Refuge. USFWS management responsibilities include, but are not limited to, restoring wetlands and managing the impoundment. In addition, the USFWS has regulatory jurisdiction over federally endangered wildlife species that could be affected by activities within the harbor complex.

United States Army Corps of Engineers

The U.S. Army Corps of Engineers (ACOE) exercises regulatory authority over actions undertaken within the waters of the United States (e.g., dredging and the placement of structures such as docks and bulkheads). Often, a separate permit is required from ACOE for actions that also require a tidal wetlands permit from NYSDEC.

11.2.2 State

New York State Department of Conservation

The New York State Department of Conservation (NYSDEC) regulates land development and other activities through their wetlands (freshwater and tidal) and State Pollution Discharge Elimination System (SPDES) programs. In general, NYSDEC is responsible for maintaining and improving the quality of New York's natural environment. NYSDEC regulates activities in and within 100 feet of New York State-designated tidal and freshwater wetlands (Part 661 of Title 6 of the New York Code of Rules and Regulations [6 NYCRR 661]). The current SPDES regulations allow NYSDEC to regulate some municipal stormwater systems, all construction activities disturbing one or more acres of land (GP-0-08-002 and GP-0-08-001 respectively), and all traditional water discharges including those from wastewater treatment plants and industrial facilities. As an example, the Oyster Bay STP effluent is regulated under this program.

New York State Department of State

The New York State Department of State (NYSDOS), Division of Coastal Resources provides technical assistance to local governments in the areas of land use regulations, site plan review and design guidelines, and provides general information on new planning techniques. NYSDOS also administers the Federal Coastal Zone Management Act of 1972 and the State Waterfront Revitalization Act of 1981, including responsibility for reviewing Local Waterfront





Revitalization Programs (LWRP), Harbor Management Plans (HMP), Watershed Management Plans, and various coastal zone projects for consistency with the State's Coastal Management Plan. NYSDOS is also responsible for the development and implementation of the Long Island Sound Coastal Management Program.

New York State Department of Health

The New York State Department of Health (NYSDOH) regulates the design and construction of sanitary sewer systems, which is a key factor that affects development patterns, land use, and pollutant sources in a watershed.

New York State Department of Transportation

Although not a directly involved in regulating land use, the New York State Department of Transportation (NYSDOT) designs and maintains state roads and the associated drainage infrastructure within the Oyster Bay/Cold Spring Harbor Complex watershed. The NYSDOT is also considered a Municipal Separate Storm Sewer System (MS4) and, therefore, regulated under NYSDEC's SPDES Phase II program.

11.2.3 County

Nassau County

Department of Public Works

The Nassau County Department of Public Works (NCDPW) is responsible for the design and maintenance of the county's roadways and associate storm drainage infrastructure. Upon the request of the Planning Commission or a municipality the NCDPW will be asked to review and approve proposed land development applications, which may be reviewed by one or more of the divisions of the NCDPW. This review may include, but is not limited to, impacts to county and local roadways and stormwater infrastructure, general site grading and drainage, and proposed sanitary facilities.

Under Municipal Law, the County Department of Public Works must review any construction for which a municipality is issuing a building permit that fronts on or abuts County roads, properties or right-of-ways (Rules and Regulations Governing Approval for Erection of Buildings on County Highways, Nassau County Department of Public Works).

The NCDPW also administers and implements the Nassau County Stormwater Management Program since the county is a regulated small MS4 under the SPDES Phase II program. The County has established an inter-municipal coalition of municipal entities within the County to implement the SPDES Phase II program regionally, consistent with the Nassau County Stormwater Management Program.

Department of Health

The Nassau County Department of Health (NCDH) is responsible for the review and approval of the design and installation of on-site sewage disposal systems that are proposed for subdivisions of five or more lots. Towns and Villages in the region may also impose NCDH design requirements for smaller systems.





Planning Commission

The Nassau County Planning Commission maintains jurisdictional authority for subdivisions of five or more lots proposed in the unincorporated areas of the County. The Planning Commission, when it deems fit, may forward land development applications to the Commissioner of Public Works and/or the Nassau County Department of Health (as per the Real Property Law, Section 334a) for review and approval.

Parks, Recreation and Museums

The Nassau County Department of Parks, Recreation and Museums is responsible for operation, maintenance, and preservation of County-owned park and preserve facilities, such as the Muttontown Preserve.

Soil and Water Conservation District

Although not a regulatory agency, the Nassau County Soil and Water Conservation District is a resource to County residents and employees providing technical assistance and information on many topics including land use practices, stormwater management, and nonpoint source pollution prevention.

Suffolk County

Department of Public Works

The Suffolk County Department of Public Works (SCDPW) constructs, maintains and operates county properties and designs, constructs and maintains county roads, sewerage systems, buildings and other facilities, such as waterways, bridges, docks and marinas. The SCDPW has responsibility primarily for projects on County-maintained roads and properties, but also has the authority to review projects that are subject to Suffolk County Planning Commission review, such as large subdivisions, projects adjacent to municipal boundaries, or those near airports.

The SCDPW, in cooperation with the Cornell University Cooperative Extension, is responsible for implementing the Suffolk County Stormwater Management Program to reduce stormwater pollution from County-owned roads and properties, as Suffolk County is also a regulated small MS4 under the SPDES Phase II program.

Department of Health Services

The Suffolk County Department of Health Services, Division of Environmental Quality (Office of Wastewater Management) is also responsible for the review and approval of the design and installation of on-site sewage disposal systems for all development, including single-family residences. The Office of Pollution Control is responsible for enforcing regulations concerning toxic and hazardous materials storage, inspection of commercial and industrial facilities, and new and existing swimming pool plan reviews and inspections.

Planning Commission

The Suffolk County Planning Commission has regulatory review authority over any municipal zoning/subdivision action that would affect real property lying within one mile of an airport or a nuclear power plant or within five hundred feet from the boundary of any village or town; the boundary of any existing or proposed county, state or federal park or other recreation area; the right-of-way of any existing or proposed county or state parkway, thruway, expressway, road or





highway; existing or proposed right-of-way of any stream or drainage channel owned by the county or for which the county has established channel lines; the existing or proposed boundary of any other county, state, or federally owned land held or to be held for governmental use; or certain designated bodies of water.

Soil and Water Conservation District

Similar to Nassau County, the Suffolk County Soil and Water Conservation District is a resource to County residents and employees providing technical assistance and information on topics related to the protection and preservation of natural resources.

Department of Environment and Energy

The primary mission of the Suffolk County Department of Environment and Energy is to safeguard the natural resources of Suffolk County and to provide a centralized office for consideration of issues and activities from the perspective of their impact on the environment. Although serving primarily an advisory role, the Department of Environment and Energy has jurisdiction over environmental protection laws enforced by the County, the County brownfields program, open space acquisition, farmland preservation, and conservation easements. The Division of Water Quality Improvement also interfaces with the SCDPW on issues related to the Suffolk County Stormwater Management Program.

11.2.4 Municipal

Local municipalities exert the most direct influence on land use and watershed development and redevelopment within their political boundaries. Typical local land use review functions that can affect water quality and natural resources include zoning, site plan review, subdivision review, sediment and erosion control, vegetation protection, and open space preservation. The degree of land use regulatory controls, which can vary significantly between municipalities, is established in the municipal code, primarily the zoning code and development-related regulations (usually amendments to the overall zoning code). Typical land use regulatory controls within the zoning code include minimum lot size, minimum building setbacks, off-street parking requirements, and maximum lot coverage, impervious cover limits, stormwater management design standards, vegetated buffer requirements, etc.

As indicated in *Section 2.1* of this document, the Town of Oyster Bay has the authority to regulate land use and the underwater lands within its boundary and within unincorporated villages and hamlets. The Town also has authority to regulate over-water use of coastal waters within its boundaries, but which lie outside of the 1,500-foot area of over-water jurisdiction of the incorporated villages. The Town of Oyster Bay shares regulatory responsibilities with the United States Fish and Wildlife Service within the Oyster Bay National Wildlife Refuge. These responsibilities extend to several Town agencies and departments, as summarized later in this section.

The Town of Huntington and the City of Glen Cove have similar regulatory authorities and jurisdictions as the Town of Oyster Bay within the harbor complex watershed and coastal areas.





The incorporated villages have authority to regulate land use activities and the use of underwater lands within their respective boundaries, as well as authority to regulate the overwater use of coastal waters within 1,500 feet of their corporate boundaries.

11.3 Land Use Regulatory Survey

Friends of the Bay distributed a land use survey to county and municipal entities in the watershed in 2008. The purpose of the questionnaire was to obtain information on the current land use regulations, policies, and planning documents related to zoning and subdivision review, wetlands and natural resources, comprehensive plans, open space, and stormwater management. The following sections summarize information obtained from the land use survey and subsequent coordination with the municipalities.

Table 11-1 summarizes the various land use departments and commissions of the county and municipal entities within the Oyster Bay/Cold Spring Harbor Complex watershed.

Table 11-1. Land Use Departments and Commissions within the Oyster Bay/Cold Spring Harbor Watershed

	- System Bay/Cola Ophing Harbor Waterenea
County or Municipality	Land Use Departments and Commissions
Oyster Bay	 Town Board Environmental Resources Department Environmental Control Commission (E.C.C.) Environmental Quality Review Division (formerly Environmental Quality Review Commission) Planning and Development Department Zoning Board of Appeals Planning Advisory Board Department of Public Works including the Divisions of Environmental Control, Engineering, and Highways Department of Parks Department of Public Safety Landmarks Preservation Commission "SEA" Fund Committee Hempstead Harbor Protection Committee Eastern Waterfront Steering Committee
Huntington	 Town Board Planning and Environment Department Zoning Board of Appeals Planning Board Engineering Services Parks & Recreation Department Public Safety Department Public Works Department Environmental Open Space and Park Fund Review Advisory (EOSPA) Committee Huntington Conservation Board Historic Preservation Commission



Table 11-1. Land Use Departments and Commissions within the Oyster Bay/Cold Spring Harbor Watershed

County or Municipality	Land Use Departments and Commissions
Glen Cove	 City Board Planning Advisory Board Zoning Board of Appeals Parks & Recreation Department Public Safety Department Public Works Department Beautification Commission
Villages	 Village Board Planning Board Zoning Board of Appeals Highway Department Environmental Conservation Commission (not all have) Landmark Preservation Commission (not all have)
Nassau County	 Planning Commission Department of Public Works Health Department Parks, Recreation and Museums Public Works Department Environmental Program Bond Act Advisory Committee
Suffolk County	 Environment and Energy Department Division of Water Quality Improvement Water Quality Review Committee (WQRC) Parks, Recreation, and Conservation Department Health Services Department Division of Environmental Quality Office of Water Resources Planning Department Council on Environmental Quality Environmental Analysis

Table 11-2 summarizes the current status of comprehensive master plans and key municipal land use regulations for the county and municipal entities within the harbor complex watershed.

Table 11-2. Municipal Land Use Regulations

Plan/Regulation	Oyster Bay	Huntington	Glen Cove	Villages	Nassau County	Suffolk County
Comprehensive Master Plan	Being Prepared	Yes (Being Updated)	Draft	No	Yes	Being Prepared
Subdivision Regulations	Yes	Yes	Yes	Yes	Yes	Yes
Zoning Regulations	Yes	Yes	Yes	Yes	No	No
Floodplain Management	Yes	Yes	Yes	Some	No	No
Stormwater Regulations	Yes	Yes	Yes	Yes	Yes	No
Wetland Regulations	Yes*	Yes*	Yes*	Yes*	No	No

^{*} Pursuant to §24-0501 of the New York State Freshwater Wetland Act (Article 24 of the New York State Environmental Conservation Law)





11.3.1 Wetland Resources

Regulations that protect wetland resources are essential to protecting and restoring the water quality and overall health of the Oyster Bay/Cold Spring Harbor Complex. In New York, activities affecting wetlands are primarily regulated at the state level and federal level. Freshwater wetlands are regulated under the Freshwater Wetlands Act (under Article 24 of the Environmental Conservation Law), while tidal wetlands are regulated under the Tidal Wetland Act of 1973.

11.3.2 Site Development

Land development and redevelopment activities in the watershed are regulated by local zoning codes and subdivision regulations. Municipal zoning and subdivision requirements dictate site development characteristics such as minimum lot size, minimum setback distances, impervious cover, roadway and drainage design standards, open space, and vegetative buffers, as well as the site plan review process itself. Local zoning and subdivision regulations vary considerably by municipality. As an example, *Table 11-3* summarizes lot specifications for each municipality in the watershed, including minimum lot size.

Table 11-3. Municipal Zoning Lot Specifications

Jurisdiction	Zone	Uses Permitted	Minimum Lot Area (SF)
	C-6 General Business	All uses	
	R-5 Residence	One & Two-family	5,000
	R-7 Residence	All uses	7,500
Town of Huntington	R-10 Residence	All uses	10,000
	R-20 Residence	All uses	20,000
	R-40 Residence	All uses	1 acre
	R-80 Residence	All uses	2 acres
	Residence A-1	1	1
Village of Lloyd Harbor	Public Beach	Recreation	
Village of Lloyd Harbor	Conservation Recreation	Recreation	
	Parkland	Recreation	
Town of Oyster Bay	R1-5A One-Family Residence	Single family	5 acres
Includes Villages of: East Norwich	R1-2A One-Family Residence	Single family	2 acres
Hamlet of Oyster Bay	R1-1A One-Family Residence	Single family	1 acre
Locust Valley	R1-20 One-Family Residence	Single family	20,000
Syosset Woodbury	R1-15 One-Family Residence	Single family	15,000
vvoodbury	R1-10 One-Family Residence	Single family	10,000
	R1-7 One-Family Residence	Single family	7,000
	R1-6 One-Family Residence	Single family	6,000
	RMF-6 Multi-Family Residence	Multi-family	5 acres
	RMF-10 Multi-Family Residence	Multi-family	5 acres
	RMF-16 Multi-Family Residence	Multi-family	5 acres
	RPH-20 Multi-Family Public Housing Residence	Multi-family	2 acres
	RSC-25 Multi-Family Senior Citizen Residence	Multi-family	2 acres



Table 11-3. Municipal Zoning Lot Specifications

Jurisdiction	Zone	Uses Permitted	Minimum Lot Area (SF)
	REC Recreation	Recreation	20 acres
	RO Residence-Office	Office	6,000
	NB Neighborhood Business	Business	10,000
	GB General Business	Business	
	LI Light Industry	Industry	1 acre
	Residence R1	Single family	8,000
Village of Mill Neck	Residence R2	Single family	3 acres
	Estate E1 Districts	Single family	5 acres
	Residence B	Single family	5,000
	Residence C	Single family	75,000
Villaga of Daywilla	Residence D	Single family	15,000
Village of Bayville	Residence E	Single family	20,000
	Residence F	Single family	40,000
	Business	Business	
	R-1 Residence	Single family	1 acre
	R-2 Residence	Single family	0.5 acre
City of Glen Cove	R-3 Residence	Single family	0.25 acre
	R-3A Residence	Single family	6,500
	R-4 Residence	One & Two-family	6,500-7,500
	A-1 Residence	Single family	2 acres
Village of Muttontown	E-3 Residence	Single family	3 acres
	E-5 Residence	Single family	5 acres
Village of Upper	R1 Residence	Single family	2 acres
Brookville	OP1 Open District (Suburban Estate)	Single family	5 acres
Village of Old	R-3A Residence	Single family	3 acres
Brookville	R-2A Residence	Single family	2 acres
	R2	Single family ²	2 acres ²
Village of Brookville	R4	Single family ²	4 acres ²
	R5	Single family ²	5 acres ²
Village of Centre	Residence A1	Single family ²	3 acres
Island	Residence A2	Single family ²	0.5 acre
	R-15	Single family	15,000
Village of Lattingtown	R-2A	Single family	2 acres
	R-4A	Single family	4 acres
Village of Laurel	R/I Residential/Industrial	Industrial	75 acres
Hollow	R Residential	Single family	15,000
Village of Oyster Bay	A-1 Residence	Single family	2 acres
Cove	A-2 Residence	Single family	6,000



Unknown at the time of printing.

²Inferred from information provided on the municipal zoning maps.



11.3.3 Open Space

Open space plays a critical role in protecting and preserving the health of a watershed by limiting development and impervious coverage, preserving natural pollutant attenuation characteristics, and supporting other planning objectives such as farmland preservation, community preservation, and passive recreation. Open space includes preserved natural areas as well as lightly developed parks and playgrounds.

While approximately 15 percent of the Oyster Bay/Cold Spring Harbor Complex watershed consists of undeveloped land uses, not all of this land is considered open space because it may be privately owned and ultimately developed. Protected open space areas include deeded open space that is privately owned, parcels owned by land trusts, state and federally-owned land, and municipal park land. Such land is protected against future development. Several of the watershed county and municipal entities have prepared open space plans for their respective jurisdictions (*Table 11-4*).

Table 11-4. Open Space Plans

Jurisdiction	Open Space Plan
Town of Oyster Bay	Yes
Town of Huntington	Yes
City of Glen Cove	No
Villages	Some
Nassau County	No
Suffolk County	Yes*

^{*}Open Space Acquisition Policy Plan

In addition to the designation of protected open space through donation, purchase of land by a municipality, conservation or land trusts, or other private and/or public agencies, municipalities may also require that new development projects set aside some land as dedicated open space. The subdivision regulations of many of the municipalities in the Oyster Bay/Cold Spring Harbor Complex watershed require the set-aside of a percentage of new subdivisions as open space, and some also have provisions for fee-in-lieu-of open space. *Table 11-5* summarizes responses from the surveyed watershed communities regarding their current open space regulations.

A majority of the surveyed watershed municipalities also allow cluster development, open space or conservation subdivisions, or other variations to standard lot layouts in their subdivision regulations. These are compact forms of development that concentrate density in one portion of the site in exchange for reduced density elsewhere, thereby reducing overall site imperviousness and associated stormwater impacts and potentially avoiding development in sensitive areas of a site.



Table 11-5.	Open	Space	Regulations

Jurisdiction	Allow Cluster	Allow Open Space	Subdivision Open Space			
Julisuiction	Development	Subdivisions	Required	Fee in lieu of		
Town of Oyster Bay	Yes	Yes	*	Yes		
Town of Huntington	Yes	Yes	No	Yes		
City of Glen Cove	Yes	Yes	Yes	Yes		
Villages	No	No	Some	Some		
Nassau County	N/A	N/A	N/A	N/A		
Suffolk County	N/A	N/A	N/A	N/A		

^{*}In Aquifer Protection Overlay District only.

11.3.4 Stormwater Management

Development of the landscape with impervious surfaces can alter the hydrology of a watershed and has the potential to adversely affect water quality and aquatic habitat. As a result of development, vegetated and forested land that consists of pervious surfaces is largely replaced by land uses with impervious surfaces. This transformation increases the amount of stormwater runoff from a site, decreases infiltration and groundwater recharge, and alters natural drainage patterns. Natural pollutant removal mechanisms provided by on-site vegetation and soils have less opportunity to remove pollutants from stormwater runoff. During construction, soils are also exposed to rainfall, which increases the potential for erosion and sedimentation. Development can also introduce new sources of pollutants from everyday activities associated with residential, commercial, and industrial land.

Stormwater runoff both during construction and following completion of construction for new development and redevelopment projects is regulated at the local and state levels. As shown in *Table 11-6*, all of the watershed municipalities have erosion and sediment control regulations as mandated by the NYSDEC Phase II Program (GP-0-08-002). All watershed municipalities have adopted regulations requiring that a soil erosion and sediment control plan be submitted with any application for development when the disturbed area of such development is more than one acre. Projects that disturb greater than one acre of land are subject to regulation under the NYSDEC SPDES General Permit for Stormwater Discharges from Construction Activity (GP-0-08-001). This permit applies to discharges of stormwater from construction activities including, but not limited to, clearing, grading, and excavation that result in the disturbance of one or more acres of total land area as part of a development or redevelopment plan.

Post-construction stormwater quantity and quality are also regulated by the watershed municipalities through municipal planning and zoning regulations. All of the watershed municipalities are subject to the requirements of the NYSDEC SPDES Phase II stormwater program, which is regulated under the NYSDEC SPDES General Permit for the Discharge of Stormwater from Municipal Separate Storm Sewer Systems (MS4s)(GP-0-08-002). The Phase II General Permit regulates the quality of municipal stormwater discharges and requires the implementation of a Stormwater Management Program that addresses the following six minimum control measures:



N/A - Not Applicable



- 1. Public education and outreach;
- 2. Public involvement/participation;
- 3. Illicit discharge detection and elimination including mapping all stormwater discharges from a pipe, conduit, or ditch owned or operated by the municipality;
- 4. Construction site runoff control;
- 5. Post-construction storm water management; and
- 6. Pollution prevention and good housekeeping for municipal operations.

All of the municipal entities within the watershed, including the Town of Oyster Bay, the Town of Huntington, the City of Glen Cove, and the villages and hamlets are regulated small MS4s under the NYSDEC SPDES Phase II program. This designation requires each municipal entity to develop and implement a Stormwater Management Program. As described previously, the municipal entities within Nassau County have formed a stormwater coalition with Nassau County for implementing their Stormwater Management Programs.

The NYSDEC has developed the *New York State Stormwater Management Design Manual* (as revised), which provides guidance on the measures necessary to protect the waters of the State of New York from the adverse impacts of post-construction stormwater runoff. It is intended for use as a planning tool and design guidance document by the regulated and regulatory communities involved in stormwater quality management in New York. The manual provides uniform guidance for developers, engineers, and review agencies on the selection, design, and application of stormwater control measures. All of the watershed municipalities in the Oyster Bay/Cold Spring Harbor Complex watershed have indicated that they use the stormwater manual in reviewing land development proposals.

Controls	Oyster Bay	Huntington	Glen Cove	Villages	Nassau County	Suffolk County
On-Site Stormwater Management Requirements/Stormwater Management Plans	Yes	Yes	Yes	Yes	Yes	No
Erosion and Sediment Control Plans	Yes	Yes	Yes	Yes	Yes	No
Site Plan Review	Yes	Yes	Yes	Yes	Yes	No
Illicit Discharge Detection and Elimination Requirements	Yes (pending)	Yes	Yes	Yes	Yes	Yes
Environmental Assessment (SEQR)	Yes	Yes	Yes	Yes	Yes	No

Table 11-6. Municipal Stormwater Management Regulations

11.3.5 On-Site Wastewater Disposal

As described in Section 6.3, significant portions of the Oyster Bay/Cold Spring Harbor Complex watershed are served by individual on-site sewage disposal systems, including cesspools and septic tank systems. These types of systems are a potential source of nitrogen, pathogens, and other pollution to surface waters and groundwater as a result of system failure





(inadequately treating sewage or by creating potential for direct or indirect contact between sewage and the public) or malfunction (typically a slow loss of function that is difficult to detect).

All of the municipalities within the watershed rely on the County Health Departments for design guidelines and the approval of on-site wastewater disposal systems. Larger systems (e.g., 3+ family development; residential buildings housing 10 or more people; commercial, industrial, and residential development generating more than 1,000 gallons/day) are required to obtain approval from the NYSDEC SPDES program. Once constructed and operational, on-site wastewater disposal systems are no longer regulated by the County Health Department and are only inspected if a failure complaint is submitted to the County. The Towns and Villages also do not have requirements for ongoing inspection or maintenance of existing systems.

11.3.6 Aquifer Protection

Several of the county and municipal entities in the watershed have enacted aquifer protection regulations to protect drinking water supplies, in addition to the state-designated Special Groundwater Protection Areas, as defined in Article 55 of the NYS Environmental Conservation Law. As summarized in *Table 11-7*, the Town of Oyster Bay has an Aquifer Protection Overlay (APO) District, adopted in 2004, which affords added protection to both the quality and quantity of groundwater resources by restricting disturbance to natural vegetation, impervious surface coverage, hazardous material storage, creation, and disposal. The Town Code also states that the use of fertilizers, pesticides, and irrigation be minimized. Suffolk County also has designated Special Groundwater Protection Areas and associated regulations, which allow the County to acquire or purchase development rights on land within designated Special Groundwater Protection Areas and establish a Suffolk County Panel on Groundwater Protection.

Table 11-7 Aquifer/Groundwater Protection Regulations

Jurisdiction	Aquifer/Groundwater Protection Regulation
Oyster Bay	Yes
Huntington	No
Glen Cove	No
Villages	No
Nassau County	No
Suffolk County	Yes



12 References

Ashton A., Donnelly J., and Evans, R. (2007). A Discussion of the Potential Impacts of Climate Change on the Shorelines of the Northeastern USA. NECIA Technical Paper Available at http://www.northeastclimateimpacts.org.

Center for Land Use Education and Research (2007) The Status of Connecticut's Coast Riparian Corridors: Research Summary.

Center for Watershed Protection (2003). *Impacts of Impervious Cover on Aquatic Systems*. March 2003.

Center for Watershed Protection (2008). Managing Stormwater in Your Community: A Guide for Building a Post-Construction Program. EPA Publication No. 833-R-08-001.

Connecticut Department of Environmental Protection (2006). 2006 Listing of Connecticut Waterbodies Not Meeting Water Quality Standards.

Connecticut Department of Environmental Protection. (2002). Surface Water Quality Standards (Effective December 17, 2002). Ground Water Quality Standards (Effective April 12, 1996).

Conolly, B.H. (1991). A Preliminary Survey of Wildlife in the Department of Interior Lands in Mill Neck Creek and Oyster Bay. Compiles by B.H. Conolly. January 1991.

Edinger, G.J., D.J. Evans, S. Gebauer, T.G. Howard, D.M. Hunt, and A.M. Olivero (editors). (2002). Ecological Communities of New York State. Second Edition. A revised and expanded edition of Carol Reschke's Ecological Communities of New York State. (Draft for review). New York Natural Heritage Program, New York Department of Environmental Conservation, Albany, NY.

Fogarty M., Inzce L., Wahle R., Mountain D., Robinson A., Pershing A., Hayhoe K., Richards A., Manning J. (2007). Potential Climate Change Impacts on Marine Resources of the Northeastern United States. NECIA Technical Paper available at http://www.northeastclimateimpacts.org.

Frumhoff, P.C., J.J. McCarthy, J.M. Melillo, S.C. Moser, and D.J. Wuebbles. (2007). Confronting Climate Change in the U.S. Northeast: Science, Impacts, and Solutions. Synthesis report of the Northeast Climate Impacts Assessment (NECIA). Cambridge, MA: Union of Concerned Scientists (UCS).

Gomez & Sullivan Engineers, P.C. (Undated). Oyster Bay Mill Pond Dam Fish Passage Assessment Project: Oyster Bay-Cold Spring Harbor Watershed. Prepared for Long Island Chapter, Trout Unlimited; Friends of the Bay; Environmental Defense.





Hayhoe, K., C.P. Wake, B. Anderson, X.-Z. Liang, E. Maurer, J. Zhu, J. Bradbury, A. DeGaetano, A. Hertel, and D. Wuebbles. (2008). <u>Regional climate change projections for the Northeast U.S.</u> *Mitigation and Adaptation Strategies for Global Change*. In press.

Kirshen, P., C. Watson, E. Douglas, A. Gontz, J. Lee, and Y. Tian. (2008). <u>Coastal flooding in the northeastern United States due to climate change</u>. *Mitigation and Adaptation Strategies for Global Change*. In press.

Kitchell, A. and T. Schueler. 2005. Urban Subwatershed Restoration Manual No. 10: Unified Stream Assessment: A User's Manual (Version 2.0). Center for Watershed Protection.

McClymonds, N.E., and Franke, O.L. (1972). Water-transmitting properties of aquifers on Long Island, New York: U.S. Geological Survey Professional Paper 627-E, 24 p.

McGee, Dorothy Horton (1997). "Oyster Bay/Cold Spring Harbor Historic and Cultural Resources Report." As included in NYSDOS Oyster Bay-Cold Spring Harbor Resource Management Plan.

Mills, Herbert C. (1974). *Geology of Long Island*. Educational Leaflet # 16 Nassau County Museum of Natural History.

Nassau County Dept. of Public Works. (2005). "Nassau County Groundwater Monitoring Program 2000 – 2003: With Historical Information."

Nassau County. (2004). "Master Plan." Available at http://www.nassaucountyny.gov/agencies/Planning/documents/MASTERPLANREVISIONDRAFTMay192004.pdf

Nationwide Urban Runoff Program (1983). Results of the Nationwide Urban Runoff Program. U.S. Environmental Protection Agency Water Planning Division, PB 84-185552, Washington, D.C. New York State Department of Environmental Conservation (NYSDEC) and Battelle. (2007). Final Report for Shellfish Pathogen TMDLs for 27 303(d)-listed Waters.

New York State Department of Environmental Conservation (NYSDEC). (2000). Atlantic Ocean/Long Island Sound Basin Waterbody Inventory and Priority Waterbodies List (PWL).

New York State Department of Environmental Conservation (NYSDEC). (2003). "Pathogen Total Maximum Daily Loads for Shellfish Waters in Oyster Bay Harbor and Mill Neck Creek, September 2003."

New York State Department of Environmental Conservation (NYSDEC). (2008). New York State Shellfish Landings from 2005 – 2007 (Not published). New York State Department of Environmental Conservation Shellfish Division.





New York State Museum (2000). Statewide Bedrock and Surficial Geology GIS Data. Available at http://www.nysm.nysed.gov/gis/ NPS. (2009). Sagamore Hill National Historic Site: Nature & Science. U.S. Department of the Interior, National Park Service. URL: http://www.nps.gov/sahi/naturescience/index.htm. Site last visited: February 17, 2009.

NQQD (2004). Findings from the National Stormwater Quality Database, Research Progress Report. Prepared by the Center for Watershed Protection.

New York Department of State (NYDOS). (1987). Coastal Fish & Wildlife Habitat Assessment Form: Cold Spring Harbor. New York State Department of State, Division of Coastal Resources. March 15, 1987.

New York Department of State (NYDOS). (2005). Coastal Fish & Wildlife Habitat Assessment Form: Mill Neck Creek, Beaver Brook and Frost Creek. New York State Department of State, Division of Coastal Resources. October 15, 2005.

New York Department of State (NYDOS). (1999). "NYS Department of State New York State's 1999 Long Island Sound Coastal Management Program" http://www.nyswaterfronts.com/downloads/pdfs/lis_cmp/Chap6.pdf, prepared by the, identifies the Oyster Bay-Cold Spring Harbor area as a Regionally Important Natural Area.

Rather, J. (2008). River Otters Reappearing on Nassau County's North Shore. New York Times. November 16, 2008.

Tetra Tech., Inc. (Undated). Spreadsheet Tool for the Estimation of Pollutant Load (STEPL). Version 4.0. Developed for the U.S. EPA.

Thieler, E.R., and Hammar-Klose, E.S. (1999). National Assessment of Coastal Vulnerability to Future Sea-Level Rise: Preliminary Results for the U.S. Atlantic Coast. U.S. Geological Survey, Open-File Report 99-593, 1 sheet

Available online at: http://pubs.usgs.gov/of/of99-593/

Town of Huntington (2008). Comprehensive Plan Update and Draft Generic Environmental Impact Statement. Town of Huntington, New York. July 2008. Draft.

U.S. Geological Survey (2003). Hydrogeology and Extent of Saltwater Intrusion in the Northern Part of the Town of Oyster Bay, Nassau County, New York: 1995-98. Water-Resources Investigations Report 03-4288 in cooperation with Nassau County Department of Public Works.

U.S. Fish & Wildlife Service. (2006). Long Island National Wildlife Refuge Complex: Comprehensive Conservation Plan. U.S. Department of the Interior, Fish and Wildlife Service.

U.S. Geological Survey. (2007). USGS Studies in Long Island Sound: Geology, Contaminants, and Environmental Issues.





U.S. Geological Survey. (2004). "Hydrogeology and Extent of Saltwater Intrusion in the Northern Part of the Town of Oyster Bay, Nassau County, New York: 1995-98." In cooperation with Nassau County Department of Public Works, Water-Resources Investigations Report 03-4288.

U.S. Fish & Wildlife Service. (2009). Oyster Bay National Wildlife Refuge: Wildlife and Habitat. U.S. Department of the Interior, Fish and Wildlife Service. URL:http://www.fws.gov/refuges/profiles/WildHabitat.cfm?ID=52563. Site last visited February 17, 2009.

Wilson, Emily. (2008). Long Island Land Cover Analysis (Not published). Center for Landuse Education and Research (CLEAR) University of Connecticut, Dept. of Extension. September 2008, using 2002 Landsat imagery. Unpublished study.

Wright, T., Swann, C., Cappiella, K. and T. Schueler. 2005. Urban Subwatershed Restoration Manual No. 11: Unified Subwatershed and Site Reconnaissance: A User's Manual (Version 2.0) Center for Watershed Protection.





Appendix A

Pollutant Loading Documentation



Pollutant Loading Analysis Oyster Bay Watershed State of the Watershed Report

1.0 INTRODUCTION

A pollutant loading analysis was performed for the Oyster Bay watershed in support of the State of the Watershed Report to assess the potential for increases in nonpoint source (NPS) pollutant loads. The model was used to compare existing nonpoint source (NPS) pollutant loads from the watershed to projected future pollutant loads that would occur under a watershed buildout scenario. The predicted change in pollutant loadings in each of the subwatersheds was then examined to assess their relative vulnerability to future development.

2.0 MODEL DESCRIPTION

A pollutant loading model was developed using the land use/land cover data described in Section 7.0 of the State of the Watershed Report (Fuss & O'Neill 2009). The model was used to compare pollutant loadings from the watershed under existing land use conditions to future pollutant loadings under a watershed buildout scenario. It is important to note that the results of this screening-level analysis are intended for the purposes of comparing existing to future conditions and not to predict future water quality.

The Spreadsheet Tool for the Estimation of Pollutant Load (STEPL), Version 4.0, was used for this analysis. This model was developed for US EPA by Tetra Tech in EPA Region 5 and has since been modified for use in other areas of the country. The model calculates watershed pollutant loads based on land use-related pollutant sources, including urban runoff, septic system failures, stream bank erosion, and agricultural activities. The model also allows simulation of best management practices (BMPs) and Low Impact Development (LID) practices to reduce pollutant loads.

The focus of the Oyster Bay watershed pollutant loading model was future development of presently undeveloped land and re-development of developed land with higher-intensity land uses (See Section 7.2 of Fuss & O'Neill 2009), since these are likely sources of increased pollutant loads. Agricultural NPS pollutant loadings were not considered in the analysis since agricultural land comprises a very small percentage of the land uses within the watershed.

The pollutants modeled in this analysis are the default pollutants contained in the STEPL model: total phosphorus, total nitrogen, biological oxygen demand, and total suspended solids. These pollutants are the major parameters of concern in environmental systems.

Nitrogen and phosphorus are nutrients that promote the growth of algae and plants in water. When this biomass dies and settles to the bottom of water bodies, its decomposition consumes oxygen which is needed by other organisms for survival. Nitrogen is generally present in relatively small quantities compared to other nutrients in salt water systems, such as Oyster Bay/Cold Spring Harbor and Long Island Sound, so limiting its concentration limits the growth of algae. In fresh water systems, such as the stream and impoundments in the Oyster Bay River watershed, phosphorus is the nutrient that is relatively scarce and thus limits algal growth.



Biological oxygen demand (BOD) is a measure of the amount of oxygen that a pollutant consumes as it decomposes (e.g., one pound of BOD consumes one pound of oxygen). A given BOD loading to a water body effectively consumes an equivalent amount of oxygen from that water body, making it unavailable to aquatic organisms.

Total suspended solids (TSS) is a measure of both biodegradable and mineral sediment. Its discharge to a water body results in turbidity and sedimentation. TSS may also have secondary effect; biodegradable TSS exerts a BOD load, and mineral TSS can be associated with particulate phosphorus.

3.0 MODEL PARAMETER SELECTION

STEPL uses algorithms that calculate nutrient and sediment loads from different land uses to determine watershed pollutant loadings. The user specifies several model parameters for each land use in the watershed that are used to estimate runoff quantity and pollutant levels. These parameters include:

- Event Mean Concentrations (EMCs), which are literature values for the mean concentration of a pollutant in stormwater runoff for each land use, and
- Curve Number (CN), which is a measure of the runoff potential of the land surface and is a function of soil type, cover condition, and slope.

The model uses these parameters to estimate the runoff quantity and pollutant loading using data specific to each subwatershed, supplied by the user, as well as default climate data for the subject county In addition to these parameters, the model includes percent impervious surface values for each land use. As part of this project, the model was modified to accept userspecified impervious surface values for each land use.

A literature review was conducted to determine EMCs values for use in the study. STEPL includes default EMC values for each land use within the watershed. Since comparison between existing and proposed watershed conditions is the focus of this project, EMC values were selected to reflect the relative difference in NPS pollutant characteristics between the existing and future land use. Table 1 shows EMC values from several sources for the pollutants of interest.

Table 1. Runoff Event Mean Concentrations (EMCs)

T --- 4 TT--

			Land Use										
Source	Pollutant	Cropland	Open Space	Commercial	High Density Residential	Institutional	Industrial	Low Density Residential	Forest	Transport	Vacant	Units	
	N	1.9	1.5	2	2.2	1.8	2.5	2.2	0.2	3	1.5	mg/L	
STEPL	P	0.3	0.15	0.2	0.4	0.3	0.4	0.4	0.1	0.5	0.15	mg/L	
SILIL	BOD	4	4	9.3	10	7.8	9	10	0.5	9.3	4	mg/L	
	TSS	-	70	75	100	67	120	100	-	150	70	mg/L	
	N*	-	1.2	2.2	2	-	2.1	-	-	2.3	-	mg/L	
NSQD	P	-	0.25	0.22	0.3	-	0.26	-	-	0.25	-	mg/L	
NSQD	BOD	-	4.2	11.9	9	-	9	-	-	8	-	mg/L	
	TSS	-	51	43	48	-	77	-	-	99	-	mg/L	
NURP	N*	-	1.5	1.75	2.6	-	-	-	-	-	-	mg/L	



		Land Use										
Source	Pollutant	Cropland	Open Space	Commercial	High Density Residential	Institutional	Industrial	Low Density Residential	Forest	Transport	Vacant	Units
	P	-	0.1	0.201	0.38	-	-	-	-	-	-	mg/L
	BOD	-	-	9.3	10	-	-	-	-	-	-	mg/L
	TSS	-	70	57	101	-	-	-	-	-	-	mg/L
	N*	-	-	2	2	-	-	2	-	2	-	mg/L
WTM	P	-	-	0.26	0.26	-	-	0.26	-	0.26	-	mg/L
WINI	BOD	-	-			-	-		-		-	mg/L
	TSS	-	-	55	55	-	-	55	-	55	-	mg/L
	N*	-	-	13.7	13.7	-	10.6	10.0	-	-	-	kg/ha/yr
BEC	P	-	-	2.7	2.7	-	2.6	1.9	-	-	-	kg/ha/yr
BEC	BOD	-	-			-			-	-	-	kg/ha/yr
	TSS	-	-	748.0	748.0	-	802.5	456.0	-	-	-	kg/ha/yr
	N*	1.9	1.5	2.2	2	1.8	2.5	1.8	0.2	3	1.5	mg/L
Selected	P	0.3	0.15	0.4	0.2	0.3	0.4	0.3	0.1	0.5	0.15	mg/L
selected	BOD	4	4	10	9.3	7.8	9	7.8	0.5	9.3	4	mg/L
	TSS	-	70	100	75	67	120	67	-	150	70	mg/L

See References for Source Information

The majority of selected values were obtained from STEPL, with adjustments to ensure consistency with other sources. These adjustments include exchanging the multi-family and commercial values, since development included in the multi-family category is assumed to be less intensive in the Oyster Bay/Cold Spring Harbor Complex watershed (See Section 4.0) than typical, and since the default commercial sediment EMC value was lower than sediment levels of other less sediment-intensive land uses. Similarly, since the single-family land use category selected for the watershed includes a majority of large lot residential areas (> 1 acre), the selected EMCs for these areas were reduced to Institutional land use levels.

As part of this project, the impervious surface coefficients in STEPL were adjusted for use in generating existing and proposed impervious surface estimates. The default factors, literature values for factors, and selected factors are presented in <u>Table 2</u>.

Table 2. Impervious Surface Coefficients

	Impervious Cover Coefficients								
Land Use	STEPL	NEMO ¹	Selected						
Commercial	0.85	0.205 - 0.557	0.50						
Industrial	0.70	0.264 - 0.557	0.40						
Institutional	0.50	-	0.30						
Transportation	0.95	0.433	0.43						
Multi-family	0.75	0.09 - 0.39	0.24						
Single-family	0.30	0.065 - 0.12	0.10						
Vacant (developed)	0.70	-	0.41						
Open Space	0.01	0.001 - 0.094	0.01						

¹Sleavin et al. (2000) and Prisloe et al. (2003)

The STEPL model also includes input parameters related to failing septic systems in the watershed. Parameters include the typical population per household and septic system failure



rate. Default values were used for the typical population per household and septic system failure rate due to the limited availability of local data.

4.0 MODEL INPUT DATA

Land use/land cover data that is described in <u>Section 7.0</u> of the State of the Watershed Report was adapted for integration into the STEPL model. Data was prepared in this manner for both the existing conditions and future conditions (watershed buildout) pollutant loading scenarios. STEPL allows fewer land use categories than contained in the land use/land cover data obtained from other sources, so several data categories were combined for use in the model. <u>Table 3</u> summarizes the assignment of STEPL land use categories for each of the land use/land cover data categories.

Table 3. Source Data - STEPL Category Correlation

STEPL Category	Oyster Bay Land Use	Huntington Land Use	
ording Category	Category	Category	
Urban			
Commercial	Commercial	Commercial	
Industrial	Industrial	Industrial	
Institutional	Community Service; Public	Institutional	
Institutional	Services	Histitutional	
Transportation	Transportation	Transportation; Utilities	
Multi family			
Single family	Residential	Residential	
Agriculture			
Vacant (developed)			
Open Space	Recreation &		
Орен зрасе	Entertainment		
Cropland	Agriculture	Agriculture	
Pastureland			
Forest	Vacant;	Open	
Totest	Wild conservation & Parks	Open	

STEPL defines urban land uses differently from agriculture and forest. All urban land uses are lumped into a single land use category, and urban land cover characteristics are distinguished based on land use subcategories, which include commercial, industrial, institutional, transportation, multi-family residential, single-family residential, urban cultivated, vacant (developed), and open space land uses. Almost all of the residential land use in the watershed is single-family so the residential category is considered all single-family in STEPL. Community Service and Public Service in Oyster Bay includes schools and other public buildings consistent with Institutional land use. Recreation and Entertainment land use includes golf courses and country clubs that are characterized as sub-category open space in the Urban land use category. Forest land in STEPL is distinguished from open space by including the Open land use in Huntington, which includes committed open space and is mostly forested, and vacant and wild, conservation and parkland in the Town of Oyster Bay.



Artificial infiltration of stormwater runoff by use of basins or sumps has been practiced on Long Island since the 1930s to recharge collected stormwater back to the groundwater system. In the 1950s, Nassau and Suffolk Counties adopted regulations requiring stormwater to be retained and infiltrated onsite. The drainage areas to recharge basins are determined using delineations from the Nassau County Stormwater Management Reports for subwatersheds, where available, and Nassau County Department of Public Works delineations otherwise. Therefore, the total land area contributing to the pollution runoff model in any particular subwatershed may be greatly reduced from the actual land area. The areas of land included in the STEPL model are outside of the drainage areas to stormwater recharge basins and are assumed to contribute direct runoff to the streams, estuary and harbor. Areas that drain to stormwater basin are considered fully treated, and not contributing to pollutant loads. Data was not available for Huntington, although aerial photographs show that recharge basins are not typically used on the western side of Suffolk County.

Although STEPL is not capable of modeling various densities of residential land use, <u>Table 4</u> summarizes the composition of single-family residential land use based on parcel size ranges.

Table 4. Composition of Single-Family Residential Land Use Based on Parcel Size

	Residential				
Watershed	Parcels	0 - 22k sf	22k sf - 2 ac	2 - 5 acres	> 5 acres
Bailey Arboretum	220	33.6%	39.5%	20.0%	6.8%
Beaver Brook	1230	23.5%	19.8%	42.3%	14.4%
Center Island	369	63.4%	10.6%	20.9%	5.1%
Cold Spring Brook*	1603*	41.2%	45.7%	12.9%	0.2%
Cold Spring Harbor*	342*	12.6%	30.1%	51.8%	5.6%
Kentuck Brook	1798	83.2%	10.5%	5.5%	0.8%
Lloyd Neck*					
Mill Neck Creek	1686	90.0%	5.9%	2.4%	1.7%
Mill River	863	66.4%	12.4%	16.8%	4.4%
Oyster Bay Harbor	864	69.7%	6.3%	18.4%	5.7%
Tiffany Brook	554	6.9%	34.3%	54.0%	4.9%
Upper Kentuck Brook	310	40.3%	33.5%	24.8%	1.3%
Upper White's Creek	1215	71.5%	16.3%	11.9%	0.2%
White's Creek	628	96.5%	2.1%	1.4%	0%

^{*} Parcel data is not available for the portion of the watershed in Huntington. Therefore, there is no data for the Lloyd Neck subwatershed and only partial data for the Cold Spring Brook and Cold Spring Harbor subwatersheds. The residential parcel size counts and area distributions presented are from parcels in the town of Oyster Bay only, which comprises 57% of the Cold Spring Harbor subwatershed and 42% of the Cold Spring Brook subwatershed.

Septic system data is also required for the STEPL model. The majority of the Oyster Bay/Cold Spring Harbor Complex Watershed is not serviced by sewer systems. The Oyster Bay Sewage Treatment Plant services the downtown area of Oyster Bay Hamlet in the subwatershed White's Creek and a portion of Oyster Bay Harbor and Mill River. A small portion of the southern watershed is also services by sewer system in the Cold Spring Brook subwatershed. None of the villages in the Town of Huntington inside the Oyster Bay/Cold Spring Harbor Complex watershed have sewer service. The sewer service area GIS data from the Town of Oyster Bay was used to screen out developed parcels in the Oyster Bay/Cold Spring Harbor Complex Watershed watershed; parcels located completely outside of mapped sewer service areas were



assumed to be served by septic systems. Since the majority of the watershed is residential properties, it was assumed that each parcel not within a sewer service area was serviced by one septic tank. The number of septic systems in Huntington was estimated by multiplying the density of septic systems in Oyster Bay in each watershed area by the area of the subwatershed in Huntington. The number of septic systems in Lloyd Harbor was estimated by multiplying the density of septic systems in Cold Spring Harbor by the residential area in the subwatershed.

Hydrologic Soil Group (HSG) data are also required by the model. This data, which is available from the U.S. Natural Resource Conservation Service (NRCS), describes the infiltration characteristics of most soils in the county. Identifiers for the soil groups range from Type A soils, including sands and other soils that are very well drained and result in little runoff, to Type D soils, which are poorly drained, often being compacted, having high clay content and high groundwater levels. Soils data were compiled for each subwatershed and assimilated into an average HSG value. Each subwatershed was found to have Type B soil characteristics on average.

5.0 CURRENT POLLUTANT LOADINGS

5.1 Input

The following land use data were entered into the STEPL spreadsheet to create an existing conditions pollutant loading model. These inputs were reduced form the data presented in Section 7.1 of the Baseline Watershed Assessment. In general, agricultural land use (i.e. cropland) was the least common of the non-urban uses. Urban uses dominate in all subwatersheds, although forests compose significant areas in Lloyd Neck and Mill River subwatersheds.

Table 5. Land Use Input Data

		Land Use A	Area (ac)	Land Use Area Composition			
Watershed	Urban	Cropland	Forest	Total	Urban	Cropland	Forest
Bailey Arboretum	428		74	502	85%		15%
Beaver Brook	2,729		596	3,325	82%		18%
Center Island	656		106	762	86%		14%
Cold Spring Brook	1,849	54	1,090	2,993	62%	1.8%	36%
Cold Spring Harbor	2,652		300	2,952	90%		10%
Kentuck Brook	440		95	535	82%		18%
Lloyd Neck	684		211	895	76%		24%
Mill Neck Creek	827		94	921	90%		10%
Mill River	1,132	15	656	1,803	63%	0.8%	36%
Oyster Bay Harbor	1,389		185	1,574	88%		12%
Tiffany Brook	1,132		180	1,312	86%		14%
Upper Kentuck Brook							
Upper White's Creek							
White's Creek	272		20	292	93%		7%
Total	14,190	69	3,607	17,866	79%	0.4%	20%

<u>Table 6</u> presents the composition of the urban land use areas listed in <u>Table 5</u>. In general, residential land use is the most prevalent in the urbanized areas, although institutional and



transportation corridors are a significant portion of the urban land use throughout the watershed. As discussed in Section 4, only land area outside of the drainage areas to recharge basins are included in the pollutant loading analysis. Since Upper Kentuck Brook and Upper White's Creek are completely self-contained and drain to recharge basins, there is no land area contributing to pollutant loads from these subwatersheds.

Table 6. Urban Land Use Composition

	Urban Land Use Composition (%)								
Watershed	Commercial	Industrial	Institutional	Transport- ation	Dense Residential	Rural Residential	Open Space		
Bailey Arboretum			9.9	6.5	27.9	55.7			
Beaver Brook			3.8	4.6	9.9	62.7	19.0		
Center Island			10.9	7.4	11.7	63.9	6.2		
Cold Spring Brook	1.9		4.7	11.1	52.8	29.6			
Cold Spring Harbor	0.9	0.2	11.5	6.4	14.2	66.9			
Kentuck Brook	2.7		8.6	11.1	42.9	34.6			
Lloyd Neck				6.5		93.5			
Mill Neck Creek	0.6		3.1	12.1	42.8	41.0	0.3		
Mill River	1.5		7.5	6.4	17.6	57.7	9.3		
Oyster Bay Harbor	1.8	0.2	8.2	7.8	13.0	68.6	0.4		
Tiffany Brook	0.1		20.7	5.6	17.7	55.7	0.1		
Upper Kentuck									
Brook									
Upper White's Creek		-							
White's Creek	19.8	2.4	10.7	15.9	42.3	8.5	0.4		

Table 7 presents the total estimated number of septic systems in the Oyster Bay/Cold Spring Harbor Complex watershed, determined using the methods described in Section 4.0. Septic systems are assumed to be present at lots not included in or abutting the sewer service area shown in the Baseline Watershed Assessment report. As discussed in Section 4.0, estimates were made for the number of septic systems in Lloyd Harbor and the portions of Cold Spring Harbor and Cold Spring Brook in Huntington for which no parcel data was available based on the average septic system density within the subwatershed in Oyster Bay. Note that these septic system estimates and are intended only for estimating increases in NPS pollutant loads and should not be used for other purposes. The majority of W

Table 7. Estimated Number of Septic Systems

Watershed	Number of Septic Systems
Bailey Arboretum	231
Beaver Brook	1345
Center Island	409
Cold Spring Brook	1926
Cold Spring Harbor	830
Kentuck Brook	237
Lloyd Neck	110
Mill Neck Creek	1803
Mill River	868



	Number of
Watershed	Septic
	Systems
Oyster Bay Harbor	345
Tiffany Brook	658
Upper Kentuck Brook	237
Upper White's Creek	929
White's Creek	35

5.2 Results

<u>Table 8</u> presents total estimated loadings of total nitrogen, total phosphorus, and TSS for each subwatershed, as well as the loading rate for each subwatershed. In terms of total existing loads, the largest loads of pollutants originate in the larger subwatersheds Cold Spring Brook, Cold Spring Harbor, and Beaver Brook. As such, pollutants from these areas are likely to have the largest effect on water quality in Oyster Bay/Cold Spring Harbor Complex.

Since these watersheds are large compared to others, it is useful to look at the data in terms of the loading rate, which is the load of pollutant per unit land area. A high loading rate indicates dense pollutant sources, which suggests that implementation of best management practices (BMPs) in these areas would be more effective in reducing pollutant loads. Pollutant loading rates are relatively uniform between many of the watersheds. The highest loading rates for Nitrogen, Phosphorus and sediment are from White's Creek, Mill Neck Creek, Center Island and, Cold Spring Harbor. These subwatersheds have low percentages of the stormwater runoff treated in recharge basins, dense residential populations (presented in <u>Table 4</u>), and commercial and institutional land uses.

Table 8. Estimated Existing Pollutant Loads

	% Contribu	N	P	Sedimen t	N	Р	Sedimen t
Watershed	ting to Recharg e Basins	lb/yr	lb/yr	t/yr	lb/ac-yr	lb/ac-yr	t/ac-yr
Cold Spring Brook (4,851 ac)	39%	17,479	3,113	324	3.6	0.6	0.07
Cold Spring Harbor (2,953 ac)	0%	16,476	2,834	314	5.6	1.0	0.11
Beaver Brook (4,862 ac)	31%	14,789	2,677	269	3.0	0.6	0.06
Oyster Bay Harbor (1,612 ac)	2%	8,769	1,494	173	5.4	0.9	0.11
Mill Neck Creek (968 ac)	5%	8,491	1,765	132	8.8	1.8	0.14
Mill River (2,175 ac)	17%	7,796	1,494	140	3.6	0.7	0.06
Tiffany Brook (1,923 ac)	31%	7,670	1,386	137	4.0	0.7	0.07
Kentuck Brook (1,538 ac)	65%	5,942	1,483	71	3.9	1.0	0.05
Center Island (762 ac)	0%	4,307	799	78	5.7	1.0	0.10
Lloyd Neck (894 ac)	0%	3,661	697	69	4.1	0.8	0.08
Bailey Arboretum (527 ac)	5%	2,929	504	53	5.6	1.0	0.10
White's Creek (292 ac)	0%	2,814	436	61	9.6	1.5	0.21
Upper White's Creek (1,317 ac)	100%	1,155	452	0	0.9	0.3	0.00
Upper Kentuck Brook (451 ac)	100%	295	115	0	0.7	0.3	0.00



- White's Creek. Although the White's Creek subwatersheds is the smallest in the study area, it is characterized by the dense residential and highest percent composition of commercial (18.4%) and industrial (2.2%) land uses in the watershed. For comparison, the next highest percentage of commercial land use is Cold Spring Brook with only 3.8% of the total subwatershed area. Transportation and other land uses are in comparable proportions to other subwatersheds in Oyster Bay. White's Creek does not contain any recharge basins, and is therefore characterized by high pollutant loading rates.
- Mill Neck Creek. Mill Neck Creek is characterized by both relatively high total pollutant loads and pollutant loading rates due to a high proportion of dense residential land use (42.8%). Other land uses are similar to other subwatershed areas. A major factor contributing the high pollutant loading rates in this subwatershed is that only 2 recharge basins are present in the watershed, with only 5% of the total area treated through recharge basins.
- *Center Island*. Center Island is characterized by rural residential land uses and no recharge basins within the subwatershed. The high loading rates for nitrogen and phosphorus are due to the septic systems.
- Cold Spring Harbor and Oyster Bay Harbor. Cold Spring Harbor and Oyster Bay Harbor
 are moderately-sized subwatersheds in which stormwater is conveyed to the harbor
 complex through stormwater collection systems and overland flow. These coastal areas
 are heavily developed, and only very small portions of these subwatersheds are served
 by recharge basins. Consequently, existing pollutant loads and loading rates for these
 subwatersheds are relatively high.

5.3 Discussion

The sources of pollutants in the watershed are generally associated with urban land use, as presented in <u>Table 9</u>. Note that urban areas are estimated to account for between 71.3% and 98.1% of the NPS pollutant load in the watershed and comprises 82% of the total watershed land use area (See <u>Table 5</u>). Significant nutrient loads are contributed by septic systems in the watershed, with close to 12.0% of the nitrogen load and 26.1% of the phosphorus load.

Table 9. Pollutant Source by Land Use

Source	N Load	P Load	Sediment Load
Urban	84.3%	67.0%	98.1%
Septic	14.4%	30.1%	0.0%
Forest	0.9%	2.4%	0.7%
Cropland	0.4%	0.4%	1.2%

By subdividing the urban pollutant loads into the distinct urban categories that were included in the model (See <u>Table 10</u>), it is apparent that dense residential and transportation land uses account for the largest NPS pollutant loads in the watershed, with transportation use being the



largest source of pollutant loads. The combined residential land uses are significant sources since it is the predominant land uses in the watershed (See <u>Table 6</u>). Institutional land uses also contribute approximately 7% of the total pollutant loads. Transportation use is a significant source since it has the highest pollutant EMCs (See <u>Table 1</u>).

Table 10. Pollutant Loads and Sources for Urban Categories

Urban Land Use	N Load	P Load	Sediment Load	N Load	P Load	Sediment Load
	lb/year	lb/year	tons/year	%	%	%
Commercial	875	159	20	2%	3%	2%
Industrial	67	11	2	0%	0%	0%
Institutional	3,735	622	70	10%	11%	9%
Transportation	11,195	1,866	280	29%	32%	35%
Dense Residential	9,590	959	180	24%	16%	22%
Rural Residential	12,968	2,161	241	33%	37%	30%
Open Space	804	80	19	2%	1%	2%
Total	39,233	5,859	811	100%	100%	100%

6.0 FUTURE POLLUTANT LOADINGS

6.1 <u>Input</u>

Future land use estimates, presented in <u>Table 11</u>, were used in the STEPL model to simulate a watershed buildout scenario. Also summarized in <u>Table 11</u> is the predicted "increase" in urban land use for each subwatershed. These model inputs were derived form the data presented in the State of the Watershed report. There is a limited amount of developable land in the watershed and all of it is currently forested, such that the increase in urban area for each subwatershed includes a corresponding reduction in forested land.

Table 11. Future Land Use Input Data

	Land Use Area (ac)			Land Us	Urban			
Watershed	Urban	Cropland	Forest	Total	Urban	Cropland	Forest	Increase
Bailey Arboretum	453		49	502	90%		10%	5.8%
Beaver Brook	2,826		499	3,325	85%		15%	3.6%
Center Island	695		67	762	91%		9%	5.9%
Cold Spring Brook	1,852	54	1,087	2,993	62%	1.8%	36%	0.2%
Cold Spring Harbor	2,677		275	2,952	91%		9%	0.9%
Kentuck Brook	480		55	535	90%		10%	9.1%
Lloyd Neck	684		211	895	76%		24%	0.0%
Mill Neck Creek	835		85	920	91%		9%	1.0%
Mill River	1,273	15	515	1,803	71%	0.8%	29%	12.5%
Oyster Bay Harbor	1,517		57	1,574	96%		4%	9.2%
Tiffany Brook	1,209		103	1,312	92%		8%	6.8%
Upper Kentuck Brook								
Upper White's Creek								
White's Creek	280		12	292	96%		4%	2.9%
Total	14,781	69	3,015	17,865	83%	0.4%	17%	4.2%



The same break-down of the urban land uses presented in <u>Table 5</u> will be used for the future pollutant analysis. Much of the future development is anticipated in areas that are currently zoned for residential uses, and that is the majority of the current land use type.

6.2 Results

<u>Table 12</u> presents projected future pollutant loads under a watershed buildout scenario. A slight increase in pollutant loads is predicted in many subwatersheds. The Mill River subwatershed is predicted to have the highest increase in nitrogen and sediment loads. Large increases are also predicted in nitrogen and phosphorus in the Oyster Bay Harbor subwatershed. Upper Kentuck Brook is anticipated to have no change in pollutant loads since no developable land exists in the subwatershed.

Table 12. Projected Future Pollutant Loads and Load Increases

	Tot	al Future l	Load	Projec	ted Load	Increase
Watershed	N	Р	Sediment	N	P	Sediment
	lb/yr	lb/yr	t/yr	lb/yr	lb/yr	t/yr
Bailey Arboretum (527 ac)	3,076	523	56	147	19	3
Beaver Brook (4,862 ac)	15,224	2,733	278	435	57	9
Center Island (762 ac)	4,521	829	83	214	30	5
Cold Spring Brook (4,851 ac)	17,502	3,115	325	23	3	0
Cold Spring Harbor (2,953						
ac)	16,614	2,853	317	138	19	3
Kentuck Brook (1,538 ac)	6,239	1,521	78	297	38	6
Lloyd Neck (894 ac)	3,661	697	69	0	0	0
Mill Neck Creek (968 ac)	8,549	1,772	133	58	7	1
Mill River (2,175 ac)	8,563	1,596	157	767	102	16
Oyster Bay Harbor 1,612 ac)	9,499	1,597	188	730	103	15
Tiffany Brook (1,923 ac)	8,112	1,447	146	443	61	9
Upper Kentuck Brook (451						
ac)	295	115	0	0	0	0
Upper White's Creek (1,317						
ac)	1,155	452	0	0	0	0
White's Creek (292 ac)	2,893	447	63	79	11	2
Total	105,903	19,700	1,891	3,332	451	70

<u>Table 13</u> presents the projected future pollutant loads in terms of the projected load increase based on existing loads (percent increase) and loading rate increase for each subwatershed. These criteria were selected to determine the most significant changes in watershed loadings since they control for the existing load quantities (percent increase) and watershed size (rate increase). The highlighting in <u>Table 13</u> identifies areas with the high (orange), moderate (yellow), and low (green) pollutant loadings or loading rate increases in the Oyster Bay watershed.



Table 13. Projected Pollutant Loading Rate Increases and Load Increases

Watershed	Projecto	ed Future l Rate	Loading	Projected Load Increase						
	N	P	Sediment	N	P	Sediment				
	lb/ac-yr	lb/ac-yr	lb/ac-yr	lb/yr	lb/yr	t/yr				
Bailey Arboretum (527 ac)	5.8	0.99	0.107	5%	4%	6%				
Beaver Brook (4,862 ac)	3.1	0.56	0.057	3%	2%	3%				
Center Island (762 ac)	5.9	1.09	0.109	5%	4%	6%				
Cold Spring Brook 4,851 ac)	3.6	0.64	0.067	0%	0%	0%				
Cold Spring Harbor (2,953 ac)	5.6	0.97	0.107	1%	1%	1%				
Kentuck Brook (1,538 ac)	4.1	0.99	0.051	5%	3%	9%				
Lloyd Neck (894 ac)	4.1	0.78	0.077	0%	0%	0%				
Mill Neck Creek (968 ac)	8.8	1.83	0.137	1%	0%	1%				
Mill River (2,175 ac)	3.9	0.73	0.072	10%	7%	11%				
Oyster Bay Harbor (1,612 ac)	5.9	0.99	0.117	8%	7%	9%				
Tiffany Brook (1,923 ac)	4.2	0.75	0.076	6%	4%	7%				
Upper Kentuck Brook (451 ac)	0.7	0.26	0.000	0%	0%	0%				
Upper White's Creek (1,317 ac)	0.9	0.34	0.000	0%	0%	0%				
White's Creek (292 ac)	9.9	1.53	0.214	3%	3%	3%				

Several of the subwatersheds are predicted to experience significantly higher increases in pollutant loads and loading rates under a watershed buildout scenario. These include Tiffany Brook, Mill River, Oyster Bay Harbor, and Kentuck Brook watersheds. The build-out conditions of the Mill River and Oyster Bay Harbor subwatersheds are projected to result in greater than 5% increase in pollutant loading rates for nitrogen, phosphorus and sediment loads. The increase in urban land use with a corresponding decrease in forest, with a proportion of the new urban land is likely to consist of new residential and industrial development. The increase in pollutant loads is the future is relatively small across the watershed because there is little opportunity for redevelopment in existing residential areas and for development in forested or vacant areas.



7.0 REFERENCES

Fuss & O'Neill, Inc. (2009) "State of the Watershed Report: Oyster Bay/Cold Spring Harbor." Prepared for the Friends of the Bay in cooperation with the Town of Oyster Bay.

NQQD (2004). Findings from the National Stormwater Quality Database, Research Progress Report. Prepared by the Center for Watershed Protection.

NURP (1983). Results of the Nationwide Urban Runoff Program. U.S. Environmental Protection Agency Water Planning Division, PB 84-185552, Washington, D.C.

Tetra Tech., Inc. Spreadsheet Tool for the Estimation of Pollutant Load (STEPL). Version 4.0. Developed for the U.S. EPA

University of Connecticut Center for Land Use Education and Research (CLEAR). Connecticut's Changing Landscape – Statewide Land Cover. URL: www.clear.uconn.edu/projects/landscape/statewide_landcover.htm.

WTM (2001). Watershed Treatment Model User's Guide - Version 3.1. Prepared by the Center for Watershed Protection.



Appendix B

Watershed Field Inventory Documentation

ATERSHED: DYSENDAN	SUBWATERSHED: Bailey ANDWETAM	UNIQUE SITE ID: 3A -	HS1-01
ATE: 8 /26/09	ASSESSED BY: CAMERA ID:	Pic#: 18	5-188
MAP GRID:	LAT 40.53 '27 "LONG 73.35	'17.3" LMK#	
A. SITE DATA AND BASIC CLASSIFIC			
Rychield Rd But parking/main facility SIC code (if available):	Category: Commercial Industrial Institutional Municipal Transport-Related Basic Description of Operation:	Miscellaneous ☐ Golf Course ☐ Marina ☐ Animal Facility	
NPDES Status: Regulated Unregulated Unknown	Locust Valley Int. School Bus s	torage & gange	- INDEX*
B. VEHICLE OPERATIONS \[\subseteq N/A (Skip to part C)	Observed Pollution Son	rce? N
B1. Types of vehicles: Fleet vehicles:	icles School buses Other:		
B2. Approximate number of vehicles	: 15 + 10 vans/other		
	apply): Maintained Repaired Recycled Fueled Was	shed Stored	0
B4. Are vehicles stored and/or repaired Are these vehicles lacking runoff dive	ed outside? Y N Can't Tell ersion methods? Y N Can't Tell		0
B5. Is there evidence of spills/leakage			0
B6. Are uncovered outdoor fueling ar			
B7. Are fueling areas directly connect	ted to storm drains? Y N Can't Tell		0
B8. Are vehicles washed outdoors?	Y N Can't Tell		0
OUTDOOR MATERIALS N/A	hed discharge to the storm drain? Y N Can't	To the same of the same of the same of	
	present? Y N Can't Tell	Observed Pollution Sou	rce?
If yes, are they uncovered and drainin		Tell	0
C2. Are materials stored outside? Where are they stored? grass/dirt	Y ☐ N ☐ Can't Tell If yes, are they ☐ Liquid ☐ So area ☐ concrete/asphalt ☐ bermed area	lid Description:	0
C3. Is the storage area directly or indi	rectly connected to storm drain (circle one)? XY N	Can't Tell	0
C4. Is staining or discoloration around	the area visible? Y N Can't Tell		0
C5. Does outdoor storage area lack a c	cover? Y N Can't Tell		0
C6. Are liquid materials stored withou	at secondary containment? 🛛 Y 🔲 N 🔲 Can't Tell		0
C7. Are storage containers missing lab	pels or in poor condition (rusting)? TY N Can	t Tell	0
D. WASTE MANAGEMENT 🗌 N/A (Skip to part E)	Observed Pollution Sou	rce?
D1. Type of waste (check all that app	ly): 🛮 Garbage 🖾 Construction materials 🔲 Hazardo		0
evidence of leakage (stains on gro		dition Leaking or	0
D3. Is the dumpster located near a stor If yes, are runoff diversion method	m drain inlet? Y N Can't Tell ds (berms, curbs) lacking? Y N Can't Tell		0
E. PHYSICAL PLANT \(\subseteq \text{N/A}\) (Skip to		Observed Pollution Sour	rce?
E1. Building: Approximate age: 5 Evidence that maintenance results in o	yrs. Condition of surfaces: Clean X Stained lischarge to storm drains (staining/discoloration)? Y	l Dirty Damaged	0
	ial pollution source: denotes confirmed pollute	and the contract of the contra	

Surface material Paved/Concrete Gravel Permea					Dir	ty [_] B	reak	ing	up					100	0	
23. Do downspouts discharge to impervious surface? Y Are downspouts directly connected to storm drains?	П. И ∑		't kn				ne vi knov								70	0	
24. Evidence of poor cleaning practices for construction activities	s (stain	s lead	ing t	to st	orm	dra	in)?		Y [IN	X	Car	n't T	Cell		0	
F. TURF/LANDSCAPING AREAS N/A (skip to part G)	\$ 9	tu	4		かが			trees.	HIVE	S. Co	- HI	S Mail	OUNU.	ourc	e?	N	
71. % of site with: Forest canopy% Turf grass% I	andsca	ping	1	%	Ba	re S	oil_	9	6							0	
2. Rate the turf management status: High Medium	Low														0	0	1,1
3. Evidence of permanent irrigation or "non-target" irrigation		IN	٦c	an'	t Te	1				_			- 7		1	ō	
	7Y	Пи			n't'	-	_			-	-	_	_			Ö	
5. Do landscape plants accumulate organic matter (leaves, grass clippin		_	_	•			ace?		Υ[IN		Can	't T	ell	100	O	
G. STORM WATER INFRASTRUCTURE N/A (skip to pa	SALE DESIGNATION	N. Take	PE .		W)			C/CS1	- 0.0	1000	1000	SUMBE		ourc	e?	A	
G1. Are storm water treatment practices present? Y N	Unk	nown	Ify	es,	plea	se d	escri			-		-				0	
G2. Are private storm drains located at the facility? Y N Is trash present in gutters leading to storm drains? If so, o				ex b	elov	v.										0	
Index Rating	for Ac	cumu	latio	n in	Gut	ters									1		-
Clean								Fi	lthy								
Sediment	□ 3					1				=	5						
Organic material 1 2	3				H	1				=	5						
Litter 1 2 G3. Catch basin inspection – Record SSD Unique Site ID here:	3	_	Cond	1:4: -	^	7 5			Clea		5						_
INITIAL HOTSPOT STATUS - INDEX RESULTS	- 1000		John	iiiio	11.	100	ity	and the	Cica	111		10	7	-		-	
A DISPERSION OF THE SECRET SERVICE SER	1 0				<i>r</i> .	10		Sont							-11-11	1	-
Not a hotspot (fewer than 5 circles and no boxes checked)			-												45		
Confirmed hotspot (10 to 15 circles and/or 1 box checked)	Sever	e not	spot	(>1	5 C11	Cles	and	OI /	or	mor	e bo	oxes	che	ckec	1)	-	
Follow-up Action: Refer for immediate enforcement	-	-		-	-	4	-	1	27						#		-
	1 1	1.1	Th.	-	-	100	-	-		_	-			-	1	1	
Al Nuggest follow-up on-site inspection		5	1 0		DIVY			-		1	12.11	-			1		
Suggest follow-up on-site inspection Test for illicit discharge	\Box	3	L O		DIVI-		+	9V	13	5		F			L	_	W
Test for illicit discharge		Russy	O					9V	13	5		-		-	4	-	S
		Marchary	_ K					ŶV	13	5			1	1	1	-	B
☐ Test for illicit discharge ☐ Include in future education effort ☐ Check to see if hotspot is an NPDES non-filer ☐ Onsite non-residential retrofit		dureum	\ \(\mathbb{E} \)					Ŷ	23	5				1	1		N
☐ Test for illicit discharge ☐ Include in future education effort ☐ Check to see if hotspot is an NPDES non-filer ☐ Onsite non-residential retrofit ☐ Pervious area restoration; complete PAA sheet and record		durenny	_ r					4	13	5]	7	1	3	2
☐ Test for illicit discharge ☐ Include in future education effort ☐ Check to see if hotspot is an NPDES non-filer ☐ Onsite non-residential retrofit ☐ Pervious area restoration; complete PAA sheet and record ☐ Unique Site ID here:	-10	dhewan	(O.					90	15	Ś	1]	7	4	3	9
☐ Test for illicit discharge ☐ Include in future education effort ☐ Check to see if hotspot is an NPDES non-filer ☐ Onsite non-residential retrofit ☐ Pervious area restoration; complete PAA sheet and record ☐ Unique Site ID here:	100/	dineum	2					97	15	s ve	1]	7	4	3	9
Test for illicit discharge ☐ Include in future education effort ☐ Check to see if hotspot is an NPDES non-filer ☐ Onsite non-residential retrofit ☐ Pervious area restoration; complete PAA sheet and record ☐ Unique Site ID here: ☐ Schedule a review of storm water pollution prevention plan	C Hop L	ducum	2					47	13	s ve	1]	/		3	9
Test for illicit discharge Include in future education effort Check to see if hotspot is an NPDES non-filer Onsite non-residential retrofit Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan	JCKepu	duraman						47	15	\$ ve	1]			3	N A
Test for illicit discharge Include in future education effort Check to see if hotspot is an NPDES non-filer Onsite non-residential retrofit Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan totes:	JCHep U	durann	3					97	13	\$ 680		1]			3	N A
Test for illicit discharge Include in future education effort Check to see if hotspot is an NPDES non-filer Onsite non-residential retrofit Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan totes:	SCHopu	dhewan	3					97	13	5	1		7			3	N 132
Test for illicit discharge Include in future education effort Check to see if hotspot is an NPDES non-filer Onsite non-residential retrofit Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan Notes: PAVAMENT Agrand looks dean where	SCHOOL	distance						4	1/4	S CSSA	1	77]			3	N A A A A A A A A A A A A A A A A A A A
Test for illicit discharge Include in future education effort Check to see if hotspot is an NPDES non-filer Onsite non-residential retrofit Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan Notes: Pavement Igranel looks dean where	J.C.Hop U	dinamin of the survey							100	S SA	1		7			3	N S Ati
Test for illicit discharge Include in future education effort Check to see if hotspot is an NPDES non-filer Onsite non-residential retrofit Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan Notes: Pavament Igranel looks dean where buses are stored In front and alarg permeter, Storage	SCHop L	durenn					<i>b</i>		100	\$ C\$\$	The transfer of the transfer o	1	7			3	N A A A A A A A A A A A A A A A A A A A
Test for illicit discharge Include in future education effort Check to see if hotspot is an NPDES non-filer Onsite non-residential retrofit Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan Notes: Paramet looks dean where buses are stored In front and along perimeter, Storage of misc. Oil storage (old equipment)		duranan							13	\$ C.S.S. (S.S.	1		7			3	N 132
Test for illicit discharge Include in future education effort Check to see if hotspot is an NPDES non-filer Onsite non-residential retrofit Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan Notes: Paramet looks dean where buses are stored In front and along perimeter, Storage of misc. Oil storage (old equipment)		dhewan					l con		13	5 35 4	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1	7			3	N 150
Test for illicit discharge Include in future education effort Check to see if hotspot is an NPDES non-filer Onsite non-residential retrofit Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan Notes: PAVAMENT Agrand looks dean where buses are stored In Front and alarg permeter, Storage		dhewan	3				l con		13	5	1	7	7			3	N 100 00 00 00 00 00 00 00 00 00 00 00 00

Hotspot Site Investigation

HSI

	17	NQUE SITE ID: 25+	T-SON COL
ATE: \$ 1 251 04	ASSESSED BY: LAB CAMERA ID:	PIC#: 7	2-78
MAP GRID:		De LMK#	
A. SITE DATA AND BASIC CLASSIFICATION			
Name and Address:		cellaneous Golf Course	
Municipal Lot	☐ Transport-Related ☐ M	M arina	
SIC code (if available):	Basic Description of Operation:	animal Facility	
NPDES Status: Regulated Unregulated Unknown	· Outhormall bootiques Parking	1	- INDEX*
B. VEHICLE OPERATIONS MINA (Skip to	part C)	Observed Pollution So	urce? N
B1. Types of vehicles: Fleet vehicles			
B2. Approximate number of vehicles: _35	_Cars		
B3. Vehicle activities (circle all that apply):	Maintained Repaired Recycled Fueled Washed	Stored	0
B4. Are vehicles stored and/or repaired outsi Are these vehicles lacking runoff diversion n	de? Y N Can't Tell nethods? Y N Can't Tell		0
B5. Is there evidence of spills/leakage from v			0
B6. Are uncovered outdoor fueling areas pre			0
B7. Are fueling areas directly connected to si			0
B8. Are vehicles washed outdoors? \[\subseteq Y \]			10
Does the area where vehicles are washed disc	charge to the storm drain? Y N Can't Tell		0
Outdoor Materials N/A (Skip to	part D) O	bserved Pollution Sou	1111
Outdoor Materials N/A (Skip to C1. Are loading/unloading operations presen	<i>part D</i>) O t? ☐ Y ☐ N ☐ Can't Tell	bserved Pollution Sou	1
Outdoor Materials N/A (Skip to C1. Are loading/unloading operations present fyes, are they uncovered and draining towards.)	part D) t?	bserved Pollution Sou	irce?
Outdoor Materials N/A (Skip to C1. Are loading/unloading operations present fyes, are they uncovered and draining towards.)	t? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell N Can't Tell If yes, are they Liquid Solid I	bserved Pollution Sou	irce?
Outdoor Materials N/A (Skip to Outdoor Materials N/A (Skip to C1. Are loading/unloading operations present yes, are they uncovered and draining toward C2. Are materials stored outside? Y Where are they stored? grass/dirt area	t? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell N Can't Tell If yes, are they Liquid Solid I concrete/asphalt bermed area	Observed Pollution Sou	O O
Outdoor Materials N/A (Skip to C1. Are loading/unloading operations present fyes, are they uncovered and draining toward. Are materials stored outside? Y Nhere are they stored? grass/dirt area C3. Is the storage area directly or indirectly compared to the control of the contr	t?	Observed Pollution Sou	O O
Outdoor Materials N/A (Skip to Outdoor Materials N/A (Skip to C1. Are loading/unloading operations present fyes, are they uncovered and draining toward C2. Are materials stored outside? Y Yhere are they stored? grass/dirt area C3. Is the storage area directly or indirectly c24. Is staining or discoloration around the area.	t? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell N Can't Tell If yes, are they Liquid Solid I concrete/asphalt bermed area connected to storm drain (circle one)? Y N ea visible? Y N Can't Tell	Observed Pollution Sou	O O O
Outdoor Materials N/A (Skip to Outdoor Materials N/A (Skip to C1. Are loading/unloading operations present fyes, are they uncovered and draining toward C2. Are materials stored outside? Y Y where are they stored? grass/dirt area C3. Is the storage area directly or indirectly c2. As the storage area directly or indirectly c2. Does outdoor storage area lack a cover?	t? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell N Can't Tell If yes, are they Liquid Solid I concrete/asphalt bermed area connected to storm drain (circle one)? Y N ea visible? Y N Can't Tell Y N Can't Tell	Observed Pollution Sou	0 0 0 0
OUTDOOR MATERIALS N/A (Skip to OUTDOOR MATERIALS N/A (Skip to C1. Are loading/unloading operations present fyes, are they uncovered and draining toward C2. Are materials stored outside? Y Where are they stored? grass/dirt area C3. Is the storage area directly or indirectly c3. Is staining or discoloration around the are C5. Does outdoor storage area lack a cover?	t? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell N Can't Tell If yes, are they Liquid Solid I concrete/asphalt bermed area connected to storm drain (circle one)? Y N can't Tell Y N Can't Tell dary containment? Y N Can't Tell	Description:	0 0 0 0 0
OUTDOOR MATERIALS N/A (Skip to OUTDOOR MATERIALS N/A (Skip to C1. Are loading/unloading operations present f yes, are they uncovered and draining toward C2. Are materials stored outside? Y Shere are they stored? grass/dirt area C3. Is the storage area directly or indirectly c24. Is staining or discoloration around the are C5. Does outdoor storage area lack a cover? C6. Are liquid materials stored without second C7. Are storage containers missing labels or	t? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Liquid Solid II rds concrete/asphalt bermed area connected to storm drain (circle one)? Y N rea visible? Y N Can't Tell rdary containment? Y N Can't Tell rin poor condition (rusting)? Y N Can't Tell	Description: Can't Tell	O O O O O O
OUTDOOR MATERIALS N/A (Skip to OUTDOOR MATERIALS N/A (Skip to C1. Are loading/unloading operations present yes, are they uncovered and draining toward towar	t? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain (circle one)? Y N Can't Tell rds visible? Y N Can't Tell	Description: Can't Tell bserved Pollution Sou	O O O O O O CO
OUTDOOR MATERIALS N/A (Skip to OUTDOOR MATERIALS N/A (Skip to C1. Are loading/unloading operations present fyes, are they uncovered and draining toward C2. Are materials stored outside? Y Where are they stored? grass/dirt area C3. Is the storage area directly or indirectly of C4. Is staining or discoloration around the area C5. Does outdoor storage area lack a cover? C6. Are liquid materials stored without second C7. Are storage containers missing labels or in the condition of	t? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain (circle one)? Y N rea visible? Y N Can't Tell rdary containment? Y N Can't Tell rdary condition (rusting)? Y N Can't Tell rdary condition (rusting)? Y N Can't Tell rdary Can't Tell rdary Condition (rusting)? Y N Can't Tell rdary Can't Tell rdary Can't Tell rdary Condition (rusting)? Y N Can't Tell rdary Can't Tell rdary Can't Tell rdary Can't Tell rdary Condition (rusting)? Y N Can't Tell rdary Can't Tell rdary Can't Tell rday Can't Tell	Description: Can't Tell bserved Pollution Sounaterials	O O O O O O O O O O O O O O O O O O O
OUTDOOR MATERIALS N/A (Skip to OUTDOOR MATERIALS N/A (Skip to OI. Are loading/unloading operations present fyes, are they uncovered and draining toward OI. Are materials stored outside? Y Where are they stored? grass/dirt area CI. Is staining or discoloration around the are CI. Does outdoor storage area lack a cover? CI. Are storage containers missing labels or in OI. WASTE MANAGEMENT N/A (Skip to OI. Type of waste (check all that apply): CI. Dumpster condition (check all that apply) evidence of leakage (stains on ground)	t? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain inlet? Y N Can't Tell rds a storm drain (circle one)? Y N rea visible? Y N Can't Tell rea visible? Y N Can't Tell rdary containment? Y N Can't Tell rdary containment? Y N Can't Tell rin poor condition (rusting)? Y N Can't Tell rin poor condition (rusting)? Y N Can't Tell reart E) Order Ell rds a storm drain inlet? Y N Can't Tell reart Ell rds a storm drain inlet? Y N Can't Tell reart Ell rds a storm drain inlet? Y N Can't Tell reart Ell rds a storm drain inlet? Y N Can't Tell reart Ell rds a storm drain inlet? Y N Can't Tell reart Ell rds a storm drain inlet? Y N Can't Tell reart Ell rds a storm drain inlet? Y N Can't Tell reart Ell rds a storm drain inlet? Y N Can't Tell reart Ell reart E	Description: Can't Tell bserved Pollution Sounaterials	O O O O O O CO
OUTDOOR MATERIALS N/A (Skip to OUTDOOR MATERIALS N/A (Skip to OI. Are loading/unloading operations present fyes, are they uncovered and draining toward. Are materials stored outside? Y Nhere are they stored? grass/dirt area C3. Is the storage area directly or indirectly of OI. Is staining or discoloration around the area C5. Does outdoor storage area lack a cover? C6. Are liquid materials stored without second OI. Type of waste (check all that apply): D1. Type of waste (check all that apply): C9. Dumpster condition (check all that apply) evidence of leakage (stains on ground) C93. Is the dumpster located near a storm drain	t?	Description: Can't Tell bserved Pollution Sounaterials	O O O O O O O O O O O O O O O O O O O
OUTDOOR MATERIALS N/A (Skip to OUTDOOR MATERIALS N/A (Skip to OI. Are loading/unloading operations present fyes, are they uncovered and draining toward OI. Are materials stored outside? Y Where are they stored? grass/dirt area CI. Is staining or discoloration around the are CI. Does outdoor storage area lack a cover? CI. Are storage containers missing labels or in OI. WASTE MANAGEMENT N/A (Skip to OI. Type of waste (check all that apply): CI. Dumpster condition (check all that apply) evidence of leakage (stains on ground)	t?	Description: Can't Tell bserved Pollution Sounaterials	O O O O O O O O O O O O O O O O O O O
OUTDOOR MATERIALS N/A (Skip to OUTDOOR MATERIALS N/A (Skip to C1. Are loading/unloading operations present fyes, are they uncovered and draining toward C2. Are materials stored outside? Y Where are they stored? grass/dirt area C3. Is the storage area directly or indirectly of C4. Is staining or discoloration around the area C5. Does outdoor storage area lack a cover? C6. Are liquid materials stored without second C7. Are storage containers missing labels or incomplete the condition of the condition (Skip to C2. Dumpster condition (Check all that apply): D2. Dumpster condition (Check all that apply): S3. Is the dumpster located near a storm drain of the condition of the conditio	t?	Description: Can't Tell Can't Tell bserved Pollution Sounaterials Can Leaking or	O O O O O O O O O O O O O O O O O O O

Hotspot Site Investigation

HSI

Surface material	Paved/Concrete [neable [Don't	knov	V				up					0
E3. Do downspouts disch Are downspout	harge to impervious s directly connected	s surface? Y [d to storm drains?				w 🔲			ole						0
E4. Evidence of poor cle									ly [IN	П	Can'	t Te	11	0
F. TURF/LANDSCAPIN												-		rce?	
F1. % of site with: Forest				ping	9/	6 Bar	e Soi	1	%	vea	РОШИ	tion	Sou	rce:	0
F2. Rate the turf manager				P8 -			0 001	-	_/0		_	-		+	0
F3. Evidence of permane	The state of the s			ONF	Can	't Tel				-				+	_
F4. Do landscaped areas			VY I			an't T						_	_	+	0
0			77						7 5	7				-	0
75. Do landscape plants acc				djacent	ımpeı	rvious	surfac	e? [X	Y	_l N		Can't	Tel		0
G. STORM WATER INI					_				bserv	ed l	Pollu	tion	Sou	rce?	
G1. Are storm water treat															0
G2. Are private storm dra Is trash present in	ins located at the fa n gutters leading to	acility? XY IN No storm drains? If so	V Uni	known te the i	Z ndex	curb below	inle	ts,	on	P0)	10-	sid	ے		0
		Index Ratin	g for Acc	umula	ion i	n Gutt	ers								
Sediment	Clean					_		F	ilthy	=					
Organic material	⊠ 1 ⊠ 1		☐ 3 ☐ 3			H4			-						
Organic material						□4									
Litter	[2]	□ 2	 3			111				\Box 5					
Litter 3. Catch basin inspectio INITIAL HOTSPOT S Not a hotspot (fewer the	STATUS - INDEX nan 5 circles and no	RESULTS boxes checked)	Potent	ial hot	spot	4 on: (5 to 1	0 circ	cles t	Clea	box	es ch	iecke	ed)		
Not a hotspot (fewer the Confirmed hotspot (10 collow-up Action: Refer for immediate en Suggest follow-up on-Test for illicit discharged Include in future educated Check to see if hotspot Onsite non-residential Pervious area restoration.	n – Record SSD Un STATUS - INDEX han 5 circles and no 0 to 15 circles and/o nforcement site inspection ge ation effort is an NPDES non- retrofit on; complete PAA series	nique Site ID here: RESULTS b boxes checked) [for 1 box checked) [-filer sheet and record	<u> </u>	ial hot	spot	(5 to 1	0 circ	cles t	out no	box	es ch	neckees ch	ed)	ed)	
Not a hotspot (fewer the Confirmed hotspot (10 confirmed hotspot (n – Record SSD Un STATUS - INDEX han 5 circles and no 0 to 15 circles and/o nforcement site inspection ge ation effort is an NPDES non- retrofit on; complete PAA series	nique Site ID here: RESULTS b boxes checked) [for 1 box checked) [-filer sheet and record	<u> </u>	ial hot	spot	(5 to 1	0 circ	cles t	out no	box	es ch	neckees ch	ed)	ed)	
Not a hotspot (fewer the Confirmed hotspot (100 ollow-up Action: Refer for immediate en Suggest follow-up on-Test for illicit discharged Include in future educated Check to see if hotspot (100 onsite non-residential Pervious area restoration Unique Site ID here confessions in the Confession of the C	n – Record SSD Un STATUS - INDEX han 5 circles and no 0 to 15 circles and/o nforcement site inspection ge ation effort is an NPDES non- retrofit on; complete PAA sere: torm water pollutio	nique Site ID here: RESULTS b boxes checked) for 1 box checked) -filer sheet and record on prevention plan	<u> </u>	ial hot	spot	(5 to 1	0 circ	cles t	out no	box	es ch	aecke es ch	ed)	ed)	
Not a hotspot (fewer the Confirmed hotspot (10 collow-up Action: Refer for immediate en Suggest follow-up on-Test for illicit discharged Include in future educated Check to see if hotspot (10 collow-up on-Test for illicit discharged Include in future educated Check to see if hotspot (10 collow-up on-Test for illicit discharged Include in future educated Check to see if hotspot (10 collow-up on-Test for illicit discharged Include in future educated Check to see if hotspot (10 collow-up on-Test) (10 co	n – Record SSD Un STATUS - INDEX han 5 circles and no 0 to 15 circles and/o nforcement site inspection ge ation effort is an NPDES non- retrofit on; complete PAA sere: torm water pollutio	nique Site ID here: RESULTS b boxes checked) for 1 box checked) -filer sheet and record on prevention plan	<u> </u>	ial hot	spot	(5 to 1	0 circ	cles t	out no	box	es ch	necke es ch	ed)	ed)	
Not a hotspot (fewer the Confirmed hotspot (10 collow-up Action: Refer for immediate end Suggest follow-up on-Test for illicit discharged Include in future educated Check to see if hotspot Consite non-residential Pervious area restoration Unique Site ID here Schedule a review of states.	n – Record SSD Un STATUS - INDEX han 5 circles and no 0 to 15 circles and/o nforcement site inspection ge ation effort is an NPDES non- retrofit on; complete PAA sere: torm water pollutio	nique Site ID here: RESULTS b boxes checked) for 1 box checked) -filer sheet and record on prevention plan	<u> </u>	ial hot	spot	(5 to 1	0 circ	cles t	out no	box	es ch	necke es ch	ed)	ed)	
Not a hotspot (fewer the Confirmed hotspot (10 collow-up Action: Refer for immediate end Suggest follow-up on-Test for illicit discharged Include in future educated Check to see if hotspot Consite non-residential Pervious area restoration Unique Site ID here Schedule a review of states.	n – Record SSD Un STATUS - INDEX han 5 circles and no 0 to 15 circles and/o nforcement site inspection ge ation effort is an NPDES non- retrofit on; complete PAA series	nique Site ID here: RESULTS b boxes checked) for 1 box checked) -filer sheet and record on prevention plan	<u> </u>	ial hot	spot	(5 to 1	0 circ	cles t	out no	box	es ch	neckees ch	ed)	ed)	
Not a hotspot (fewer the Confirmed hotspot (10 collow-up Action: Refer for immediate end Suggest follow-up on-Test for illicit discharged Include in future educated Check to see if hotspot Consite non-residential Pervious area restoration Unique Site ID here Schedule a review of states.	n – Record SSD Un STATUS - INDEX han 5 circles and no 0 to 15 circles and/o nforcement site inspection ge ation effort is an NPDES non- retrofit on; complete PAA sere: torm water pollutio	nique Site ID here: RESULTS b boxes checked) for 1 box checked) -filer sheet and record on prevention plan	<u> </u>	ial hot	spot	(5 to 1	0 circ	cles t	out no	box	es ch	necke es ch	ed)	ed)	
Not a hotspot (fewer the Confirmed hotspot (10 collow-up Action: Refer for immediate end Suggest follow-up on-Test for illicit discharged Include in future educated Check to see if hotspot Consite non-residential Pervious area restoration Unique Site ID here Schedule a review of states.	n – Record SSD Un STATUS - INDEX han 5 circles and no 0 to 15 circles and/o nforcement site inspection ge ation effort is an NPDES non- retrofit on; complete PAA sere: torm water pollutio	nique Site ID here: RESULTS b boxes checked) for 1 box checked) -filer sheet and record on prevention plan	<u> </u>	ial hot	spot	(5 to 1	0 circ	cles t	out no	box	es ch	neckees ch	ed)	ed)	
Not a hotspot (fewer the Confirmed hotspot (100 ollow-up Action: Refer for immediate en Suggest follow-up on-Test for illicit discharged Include in future educated Check to see if hotspot (100 onsite non-residential Pervious area restoration Unique Site ID here confessions in the Confession of the C	n – Record SSD Un STATUS - INDEX han 5 circles and no 0 to 15 circles and/o nforcement site inspection ge ation effort is an NPDES non- retrofit on; complete PAA sere: torm water pollutio	nique Site ID here: RESULTS b boxes checked) for 1 box checked) -filer sheet and record on prevention plan	<u> </u>	ial hot	spot	(5 to 1	0 circ	cles t	out no	box	es ch	neckees ch	ed)	ed)	

Hotspot Site Investigation

ATERSHED:	SUBWATERSHED: Center Suland	UNIQUE SITE ID: (TR-	HST-01
ATE: \$ 16 1009	ASSESSED BY: TES CAMERA ID:	oner Pic#: 16	
MAP GRID:	LAT 410 54 . 8.8 "LONG 73 . 30	55.6" LMK#	
A. SITE DATA AND BASIC CLASSIFICATIO			
Name and Address:	Institutional Municipal	∕liscellaneous ☐ Golf Course ☐ Marina ☐ Animal Facility	
SIC code (if available): NPDES Status: Regulated Unknown	DENTED ACCESS!	1/AG	- INDEX*
B. VEHICLE OPERATIONS N/A (Skip to	o part C)	Observed Pollution Son	ırce?
B1. Types of vehicles: Fleet vehicles	School buses Other:	.,	
B2. Approximate number of vehicles:			
	: Maintained Repaired Recycled Fueled Wash	ned Stored	0
B4. Are vehicles stored and/or repaired outs Are these vehicles lacking runoff diversion			0
B5. Is there evidence of spills/leakage from		1	0
B6. Are uncovered outdoor fueling areas pro	esent? Y N Can't Tell		0
B7. Are fueling areas directly connected to	storm drains? Y N Can't Tell	7	0
B8. Are vehicles washed outdoors? Y Does the area where vehicles are washed dis	N Can't Tell Scharge to the storm drain? ✓Y ✓N Can't	ГеИ	0
OUTDOOR MATERIALS N/A (Skip to	p part D)	Observed Pollution Sou	rce?
C1. Are loading/unloading operations present of the control of the	ards a storm drain inlet? \(\subseteq \forall \) \(\subseteq \text{N} \) \(\subseteq \text{Can't'} \)	Tell	0
C2. Are materials stored outside? ☐ Y ☐ Where are they stored? ☐ grass/dirt area	N ☐ Can't Tell If yes, are they ☐ Liquid ☐ Soli ☐ concrete/asphalt ☐ bermed area	d Description:	0
C3. Is the storage area directly or indirectly	connected to storm drain (circle one)? Y N	Can't Tell	0
C4. Is staining or discoloration around the a	rea visible? Y N Can't Tell		0
C5. Does outdoor storage area lack a cover?			0
C6. Are liquid materials stored without seco	ndary containment?		0
C7. Are storage containers missing labels or	in poor condition (rusting)? Y N Can't	Tell	0
D. WASTE MANAGEMENT N/A (Skip to	p part E)	Observed Pollution Sou	rce?
D1. Type of waste (check all that apply): [Garbage Construction materials Hazardou		0
evidence of leakage (stains on ground)		lition	0
D3. Is the dumpster located near a storm dra If yes, are runoff diversion methods (ber			0
E. PHYSICAL PLANT N/A (Skip to part I	7)	Observed Pollution Sou	rce?
E1. Building: Approximate age:Evidence that maintenance results in dischar	yrs. Condition of surfaces: Clean Stained rge to storm drains (staining/discoloration)? Y	☐ Dirty ☐ Damaged	0

CTR-H91-01

Hotspot Site Investigation

2. Parking Lot: Approximate age yrs. Condition: Confidence material Paved/Concrete Gravel Perm	eable 🗌	Don	't kr	iow								C)
E3. Do downspouts discharge to impervious surface? Y Are downspouts directly connected to storm drains?]и ['t k			one v						(5
E4. Evidence of poor cleaning practices for construction activiti					1000			П	νП	Can't	Tell	C)
F. TURF/LANDSCAPING AREAS N/A (skip to part G)							0.00			tion S			_
F1. % of site with: Forest canopy% Turf grass%	Landsca	ping		%	Bare	Soil	%		Tona	tion S	ouic	C)
F2. Rate the turf management status: High Medium												Č	_
F3. Evidence of permanent irrigation or "non-target" irrigation	□Y [] N [] (an't	Геll							C	_
F4. Do landscaped areas drain to the storm drain system?	□Y [N		Can	't Te	11						C	_
F5. Do landscape plants accumulate organic matter (leaves, grass clippi	ngs) on a	djacer	nt im	pervio	us su	rface?	□ Y		1 🗆 0	Can't T	Геll	C	_
G. STORM WATER INFRASTRUCTURE N/A (skip to p							TAX III		STE A L	tion S			
G1. Are storm water treatment practices present? $\square Y \square N$	Unkn	own	If y	es, pl	ease	descr				tion D	Juice	C)
G2. Are private storm drains located at the facility? \(\subseteq Y \subseteq N \) Is trash present in gutters leading to storm drains? If so,	☐ Unl	cnow	n									0	
Index Rating						S				-			_
Clean							Filth	ny					
Sediment □ 1 □ 2 Organic material □ 1 □ 2 Litter □ 1 □ 2	☐ 3 ☐ 3 ☐ 3] 4] 4] 4				5 5 5				
C3. Catch basin inspection – Record SSD Unique Site ID here:		C	ond	ition:		Dirty	☐ C	lean					
□ Not a hotspot (fewer than 5 circles and no boxes checked) □ Confirmed hotspot (10 to 15 circles and/or 1 box checked) □ Follow-up Action: □ Refer for immediate enforcement □ Suggest follow-up on-site inspection □ Test for illicit discharge □ Include in future education effort □ Check to see if hotspot is an NPDES non-filer □ Onsite non-residential retrofit	Potent Severe	hots	pot (ot (5)	to 10	circles and	es but i	no bo	xes ch	necked es che	cked)		
Pervious area restoration; complete PAA sheet and record Unique Site ID here: Schedule a review of storm water pollution prevention plan												id jal Palad	
Notes:													

Hotspot Site Investigation

Name and Address: Category: SIC code (if available): Basic Descri NPDES Status: Regulated Unknown B. Vehicle Operations N/A (Skip to part C) B1. Types of vehicles: Fleet vehicles School buses B2. Approximate number of vehicles: School buses B3. Vehicle activities (circle all that apply): Maintained Rep B4. Are vehicles stored and/or repaired outside? Y N Are these vehicles lacking runoff diversion methods? Y N B5. Is there evidence of spills/leakage from vehicles? Y N B6. Are uncovered outdoor fueling areas present? Y N B7. Are fueling areas directly connected to storm drains? N B8. Are vehicles washed outdoors? Y N Can't T Does the area where vehicles are washed discharge to the storm Outdoor Materials N/A (Skip to part D) C1. Are loading/unloading operations present? Y N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	Can't Tell Can't Tell N Can't Tell N Can't Tell Can't Tell Can't Tell Can't Tell	ial Miscellaneous pal Golf Course Marina Animal Facility Observed Poll Washed Stored	INDEX ution Source?
A. SITE DATA AND BASIC CLASSIFICATION Name and Address: Category: SIC code (if available): Basic Descri NPDES Status: Regulated Unknown B. VEHICLE OPERATIONS N/A (Skip to part C) B1. Types of vehicles: Fleet vehicles School buses B2. Approximate number of vehicles: B3. Vehicle activities (circle all that apply): Maintained Rep B4. Are vehicles stored and/or repaired outside? Y N Are these vehicles lacking runoff diversion methods? Y S B5. Is there evidence of spills/leakage from vehicles? Y B6. Are uncovered outdoor fueling areas present? Y B7. Are fueling areas directly connected to storm drains? S B8. Are vehicles washed outdoors? Y B9. Are vehicles washed outdoors? Y B1. Y B2. Are vehicles washed outdoors? Y B3. Are vehicles washed outdoors? Y B4. Are vehicles washed outdoors? Y B5. Are vehicles washed outdoors? Y B6. Are uncovered outdoors? Y B7. Are fueling areas directly connected to storm drains? Y B8. Are vehicles washed outdoors? Y B9. Are vehicles washed outdoors? Y B1. Types of vehicles are washed discharge to the storm OUTDOOR MATERIALS Y B1. Types of vehicles are washed discharge to the storm OUTDOOR MATERIALS Y B1. Types of vehicles are washed discharge to the storm OUTDOOR MATERIALS Y B2. Are materials stored outside? Y B3. Y B4. Are materials stored outside? Y B5. Are materials stored outside? Y B6. Are materials stored outside? Y B7. Are materials stored outside? Y B8. Are well as a storm of the material outside? Y B7. Are materials stored outside? Y B8. Are well as a storm of the material outside? Y B8. Are vehicles are washed discharge to the storm of the material outside? Y B6. Are uncovered outside? Y B7. Are fueling areas present? Y B8. Are vehicles are where vehicles are washed discharge to the storm of the material outside? Y B8.	Commercial Industrict Institutional Munici Munici Transport-Related ption of Operation: Other: Can't Tell Can't Tell Can't Tell Can't Tell Can't Tell Can't Tell Can't Tell	ial Miscellaneous pal Golf Course Marina Animal Facility Observed Poll Washed Stored	INDEX ution Source?
Name and Address:	Institutional Munici Institutional Munici Transport-Related ption of Operation: Other: Other: Can't Tell N Can't Tell N Can't Tell N Can't Tell Can't Tell Can't Tell Can't Tell	Dan't Tell	INDEX
SIC code (if available): Regulated	Institutional Munici Institutional Munici Transport-Related ption of Operation: Other: Other: Can't Tell N Can't Tell N Can't Tell N Can't Tell Can't Tell Can't Tell Can't Tell	Dan't Tell	INDEX ution Source?
NPDES Status: Regulated Unknown B. VEHICLE OPERATIONS N/A (Skip to part C) B1. Types of vehicles: Fleet vehicles School buses B2. Approximate number of vehicles: B3. Vehicle activities (circle all that apply): Maintained Rep B4. Are vehicles stored and/or repaired outside? Y N Are these vehicles lacking runoff diversion methods? Y N B5. Is there evidence of spills/leakage from vehicles? Y N B6. Are uncovered outdoor fueling areas present? Y N B7. Are fueling areas directly connected to storm drains? N B8. Are vehicles washed outdoors? Y N Can't T Does the area where vehicles are washed discharge to the storm OUTDOOR MATERIALS N/A (Skip to part D) C1. Are loading/unloading operations present? Y N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	Other:	Washed Stored Va p M A m gav	oution Source?
B. VEHICLE OPERATIONS N/A (Skip to part C) B1. Types of vehicles: Fleet vehicles School buses B2. Approximate number of vehicles: B3. Vehicle activities (circle all that apply): Maintained Rep B4. Are vehicles stored and/or repaired outside? Y N N Are these vehicles lacking runoff diversion methods? Y S B5. Is there evidence of spills/leakage from vehicles? Y N B6. Are uncovered outdoor fueling areas present? Y N B7. Are fueling areas directly connected to storm drains? S B8. Are vehicles washed outdoors? Y N Can't T Does the area where vehicles are washed discharge to the storm OUTDOOR MATERIALS N/A (Skip to part D) C1. Are loading/unloading operations present? Y N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	Other: Daired Recycled Fueled Can't Tell N Can't Tell N Can't Tell Can't Tell Can't Tell Can't Tell Can't Tell Can't Tell	Washed Stored Va p M A m gav	oution Source?
B2. Approximate number of vehicles: B3. Vehicle activities (circle all that apply): Maintained Rep B4. Are vehicles stored and/or repaired outside? Y N Are these vehicles lacking runoff diversion methods? Y E B5. Is there evidence of spills/leakage from vehicles? Y N B6. Are uncovered outdoor fueling areas present? Y N B7. Are fueling areas directly connected to storm drains? B8. Are vehicles washed outdoors? Y N Can't T Does the area where vehicles are washed discharge to the storm OUTDOOR MATERIALS N/A (Skip to part D) C1. Are loading/unloading operations present? Y N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	Paired Recycled Fueled Can't Tell N Can't Tell N Can't Tell Can't Tell Can't Tell Can't Tell Can't Tell	Washed Stored A POWA IN PAY Can't Tell	0
B3. Vehicle activities (circle all that apply): Maintained Rep B4. Are vehicles stored and/or repaired outside? Y N Are these vehicles lacking runoff diversion methods? Y P B5. Is there evidence of spills/leakage from vehicles? Y P B6. Are uncovered outdoor fueling areas present? Y N B7. Are fueling areas directly connected to storm drains? S B8. Are vehicles washed outdoors? Y N Can't T Does the area where vehicles are washed discharge to the storm OUTDOOR MATERIALS N/A (Skip to part D) C1. Are loading/unloading operations present? Y N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	Paired Recycled Fueled Can't Tell N Can't Tell N Can't Tell Can't Tell Can't Tell Can't Tell Can't Tell	Can't Tell	0
B4. Are vehicles stored and/or repaired outside? Y N Are these vehicles lacking runoff diversion methods? Y E B5. Is there evidence of spills/leakage from vehicles? Y E B6. Are uncovered outdoor fueling areas present? Y N B7. Are fueling areas directly connected to storm drains? Y B8. Are vehicles washed outdoors? Y N Can't T Does the area where vehicles are washed discharge to the storm OUTDOOR MATERIALS N/A (Skip to part D) C1. Are loading/unloading operations present? Y N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	Can't Tell Can't Tell N Can't Tell N Can't Tell Can't Tell Can't Tell Can't Tell	Can't Tell	0
Are these vehicles lacking runoff diversion methods? B5. Is there evidence of spills/leakage from vehicles? B6. Are uncovered outdoor fueling areas present? B7. Are fueling areas directly connected to storm drains? B8. Are vehicles washed outdoors? B9. Are vehicles washed	N Can't Tell N Can't Tell Can't Tell N Can't Tell Can't Tell Can't Tell	Can't Tell	0
B6. Are uncovered outdoor fueling areas present? B7. Are fueling areas directly connected to storm drains? B8. Are vehicles washed outdoors? Does the area where vehicles are washed discharge to the storm OUTDOOR MATERIALS N/A (Skip to part D) C1. Are loading/unloading operations present? Y N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	Can't Tell Y N Can't Tell ell		0
B7. Are fueling areas directly connected to storm drains? B8. Are vehicles washed outdoors? Y N Can't T Does the area where vehicles are washed discharge to the storm OUTDOOR MATERIALS N/A (Skip to part D) C1. Are loading/unloading operations present? Y N N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	Y □ N □ Can't Tell		0
B8. Are vehicles washed outdoors? Y N Can't T Does the area where vehicles are washed discharge to the storm OUTDOOR MATERIALS N/A (Skip to part D) C1. Are loading/unloading operations present? Y N N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	ell		0
Does the area where vehicles are washed discharge to the storm OUTDOOR MATERIALS N/A (Skip to part D) C1. Are loading/unloading operations present? Y N N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? Y N Can't Tell	ell drain? 🗌 Y 🔲 N 🔀 (
C1. Are loading/unloading operations present? ☑ Y ☐ N If yes, are they uncovered and draining towards a storm drain in C2. Are materials stored outside? ☑ Y ☐ N ☐ Can't Tell			1 /
If yes, are they uncovered <i>and</i> draining towards a storm drain in C2. Are materials stored outside? X Y N Can't Tell		Observed Pollu	ition Source?
C2. Are materials stored outside? X Y N Can't Tell		Can't Tell Salt	•
Where are they stored? grass/dirt area concrete/asphalt	If yes, are they ☐ Liquid ☐ bermed area	Solid Description: S	0
C3. Is the storage area directly or indirectly connected to storm	drain (circle one)? X Y	□ N □ Can't Tell	0
C4. Is staining or discoloration around the area visible?	□ N		0
C5. Does outdoor storage area lack a cover? 🛮 Y 🔲 N 📗	Can't Tell		0
C6. Are liquid materials stored without secondary containment?	Y N Can't 7	Tell	0
C7. Are storage containers missing labels or in poor condition (rusting)? 🗌 Y 🔲 N 🐰	Can't Tell	0
D. WASTE MANAGEMENT N/A (Skip to part E)		Observed Pollu	- A
D1. Type of waste (check all that apply): ☐ Garbage ☐ Co	nstruction materials		lon source:
D2. Dumpster condition (<i>check all that apply</i>): ☐ No cover/Li evidence of leakage (stains on ground) ☐ Overflowing		THE PARTY OF THE PARTY TO THE	
D3. Is the dumpster located near a storm drain inlet? Y The If yes, are runoff diversion methods (berms, curbs) lacking?		ell	0
E. PHYSICAL PLANT N/A (Skip to part F)		Observed Pollu	tion Source?
E1. Building: Approximate age: yrs. Condition of Evidence that maintenance results in discharge to storm drains	surfaces: Clean St	ained Dirty Dar	maged O

MRV-451-01

Hotspot Site Investigation

". Parking Lot: Approximate age yrs. Condition: Surface material ☑ Paved/Concrete ☐ Gravel ☐ F	☐ Clean ☐ Permeable ☐] Stain Don't	ed 🔲 know	Dirty	□в	reaking	g up				0
E3. Do downspouts discharge to impervious surface? X Y Are downspouts directly connected to storm drain			know N 🗵								0
E4. Evidence of poor cleaning practices for construction ac							ПΝ	NO	an't Te	ell	0
F. TURF/LANDSCAPING AREAS N/A (skip to par						930.00		11116	ion Sou	-	
F1. % of site with: Forest canopy% Turf grass	% Landsca	ping_	%	Bare S			Yeu I	onat	ion Soc	T.	0
F2. Rate the turf management status: High Medium											0
F3. Evidence of permanent irrigation or "non-target" irrigat	ion 🗆 Y 🗀	N	Can't	Tell						+	O
F4. Do landscaped areas drain to the storm drain system?	□Y [N	☐ Car	n't Tel	1					+	0
F5. Do landscape plants accumulate organic matter (leaves, grass of	clippings) on a					ПУ	Пи	ПС	n't Te	11	0
G. STORM WATER INFRASTRUCTURE N/A (skip					× 1	. 10.11	-	5.00	on Sou		
G1. Are storm water treatment practices present? ☐ Y ⊠		own I	f ves. r	lease d			veu I	onuti	011 301	rce.	•
G2. Are private storm drains located at the facility?			, jes, F	- Touge C							
Is trash present in gutters leading to storm drains?	If so, complet	e the ir	idex be	elow.							0
	ating for Acc	ımulat	ion in	Gutters	\$						
Clean						Filthy					
Sediment 1 2 Organic material 1 2	∐3 □3		÷	∃4			<u>5</u>				
Litter			F	74			☐ 5 ☐ 5				
C3. Catch basin inspection – Record SSD Unique Site ID he		Co	ndition	: \(\text{D}\)	irty	Cle	-				
INITIAL HOTSPOT STATUS - INDEX RESULTS											
☐ Not a hotspot (fewer than 5 circles and no boxes checked	1) Potent	al hots	pot (5	to 10	circles	but no	hoxe	es che	cked)		
Confirmed hotspot (10 to 15 circles and/or 1 box checke	ed) Severe	hotspo	t (>15	circles	and/o	or 2 or	more	boxe	s check	ed)	
Follow-up Action:		H						TT			TT
Refer for immediate enforcement											+
Suggest follow-up on-site inspection Test for illicit discharge				+++	1	+		+	-	+	++
Include in future education effort			++	++	-	-	-	++	-		++
Check to see if hotspot is an NPDES non-filer	1	++-	++	++	+	-		+	-	-	-
Onsite non-residential retrofit			++	+++	+	+		+			
Pervious area restoration; complete PAA sheet and record Unique Site ID here:	d	-	++	-	-	-		-		-	
Schedule a review of storm water pollution prevention pl	an	-	+-		-			11			
F. Carrier F.			11								E
Notes:										E E	
Followup for Clinate	100	1.1									
wal the treling Station, Starm			11								
are draining and storage	-41				-					1 1	
of materials, esp. calling	1/0	111111					4177				
Followup for Fieling station, storm water drainage and storage of materials. esp, salt/soud p	1,10				7 71	17 -					
and vehides		111				11	11	11			
									11		
								+			
			1	-						= 1,100	

Hotspot Site Investigation

ATERSHED: OYSER BAN	SUBWATERSHED: OBA	UNIQUE SITE ID: OF	-451-01
ATE: 8/25/09	ASSESSED BY: EMB CAMERA		19-119
MAP GRID:	LAT 410 52 '2619" LONG 73	031 144,8" LMK#	1
A. SITE DATA AND BASIC CLASSIFICATION			
Name and Address: LIFR Oycler Bay Yava I Rail float Plaza, SIC code (if available): 40 ()	Category: Commercial Indus Institutional Muni Transport-Related Basic Description of Operation:		
NPDES Status: Regulated Unregulated Unknown	Railyand		- INDEX*
B. VEHICLE OPERATIONS \(\subseteq \text{N/A} \) (Skip to	part C)	Observed Pollution So	urce?
B1. Types of vehicles: X Fleet vehicles	School buses Other: Trains		
B2. Approximate number of vehicles: 3	trains 10 employee parking		
B3. Vehicle activities (circle all that apply):	: Maintained Repaired Recycled Fueled	Washed Stored	0
B4. Are vehicles stored and/or repaired outs			0
Are these vehicles lacking runoff diversion a B5. Is there evidence of spills/leakage from			- 7
B6. Are uncovered outdoor fueling areas pre		1	0
B7. Are fueling areas directly connected to s		trains	0
B8. Are vehicles washed outdoors? Y			0
Does the area where vehicles are washed dis	scharge to the storm drain? Y N	Can't Tell	0
OUTDOOR MATERIALS N/A (Skip to	part D)	Observed Pollution So	urce?
C1. Are loading/unloading operations present If yes, are they uncovered and draining toward.] Can't Tell	0
C2. Are materials stored outside? ☐ Y ☐ Where are they stored? ☐ grass/dirt area [N ☐ Can't Tell If yes, are they ☐ Liquid deconcrete/asphalt ☐ bermed area	Solid Description:	5 0
C3. Is the storage area directly or indirectly	connected to storm drain (circle one)?	□ N ☑ Can't Tell Savet	0
C4. Is staining or discoloration around the ar	rea visible? Y N Can't Tell		0
C5. Does outdoor storage area lack a cover?	Y N Can't Tell		0
C6. Are liquid materials stored without secon	ndary containment? Y N Can't	t Tell	0
C7. Are storage containers missing labels or	in poor condition (rusting)? Y N	Can't Tell	0
D. WASTE MANAGEMENT N/A (Skip to	part E)	Observed Pollution Sou	1.71
D1. Type of waste (check all that apply):	Garbage Construction materials H		0
D2. Dumpster condition (check all that apple evidence of leakage (stains on ground)	y): ⊠ No cover/Lid is open □ Damaged/po ☑ Overflowing	TEN THE TOTAL PROPERTY OF THE PARTY OF THE P	•
D3. Is the dumpster located near a storm drain If yes, are runoff diversion methods (ber	in inlet? \[Y \[N \] Can't Tell ms, curbs) lacking? \[Y \[N \] Can't	Tell	0
E. PHYSICAL PLANT N/A (Skip to part F	7)	Observed Pollution Sou	rce? V
	yrs. Condition of surfaces: Clean ge to storm drains (staining/discoloration)?	Stained Dirty Damaged	0

Hotspot Site Investigation

2. Parking Lot: Approximate age yrs. Condition: Condition: Payed/Concrete Gravel Perme				Dirty	Br	eaking	up				0
E3. Do downspouts discharge to impervious surface? Y Are downspouts directly connected to storm drains?	and the same of th	Don't	know	_	one vis					t	0
E4. Evidence of poor cleaning practices for construction activitie							٦N	ПС	an't Tel	1	0
F. TURF/LANDSCAPING AREAS N/A (skip to part G)	(7,000	5 10 01							-	NIA
F1. % of site with: Forest canopy% Turf grass% 1	andecan	ina	O/o	Rara 9	Soil _		ved P	ollutio	on Sou	rce?	
	Low	g		Date	30II	70	_			-	0
F3. Evidence of permanent irrigation or "non-target" irrigation		N \square	Can't	Tall				-	_	+	0
		N		i't Tell						-	0
F5. Do landscape plants accumulate organic matter (leaves, grass clippin						727	TNE	7.0	'- T-11	-	0
G. STORM WATER INFRASTRUCTURE N/A (skip to pe		acenti	mpervi	ous sur			70.00				0
							ed Po	llutio	n Sour	ce?	~
G1. Are storm water treatment practices present? Y N			yes, p	lease c	lescrib	e:					0
G2. Are private storm drains located at the facility? \(\subseteq \text{Y} \subseteq \text{N} \) Is trash present in gutters leading to storm drains? If so,	complete	the in									0
Index Rating Clean	for Accu	mulati	on in (Gutters	3						
Sediment 1 12	□ 3	-	Г	74	_	Filthy	П5	-			
Organic material 1 2 Litter 1 2	☐3 ☐3		į] 4] 4			5 5				
C3. Catch basin inspection - Record SSD Unique Site ID here:		Cor	dition	: 🗌 D	irty [Clea	n				
□ Not a hotspot (fewer than 5 circles and no boxes checked) □ Confirmed hotspot (10 to 15 circles and/or 1 box checked) □ Follow-up Action: □ Refer for immediate enforcement □ Suggest follow-up on-site inspection □ Test for illicit discharge □ Include in future education effort □ Check to see if hotspot is an NPDES non-filer □ Onsite non-residential retrofit □ Pervious area restoration; complete PAA sheet and record □ Unique Site ID here: □ □ Schedule a review of storm water pollution prevention plan Notes:	Potentia Severe I	l hotspoortspo	pot (5 t (>15	to 10 circles	circles s and/o	but no	boxe more I	s chec	checke	d)	

WATERSHED: Ogster Bay	SUBWATERSHED: Onler Bay Harber UNIQ	DUE SITE ID: OBH-HS1-02
(E: 9 175104	ASSESSED BY: KMB CAMERA ID:	Pic#: 94-103
MAP GRID:	LAT40 . 52 . 146 "LONG 73 . 31 287	LMK#
A. SITE DATA AND BASIC CLASSIFICATION		
Name and Address:		laneous
Dyslex Bay High School		lf Course rina
Mainst	_ Ani	imal Facility
SIC code (if available):	Basic Description of Operation:	500000000
NPDES Status: Regulated	school buildings toparking	INDEX*
Unregulated Unknown	CONTRACTOR OF THE PROPERTY OF	() () () () () () () () () ()
B. VEHICLE OPERATIONS N/A (Skip to	100	served Pollution Source?
B1. Types of vehicles: Fleet vehicles		
B2. Approximate number of vehicles:		g: 1
B4. Are vehicles stored and/or repaired outs	: Maintained Repaired Recycled Fueled Washed	Stored
Are these vehicles lacking runoff diversion		0
B5. Is there evidence of spills/leakage from	vehicles? Y N Can't Tell	0
B6. Are uncovered outdoor fueling areas pro	esent? 🗌 Y 📈 N 🔲 Can't Tell	0
	storm drains? Y N Can't Tell	0
B8. Are vehicles washed outdoors? Y Does the area where vehicles are washed dis		O
C OUTDOOR MATERIALS N/A (Skip to	o part D) Ob	served Pollution Source?
. Are loading/unloading operations present		H. CO. CO.
If yes, are they uncovered and draining towa	ards a storm drain inlet? Y N Can't Tell	0
C2. Are materials stored outside? Y Where are they stored? grass/dirt area	N ☐ Can't Tell If yes, are they ☐ Liquid ☐ Solid De☐ concrete/asphalt ☐ bermed area	escription:O
C3. Is the storage area directly or indirectly	connected to storm drain (circle one)?	Can't Tell O
C4. Is staining or discoloration around the a	rea visible? Y N Can't Tell	0
C5. Does outdoor storage area lack a cover?	P ☐ Y ☐ N ☐ Can't Tell	0
C6. Are liquid materials stored without seco	ondary containment?	0
C7. Are storage containers missing labels or	r in poor condition (rusting)? \square Y \square N \square Can't Tell	0
D. WASTE MANAGEMENT N/A (Skip t	o part E) Ob	served Pollution Source?
D1. Type of waste (check all that apply):	Garbage Construction materials Hazardous ma	aterials O
evidence of leakage (stains on ground)		Leaking or
D3. Is the dumpster located near a storm dra If yes, are runoff diversion methods (be		0
E. PHYSICAL PLANT N/A (Skip to part		served Pollution Source?
E1. Building: Approximate age: 1928	yrs. Condition of surfaces: Clean Stained	Dirty Damaged O
	arge to storm drains (staining/discoloration)? Y N	
*Index: O denotes notential no	ollution source: denotes confirmed polluter (ev	

Parking Lot: Approximate age 20 yrs. Condition: Clear Surface material Paved/Concrete Gravel Permeable	e 🗌 Doi	ı't kn	ow							0
E3. Do downspouts discharge to impervious surface? Y N Are downspouts directly connected to storm drains?		n't kr		∐Non Don't l		•			7	0
E4. Evidence of poor cleaning practices for construction activities (s	tains lea	ding	to stor	m drai	n)? 🔲 '	Y N		an't Te	11	0
F. TURF/LANDSCAPING AREAS \[\sum N/A \((skip to part G) \)			川家	700	Obs	erved	Pollut	ion Sou	rce?	N
F1. % of site with: Forest canopy 5 % Turf grass 8 % Lan	dscaping	10	% B	are Sc	il Ø	6			130	0
F2. Rate the turf management status: High Medium Lo	ow (o	JE	red						N	0
F3. Evidence of permanent irrigation or "non-target" irrigation	Z N		an't T	ell	cont.	avas	5		V	0
F4. Do landscaped areas drain to the storm drain system?			Can'						100	0
F5. Do landscape plants accumulate organic matter (leaves, grass clippings)	on adjac	ent in	pervio	us surfa	ice?	YZN	ПС	an't Tel	1	0
G. STORM WATER INFRASTRUCTURE N/A (skip to part	H) -		1	-	Obs	erved	Pollut	ion Sou	rce?	N
G1. Are storm water treatment practices present? YN N X	Jnknow	ı If y	es, ple	ase de	scribe:	prob	rloly	NOT	7	0
G2. Are private storm drains located at the facility? X Y N I Is trash present in gutters leading to storm drains? If so, cor	Unknownplete th	vn e ind	ex bel	ow.					1	0
Index Rating for	Accum	ılatio	n in G	utters						
Clean	1 2			159	Fi	lthy	-			
Organic material 1 2]3]3]3		Ē	4 4 4			5 5 (eo 5	¢ mo	Me)	P
G3. Catch basin inspection – Record SSD Unique Site ID here:		Cond	lition:	☐ Di	rty 🗌	Clean				
Not a hotspot (fewer than 5 circles and no boxes checked) P									ed)	

WATERSHED: Whiter Creek	SUBWATERSHED: W	UNIQUE SITE ID: WC Z-	451-01
E: 8/25/09	ASSESSED BY: DCB CAMERA ID: C	onen Pic#: 0053	
MAP GRID:	LAT 40 ° 52 '31.0" LONG 73 ° 31	137.6" LMK#	
A. SITE DATA AND BASIC CLASSIFICATI		The state of the last two	5 - 18
Name and Address: Common Ser	Category: Commercial Industrial Institutional Municipal	Miscellaneous ☐ Golf Course	
Of Terminal	Transport-Related	☐ Marina	
1 Communater Square	Paris Description of Occupit	Animal Facility	
SIC code (if available): 517	Basic Description of Operation:		New York
NPDES Status: ☐ Regulated ☐ Unknown	Durk ou receiving to	Morage	INDEX*
B. VEHICLE OPERATIONS N/A (Skip	to part C)	Observed Pollution Sou	rce? N
B1. Types of vehicles: Fleet vehicles	School buses Other: Boufe		
B2. Approximate number of vehicles: _C	(In Gorge: Bory side of fortion only a	in be mined	
	y): Maintained Repaired Recycled Fueled Wa	shed Stored	0
B4. Are vehicles stored and/or repaired of Are these vehicles lacking runoff diversion			0
B5. Is there evidence of spills/leakage fro			0
B6. Are uncovered outdoor fueling areas	present? Y N Can't Tell		0
B7. Are fueling areas directly connected to	o storm drains? Y N Can't Tell Unlike	plu	0
B8. Are vehicles washed outdoors? You Does the area where vehicles are washed	N Can't Tell)	0
C OUTDOOR MATERIALS N/A (Skip		Observed Pollution Sou	rce? N
Are loading/unloading operations pre	sent? XY N Can't Tell Directly ov	er water	0
If yes, are they uncovered and draining to	wards a storm drain inlet? Y Y Can'	't Tell	0
C2. Are materials stored outside? X Y Where are they stored? grass/dirt area	□ N □ Can't Tell If yes, are they ☒ Liquid □ So □ □ concrete/asphalt ☒ bermed area	olid Description: oil	0
C3. Is the storage area directly or indirect	ly connected to storm drain (circle one)? TY	M Can't Tell Unlikely	0
C4. Is staining or discoloration around the	e area visible? 🗌 Y 🔀 N 🔲 Can't Tell		0
C5. Does outdoor storage area lack a cove	er? X Y N Can't Tell		0
C6. Are liquid materials stored without se	condary containment? Y N Can't Tell		0
C7. Are storage containers missing labels	or in poor condition (rusting)? ☑ Y ☐ N ☐ Car	i't Tell Key mines	0
D. WASTE MANAGEMENT N/A (Ski)		Observed Pollution Sou	rce? Const
D1. Type of waste (check all that apply):	☐ Garbage ☐ Construction materials ☐ Hazard		0
D2. Dumpster condition (check all that a evidence of leakage (stains on ground	pply): No cover/Lid is open Damaged/poor co	ndition Leaking or	0
D3. Is the dumpster located near a storm of the storm of	drain inlet? Y N Can't Tell berms, curbs) lacking? Y N Can't Tell		0
E. PHYSICAL PLANT \[\sum N/A \(\sum N/A \) (Skip to pa	nF)	Observed Pollution Sou	rce?
E1. Building: Approximate age: _ 5	O yrs. Condition of surfaces: ☐ Clean Staine	ed Dirty Damaged	0
	charge to storm drains (staining/discoloration)? \(\square\) Y		0
*Index: O denotes potential	pollution source; denotes confirmed pollu	ter (evidence was seen)	

NCE-1451-01

Parking Lot: Approx Surface material	Paved/Concrete	Gravel Perme	able 🔀 D	on't k	now			Ca	g up	rice	w		0
E3. Do downspouts disch Are downspouts	arge to impervious directly connected		I Q N [Y □				one vis 't knov	sible					0
E4. Evidence of poor clea	aning practices for	construction activitie	es (stains l	eading	to st	orm d	rain)?	Y	□N	PA-C	an't Te	ell	0
F. TURF/LANDSCAPIN	GAREAS N/A	(skip to part G)	3. 16		Will	(Care		Obser	ved P	olluti	ion Sor	arce?	NA
F1. % of site with: Forest	canopy% T	urf grass%	Landscapi	ng	%	Bare		_%					0
F2. Rate the turf manager	ment status: H	igh Medium	Low										0
F3. Evidence of permane	nt irrigation or "no	n-target" irrigation [□ Y □ :	N 🗆	Can't	Tell						100	0
F4. Do landscaped areas	drain to the storm of	Irain system?] Y [N [Ca	n't Te	:11						0
F5. Do landscape plants acc	umulate organic matt	er (leaves, grass clippi	ngs) on adj	acent in	mperv	ious s	ırface?	☐ Y	□N	☐ Ca	an't Te	11	0
G. STORM WATER IN	FRASTRUCTURE	N/A (skip to p	art H)		37 9	7 3 3		Obser	ved P	olluti	ion Sou	arce?	
G1. Are storm water trea	tment practices pre	sent? Y N	X Unkno	wn If	yes,	please	_					7	0
G2. Are private storm dra Is trash present i		acility? Y N			dex b	elow.							0
		Index Rating	for Accu	mulati	on in	Gutte	rs C	onn		veu	/		
Sediment	Clean	Π2	П3					Filth	у П 5				
Organic material	Hi				9	H 4							
Litter	□ i		□3			4			□ 5	į.			
G3. Catch basin inspection				Cor	iditio	n: 🗌	Dirty	☐ Cl	ean				
INITIAL HOTSPOT	Or of the state of	Surgicial Control of the Control of		37			111			No.	×	- 20.00	No. 1
Not a hotspot (fewer t		젊게 되는데 이번 그를 하는 것이 잘하다고 것											
Confirmed hotspot (1 Follow-up Action:	0 to 15 circles and	or I box checked)	Severe	notspo	t (>1	circ	les and	or 2 o	r more	e boxe	s chec	ked)	
Refer for immediate e	enforcement				+			++				++	
Suggest follow-up on	-site inspection				+	+	in	VET .				+	
Test for illicit dischar					+	Con	1000	un	+	-	H	-	
Check to see if hotspo		n-filer			+		-	\mathbf{H}			+	++	
Onsite non-residentia					13	-11	100	12	ulis		1		
Pervious area restorat		sheet and record			121	-11	00	1 1/			1	11	4 - 14-1
Unique Site ID	storm water polluti	on prevention plan	I E	1	8	-11	100	1	1	1	-	11	
Benediale a review of	storm water ponds	on prevention plan			M	-11	1		X		-	-	4 1 1 5
Notes:				12 14	MUE	-11	1	1	1	7		111/2	3 4 1 1
			1,111,11		3	-11	01	1	X		1)	11	100
			1546	13, 17	1		10	X	1/		1	1	
					1	9	1		3				
				1			1	5		11	2		3=11 =1
			X	h II) i		OIL		13/2	2	11	30	11	
			1			SPIC	54)	K	18	_		M	
						150	0,0	11.	250	=	X	11	
				7-11	-	01	LFU	1					
						1	NIS	1					

** ATERSHED: O YGUR BOY	SUBWATERSHED: Whole's Creek	UNIQUE SITE	ID: WCR-451-05
TE: R /TG/ 6A	ASSESSED BY: GMB CAMERA ID:		PIC#: 163 - 173
MAP GRID:	LAT 40° 51 ' 26.3' LONG 73° 32	-06-0. (CB)	LMK#
A. SITE DATA AND BASIC CLASSIFIC			
Name and Address: Stop & Shop Plana / Pite A Plant Hollow Shopping SIC code (if available):	Institutional Municipal	Miscellaneous Golf Course Marina Animal Faci	
NPDES Status: Regulated Unregulated Unknow	Convertal Shap S (not be	ethy stnor p	INDEX
B. VEHICLE OPERATIONS N/A	Skip to part C)	Observed P	Pollution Source?
B1. Types of vehicles: A Fleet vehicles:	cles School buses Other: Unployed CAKS		vides
B2. Approximate number of vehicles:	10 small truck, I have truck		
	pply): Maintained Repaired Recycled Fueled Wa	shed Stored	9
B4. Are vehicles stored and/or repaire Are these vehicles lacking runoff dive	d outside? XY N Can't Tell Stock rsion methods? Y N Can't Tell		9
B5. Is there evidence of spills/leakage	from vehicles? Y N Can't Tell		0
B6. Are uncovered outdoor fueling are	eas present? Y N Can't Tell		0
B7. Are fueling areas directly connected	ed to storm drains? Y N Can't Tell		0
	ed discharge to the storm drain? Y N Can'	t Tell	0
OUTDOOR MATERIALS N/A (S	Skip to part D)	Observed P	ollution Source?
C1. Are loading/unloading operations If yes, are they uncovered <i>and</i> draining	present? ☑ Y ☐ N ☐ Can't Tell g towards a storm drain inlet? ☑ Y ☐ N ☐ Can'	t Tell	9
C2. Are materials stored outside? Where are they stored? ☐ grass/dirt a	Y ☐ N ☐ Can't Tell If yes, are they ☐ Liquid 🗹 So area 🗵 concrete/asphalt ☐ bermed area		pallets on the same
C3. Is the storage area directly or indir	rectly connected to storm drain (circle one)? X Y	Can't Tel	0
C4. Is staining or discoloration around	the area visible? Y N M.Can't Tell		0
C5. Does outdoor storage area lack a c	over? Y N Can't Tell		9
C6. Are liquid materials stored without	t secondary containment? Y N Can't Tell	prob NUT	0
C7. Are storage containers missing lab	els or in poor condition (rusting)? 🗌 Y 🛛 N 🔲 Can	't Tell	0
D. WASTE MANAGEMENT N/A (Skip to part E)	Observed P	ollution Source?
D1. Type of waste (check all that app	ly): 🛮 Garbage 🔲 Construction materials 🔲 Hazard		0
evidence of leakage (stains on gro			eaking or
D3. Is the dumpster located near a stor If yes, are runoff diversion method	m drain inlet? XY N Can't Tell ls (berms, curbs) lacking? Y N Can't Tell	4	0
E. PHYSICAL PLANT N/A (Skip to	part F)	Observed P	ollution Source?
E1. Building: Approximate age: 20 Evidence that maintenance results in o	- 10 yrs. Condition of surfaces: ☐ Clean ☒ Staine lischarge to storm drains (staining/discoloration)? ☐ Y	d Dirty D	Damaged 🔵
*Index: O denotes notant	al pollution source: denotes confirmed pollu	an lavidance	ora produc

WCR-HS1-02

Hotspot Site Investigation

Surface material	ximate age <u>30</u> yrs Paved/Concrete _	Gravel Perr	neable 🔲 🛭	Oon't kno	w			ig up				0
E3. Do downspouts disci Are downspout	harge to impervious s is directly connected t	urface? Y to storm drains?	I N N X			None on't kn					1	0
E4. Evidence of poor cle								Пи	Пс	an't Tel	1	0
F. TURF/LANDSCAPIN							100000	-77		on Sour		_
F1. % of site with: Fores	t canopy <u>0</u> % Tu	rf grass _ O _ %	Landscapi	ing 5	% Ba	re Soil	0%		Ontil	on both	-	0
F2. Rate the turf manage	ment status: Hig	h Medium	Low								-	0
F3. Evidence of permane	nt irrigation or "non-	target" irrigation	□ Y 🛛	N 🗆 Ca	n't Te	11					_	0
F4. Do landscaped areas	drain to the storm dra	nin system?	XY 🗆	N \square	Can't	Tell					_	ō
F5. Do landscape plants acc	umulate organic matter	(leaves, grass clip)	pings) on adj	acent imp	ervious	surface	? 🔲 Y	⊠ N	☐ Ca	n't Tell		0
G. STORM WATER IN	the state of the s									on Sour	00.9	
G1. Are storm water trea	ment practices prese	nt? 🗆 Y 🖾 N	Unkno	wn If ye	s, plea	se descr		· · · · · ·	onuen	on Sour		0
G2. Are private storm dra		ility? 🗌 Y 🔯 1	N Unkn	own								0
30,000,000	8		g for Accur						_	_		
	Clean		8		in ou		Filth	y			_	
Sediment		□ 2	□3			1		□ 5	4.			
Organic material Litter	H:		□ 3 □ 3					□ 5				
C3. Catch basin inspection	n – Record SSD Unio			10 Condit	ion: [Diety	⊠ Cl	5				_
. INITIAL HOTSPOT S				Condit	OH. L	1 Ditty	Z	can	-			
Not a hotspot (fewer the	Commence of the Commence of th		Potentia	hotspot	(5 to	10 circl	es hut r	o boy	es che	cked)		
Confirmed hotspot (1	0 to 15 circles and/or	1 box checked)	Severe h	otspot (>	15 cir	cles and	l/or 2 or	r more	boxes	checke	d)	
Follow-up Action:				1 1					T		ŤT	
Refer for immediate en			1 1			- (11)						
Suggest follow-up on- Test for illicit discharg				FIT II		-			++		++	
Include in future educa					0			1	+			+
Check to see if hotspor		ler			 	1	1		+	++		+
Onsite non-residential						+			+		++	1
Pervious area restorati Unique Site ID h		eet and record		11.			++	+	+		++	-
Schedule a review of s		prevention plan		1	1	1	1+	17	-	-	1-1-	-
7					$\downarrow \parallel$	13	11	1781	++		1	
Notes:				+	1	12	1 1	01	44			
				- 1 11 -	1	12	11					1
				1 5	1	10	44		1	\perp		
						1					**	
				1115	L III	1	> {	P		H H, I		
							1111	11				
			1		- 1			-	-		_	_
				C				Lon				
				C			5	hop				

WATERSHED: OYSTER BOLY	SUBWATERSHED: Bailey Arb	UNIQUE	SITE ID: BAI - A	5A-01
DATE: GILLI OF	ASSESSED BY: THE ME		AID: Couran	PIC#: 5]-/5
A. NEIGHBORHOOD CHARACTERI	ZATION			
Neighborhood/Subdivision Name:/		1	Neighborhood Area (a	cres)
If unknown, address (or streets) surveye	d: Park Ave, Egypt/	V		
Homeowners Association? TY N	Unknown If yes, name and con	tact information:		
Residential (circle average single famil				
☐ Single Family Attached (Duplexes, I Single Family Detached	Row Homes) <1/8 1/8 1/4 1/3 1/3	acre Multi	family (Apts, Townho	mes, Condos)
Estimated Age of Neighborhood: 50-60	years Percent of Homes with Gar years Percent of Homes with H		ile Home Park	INDEX*
Sewer Service? ☐ Y ☐ N ?	Jours Tereent of Homes with Gar	ages. 20 %	itii Basements 100 %	
Index of Infill, Redevelopment, and Ren	nodeling No Evidence 7 500	of units D 5 10	07. T > 1007	0
Record percent observed for each		or units [] 3-10	% <u> >10%</u>	0
depending on applicability		Percentage	Comments/Notes	
B. YARD AND LAWN CONDITIONS				
B1. % of lot with impervious cover		30		
B2. % of lot with grass cover		3, 5		0
B3. % of lot with landscaping (e.g., mul	ched bed areas)	35		\Q
B4. % of lot with bare soil		0		0
*Note: B1 through B4 must total	d 100%			
B5. % of lot with forest canopy		50		\Q
B6. Evidence of permanent irrigation or	"non-target" irrigation	50		0
		High: <u>\$0</u>		0
B7. Proportion of total neighborhood turmanagement status:	f lawns with following	Med: 20		
management status.		Low: _O_		-
B8. Outdoor swimming pools? □Y □N	Can't Tell Estimated #			0
B9. Junk or trash in yards? ☐ Y ☒	N 🗌 Can't Tell			0
C. DRIVEWAYS, SIDEWALKS, AND	CURBS			
C1. % of driveways that are impervious	□ N/A 75%			
C2. Driveway Condition 🖾 Clean 🔲	Stained Dirty Breaking up			0
C3. Are sidewalks present? TYN				
	with lawn clippings/leaves Rece	eiving 'non-target	' irrigation	0
What is the distance between the	sidewalk and street? ft.		***************************************	\Q
Is pet waste present in this area?			***************************************	0
	N If yes, check all that apply:			
	or standing water Long-term car	************		O .
Organic matter, leaves, lawn	clippings Trash, litter, or debr tial pollution source; denotes			\Diamond

NSA

D. ROOFTOPS						37	
D1. Downspouts are directly connected to storm drains or	sanitary sewer	10					0 0
D2. Downspouts are directed to impervious surface		50	,				1111
D3. Downspouts discharge to pervious area		50					
D4. Downspouts discharge to a cistern, rain barrel, etc.		^				-	
*Note: C1 through C4 should total 100%						-	
D5. Lawn area present downgradient of leader for rain gar	den? Y N	80	/				\Q
E. COMMON AREAS				-		10	
E1. Storm drain inlets? Y N If yes, are they stence Catch basins inspected? Y N If yes, inclu	de Unique Site ID	from SSD	sheet:	*******			0
E2. Storm water pond? Y N Is it a wet pond What is the estimated pond area? <1 acre	or ∐ dry pond? about 1 acre ☐ :	Is it overg	rown?	Y [N		\Q
E3. Open Space? ☐ Y ☒ N If yes, is pet waste present Buffers/floodplain present: ☐ Y ☒ N If yes, is	? □Y ⊠N dı	umping?		1			0
F. INITIAL NEIGHBORHOOD ASSESSMENT AND REC			Пи				
Based on field observations, this neighborhood has signific Nutrients Oil and Grease Trash/Litter Back	ant indicators for t	the followin	g: (chec	k all the	ut apply)		0
 ☑ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? ☐ Multi-family Parking Lot Retrofit? ☐ Other action(s) 							
Initial Assessment	- 17 13 13 13		100		T		1
NSA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) Neighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked) Low (Fewer than 3 diamonds checked)							
NOTES:							

WATERSHED: UYSLUK BOY	SUBWATERSHED: (old S	my Handra UNIQUE	SITE ID: CSH-A	15A-01
DATE: 8/25/09	ASSESSED BY: KMB	CAMERA		Pic#: 55-6
A. NEIGHBORHOOD CHARACTE	RIZATION START	405147,67		
Neighborhood/Subdivision Name:	orbor load - west of co		Neighborhood Area (ac	eres)
If unknown, address (or streets) surve	yed:			
Homeowners Association? TY	N W Unknown If yes, name and	contact information:		
Residential (circle average single fan	nily lot size):			
☐ Single Family Attached (Duplexes Single Family Detached	, Row Homes) <1/8 1/8 1/4 1/3	1/3 acre Mult	ifamily (Apts, Townho	mes, Condos)
Estimated Age of Neighborhood: 80	60 years Percent of Homes with		ile Home Park Vith Basements%	I IMPEN
Sewer Service? Y N Care		Garages/// V	itii Basements%	INDEX*
Index of Infill, Redevelopment, and R	The state of the s	<5% of units □ 5-10	% ☑ >10%	0
Record percent observed for ea	ich of the following indicators,	Percentage	Comments/Notes	
depending on applicabili B. YARD AND LAWN CONDITIONS		- Tercentage	comments/14otes	
B1. % of lot with impervious cover		1 40	Huse	
B2. % of lot with grass cover		40	()	0
B3. % of lot with landscaping (e.g., m	ulched bed areas)	10		0
B4. % of lot with bare soil	***************************************	0		Ŏ
*Note: B1 through B4 must to	otal 100%			
B5. % of lot with forest canopy		10		\Q
B6. Evidence of permanent irrigation of	or "non-target" irrigation	80	water they	
		High: <u>loo</u>	clean & cared for	0
B7. Proportion of total neighborhood t management status:	urf lawns with following	Med:		
management status.		Low:		
B8. Outdoor swimming pools? ☐Y ☐	N Can't Tell Estimated #			0
B9. Junk or trash in yards?	N ☐ Can't Tell			0
C. DRIVEWAYS, SIDEWALKS, AND	CURBS			
C1. % of driveways that are impervious	ıs N/A	100		
C2. Driveway Condition Clean	Stained Dirty Breaking	up		0
C3. Are sidewalks present? 🖳 Y 🗵	N If yes, are they on one side of s	treet or along both	n sides 🔲	
	ed with lawn clippings/leaves	Receiving 'non-targe	t' irrigation	0
What is the distance between t	he sidewalk and street? ft.			♦
Is pet waste present in this are			5,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1	0
C4. Is curb and gutter present?	N If yes, check all that app	oly: upper port	ÞΛ	
	g or standing water Long-term			0
Organic matter, leaves, lav	ential pollution source; deno	debris Overhead		\Diamond

D. ROOFTOPS							35				
D1. Downspouts are directly connected to storm drains or	sanitary sewer	0100	400		THE W					0	0
D2. Downspouts are directed to impervious surface		1	09	6							
D3. Downspouts discharge to pervious area	900/11	WEST	W	11	TX.	EN	201	#1	49		
D4. Downspouts discharge to a cistern, rain barrel, etc.	10/14	PA TES			0,1-	100	anto	eno	1		
*Note: C1 through C4 should total 100%					_				1		
D5. Lawn area present downgradient of leader for rain gar	den? X Y 🗆	V		D	rivor	tep	roa	de	4		•
E. COMMON AREAS				1		1	-		1		
E1. Storm drain inlets? Y N If yes, are they stenci Catch basins inspected? Y N If yes, inclu						Dir	ty				◊
E2. Storm water pond? YN Is it a wet pond What is the estimated pond area? <1 acre	or dry pond?	Is it	overg				N			_	\rightarrow
E3. Open Space? ☐ Y ☒ N If yes, is pet waste present Buffers/floodplain present: ☐ Y ☐ N If yes, is										(0
F. INITIAL NEIGHBORHOOD ASSESSMENT AND REC											-
Based on field observations, this neighborhood has signific Nutrients Oil and Grease Trash/Litter Bac	ant indicators for	r the fol	lowin Other	g: (ch	eck al	l that	арр	ly)	1	(3
Specific Action Onsite retrofit potential? Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s)	rain likely i	barre use fi	ls t erti	for i	rnig s ov	atio la	wn	15			
Initial Assessment NSA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) Neighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked) Low (Fewer than 3 diamonds checked)	HARBOK.	1ARBOR 1/20	year S danser	A Co	CS ST	H		1	M	03.0	ope.

WATERSHED: Uyslea Bay	SUBWATERSHED: (entre	Sand UNIQUE	SITE ID: LTR-N	SA-01
DATE: 8 124109	ASSESSED BY: MAG	CAMER		PIC#: 160
A. NEIGHBORHOOD CHARACTER	IZATION	•		1,00
Neighborhood/Subdivision Name:			Neighborhood Area (acr	res)
If unknown, address (or streets) survey	ed:			
Homeowners Association? TY		contact information		
Residential (circle average single fam			\$ 20 gares	
☐ Single Family Attached (Duplexes, Single Family Detached	Row Homes) <\\\^{1}\/8 \\^{1}\/4 \\^{1}\/3 \\^{1}\/4 \\^{1}\/2 1 \left(1/3 acre Mul	tifamily (Apts, Townhor	nes, Condos)
Estimated Age of Neighborhood?			vith Basements / 0.0%	INDEX*
Sewer Service? ☐ Y ☒ N	_ years Teresia of Fromes with	Surages. 1 2 70	vitii Basements (200%)	INDEA.
Index of Infill, Redevelopment, and Re	modeling No Evidence	5% of units □ 5-10	0% 🗆 >10%	
Record percent observed for each				0
depending on applicabilit	y and/or site complexity	Percentage	Comments/Notes	
B. YARD AND LAWN CONDITIONS				
B1. % of lot with impervious cover		20	driveway & house	
B2. % of lot with grass cover		60	0	0
B3. % of lot with landscaping (e.g., mu	llched bed areas)	20		\Q
B4. % of lot with bare soil		0		0
*Note: B1 through B4 must to	al 100%			
B5. % of lot with forest canopy		30		\Q
B6. Evidence of permanent irrigation or	"non-target" irrigation	100		0
Late of the second		High: 100		0
B7. Proportion of total neighborhood to	rf lawns with following	Med:		
management status:		Low: D		
B8. Outdoor swimming pools? XY	N Can't Tell Estimated #		Likely	0
B9. Junk or trash in yards? ☐ Y 🄀	N Can't Tell			0
C. DRIVEWAYS, SIDEWALKS, AND	CURBS			
C1. % of driveways that are impervious	s □ N/A	100	long frie wars	
C2. Driveway Condition 🛛 Clean 🔲	Stained Dirty Breaking	ар	0	0
C3. Are sidewalks present? Y	N If yes, are they on one side of st	reet or along bot	h sides	
	l with lawn clippings/leaves 🔲 l			0
What is the distance between the	e sidewalk and street? ft.		*******************	\Diamond
Is pet waste present in this area		7		0
	☐ N If yes, check all that app			
	or standing water Long-term			O
	n clippings			•

CTR-NSA-01

Neighborhood Source Assessment

NSA

D. ROOFTOPS NOT assessed -	In Acres	5			_				1	- 17
D1. Downspouts are directly connected to storm drains or					Т				0	0
D2. Downspouts are directed to impervious surface	3.00								\ \ \	_
D3. Downspouts discharge to pervious area			_						-	-
D4. Downspouts discharge to a cistern, rain barrel, etc.								-		-
*Note: C1 through C4 should total 100%		_		-	L-	-			-	
D5. Lawn area present downgradient of leader for rain gar	rden? Y]N	****						0	>
E. COMMON AREAS No access										
E1. Storm drain inlets? Y N If yes, are they stend Catch basins inspected? Y N If yes, inclu E2. Storm water pond? Y N Is it a wet pond	ude Unique Site	e ID f	rom S	SD she	et:	*****	******	******	0)
What is the estimated pond area? \square <1 acre	about 1 acre	a? □>:	Is it o	vergrov	vn? L] Y	∐N		0	>
E3. Open Space? Y N If yes, is pet waste present	t? 🗌 Y 🔲 N	dun	ping'	Y 🗆 Y	*****	1	******		0)
Buffers/floodplain present: Y N If yes, is			ent? L	JY L	JN					
F. INITIAL NEIGHBORHOOD ASSESSMENT AND REC Based on field observations, this neighborhood has signific Nutrients Oil and Grease Trash/Litter Bac	ant indicators	for the	follo	wing:	(chec	k all	that ap	ply)	0	
 ☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? ☐ Multi-family Parking Lot Retrofit? ☐ Other action(s) 	(no						*			
Initial Assessment								П		1
NSA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) Neighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked) Low (Fewer than 3 diamonds checked)										
NOTES:										

WATERSHED: OYSEW Bay	SUBWATERSHED: MILL NECK CA	UNIQUE	SITE ID: MNC-N	(A-01
DATE: 6 125/ 09	ASSESSED BY: KMB	CAMER	A Committee of the Comm	Pic#: 142
A. NEIGHBORHOOD CHARACTER	RIZATION			
Neighborhood/Subdivision Name:			Neighborhood Area (acr	es)
If unknown, address (or streets) survey	llison			
	N Unknown If yes, name and conta	ct information:		
Residential (circle average single fam				
☐ Single Family Attached (Duplexes. ☐ Single Family Detached	Row Homes) <1/8 1/8 1/4 1/3 1/3 a		tifamily (Apts, Townhon	nes, Condos)
Estimated Age of Neighborhood: 50	/4 (1/4) 1/2 1 1 a years Percent of Homes with Gara		vile Home Park With Basements %	INDEX*
Sewer Service? Y N	_ years Telectit of Homes with Gara;	ges	with Basements%	
The state of the s	emodeling ☐ No Evidence ☒ <5% o	funits 7 5-10	0% 🗖 >10%	0
Record percent observed for ea				0
depending on applicability	y and/or site complexity	Percentage	Comments/Notes	
B. YARD AND LAWN CONDITIONS				
B1. % of lot with impervious cover		60		
B2. % of lot with grass cover		20	Same not cared	0
B3. % of lot with landscaping (e.g., m	ulched bed areas)	10		\Q
B4. % of lot with bare soil		10		0
*Note: B1 through B4 must to	tal 100%			
B5. % of lot with forest canopy		< 5		\Q
B6. Evidence of permanent irrigation o	r "non-target" irrigation			0
		High: 80		•
B7. Proportion of total neighborhood to management status:	arf lawns with following	Med: 10		
management status.		Low: <u>10</u>	En really overgroun	*******
B8. Outdoor swimming pools?	N Can't Tell Estimated #		CV 1 - 1 - 1C3 - 100VI	0
B9. Junk or trash in yards?	N Can't Tell			0
C. DRIVEWAYS, SIDEWALKS, AND	CURBS			
C1. % of driveways that are imperviou	s N/A	90	Come aravel	
C2. Driveway Condition Clean	Stained Dirty Breaking up			0
C3. Are sidewalks present? TY	N If yes, are they on one side of street [or along bot	h sides 🗌	
☐ Spotless ☐ Covere	d with lawn clippings/leaves 🔲 Recei	ving 'non-targe	et' irrigation	0
What is the distance between t	he sidewalk and street? ft.			\Q
Is pet waste present in this area				0
	N If yes, check all that apply:			
	or standing water \[\sum Long-term car pa			•
	n clippings Trash, litter, or debris			♦

MNC-USA-01

Neighborhood Source Assessment

NSA

D1. Downspouts are directly connected to storm drains or	canitary causer	1 1	1			1	_
D2. Downspouts are directed to impervious surface	samiary sewer	4	144-	Ja Ja	To the second		C
		80	100 miles	1 Led	1		
D3. Downspouts discharge to pervious area		20	mule	hed are	e 5		
D4. Downspouts discharge to a cistern, rain barrel, etc.		Ø	- 1/				
*Note: C1 through C4 should total 100%							
D5. Lawn area present downgradient of leader for rain gar	rden? Y N					•	
E. COMMON AREAS							
E1. Storm drain inlets? Y ☐ N If yes, are they stence Catch basins inspected? Y ☐ N If yes, included.	ide Unique Site ID	from SSD s	heet: M	JK-55	0-01	0	
E2. Storm water pond? Y N Is it a wet pond What is the estimated pond area? <1 acre	about 1 acre 🔲 >	> 1 acre		Y 🗆 N		•	
3. Open Space? Y N If yes, is pet waste present	***************		*********			0	
Buffers/floodplain present: Y N If yes, is	encroachment evi	dent? 🗌 Y	\square N		000000	300000000	
F. INITIAL NEIGHBORHOOD ASSESSMENT AND REC	COMMENDATION	S					
Based on field observations, this neighborhood has signific	ant indicators for t	he following	;: (check	all that a	pply)		
Nutrients Oil and Grease Trash/Litter Bac	cteria Sedimen	t Other				0	
Recommended Actions	Describe R	ecommende	d Actions	:			
Specific Action	Bayvie	AVe	not p	wed, c	my o	(rue)	
Onsite retrofit potential?	1 ve	un broke	min	- 10 60	- 1	drew	
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice?	1 ve	nd prola	nob	- b w	tra	do	
	Landsca	is prola	some	- low	t was	don	
☑ Better lawn/landscaping practice?	Landsca	ibind on	some dlots	- but	t ha	don ose	
☑ Better lawn/landscaping practice?☑ Better management of common space?☑ Pond retrofit?	Landson Sh	up broken	some dlass	laws	t hai	dol ose	
 ☑ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? ☐ Multi-family Parking Lot Retrofit? 	landsia to sh	young on	some d lats sedin	laws	t had	dol ose	
☑ Better lawn/landscaping practice?☑ Better management of common space?☑ Pond retrofit?	Landsca to Sh	y broker	some some d lots sedin	laws	t had	don ose	T
 ☑ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? ☐ Multi-family Parking Lot Retrofit? ☐ Other action(s) 	Landson Sh	y broken	some some d lots sedin	laws	t nais of	don o se and	1
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index	Landsca to Sh	y broken	some some d lots sedin	- but lawn of 1	t nais	don o se and	I
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) nitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked)	Landsca to Sh			- but laws of d	t nais	don o se	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) itial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked)	Land Sca		libon	- but laws of d	t nais	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked)	Land Sca to Sh			- but lawn of 1	t nais	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) itial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked)	Landsca to Sh	\$ \$ \$	libon	- but lawn of 1	t Nais ch	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked)	Land Sca to Sh	Ser to the series of the serie	libon	- but laws of d	t nais	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) None (No circles checked)	Land Sca to Sh	\$ \$ \$	libon	- but lawn of d	t nais	don ose and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) nitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) eighborhood Restoration Opportunity Index High (More than 5 diamonds checked)	Land Sca to Sh	Ser to the series of the serie	lison pand	- but lawn of 1	t Nais ch	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) nitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) eighborhood Restoration Opportunity Index High (More than 5 diamonds checked)	Land Sca to Sh	Ser to the series of the serie	lison pand	- but lawn of 1	t nais	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) eighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked)	Land Sca to Sh	Ser to the series of the serie	lison pand	- but lawn of d ent in	t nais	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) eighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked)	Land Sca to Sh I am	Ser to the series of the serie	lison pand	- but lawn of 1	t Nais chans	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) eighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked)	Land Sca to Sh	Ser to the series of the serie	lison pand	- but lawn of 1	t Nais 1's cr elons road	854 8-8	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) eighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked)	Land Sca to Sh	Ser to the series of the serie	lison pand	- but lawn of 1	t nais	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) eighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked)	Land Sca to Sh I am	Ser to the series of the serie	lison pand	- but lawn of d ent in	t nais chebras tond	don o se and	
Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s) mitial Assessment SA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) eighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked)	Land Sca to Sh	Ser to the series of the serie	lison pand	- but lawn of 1	t Nais ch	don o se and	

WATERSHED: OYS EX Bay	SUBWATERSHED: MILL Neck (VE	ec Unique	SITE ID: MMC-A	54-07
DATE: 8/26/09	ASSESSED BY: KMB	CAMER		PIC#: 54- 5
A. NEIGHBORHOOD CHARACTER	IZATION			
Neighborhood/Subdivision Name:			Neighborhood Area (ac	res)
If unknown, address (or streets) survey	Out-fall elud to	DAKNEC	K Creek (Am	of VK
Homeowners Association? TY	N 🔲 Unknown If yes, name and contact	ct information:		
Residential (circle average single fam				
 Single Family Attached (Duplexes, Single Family Detached 	Row Homes) <1/8 1/8 1/4 1/3 1/3 acc		ifamily (Apts, Townhorile Home Park	nes, Condos)
Estimated Age of Neighborhood: 50			Vith Basements%	INDEX*
Sewer Service? Y N 2		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	, in Busements/v	O
	emodeling ☑ No Evidence ☐ <5% o	f units 75-10	0% □ >10%	0
Record percent observed for ea depending on applicabilit		Percentage	Comments/Notes	
B. YARD AND LAWN CONDITIONS	y ana/or suc complexity			
B1. % of lot with impervious cover		60		
B2. % of lot with grass cover		10		0
B3. % of lot with landscaping (e.g., m	ulched bed areas)	30		0
B4. % of lot with bare soil		D		0
*Note: B1 through B4 must to	tal 100%			
B5. % of lot with forest canopy		<5		0
B6. Evidence of permanent irrigation of	r "non-target" irrigation			0
Safet Berg Barrier		High: <u>100</u>		0
B7. Proportion of total neighborhood to management status:	arf lawns with following	Med: _0_		1
management status.	1	Low:	7	
B8. Outdoor swimming pools?	N 🖾 Can't Tell Estimated #		probably-force	0
B9. Junk or trash in yards?	N Can't Tell			0
C. DRIVEWAYS, SIDEWALKS, AND	CURBS			
C1. % of driveways that are imperviou	s N/A	OD		
C2. Driveway Condition 🛛 Clean 🗌	Stained Dirty Breaking up			0
C3. Are sidewalks present? TY	N If yes, are they on one side of street	or along both	h sides 🗌	
	d with lawn clippings/leaves	ing 'non-targe	t' irrigation	0
	ne sidewalk and street? ft.			♦
Is pet waste present in this area				0
	□ N If yes, check all that apply:		F8V	
Organic matter, leaves, law	or standing water Long-term car pa			0
	n clippings Trash, litter, or debris			•

Assessment NSA

Neighborhood Source Assessment

D. ROOFTOPS D1. Downspouts are directly connected to storm drains or	canitary conver	T	-		7	-		-		-	_	
D2. Downspouts are directed to impervious surface	samary sewer		1	0	+	-		-		-	<	> (
D3. Downspouts discharge to pervious area		-4	2	_	-	la la	1.5		-	-		
		-	8	-	-	Sely:	4)	rie!	15?			
D4. Downspouts discharge to a cistern, rain barrel, etc. *Note: C1 through C4 should total 100%		- 11	C	Ĵ			Ü			_		
D5. Lawn area present downgradient of leader for rain gar	rden? 🗆 V 🖸	an I		-	1		· A · · ·	· · · · · · · · · · · · · · · · · · ·	1	\dashv		^
E. COMMON AREAS	iden. Li I	211	-	-		Svi	J. y	are	5			♦
E1. Storm drain inlets? X Y N If yes, are they stenci												\phi
Catch basins inspected? Y IN If yes, inclu	ide Unique Site	e ID fr	om S	SD s	sheet	. M/	1/4	-555	>0.	2_		0
E2. Storm water pond? ☐ Y ☐ N Is it a ☐ wet pond What is the estimated pond area? ☐ <1 acre ☐	or dry pond about Lacre	d? I ⊠ > 1	s it o	verg	rowr	1? 🛚	Y [N				•
E3. Open Space? Y N If yes, is pet waste present							Sha	el-ly	120			0
Buffers/floodplain present: \(\sum Y \subseteq N \) If yes, is												·
F. INITIAL NEIGHBORHOOD ASSESSMENT AND REC			ut; _] I	Н	IN	-					_
Based on field observations, this neighborhood has signific	CONTRACTOR DELEVATION		follo	wine	n: (c	hack	all +la	at an	- /-· \	-		
☐ Nutrients ☐ Oil and Grease ☐ Trash/Litter ☐ Bac	cteria Sedi	ment		ther	g. (c	песк	au in	ат ар	pty)			0
Recommended Actions	Describ					ction	s:			-		-
6 76 4 7								18100	v /	3.5		
Specific Action	4010	~ MD	DAG	13	MAIL	rukan	52	240	-1 -4	3.0		
Specific Action Onsite retrofit potential?	40110	meint	1001	Van I	Jan	40	Oal	N	20/0	Bu	dot	He
☐ Onsite retrofit potential?☐ Better lawn/landscaping practice?	Follo	reigh Swh	100x 1	noo!	7	To	Oal	ho	ecle	e al	d of	He
 ☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? 	40110	and styl	land I	Man A	7	To av	Onlea	be be	ecle	e al	d of	He
 ☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☑ Pond retrofit? wet lawdard 	4010	St-1	land l	t la	on on	To av	ea	be o	ecle you	~d	d of	He
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Wet land And A	4010	st 1	land l	1/4	on	To av	Par	be p	eck.	~d	-d of	He
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Wet A A A A A A A A A A A A A A A A A A	10110	ST-1	lani l	han ha	on	to av	on ea	be o	eck.	~d ~d	d o	He
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Wet A A A A A A A A A A A A A A A A A A	1000	awa Ist I	long l	1/4	on	To av	Paren	No los	eck you	~! ~! ~!	d o	the
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☑ Pond retrofit? ખાદ્યો તે	4010	nel gla	land l	1 / la	00	10 0 V	Par	be be	La	~d ~d		He
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Wet A A A A A A A A A A A A A A A A A A	4000	AND IST I	lan l	t la	02	HO OVE	Ontea	Le be	eck you	~!	0	He
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Wet A A A A A A A A A A A A A A A A A A A	4000	2019 2017 2017	lani l	1 / la	0	to av	PVIE ATT	Le P	eck you	~! ~!		He
Onsite retrofit potential? Better lawn/landscaping practice? Better management of common space? Pond retrofit? Wet lawd and a law	4000	nel ava	lani l	Mau	on On	To av	On Par	Le P	eck you	e de		- He
Onsite retrofit potential? Better lawn/landscaping practice? Better management of common space? Pond retrofit? Wet lawd And A Multi-family Parking Lot Retrofit? Other action(s) Initial Assessment NSA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked)	1000	2017 2017 157-1	interiors	Nou Ala	On On	to aven	PVIE ATT	Le P	eck you			- i\e
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Wet A A A A A A A A A A A A A A A A A A A	W 0 (10-	nel ava	land l	May Ala	on On	to average	PVIE ATT	Le P	Za F			
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☑ Pond retrofit? Wet Lawton ☐ Multi-family Parking Lot Retrofit? ☐ Other action(s) ☐ Other action(s) ☐ Minitial Assessment NSA Pollution Severity Index ☐ Severe (More than 10 circles checked) ☐ High (5 to 10 circles checked) ☑ Moderate (Fewer than 5 circles checked) ☐ None (No circles checked) ☐ None (No circles checked) Neighborhood Restoration Opportunity Index	W 0 (10-	religion and	land land	Nau Ala	NAV.	to aven	PVIE ATT	Le P	La P	- d - ce		
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Well And	4000	nel ava	land land	1	ENTAN OF STATE OF STA	The average	PVIE ATT	Le P	eck you	- d		
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Well And	10110	religion and	land land	1	NAMA ON	to aven	PVIE ATT	Le P	ecle you	e ~! ~! ~!		- 11-
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Well And	1000	nel ava	land land	1	NAMA ON	to average	PVIE ATT	Le P	eck you	- d		- 140
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Wet A A A A A A A A A A A A A A A A A A A	1010	nel ava	land land	1	NAMA ON	to average	PVIE ATT	Le P	ecle you	200		- 1
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Wet A A A A A A A A A A A A A A A A A A A	10110	PALAN IST I	land land	1	Non	to avair	PVIE ATT	Le P	ecke go	- d - ce		9/4
☐ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? Wet A A A A A A A A A A A A A A A A A A A	10110	nel ava	000	1	Non On On One of the Original Property of the	to average	PVIE ATT	Le P	ecke you	- d - ce		

A-4

WATERSHED: OTSLEY BAY	SUBWATERSHED: MILL RIVE	Unique	SITE ID: MEV-A	JSA-01
DATE: 8 127 0 1	ASSESSED BY: KMB	CAMERA		PIC#: 229-7
A. NEIGHBORHOOD CHARACTER	IZATION	д.		
Neighborhood/Subdivision Name:	yster bay Gardens - H.		Neighborhood Area (ac	res)
If unknown, address (or streets) survey	red:			
Homeowners Association? TY	N Unknown If yes, name and cor	ntact information:		
Residential (circle average single fam				4
☐ Single Family Attached (Duplexes,☐ Single Family Detached				nes, Condos)
Estimated Age of Neighborhood: 46	<pre></pre>		ile Home Park	INDEX.
Sewer Service? Y N Check	_ years refeelt of Hollies with Ga	rages% w	7ith Basements MA %	INDEX*
Index of Infill, Redevelopment, and Re	emodeling No Evidence N < 5%	of units \square 5-10	% □ >10%	0
Record percent observed for ea				0
depending on applicabilit	y and/or site complexity	Percentage	Comments/Notes	
B. YARD AND LAWN CONDITIONS		1 110		
B1. % of lot with impervious cover		40		
B2. % of lot with grass cover		40		0
B3. % of lot with landscaping (e.g., m	ilched bed areas)	20		\Q
B4. % of lot with bare soil			1	0
*Note: B1 through B4 must to	tal 100%			
B5. % of lot with forest canopy		10		\Q
B6. Evidence of permanent irrigation of	"non-target" irrigation			0
		High:		0
B7. Proportion of total neighborhood to management status:	urf lawns with following	Med:		
Salara Salara		Low:		
B8. Outdoor swimming pools?	N Can't Tell Estimated #			0
B9. Junk or trash in yards?	N ☐ Can't Tell			0
C. DRIVEWAYS, SIDEWALKS, AND	CURBS			
C1. % of driveways that are imperviou	s 🔀 N/A	, -	parking lots	
C2. Driveway Condition Clean	Stained Dirty Breaking up		The state of the s	0
C3. Are sidewalks present? 💹 Y 🔲				
**********************************	d with lawn clippings/leaves Rec	eiving 'non-targe	t' irrigation	0
What is the distance between the	ne sidewalk and street? 7,5 ft.			♦
Is pet waste present in this area				0
	☐ N If yes, check all that apply:			
☐ Clean and Dry ☐ Flowing	or standing water Long-term car	parking [A] Sedi	ment 3 incles	0
	n clippings Trash, litter, or deb ntial pollution source; denotes			\Q

D1. Downspouts are directly connected to storm drains or	sanitary sewer	0				0 C
D2. Downspouts are directed to impervious surface		50				, , , ,
D3. Downspouts discharge to pervious area		50	1.00	ched be	1	
D4. Downspouts discharge to a cistern, rain barrel, etc.		0	1 may 2	evea be		
*Note: C1 through C4 should total 100%					_	
D5. Lawn area present downgradient of leader for rain gar	den? YN					0
E. COMMON AREAS					7	
E1. Storm drain inlets? Y N If yes, are they stence Catch basins inspected? Y N If yes, inclu E2. Storm water pond? Y N Is it a wet pond	de Unique Site ID	from SSD sh	neet:	*********		♦
What is the estimated pond area? ☐ <1 acre ☐	about 1 acre \square >	· 1 acre	JWII! [] 1			♦
E3. Open Space? Y N If yes, is pet waste present Buffers/floodplain present: Y N If yes, is				7		0
F. INITIAL NEIGHBORHOOD ASSESSMENT AND REC						
Based on field observations, this neighborhood has significe. ☐ Nutrients ☑ Oil and Grease ☐ Trash/Litter ☐ Back	ant indicators for the	he following:	(check a	ll that app	ly)	•
Better lawn/landscaping practice?	1017 61	01 51011	my Or	DOG FIN	7 71	
☐ Better management of common space? ☐ Pond retrofit? ☐ Multi-family Parking Lot Retrofit? ☐ Other action(s)		viring ar			1 0	47.)
☐ Pond retrofit?					\ 0	· · · ·
☐ Pond retrofit? ☑ Multi-family Parking Lot Retrofit? ☐ Other action(s)					\ \ \	

	A 10	
	6. V	
TA	DA	

WATERSHED: Myen Buy	SUBWATERSHED: OB HANDON	UNIQUE	SITE ID: OBH - NX	SA-01
DATE: 8 /25/09	ASSESSED BY: UMB	CAMERA		PIC#: 79-93
A. NEIGHBORHOOD CHARACTERIZ	ZATION			
Neighborhood/Subdivision Name: _ 5h			Neighborhood Area (acr	res)
If unknown, address (or streets) surveyed Ships Pt Lave, Mellywee	clown Planence			
Homeowners Association? TYN	Unknown If yes, name and cont	act information:		
Residential (circle average single family			A areas areas	
☐ Single Family Attached (Duplexes, R ☐ Single Family Detached	(4) 1/4 1/2 1 >1		ifamily (Apts, Townhor ile Home Park	nes, Condos)
Estimated Age of Neighborhood: 20^{-10}	years Percent of Homes with Gar	ages: 50% V	With Basements%	INDEX*
Sewer Service? Y N				0
Index of Infill, Redevelopment, and Rem	nodeling No Evidence <a> <5%	of units 5-10	0% 🔯 >10%	0
Record percent observed for each depending on applicability		Percentage	Comments/Notes	
B. YARD AND LAWN CONDITIONS				
B1. % of lot with impervious cover		50		
B2. % of lot with grass cover		20	fortilizers	0
B3. % of lot with landscaping (e.g., mulc	ched bed areas)	20		♦
B4. % of lot with bare soil				0
*Note: B1 through B4 must total	l 100%			
B5. % of lot with forest canopy		10	Colores of	\Q
B6. Evidence of permanent irrigation or '	"non-target" irrigation	50	Very areal lance	0
		High: <u>91</u>	ferthans	0
B7. Proportion of <i>total neighborhood</i> turn management status:	f lawns with following	Med: 10		
management status.		Low:		
B8. Outdoor swimming pools? □Y ☑N	Can't Tell Estimated #		-1	0
B9. Junk or trash in yards?	N Can't Tell		1	0
C. DRIVEWAYS, SIDEWALKS, AND C	CURBS			
C1. % of driveways that are impervious	□ N/A	80	many gravel	
C2. Driveway Condition 🖂 Clean 🔲 S	Stained Dirty Breaking up			0
C3. Are sidewalks present? \square Y \square N	If yes, are they on one side of street	or along bot	h sides [Miked ay	4 bre since
	with lawn clippings/leaves Reco	eiving 'non-targe	et' irrigation overgous	0
What is the distance between the	************************************			
Is pet waste present in this area?				0
	☐ N If yes, check all that apply: or standing water ☐ Long-term car	parking M Sad	imant	
Organic matter, leaves, lawn				0
	tial pollution source; \diamondsuit denotes			

OBH-MA-OL Sment NSA

Neighborhood Source Assessment

D. ROOFTOPS								
D1. Downspouts are directly connected to storm drains or	sanitary sewer	10	- Un	chow	n		1	> 0
D2. Downspouts are directed to impervious surface		20						
D3. Downspouts discharge to pervious area		70						-
D4. Downspouts discharge to a cistern, rain barrel, etc.		0	S	hould	mplen	ent		
*Note: C1 through C4 should total 100%		7				1		
D5. Lawn area present downgradient of leader for rain gar	rden? X Y N	100)					\rightarrow
E. COMMON AREAS								
E1. Storm drain inlets? Y N If yes, are they stend. Catch basins inspected? Y N If yes, inclu E2. Storm water pond? Y N Is it a wet pond What is the estimated pond area? <	ude Unique Site II	from SSI	sheet:	OBH-	55D-	-01		♦ •
							-	
E3. Open Space? Y N If yes, is pet waste presen								0
Buffers/floodplain present: \(\sum Y \subseteq N \) If yes, is			Y					
F. INITIAL NEIGHBORHOOD ASSESSMENT AND REC	CALADA SANDA							
Based on field observations, this neighborhood has signific Nutrients Oil and Grease Trash/Litter Ba				eck all	that app	oly)		0
Specific Action	a coen a	treats re	tro C+	·				
 ☑ Onsite retrofit potential? ☐ Better lawn/landscaping practice? ☐ Better management of common space? ☐ Pond retrofit? ☐ Multi-family Parking Lot Retrofit? 	green s	theets re	tro fit progra	ine j	nple	rend	hati	n
 ☑ Onsite retrofit potential? ☑ Better lawn/landscaping practice? ☑ Better management of common space? ☑ Pond retrofit? 	given s	heets re	trofit	· ·	nple	rend	hati	m

NOTES:

WATERSHED: O'GHER BAY	SUBWATERSHED: OBH	UNIQUE	SITE ID: OBH - NO	A-02
DATE: 8/26/09	ASSESSED BY: KMB	CAMER		PIC#: 205-Z
A. NEIGHBORHOOD CHARACTE	CRIZATION			
Neighborhood/Subdivision Name:	Maxwell Street		Neighborhood Area (ac	res)
If unknown, address (or streets) surviv	W			
Homeowners Association? TY	N ☐ Unknown If yes, name and	contact information:		
Residential (circle average single fa	mily lot size):			
☐ Single Family Attached (Duplexe ☐ Single Family Detached	s, Row Homes) <1/8 1/8 1/4 1/3 <1/4 1/4 1/2 1		rifamily (Apts, Townho oile Home Park	mes, Condos)
Estimated Age of Neighborhood:	years	Garages: 50% V	With Basements%	INDEX*
Sewer Service? X Y N				0
Index of Infill, Redevelopment, and I	Remodeling No Evidence	<5% of units 5-10	0% 🔲 >10%	0
Record percent observed for e depending on applicable	ach of the following indicators, lity and/or site complexity	Percentage	Comments/Notes	
B. YARD AND LAWN CONDITION	S			
B1. % of lot with impervious cover		80	100 on some	
B2. % of lot with grass cover		5		0
B3. % of lot with landscaping (e.g., r	nulched bed areas)	15		\Q
B4. % of lot with bare soil		6		0
*Note: B1 through B4 must t	total 100%			
B5. % of lot with forest canopy		5		\Q
B6. Evidence of permanent irrigation	or "non-target" irrigation	0		0
		High: 10		0
B7. Proportion of total neighborhood	turf lawns with following	Med: 50		
management status:		Low: 30		
B8. Outdoor swimming pools? □Y □	N Can't Tell Estimated #_			0
B9. Junk or trash in yards?	□ N □ Can't Tell			0
C. DRIVEWAYS, SIDEWALKS, AN	D CURBS		-	
C1. % of driveways that are impervious	us N/A	90		
C2. Driveway Condition Clean	☐ Stained ☐ Dirty ☐ Breaking	up		0
C3. Are sidewalks present? X Y	N If yes, are they on one side of	street or along bot	h sides 🛛	
☐ Spotless ☒ Cover	ed with lawn clippings/leaves	Receiving 'non-targe	t' irrigation	0
What is the distance between	the sidewalk and street? ft.			♦
Is pet waste present in this ar		200000000000000000000000000000000000000	***************************************	0
	Y N If yes, check all that ap			
	ng or standing water \(\sum \text{Long-term} \)			O.
Organic matter, leaves, la	wn clippings	debris Overhead		

08H-NSA-02

Neighborhood Source Assessment

NSA

sanitary sewer	0						0	0
D2. Downspouts are directed to impervious surface								
			_			1		
	Λ				-	1		
	0		_			+		_
rden? Y N	50	1/2					0	>
ide Unique Site ID	from SSD	sheet: _			******		0	
or ☐ dry pond? about 1 acre ☐ >	Is it overg lacre	grown?	Y	□N	4		\Q	,
		*******	N				0	
		ПИ	-					_
ant indicators for t	he followin	g: (che	ck all	that a	pply)		0	
8				21	y			-10
				T	T			_
1	rden? Y N iled? Y N ide Unique Site ID or dry pond? about 1 acre > t? Y N du encroachment evi commendation ant indicators for to the cteria Sedimen Describe Re	rden? Y N Condition: ade Unique Site ID from SSD or dry pond? Is it overg about 1 acre > 1 acre t? Y N dumping? cencroachment evident? Y COMMENDATIONS ant indicators for the following cteria Sediment Other Describe Recommender	rden? Y N SO % iled? Y N Condition: Clear de Unique Site ID from SSD sheet: or dry pond? Is it overgrown? about 1 acre > 1 acre t? Y N dumping? Y N commended Notice of the following: (checciteria Sediment Other Describe Recommended Actions	90 10 10 10 10 10 10 10	90 0 0 0 0 0 0 0 0 0	90 0 0 0 0 0 0 0 0 0	90 10 10 10 10 10 10 10	90 0 0 0 0 0 0 0 0 0 0

WATERSHED: DYSTER BAY	SUBWATERSHED: White 4 (1)	UNIQUE	SITE ID: WCR -	15A-101
DATE: 8 /26 / 09	ASSESSED BY: DRB	CAMERA		PIC#: 148
A. NEIGHBORHOOD CHARACTE	RIZATION			
Neighborhood/Subdivision Name: If unknown, address (or streets) surve Show the literal of Homeowners Association?	yed:		Neighborhood Area (act	res)
Residential (circle average single fan Single Family Attached (Duplexes Single Family Detached	nily lot size): s, Row Homes) $<\frac{1}{8}$ $\frac{1}{8}$ $\frac{1}{4}$ $\frac{1}{3}$ $\frac{1}{3}$ acr	re Multi	family (Apts, Townhor	
Estimated Age of Neighborhood: 50-	years Percent of Homes with Garage	es: <u>20</u> % W	7ith Basements 100 %	INDEX*
Sewer Service? Y N		. 69		0
	emodeling No Evidence <5% of	units 🔀 5-10	% ∐ >10%	0
Record percent observed for ed depending on applicabili	ich of the following indicators, ity and/or site complexity	Percentage	Comments/Notes	
B. YARD AND LAWN CONDITIONS				
B1. % of lot with impervious cover		50		
B2. % of lot with grass cover		25		0
B3. % of lot with landscaping (e.g., n	nulched bed areas)	15		♦
B4. % of lot with bare soil				0
*Note: B1 through B4 must to	ptal 100%			Y
B5. % of lot with forest canopy		25		\Q
B6. Evidence of permanent irrigation of	or "non-target" irrigation	25		0
22 5. 10. 07. 10. 10. 10. 10. 10.		igh: <u>90</u>		0
B7. Proportion of total neighborhood to management status:	turf lawns with following	led: 10		
management status.	L	ow:	1	
B8. Outdoor swimming pools? TY	N Can't Tell Estimated #			0
B9. Junk or trash in yards?	N ☐ Can't Tell			0
C. DRIVEWAYS, SIDEWALKS, ANI	CURBS			
C1. % of driveways that are impervious	is N/A	70		
C2. Driveway Condition ☑ Clean ☐	Stained Dirty Breaking up			0
C3. Are sidewalks present? ✓ Y ✓ Spotless ✓ Covere	N If yes, are they on one side of street ⊠ed with lawn clippings/leaves ☐ Receivi	or along both	sides irrigation	0
What is the distance between	the sidewalk and street? 3_ ft.	************		\Diamond
Is pet waste present in this are				0
	N If yes, check all that apply:		***************************************	
Organic matter, leaves, lav	g or standing water A Long-term car par vn clippings Trash, litter, or debris	Overhead	tree canopy	•
* INDEX: O denotes pot	ential pollution source; 🔷 denotes a n	eighborhood	restoration opportun	itv

A-3

WCR-NSA-01

D. ROOFTOPS											-0
D1. Downspouts are directly connected to storm drains or	sanitary sewe	r		N						1	> 0
D2. Downspouts are directed to impervious surface				V		da	pice	al			
D3. Downspouts discharge to pervious area				4		- 6	Story		and		
D4. Downspouts discharge to a cistern, rain barrel, etc.				11		ZIM	9947.44	N.B	W452		
*Note: C1 through C4 should total 100%				10							
D5. Lawn area present downgradient of leader for rain gar	rden? Y[□N		5	an	11	ON	es			1
E. COMMON AREAS										Wit.	
E1. Storm drain inlets? Y N If yes, are they stence Catch basins inspected? Y N If yes, included the stence of the	ide Unique Si	te ID	fror	n SSI	shee	et:			******		0
E2. Storm water pond? ☐ Y ☐ N Is it a ☐ wet pond What is the estimated pond area? ☐ <1 acre ☐	or dry por about 1 acre	nd? □>	Is:	it ove cre	rgrow	/n? [Y]N			•
E3. Open Space? Y N If yes, is pet waste present Buffers/floodplain present: Y N If yes, is		******							*****		0
F. INITIAL NEIGHBORHOOD ASSESSMENT AND REC						1.11	-				-
Based on field observations, this neighborhood has signific Nutrients Oil and Grease Trash/Litter Bac	ant indicators	for the	ne fo	ollow	ing: (check	all th	at app	oly)		0
Onsite retrofit potential? Better lawn/landscaping practice? Better management of common space? Pond retrofit? Multi-family Parking Lot Retrofit? Other action(s)	77	AIN	r 1.	3472	REL	- D	2154	TEITS	UTB	iv.	
Initial Assessment		1	T		1				1		TEL
NSA Pollution Severity Index Severe (More than 10 circles checked) High (5 to 10 circles checked) Moderate (Fewer than 5 circles checked) None (No circles checked) Neighborhood Restoration Opportunity Index High (More than 5 diamonds checked) Moderate (3-5 diamonds checked) Low (Fewer than 3 diamonds checked)											
NOTES:			1							8	

Retrofit Reconnaissance Investigation | RRI




WATERSHED: BAI	SUBWATERSHEI	D:	UNIQUE	SITE ID: BAI-1777-01
DATE: 8/16/09	ASSESSED BY: THE	CAMERA ID:	von	PICTURES: 187-192
GPS ID:	LMK ID:		160"N	LONG: 73 ° 35 19.57
SITE DESCRIPTION	17-24			
Name: Focust 9 Address: 119 kys	Talky Internedial			
Ownership: If Public, Government Jurisdi	Public Priction: Local Sta	vate Unknown DOT	Other:_	
Corresponding USSR/USA Fi	eld Sheet? Xes	☐ No If yes,	Unique S	ite IDBHHSI-01
☐ Below Outfall ☐ In C	ve Roadway Culvert onveyance System r Large Parking Lot	On-Site Hotspot Operation Small Parking Londing Individual Street Underground	ot 🕥	Individual Rooftop Small Impervious Area Landscape / Hardscape Other:
DRAINAGE AREA TO PROF	POSED RETROFIT		-	
Drainage Area ≈ Imperviousness ≈ Impervious Area ≈ Notes:	%	Drainage Area Lan Residential SFH (< 1 ac SFH (> 1 ac Townhouses Multi-Family Commercial	lots) lots)	☐ Institutional ☐ Industrial ☐ Transport-Related ☐ Park ☐ Undeveloped ☐ Other:
EXISTING STORMWATER N Existing Stormwater Practic	000000000000000000000000000000000000000	Possible		
If Yes, Describe: School Drawn Bus parking	risa overlord fla playground	The state of the s	ond	o grossed area
Describe Existing Site Condition 10-15 feet Bus porting	-1.11	Drainage and Conve	yance:	
Existing Head Available and	Points Where Measured:			

Retrofit Reconnaissance Investigation RRI

PROPOSED RETROFIT					
Purpose of Retrofit: Water Quality Demonstration / Education	Recharge Repair		Channel Protecti	on	☐ Flood Control
Retrofit Volume Computations	- Target Storage:		Retrofit Volum	e Computa	ations - Available Storage:
	et Pond	l Wetl	and ☑ Bio	retention er:	
SITE CONSTRAINTS Adjacent Land Use:			Acc	ess:	
Residential Commercial Industrial Transport-R Undeveloped Other: Possible Conflicts Due to Adjace If Yes, Describe:	elated Park ent Land Use?	Yes	Con	No Constrainstrained due Slope Utilities Structur Other:	Space Tree Impacts
Conflicts with Existing Utilities: None Unknown Yes Possible Sewer Water Gas Cable Electric Electric to Stree Overhead Wires Other:	Dam Impa Impa Flood Impa Impa Impa Impa	Safet cts to cts to dplain cts to cts to How r Appro	Permitting Factory Permits Necessary Wetlands a Stream Fill Forests Specimen Trees nany? 2 x. DBH /3	ary	Probable Not Probable
Soils: Soil auger test holes: Evidence of poor infiltration (clays Evidence of shallow bedrock: Evidence of high water table (gley	s, fines):	Yes Yes Yes Yes	□ No □ No □ No □ No □ No		

Retrofit Reconnaissance Investigation

RRI



Retrofit Reconnaissance Investigation | RRI



DESIGN OR DELIVERY NOTES	
FOLLOW-UP NEEDED TO COMPLETE FIELD C	CONCEPT
Confirm property ownership	Obtain existing stormwater practice as-builts
Confirm drainage area Confirm drainage area impervious cover	Obtain site as-builts Obtain detailed topography
Confirm volume computations	Obtain utility mapping
Complete concept sketch	Confirm storm drain invert elevations Confirm soil types
Other: ALL ABOVE	
INITIAL FEASIBILITY AND CONSTRUCTION CO	ONSIDERATIONS
SITE CANDIDATE FOR FURTHER INVESTIGATI	
IS SITE CANDIDATE FOR EARLY ACTION PRO IF NO, SITE CANDIDATE FOR OTHER RESTORA	JECT(S): YES NO MAYBE ATION PROJECT(S): YES NO MAYBE
IF YES, TYPE(S):	

Retrofit Reconnaissance Investigation | RRI


WATERSHED: BAT-TER	SUBWATERSHED	BAILEY'S UNIQUE	SITE ID: BAI-REI-00
DATE: 8/26/09	ASSESSED BY: TE/KD	CAMERA ID: Canon	PICTURES: 92-95
GPS ID:	LMK ID:	LAT: 40'52 56.6 "N	LONG: 73 "35 14,5"4
SITE DESCRIPTION			
Name: Am / Address: 100 Ry	MocArelyn Priman	st Valley	
Ownership: If Public, Government Jurisdic	Public Prinction: Local Sta	vate Unknown te DOT Other:_	
Corresponding USSR/USA Fi	eld Sheet? Yes	No If yes, Unique S	ite ID:
Below Outfall In C	ve Roadway Culvert onveyance System Large Parking Lot	On-Site Hotspot Operation Small Parking Lot Individual Street Underground	Individual Rooftop Small Impervious Area Landscape / Hardscape Other:
DRAINAGE AREA TO PROP	OSED RETROFIT		
Drainage Area ≈ Imperviousness ≈ Impervious Area ≈ Notes:		Drainage Area Land Use: Residential SFH (< 1 ac lots) SFH (> 1 ac lots) Townhouses Multi-Family Commercial	☐ Institutional ☐ Industrial ☐ Transport-Related ☐ Park ☐ Undeveloped ☐ Other:
EXISTING STORMWATER N	IANAGEMENT		
Existing Stormwater Practice If Yes, Describe:	e: ☐ Yes ♠ No	Possible	
Describe Existing Site Condit One stony, Aproma Aurfoce, but Site lats) and accommoderate Existing Head Available and	ling elementary so	had, a some reof was to building.	
well poor a	andiklate, since 1	they to poor below tend downspor	building state.

BAI- EKI-OZ

Retrofit Reconnaissance Investigation RRI

PROPOSED RETROFIT				
Purpose of Retrofit: Water Quality Demonstration / Education Repair		Channel Protection	n	☐ Flood Control
Retrofit Volume Computations - Target Stora	ge:	Retrofit Volume	e Computatio	ons - Available Storage:
	Created Wetla	and Bior	etention r:	
SITE CONSTRAINTS Adjacent Land Use: Residential Commercial Institution Industrial Park	utional		o Constraints trained due to	0
Undeveloped Other: Possible Conflicts Due to Adjacent Land Use? If Yes, Describe: Child safety	Yes Yes	□ No □ □ □	Slope Utilities Structures Other:	☐ Space ☐ Tree Impacts ☐ Property Ownership
Conflicts with Existing Utilities: None Unknown Yes Possible Sewer Gas Gas Cable Electric Electric to Streetlights Overhead Wires Other:	Dam Safety Impacts to Impacts to Floodplain Impacts to Impacts to How m	a Stream Fill Forests Specimen Trees nany? Depend x. DBH_	ry Pro	bable Not Probable
Soils: Soil auger test holes: Evidence of poor infiltration (clays, fines): Evidence of shallow bedrock: Evidence of high water table (gleying, saturation):	☐ Yes ☐ Yes ☐ Yes ☐ Yes	□ No □ No □ No □ No □ No		

RRI




BAI-PRI-02

DESIGN OR DELIVERY NOTES	
k	
<i>V</i>	
	[]
FOLLOW-UP NEEDED TO COMPLETE FIELD CONC	CEPT
Confirm property ownership Confirm drainage area	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts
Confirm drainage area impervious cover Confirm volume computations	Obtain detailed topography
Complete concept sketch	Obtain utility mapping Confirm storm drain invert elevations
Other: ALL OF ABOUT	Confirm soil types
INITIAL FEASIBILITY AND CONSTRUCTION CONSI	DERATIONS
SITE CANDIDATE FOR FURTHER INVESTIGATION:	YES NO MAYBE
IS SITE CANDIDATE FOR EARLY ACTION PROJECT IF NO, SITE CANDIDATE FOR OTHER RESTORATION	r(s): YES NO MAYBE
IF YES, TYPE(S):	INITION INTERPRETATION INTERPRETATIO

WATERSHED: COLD	PRUDICK SUBWATERSH	ED: UNIQUE	E SITE ID: CSB-TURT-01
DATE: 8/77/09	ASSESSED BY: DRB	CAMERA ID: Course	PICTURES: ZII-ZIS
GPS ID:	LMK ID:	LAT: 40° 50' 8 0"N	LONG: 73° 27' 8,8%
SITE DESCRIPTION		2.0	
Name: Cold Sorm Address: 570 w Pala	Harlor Commed	er Rail Sention (MIA Station
Ownership: If Public, Government Juris	Public 1 diction: Local 5	Private Unknown State DOT Other:_	MTA
Corresponding USSR/USA	Field Sheet? Yes	☐ No If yes, Unique S	Site ID:
Below Outfall Ir	bove Roadway Culvert Conveyance System Lear Large Parking Lot	On-Site Hotspot Operation Small Parking Lot Individual Street Underground	Individual Rooftop Small Impervious Area Landscape / Hardscape Other:
DRAINAGE AREA TO PR	OPOSED RETROFIT		****
Drainage Area ≈		Drainage Area Land Use: Residential SFH (< 1 ac lots) SFH (> 1 ac lots) Townhouses Multi-Family Commercial	☐ Institutional ☐ Industrial ☐ Transport-Related ☐ Park ☐ Undeveloped ☐ Other:
EXISTING STORMWATER	R MANAGEMENT		
	ditions, Including Existing Si	ite Drainage and Conveyance:	= 0 . 1 R .
recieves draw	age from a rel	levels throughout. E aturely long one of ser y, or long run of ser to a grossed stry force. Dire is a	of porlugial.
Existing Head Available an	d Points Where Measured:	system one fairly leignound as inte e system.	deep hochers

PROPOSED RETROFIT		
Purpose of Retrofit: ☑ Water Quality ☐ Demonstration / Education ☐ Repair	Channel Protection	Flood Control
Retrofit Volume Computations - Target Stor	Retrofit Volume Computations	- Available Storage:
Proposed Treatment Option: Extended Detention Filtering Practice Describe Elements of Proposed Retrofit, Including	Created Wetland Swale Other:	
SITE CONSTRAINTS		
Adjacent Land Use:	Yes No Utilities	Space Tree Impacts Property Ownership
Conflicts with Existing Utilities: None Unknown Yes Possible Sewer Super Supe	Potential Permitting Factors: Dam Safety Permits Necessary Impacts to Wetlands Impacts to a Stream Floodplain Fill Impacts to Forests Probab Probab Probab	Not Probable le Not Probable
Soils: Soil auger test holes: Evidence of poor infiltration (clays, fines): Evidence of shallow bedrock: Evidence of high water table (gleying, saturation)	☐ Yes ☐ No	

RRI



(SB-RH-01

DESIGN OR DELIVERY NOTES	
FOLLOW-UP NEEDED TO COMPLETE FIELD C	ONCERT
Confirm property ownership	Obtain existing stormwater practice as-builts
Confirm drainage area	Obtain site as-builts
Confirm drainage area impervious cover Confirm volume computations	Obtain detailed topography Obtain utility mapping
Complete concept sketch	Confirm storm drain invert elevations
Other:	☐ Confirm soil types
INITIAL FEASIBILITY AND CONSTRUCTION CO	ONSIDERATIONS
	y and the second
SITE CANDIDATE FOR FURTHER INVESTIGATI	
Is SITE CANDIDATE FOR EARLY ACTION PRO IF NO, SITE CANDIDATE FOR OTHER RESTORA	
	ATION PROJECT(S): YES NO MAYBE




WATERSHED: OBH	SUBWATERSHI	ED: UNIQUE	E SITE ID: 6BA-REI-01
DATE: 8/21/09	ASSESSED BY: 723	CAMERA ID: Conor	PICTURES: 219-272
GPS ID:	LMK ID:	LAT: 40'52 14,4"	LONG: 43031 245
SITE DESCRIPTION			
Name: Oyata Address: 150 (By High John	ol Ster Pay	
Ownership: If Public, Government Juris		Private Unknown State DOT Other:_	
Corresponding USSR/USA	Field Sheet? X Yes	☐ No If yes, Unique S	Site ID: <u>(754-1451-02</u>
Below Outfall In	ove Roadway Culvert Conveyance System ear Large Parking Lot	On-Site Hotspot Operation Small Parking Lot Individual Street Underground	Individual Rooftop Small Impervious Area Landscape / Hardscape Other:
DRAINAGE AREA TO PRO	POSED RETROFIT		
Drainage Area ≈ Imperviousness ≈ Impervious Area ≈ Notes:	%	Drainage Area Land Use: Residential SFH (< 1 ac lots) SFH (> 1 ac lots) Townhouses Multi-Family Commercial	☐ Institutional ☐ Industrial ☐ Transport-Related ☐ Park ☐ Undeveloped ☐ Other:
EXISTING STORMWATER	MANAGEMENT		
Existing Stormwater Pract If Yes, Describe:	ice: 🗌 Yes 🕅 N	o Possible	
		te Drainage and Conveyance:	unege system
Existing Head Available and	d Points Where Measured:		



PROPOSED RETROFIT		
Purpose of Retrofit: Water Quality Demonstration / Education Recharge	Channel P	rotection
Retrofit Volume Computations - Target Stora	ge: Retrofit	Volume Computations - Available Storage:
	Swale [Bioretention Other:
SITE CONSTRAINTS Adjacent Land Use: Residential Commercial Industrial Transport-Related Park Undeveloped Other:	utional	Access: ☐ No Constraints Constrained due to ☐ Space
Possible Conflicts Due to Adjacent Land Use? If Yes, Describe:	Yes No	Utilities Tree Impacts Structures Property Ownership Other:
Conflicts with Existing Utilities: None Unknown Yes Possible Sewer Water Gas Cable Electric Electric to Streetlights Overhead Wires Other:	Potential Permitting Dam Safety Permits N Impacts to Wetlands Impacts to a Stream Floodplain Fill Impacts to Forests Impacts to Specimen How many? Approx. DBH Other factors:	Factors: Necessary
Soils: Soil auger test holes: Evidence of poor infiltration (clays, fines): Evidence of shallow bedrock: Evidence of high water table (gleying, saturation):	☐ Yes ☐ No ☐ Yes ☐ No ☐ Yes ☐ No ☐ Yes ☐ No	






FOLLOW-UP NEEDED TO COMPLETE FIELD CO	ONCEPT
Confirm property ownership	Obtain existing stormwater practice as-builts
☐ Confirm property ownership ☐ Confirm drainage area ☐ Confirm drainage area impervious cover	Obtain existing stormwater practice as-builts Obtain site as-builts
☐ Confirm drainage area ☐ Confirm drainage area impervious cover ☐ Confirm volume computations	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts ☐ Obtain detailed topography ☐ Obtain utility mapping
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts ☐ Obtain detailed topography
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch Other:	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts ☐ Obtain detailed topography ☐ Obtain utility mapping ☐ Confirm storm drain invert elevations ☐ Confirm soil types
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch Other:	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts ☐ Obtain detailed topography ☐ Obtain utility mapping ☐ Confirm storm drain invert elevations ☐ Confirm soil types
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch Other:	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts ☐ Obtain detailed topography ☐ Obtain utility mapping ☐ Confirm storm drain invert elevations ☐ Confirm soil types
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch Other:	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts ☐ Obtain detailed topography ☐ Obtain utility mapping ☐ Confirm storm drain invert elevations ☐ Confirm soil types
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts ☐ Obtain detailed topography ☐ Obtain utility mapping ☐ Confirm storm drain invert elevations ☐ Confirm soil types
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch Other:	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts ☐ Obtain detailed topography ☐ Obtain utility mapping ☐ Confirm storm drain invert elevations ☐ Confirm soil types
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch Other:	☐ Obtain existing stormwater practice as-builts ☐ Obtain site as-builts ☐ Obtain detailed topography ☐ Obtain utility mapping ☐ Confirm storm drain invert elevations ☐ Confirm soil types
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch Other: All ABOUT INITIAL FEASIBILITY AND CONSTRUCTION CO	Obtain existing stormwater practice as-builts Obtain site as-builts Obtain detailed topography Obtain utility mapping Confirm storm drain invert elevations Confirm soil types
Confirm property ownership Confirm drainage area Confirm drainage area impervious cover Confirm volume computations Complete concept sketch Other:	Obtain existing stormwater practice as-builts Obtain site as-builts Obtain detailed topography Obtain utility mapping Confirm storm drain invert elevations Confirm soil types ONSIDERATIONS ON: YES NO MAYBE ECT(S): YES NO MAYBE



WATERSHED: OYCLER	Say SUBWATERSHI	ED: UNK	UNIQUE SITE ID: MNC-RR)-0
DATE: 8/26/09	ASSESSED BY: KMB	CAMERA ID:	PICTURES: [96-198
GPS ID:	LMK ID:	LAT: 40"54"	9,1" LONG: 73'34'51.9"
SITE DESCRIPTION			
Name: END of Wolf Address:	In sovenive		
Ownership: If Public, Government Juriso		rivate Unknown tate DOT	Other: NWB
Corresponding USSR/USA	Field Sheet? Yes	☑ No If yes	s, Unique Site ID:
Below Outfall In	oove Roadway Culvert Conveyance System ear Large Parking Lot	On-Site Hotspot Operat Small Parking I Individual Stree Underground	Lot Small Impervious Area
DRAINAGE AREA TO PRO	POSED RETROFIT		
Drainage Area ≈		Drainage Area Land Use: ☐ Residential ☐ Institutional ☐ SFH (< 1 ac lots) ☐ Industrial ☐ SFH (> 1 ac lots) ☐ Transport-Related ☐ Townhouses ☐ Park	
		Multi-Fami	
EXISTING STORMWATER	MANAGEMENT		
Existing Stormwater Practi If Yes, Describe:	ice: 🗌 Yes 🖾 N	o Possible	
Rooftop, lann & d	litions, Including Existing Sin riversay remost f/ radistonal costch try to methand	residential hobasin & pipe	system. I walton Aven
Existing Head Available and	AVE	e Bugueur Place	


PROPOSED RETROFIT	
Purpose of Retrofit: Water Quality Demonstration / Education Recharg	ge Channel Protection Flood Control Other:
Retrofit Volume Computations - Target Stor	rage: Retrofit Volume Computations - Available Storage:
	Created Wetland Bioretention Swale Other:
SITE CONSTRAINTS	& Bagueur Place to corner and into
Adjacent Land Use:	refuge Slope Space
Conflicts with Existing Utilities: None Unknown Yes Possible Sewer Gas Gas Cable Electric Electric to Streetlights Overhead Wires Other:	Potential Permitting Factors: Dam Safety Permits Necessary Impacts to Wetlands Impacts to a Stream Floodplain Fill Impacts to Forests Impacts to Specimen Trees How many? Approx. DBH Probable Not Probable Not Probable Not Probable Not Probable Not Probable Not Probable Not Probable Not Probable Not Probable Not Probable Not Probable
Soils: Soil auger test holes: Evidence of poor infiltration (clays, fines): Evidence of shallow bedrock: Evidence of high water table (gleying, saturation)	☐ Yes ☒ No ☐ Yes ☒ No ☐ Yes ☒ No ☐ Yes ☒ No): ☒ Yes ☐ No



DESIGN OR DELIVERY NOTES	
PT	
FOLLOW-UP NEEDED TO COMPLETE FIELD C	ONCEPT
Confirm property ownership	Obtain existing stormwater practice as-builts
Confirm drainage area	Obtain site as-builts
Confirm drainage area impervious cover Confirm volume computations	Obtain detailed topography
Complete concept sketch	Obtain utility mapping Confirm storm drain invert elevations
Other: All of A Bout	Confirm soil types
INITIAL FEASIBILITY AND CONSTRUCTION C	ONCIDED ATIONS
INITIAL PEASIBILITY AND CONSTRUCTION C	ONSIDERATIONS
Cymp C Lypyn (mp = 5 Fee	
SITE CANDIDATE FOR FURTHER INVESTIGAT IS SITE CANDIDATE FOR EARLY ACTION PRO	
IF NO, SITE CANDIDATE FOR OTHER RESTORA	ATION PROJECT(S): YES NO MAYBE
IF YES, TYPE(S):	

WATERSHED:	SUBWATERSHED	:	UNIQUE SITE ID: WCE- RET-O
DATE: 6/26/09	ASSESSED BY: TB/bB	CAMERA ID:	Mon PICTURES: 177
GPS ID:	LMK ID:	LAT: 40051 4	18.8"N LONG: 73 32 3,3
SITE DESCRIPTION			
Name: Flow-Address:	thru (Big Ffall	on Rood) Ke	charge Brien WSDOT # 15
Ownership: If Public, Government Jurisdic	Public Privation: Local Sta		Other:
Corresponding USSR/USA Fi	eld Sheet? Xes	☐ No If yes,	Unique Site ID: W/C/E SSD - 10
Below Outfall In C	ve Roadway Culvert onveyance System Large Parking Lot	On-Site Hotspot Operation Small Parking Londing Individual Street Underground	ot Small Impervious Area
DRAINAGE AREA TO PROP	OSED RETROFIT		
Drainage Area ≈ Imperviousness ≈ Impervious Area ≈ Notes:		Drainage Area Lan Residential SFH (< 1 ac SFH (> 1 ac Townhouses Multi-Family	Institutional lots) Industrial lots) Transport-Related Park y Undeveloped
EXISTING STORMWATER M	Title control	Commercial	Other:
Existing Stormwater Practice If Yes, Describe: Dov Ochory Box	" Yes □ No	Possible flow out	
Dook is or	porking loss, no be	few, piped on standing	directly to bash.
Existing Head Available and I	Points Where Measured:	to conclusy	owfore elev.


PROPOSED RETROFIT			
Purpose of Retrofit: Water Quality Demonstration / Education Rech		el Protection	☐ Flood Control
Retrofit Volume Computations - Target S	torage: Retro	ofit Volume Compu	tations - Available Storage:
Proposed Treatment Option: ☐ Extended Detention ☐ Wet Pond ☐ Filtering Practice ☐ Infiltration	☐ Created Wetland ☐ Swale	☐ Bioretention	
SITE CONSTRAINTS Adjacent Land Use: Residential Commercial In Including In		☐ Struct	Space Space Tree Impacts Ures Property Ownership
Conflicts with Existing Utilities: None Unknown Yes Possible Gas Cable Electric Electric to Streetlights Overhead Wires Other:	Potential Permitt Dam Safety Permit Impacts to Wetlan Impacts to a Streat Floodplain Fill Impacts to Forests Impacts to Specim How many? Approx. DBH Other factors:	its Necessary ids m m men Trees	Probable Not Probable
oils: oil auger test holes: vidence of poor infiltration (clays, fines): vidence of shallow bedrock: vidence of high water table (gleying, saturati	Yes		



DESIGN OR DELIVERY NOTES	
FOLLOW-UP NEEDED TO COMPLETE FIELD O	CONCEPT
Confirm property ownership	Obtain existing stormwater practice as-builts
Confirm drainage area	Obtain site as-builts
Confirm drainage area impervious cover Confirm volume computations	 ✓ Obtain detailed topography ✓ Obtain utility mapping
Complete concept sketch	Confirm storm drain invert elevations
Other:	☑ Confirm soil types
INITIAL FEASIBILITY AND CONSTRUCTION C	ONSIDERATIONS
property ownered	M
SITE CANDIDATE FOR FURTHER INVESTIGAT	ION: YES NO MAYBE
IS SITE CANDIDATE FOR EARLY ACTION PRO	
ENO CITE CANDIDATE FOR OTHER DECTOR	
IF NO, SITE CANDIDATE FOR OTHER RESTORA IF YES, TYPE(S):	ATION PROJECT(S): YES NO MAYBE

WATERSHED: W(>	SUBWATERSHED	: UMER I	INIQUE	SITE ID: WCZ-TZTZI 07
DATE: 8/26/09	ASSESSED BY: DTZIS		nda.	PICTURES: 199-204
GPS ID:	LMK ID:	LAT: 40 52 26. (LONG: 73 31 41.1"
SITE DESCRIPTION		18.00		73 / 114
Name: White's Address: So. 4h	Gereek Culvert	V		
Ownership: If Public, Government Jurisdi	Public Privation: Local State		Other:	
Corresponding USSR/USA F	ield Sheet? Yes	☐ No If yes, U	nique Si	te ID:
Below Outfall In C	ove Roadway Culvert Conveyance System ir Large Parking Lot	On-Site Hotspot Operation Small Parking Lot Individual Street Underground	4	Individual Rooftop Small Impervious Area Landscape / Hardscape Other:
DRAINAGE AREA TO PROI				
Drainage Area ≈		Drainage Area Land Use: Residential Institutional SFH (< 1 ac lots) Industrial		
Notes:		Townhouses Park Multi-Family Unde		☐ Transport-Related ☐ Park ☐ Undeveloped ☐ Other:
EXISTING STORMWATER I	MANAGEMENT			
Existing Stormwater Practic If Yes, Describe:	e: Yes No	Possible	še Č	reck
White Cred	tions, Including Existing Site I flows through ifall investigably	sulvert belo	a p	orbug let occess. livert
Existing Head Available and		/A		

PROPOSED RETROFIT	
Purpose of Retrofit: Water Quality Demonstration / Education Recharg	Channel Protection Flood Control
Retrofit Volume Computations - Target Stor	age: Retrofit Volume Computations - Available Storage:
Proposed Treatment Option: Extended Detention Wet Pond Siltering Practice Infiltration	Created Wetland Bioretention Swale Other:
level of stormwork	al natural cordition. Purisherone releasement for received stormward
Adjacent Land Use: Residential Commercial Institution Industrial Transport-Related Park Undeveloped Other: Mound store Possible Conflicts Due to Adjacent Land Use?	Slope Space Syes No Utilities Tree Impacts
If Yes, Describe: Culvert runs below or	Ccess dive to Structures Property Ownership Other:
Conflicts with Existing Utilities: None Unknown Yes Possible Sewer Gas Gas Cable Electric Electric to Streetlights Overhead Wires Other:	Potential Permitting Factors: Dam Safety Permits Necessary Impacts to Wetlands Impacts to a Stream Floodplain Fill Impacts to Forests Impacts to Specimen Trees How many? Approx. DBH (O=-/4) Other factors: Inches Approx.
Soils: Soil auger test holes: Evidence of poor infiltration (clays, fines): Evidence of shallow bedrock: Evidence of high water table (gleying, saturation)	☐ Yes ☐ No ☐ Yes ☐ No ☐ Yes ☐ No ☐ Yes ☐ No



DESIGN OR DELIVERY NOTES	
FOLLOW-UP NEEDED TO COMPLETE FIELD COM	NCEPT
Confirm property ownership	Obtain existing stormwater practice as-builts
Confirm drainage area Confirm drainage area impervious cover	☐ Obtain site as-builts ☐ Obtain detailed topography
Confirm volume computations	Obtain detailed topography Obtain utility mapping
Complete concept sketch	Confirm storm drain invert elevations
Other:	Confirm soil types
INITIAL FEASIBILITY AND CONSTRUCTION CON-	SIDERATIONS
TANKET EASIBILITY AND CONSTRUCTION CON-	SIDERATIONS
SITE CANDIDATE FOR FURTHER INVESTIGATION	
IS SITE CANDIDATE FOR EARLY ACTION PROJECT	CT(S): YES NO MAYBE
IF NO, SITE CANDIDATE FOR OTHER RESTORATI IF YES, TYPE(S):	ON PROJECT(S): YES NO MAYBE

WATERSHED: CYSTER BAY	SUBWATERSHED: CSH		UNIQUE SITE ID: CSH-550-01		
DATE: 8/25/ 09	ASSESSED BY: KMB		CAMERA ID:		
Map Grid	RAIN IN LA	ST 24 HOURS Y N	Pic# 68-69		
A. LOCATION					
A1. Street names or neighborhoods	surveyed:	SP & Main Stree	et through Hentington		
A2. Adjacent land use: X Resident	ial Comm		stitutional		
A3. Corresponding HSI or NSA field	ld sheet? If so	, circle HSI or NSA and reco	ord its Unique Site ID here CSH-NSA-C		
B. STREET CONDITIONS					
B1. Road Type: Arterial Co	ollector 🔲 l	Local Alley Other:			
B2. Condition of Pavement: Ne	w 🛛 Good	Cracked Broken			
B3. Is on-street parking permitted [JY⊠N I	f yes, approximate number o	f cars per block:		
B4. Are large cul-de-sacs present?					
B5. Is trash present in curb and gutte		Index Rating	for Accumulation in Gutters		
use the index to the right to record a		Clean	Filthy		
	Sediment	1 🖂 2			
Organi	ic Material	□ 1 × 2	3 3 5		
	Litter	□ 1 □ 2	□3 □4 □5		
C. STORM DRAIN INLETS AND C	CATCH BASI	NS			
C1. Type of storm drain conveyance	: open	enclosed M mixed			
C2. Percentage of inlets with catch b		N/A			
Sample 1-2 catch basins per NSA/H		C3. Catch basin #1	C4. Catch basin #2		
Latitude		0 1 11	0 1 11		
Longitude		0 1 11	0 1 11		
LMK#		Harbor Rd	terrace Place		
Picture #		68	10 miles		
Current Condition		☐ Wet ⊠ Dry	☐ Wet ⊠ Dry		
Condition of Inlet		☐Clear ☐Obstructed	⊠Clear □Obstructed		
Litter Accumulation		⊠Y □N	□Y ⋈N		
Organics Accumulation		⊠Y □N	□Y ⊠N		
Sediment Accumulation		□Y ⊠N	□Y N		
Sediment Depth (in feet)		SUMP ft.	Sump ft.		
Water Depth		ft.	445 ft.		
Evidence of oil and grease		□Y ⊠N	□Y ⊠N		
Sulfur smell		□Y ⊠N	□Y ⊠N		
Accessible to vacuum truck		⊠Y □N	⊠Y □ N		
D. NON-RESIDENTIAL PARKING	LOT (>2 acr	res)			
D1. Approximate size: 2 ac	eres /	unicipal lot on	Main Street		
D2. Lot Utilization: Full Abo					
	Smooth (1		cracks) Rough (many cracks)		
D4. Is lot served by a storm water tre					
D5. On-site retrofit potential: Exc					

CSH-SSD-01

Streets and Storm Drains SSD

E. MUNICIPAL POLLUTANT REDUCT	ION STRATEGIES
E1. Degree of pollutant accumulation in the	ne system: High Medium Low None
E2. Rate the feasibility of the following po	ollution prevention strategies:
Street Sweeping:	☐ High ☐ Moderate ☐ Low
Storm Drain Stenciling:	☐ High ☐ Moderate ☐ Low
Catch Basin Clean-outs:	☐ High ☐ Moderate ☐ Low
Parking Lot Retrofit Potential:	☐ High ☐ Moderate ☐ Low
CATCH BASIN SKETCHES \$1	1.40
.1	#2
	e-16
curb	
()	
	INLET
	INLET
	1 cat lova
leat	delovis.
Lebris	200
Notes:	

WATERSHED: BULLO O SAN SAN	SUBWATER	SHED: M	ill Neck (veek	UNIQUE SITE II	D: 200-0
DATE: 4 125109	ASSESSED B	NY	75	CAMERA ID:	Course
MAP GRID	RAIN IN LAS		urs 🗆 Y 🔲 N	- TANK	July 111/
A. LOCATION	TCAII III LIA	51 24110	OKS [] I [] N	PIC# 14Z	-148
A1. Street names or neighborhood s	urveyed:	syvieu	(Broken)		
A2. Adjacent land use: Residenti	al 🔲 Comme icipal 🔲 Tra	rcial nsport-Re	Industrial Install	titutional	
A3. Corresponding HSI or NSA field	sheet? If so,	circle HS	I or NSA and recor	rd its Unique Site I	D here
B. STREET CONDITIONS				•	
B1. Road Type: Arterial Co	llector 🗵 L	ocal \square	Alley Other:		
B2. Condition of Pavement: Nev					
B3. Is on-street parking permitted				Casar and the term	
		yes, appr	oximate number of	cars per block:	
B4. Are large cul-de-sacs present?					
B5. Is trash present in curb and gutte			Index Rating f	or Accumulation in	Gutters
use the index to the right to record at	nount.	Clean			Filthy
	Sediment	1	⊠ 2	□3 [45
Organi	Material		⊠ 2	□3 [□ 4 □ 5
C Company Dry in the same in a	Litter	\sqrt 1	2	3 [4 5
C. STORM DRAIN INLETS AND C		100			
C1. Type of storm drain conveyance:		enclosed			
C2. Percentage of inlets with catch b			□ N/A		
Sample 1-2 catch basins per NSA/H		C3. Catch basin #1		C4. Ca	tch basin #2
Latitude			300 m		14,08 "
Longitude		13° 33	169"	73°	33: 76/"
LMK #					
Picture #		142		146	
Current Condition			t 🔀 Dry		Wet 🛛 Dry
Condition of Inlet		Clea	r Obstructed		lear Obstructed
Litter Accumulation		□Y	Ŋ N	AY	N
Organics Accumulation	-1	УY	N	₩Y	N
Sediment Accumulation		□Y	□N	✓Y	□N
Sediment Depth (in feet)		11	ft.		tft.
Water Depth		0	ft.	_6	0-5 ft.
Evidence of oil and grease		□Y	N	\square Y	· ✓ N
Sulfur smell		□Y	N N	□Y	
accessible to vacuum truck		ŲΥ	□N	XY	□N
). NON-RESIDENTIAL PARKING	LOT (>2 acre	es)			
O1. Approximate size: ac	res				
2. Lot Utilization: Full Abo	ut half full] Empty			
3. Overall condition of Pavement:	Smooth (n	o cracks)	Medium (few ous cracks and dep	cracks) Rough	(many cracks)
04. Is lot served by a storm water trea	tment practic	e? 🔲 Y	☐ N If yes, desc	ribe:	
05. On-site retrofit potential: Exc		od P			
			Y. Y. A.		

Streets and Storm Drains SSD

E. MUNICIPAL POLLUTANT REDUCTION	ON STRATEGIES
E1. Degree of pollutant accumulation in the	
E2. Rate the feasibility of the following pol Street Sweeping: Storm Drain Stenciling: Catch Basin Clean-outs: Parking Lot Retrofit Potential:	
CATCH BASIN SKETCHES	Ingli Moderate Low
#1	mountain & against sediment
Notes:	

WATERSHED: (YSHU BAY	SUBWATERS	HED:	MNC	UNIQUE	SITE ID: MAC	1-550-02
DATE: 5 1761 09	ASSESSED B	Y: 1	723	CAMERA	ID:	
MAP GRID	RAIN IN LAS	т 24 Нот	URS Y N	PIC#	155-15	7
A. LOCATION				1		
A1. Street names or neighborhood	1 11	mon	Ove			
A2. Adjacent land use: Resider	ntial Commer nicipal Tran	cial sport-Rel	Industrial Instated	stitutional		
A3. Corresponding HSI or NSA fie	eld sheet? If so,	circle HS	or NSA and reco	rd its Uniqu	e Site ID here	
B. STREET CONDITIONS						
B1. Road Type: Arterial C	Collector \ \ \	ocal \square	Alley Other:			
B2. Condition of Pavement:						
B3. Is on-street parking permitted				f care per bl	ock	
B4. Are large cul-de-sacs present?		yes, appre	oximate number o	i cars per bi	ock	
				2 22 2 2		
B5. Is trash present in curb and gut use the index to the right to record		~	Index Rating f	or Accumu	lation in Gutters	
ase the mack to the right to record		Clean		D) a		Filthy
Organ	Sediment nic Material		\square 2 \square 2	∑ 3 □ 3		□ 5 □ 5
Organ	Litter	\boxtimes 1		□3 □3	☐ 4 ☐ 4	□ 5 □ 5
C. STORM DRAIN INLETS AND					Ш#	
C1. Type of storm drain conveyance	The state of the s	enclosed	mixed			
C2. Percentage of inlets with catch		eliciosed	□ N/A			
Sample 1-2 catch basins per NSA/		C3. Catch			C4. Catch basin	#2
Latitude			0741		40° 54.08	
Longitude			6791		730 3468	
LMK #			14/5		13 34100	2
Picture #		155	-		156 - 15	1
Current Condition			Dry		☐ Wet 🔯	Dry
Condition of Inlet			r Obstructed		Clear C	
Litter Accumulation		XY	ΠN		DY N	
Organics Accumulation		ŊΥ	ΠN		VY DN	
Sediment Accumulation		XY	□N		⊠Y □N	
Sediment Depth (in feet)	4 9 1	0,0	ft.		f	
Water Depth		<01			f	
Evidence of oil and grease		□Y	⊠N		DY N	
Sulfur smell		□Y	⊠N		□Y ⊠N	
Accessible to vacuum truck		$\boxtimes Y$	□ N		⊠Y □N	
O. NON-RESIDENTIAL PARKING	GLOT (>2 acre	s)				
O1. Approximate size:a	icres					
2. Lot Utilization: Full At	out half full	Empty				
O3. Overall condition of Pavement:	Smooth (no	cracks)	Medium (few ous cracks and de	cracks)	Rough (many c	racks)
D4. Is lot served by a storm water tr	eatment practice	? 🗆 Y	N If yes, desc	cribe:		
05. On-site retrofit potential: E				0.00 / -		

E. MUNICIPAL POLLUTANT REDUC	TION STRATEGIES
E1. Degree of pollutant accumulation in	the system: High Medium Low None
E2. Rate the feasibility of the following I	pollution prevention strategies:
Street Sweeping:	☐ High ☑ Moderate ☐ Low
Storm Drain Stenciling:	☐ High ☑ Moderate ☐ Low
Catch Basin Clean-outs:	High Moderate Low
Parking Lot Retrofit Potential: CATCH BASIN SKETCHES	☐ High ☐ Moderate ☐ Low
#1	1#2 Tree/Shwb
1///	Correpy
VI //Y	
1/1/1/20	parel ()
	GRATE CORCALICS
	(andrews)
18/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/	price 1
/ / / / / / / / or	GRATE IS
//Y/J/M/	went (sue set In)
11/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1	CONSTRUCTION OF THE PARTY OF TH
	SEDWENT/ORGANICS
Notes:	· · · · · · · · · · · · · · · · · · ·
Enwh/treas	aresharaung troub sede of
, 0	prevented proper mointeren deriver system.
rood has	Articated diason invite
	production proportion
of storn	hornes de stone
9 200	anoge oguen.
,	

- 2		
C	101	
. ~	. 9	ш
	נטי	U


WATERSHED: Oyster Bay	SUBWATERS	HED: Oys	Ler Bay Hawho	UNIQUE SITE ID: OBH - SSD - C
DATE: 8 /25/ 09	ASSESSED B	Y: KNE	3	CAMERA ID:
MAP GRID	RAIN IN LAST 24 HOURS Y N PIC# 87 92			
A. LOCATION				
A1. Street names or neighborhood su	rveyed:	ence le	Sidney	
A2. Adjacent land use: 🔀 Residentia	ıl 🔲 Commer cipal 🔲 Trai	rcial 🔲 Innsport-Rela	ndustrial In ted	stitutional
A3. Corresponding HSI or NSA field	sheet? If so,	circle HSI	NSA and reco	ord its Unique Site ID here OBH-NSA-0
B. STREET CONDITIONS				
B1. Road Type: Arterial Col	lector 🛛 L	ocal A	lley Other:	
B2. Condition of Pavement: New	□ Good 5	Cracked	Broken	
B3. Is on-street parking permitted 🔽				of cars per block:
B4. Are large cul-de-sacs present?		Jes, effect		cuts per block.
B5. Is trash present in curb and gutter			Index Rating	for Accumulation in Gutters
use the index to the right to record an		Clean	moen runing	Filthy
	Sediment		⊠ 2	3
	Material	⊠ 1		3 4 5
	Litter	≥ 1	□ 2	□3 □4 □5
C. STORM DRAIN INLETS AND CA	TCH BASIN	S		
C1. Type of storm drain conveyance:	open 🛛	enclosed	mixed	
C2. Percentage of inlets with catch ba	sin storage:		N/A	
Sample 1-2 catch basins per NSA/HS	I	C3. Catch b	asin #1	C4. Catch basin #2
Latitude		0	9	0 1 11
Longitude		0		0 1 11
LMK #	Corner	Ships Pt	& Melbourne	Corner Ships At & Sidney
Picture #		87		92
Current Condition		☐ Wet	☑ Dry	☐ Wet ☑ Dry
Condition of Inlet		Clear	Obstructed	☑Clear ☐Obstructed
Litter Accumulation		Y [N⊠	□Y ⊠N
Organics Accumulation		□Y [Ν	⊠Y □N
Sediment Accumulation		$\square Y$	≤ N	XY NIHLE
Sediment Depth (in feet)	Curb Tale	-	ft. ~	ft.
Water Depth			ft. 2	probably ft.
Evidence of oil and grease			×Ν	□Y ⊠N
Sulfur smell			∠ N	□Y X N
Accessible to vacuum truck		XY [N	ŊY □N
D. NON-RESIDENTIAL PARKING I	LOT (>2 acre	(s) / / /	+	
D1. Approximate size: acr				
D2. Lot Utilization: 🗌 Full 🔲 Abou	it half full	Empty		
D3. Overall condition of Pavement:	Smooth (no	cracks) [Medium (few as cracks and de	cracks) Rough (many cracks)
D4. Is lot served by a storm water trea				
D5. On-site retrofit potential: Exce			the second secon	

E1. Degree of pollutant accumulation in the system:	High Medium Low None
E2. Rate the feasibility of the following pollution prevent	
	Moderate Low
Storm Drain Stenciling:	Moderate \(\sum_{\text{Low}} \) Low \(\text{Low} \)
	Moderate Low
Parking Lot Retrofit Potential: High	Moderate ☑ Low N/P
CATCH BASIN SKETCHES	(Art)
1	#2
.6//	
gras (tover)	Frass
grass Tover	
	1
(metal)	Matal
1 1 1 1 Store curlo	7 21
	F 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
C	1 / / / / / / pi
(on one of	/- /- / P:
Concrete /	
Prold	c- 3f+ ->
otes:	
"Pick up dog waste" sign poster	on Florence - pic
I must and master sign poster	f on Florence - pic
I want and maste sign poster	f on Florence - pic
I waste Sign poster	f on Florence - pic
I waste Sign poster	f on Florence - pic
I waste Sign poster	f on Florence - pic
The my and maste sign poster	f on Florence - pic
I we what and haste sign poster	f on Florence - pic
I we what and make sign poster	f on Florence - pic
I want and maste sign poster	f on Florence - pic
I would and make Sign poster	f on Florence - pic
I may and maste sign poster	f on Florence - pic

ASSESSED BY: DE CAMERA ID:	WATERSHED: OYSTEY Bay	SUBWATERSHED: 1 Muse Cook			UNIQUE SITE ID: WCZ-SSD-OI			
A. LOCATION A1. Street names or neighborhood surveyed; A2. Adjacent land use: Residential Commercial Industrial Institutional Municipal Transport-Related A3. Corresponding/HSI or NSA field sheet? If so, circle/HSI or NSA and record its Unique Site ID here A5. Corresponding/HSI or NSA field sheet? If so, circle/HSI or NSA and record its Unique Site ID here A5. Condition of Pavement: New Good Cracked Broken B3. Is on-street parking permitted Y N If yes, approximate number of cars per block: B4. Are large cul-de-sacs present? Y N N Sediment Day Sediment Day D	DATE: 8/26/09	1190						
A.L. Street names or neighborhood surveyed: A2. Adjacent land use: Residential Commercial Industrial Institutional Municipal Transport-Related A3. Corresponding HSI or NSA field sheet? If so, circle HSI or NSA and record its Unique Site ID here Solution B. STREET CONDITIONS B1. Road Type: Arterial Collector Local Alley Other: B2. Condition of Pavement: New Good Cracked Broken B3. Is on-street parking permitted Y N If yes, approximate number of cars per block: B4. Are large cul-de-sacs present? Y N B5. Is trash present in curb and gutter? If so, use the index to the right to record amount. Sediment 1 2 3 4 5 Clean Filthy Clean Filthy Clean Solution Clean Filthy Sediment 1 2 3 4 5 C. STORM DRAIN INLETS AND CATCH BASINS C1. Type of storm drain conveyance: open enclosed mixed C2. Percentage of inlets with catch basin storage: N/A Sample 1-2 catch basins per NSA/HSI C3. Catch basin #1 C4. Catch basin #2 Latitude 25 26 3 4 5 C. Percentage of inlets with catch basin storage: N/A Sample 1-2 catch basins per NSA/HSI C3. Catch basin #1 C4. Catch basin #2 Latitude 25 26 3 4 5 Current Condition Wet Dry Wet Dry Condition of Inlet Calcar Obstructed Calcar Obstructed Litter Accumulation Y N Y N Sediment Depth (in feet) ft. ft. Wetcome Water Depth Sediment Depth (in feet) ft. ft. Wetcome Water Depth Sediment Depth (in feet) ft. ft. Water Depth Accessible to vacuum truck Type Now, N Y N D. NON-RESIDENTIAL PARKING LOT (>2 acres) D1. Approximate size: Sacres D2. Lot Utilization: Full About half full Empty D3. Overall condition of Pavement: Smooth (no cracks) Medium (few cracks) Rough (many cracks) Very Rough (numerous cracks and depressions)	MAP GRID	RAIN IN LAST 24 HOURS Y N			PIC# 163-166			
A2. Adjacent land use:	A. LOCATION							
Municipal Transport-Related A3. Corresponding HSI or NSA field sheet? If so, circle HSI or NSA and record its Unique Site ID here A5. Corresponding HSI or NSA field sheet? If so, circle HSI or NSA and record its Unique Site ID here A5. Condition of Pavement: New Good Cracked Broken B5. Is on-street parking permitted Y N If yes, approximate number of cars per block: B4. Are large cul-de-sacs present? Y N B5. Is trash present in curb and gutter? If so, use the index to the right to record amount. Clean Filthy Sediment Organic Material 1 2 3 4 5 5 5 1 5 5 5 5 5 5	A1. Street names or neighborhood	surveyed:	Lat or 10	6				
B. STREET CONDITIONS B1. Road Type: Arterial				ıl 🗌 Ins	stitutional			
B1. Road Type:	A3. Corresponding HSI or NSA fie	ld sheet? If so	, circle HSI or NSA	and reco	rd its Unique Site ID here + 51-01			
B2. Condition of Pavement: New Good Cracked Broken B3. Is on-street parking permitted Y N If yes, approximate number of cars per block: B4. Are large cul-de-sacs present? Y N B5. Is trash present in curb and gutter? If so, use the index to the right to record amount. Clean Filthy Sediment Organic Material Litter 1 2 3 4 5 C.STORM DRAIN INLETS AND CATCHE ASINS C1. Type of storm drain conveyance: open enclosed mixed C2. Percentage of inlets with catch basin storage: N/A Sample 1-2 catch basins per NSA/HSI C3. Catch basin #1 C4. Catch basin #2 Latitude	B. STREET CONDITIONS							
B3. Is on-street parking permitted	B1. Road Type: Arterial C	ollector	Local Alley	Other:				
B3. Is on-street parking permitted								
B4. Are large cul-de-sacs present?					f cars per block:			
BS. Is trash present in curb and gutter? If so, use the index to the right to record amount. Clean					tems per block.			
Clean Filthy			Index	Rating f	for Accumulation in Gutters			
Sediment				rating 1	- ALCONOMIC AND			
Organic Material 1		Sediment		П2				
C. STORM DRAIN INLETS AND CATCH BASINS C1. Type of storm drain conveyance:	Organ			-				
C1. Type of storm drain conveyance: open enclosed mixed C2. Percentage of inlets with catch basin storage: N/A Sample 1-2 catch basins per NSA/HSI C3. Catch basin #1 C4. Catch basin #2 Latitude				□ 2	□3 □4 □5			
C2. Percentage of inlets with catch basin storage:	C. STORM DRAIN INLETS AND	CATCH BASI	INS					
C3. Catch basin #1 C4. Catch basin #2	C1. Type of storm drain conveyance	e: open [enclosed mix	ed				
Latitude	C2. Percentage of inlets with catch	basin storage:	N/A					
Longitude 13°37'06.0" 15°57'06.2"	Sample 1-2 catch basins per NSA/I	ISI	C3. Catch basin #1		C4. Catch basin #2			
LMK # Picture # Current Condition Description of Inlet Litter Accumulation Organics Accumulation Organics Accumulation Description of Infect Description of Infect Description of Infect Description of Inlet Litter Accumulation Description of Infect Description of Inlet Des	Latitude		40.51 76.3		40° 51 '31-1"			
Picture # Current Condition \[\text{Wet} \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Longitude		73.32 06.0	,	13.37 106.7 "			
Current Condition Wet Dry Wet Dry Condition of Inlet Clear Obstructed Clear Obstructed Litter Accumulation Y N Y N Organics Accumulation Y N Y N Sediment Accumulation Y N Y N Sediment Depth (in feet) ft. ft. Water Depth ft. ft. Evidence of oil and grease Y N Y N Sulfur smell Y N Y N Accessible to vacuum truck Y N Y N D. NON-RESIDENTIAL PARKING LOT (>2 acres) D1. Approximate size: S acres D2. Lot Utilization: Full About half full Empty D3. Overall condition of Pavement: Smooth (no cracks) Medium (few cracks) Rough (many cracks) Very Rough (numerous cracks and depressions) D4. Is lot served by a storm water treatment practice? Y N If yes, describe: Pathony Basser Pathony Met Double Pathony Basser D4. Is lot served by a storm water treatment practice? Y N If yes, describe: Pathony Basser D4. Is lot served by a storm water treatment practice? Y N If yes, describe: Pathony Basser D5. Pathony Met Pathony Basser D6. Pathony Basser Pathony Basser D6. Pathony Basser Pathony Basser D7. Pathony Basser Pathony Basser D8.	LMK #							
Condition of Inlet Clear Obstructed Clear Obstructed	Picture #		163		166			
Litter Accumulation	Current Condition		☑ Wet ☐ Dry		☐ Wet ☑ Dry			
Organics Accumulation Sediment Accumulation Sediment Depth (in feet) Water Depth Evidence of oil and grease Sulfur smell Accessible to vacuum truck D. Non-Residential Parking Lot (>2 acres) D1. Approximate size: Smooth (no cracks) Wedium (few cracks) Nough (many cracks) Very Rough (numerous cracks and depressions) D4. Is lot served by a storm water treatment practice? Y N I Y N PAN N Y N N Y N N Y N N WY N	Condition of Inlet		☑Clear ☐Obst	ructed				
Sediment Accumulation Sediment Depth (in feet) Water Depth Evidence of oil and grease Sulfur smell Accessible to vacuum truck D. Non-Residential Parking Lot (>2 acres) D1. Approximate size: Smooth (no cracks) Wedium (few cracks) Rough (many cracks) Very Rough (numerous cracks and depressions) D4. Is lot served by a storm water treatment practice? Y N If yes, describe: Parking D7 N If yes, describe: Parking D8 N If yes, describe	Litter Accumulation		□Y ⊠N		□Y ⋈ N			
Sediment Accumulation Sediment Depth (in feet) Water Depth Water Depth Evidence of oil and grease MY N M MY N Sulfur smell Accessible to vacuum truck MY N M MY N Sulfur smell Accessible to vacuum truck MY N M MY N D. NON-RESIDENTIAL PARKING LOT (>2 acres) D1. Approximate size: Sediment Accumulation MY N M MY N MY N MY N DY	Organics Accumulation		□Y ⊠N		□Y ⊠N			
Sediment Depth (in feet) Water Depth Evidence of oil and grease MY N M MY N Sulfur smell Accessible to vacuum truck MY N M MY N D. NON-RESIDENTIAL PARKING LOT (>2 acres) D1. Approximate size: acres D2. Lot Utilization: Full	Sediment Accumulation		⊠Y □N					
Water Depth Evidence of oil and grease Sulfur smell Accessible to vacuum truck D. NON-RESIDENTIAL PARKING LOT (>2 acres) D1. Approximate size: D2. Lot Utilization: Full Smooth (no cracks) Wery Rough (numerous cracks and depressions) D4. Is lot served by a storm water treatment practice? Y N If yes, describe: Parking Tt. Tt. Tt. Tt. Tt. Tt. Tt. Tt	Sediment Depth (in feet)		_ ~ _ ft.					
Sulfur smell Accessible to vacuum truck D. NON-RESIDENTIAL PARKING LOT (>2 acres) D1. Approximate size:	Water Depth		_0.5 ft.		17 - 17 -			
Accessible to vacuum truck D. NON-RESIDENTIAL PARKING LOT (>2 acres) D1. Approximate size:			⊠Y □ N		ŊY □N			
D. NON-RESIDENTIAL PARKING LOT (>2 acres) D1. Approximate size:					□Y ⋈N			
D1. Approximate size: acres D2. Lot Utilization: □ Full ☑ About half full □ Empty D3. Overall condition of Pavement: □ Smooth (no cracks) ☑ Medium (few cracks) □ Rough (many cracks) □ Very Rough (numerous cracks and depressions) D4. Is lot served by a storm water treatment practice? ☑ Y □ N If yes, describe: ☐ Colored ☐ Basing					√Y □ N			
D2. Lot Utilization: ☐ Full ☐ About half full ☐ Empty D3. Overall condition of Pavement: ☐ Smooth (no cracks) ☐ Medium (few cracks) ☐ Rough (many cracks) ☐ Very Rough (numerous cracks and depressions) D4. Is lot served by a storm water treatment practice? ☐ Y ☐ N If yes, describe: ☐ Pachage ☐ Boston	D. NON-RESIDENTIAL PARKING	LOT (>2 ac	res)					
D3. Overall condition of Pavement: Smooth (no cracks) Medium (few cracks) Rough (many cracks) Very Rough (numerous cracks and depressions) D4. Is lot served by a storm water treatment practice? Y N If yes, describe: Pedrage Boston	D1. Approximate size:a	cres						
Very Rough (numerous cracks and depressions) D4. Is lot served by a storm water treatment practice? XY N If yes, describe: Pedrage Basin	D2. Lot Utilization: 🗌 Full 🛛 Ab	out half full [Empty					
D4. Is lot served by a storm water treatment practice? XY N If yes, describe: Pechange Basin	D3. Overall condition of Pavement:		no cracks) Medi	um (few	cracks) Rough (many cracks)			
	D4. Is lot served by a storm water tre							
		The state of the s		A	VALUE OF THE PROPERTY OF THE P			

Streets and Storm Drains SSD

E MUNICIPAL DOLLUMANT DEDUCTION CON	
E. MUNICIPAL POLLUTANT REDUCTION STRA	
E1. Degree of pollutant accumulation in the system:	
E2. Rate the feasibility of the following pollution pre	
Street Sweeping: High	
Storm Drain Stenciling: High	
Catch Basin Clean-outs: High	
	Moderate Low
CATCH BASIN SKETCHES #1	1.42
#1	#2
a said	
Don Galle	
F) CB	Stores 1 10
X	K CB CB
UNT -	
VAII	
M Island	
100 1	
Notes:	
10-11	at commercial along in 11
Sillelled the wind	of commerces sory mall
C 0 1	1 1 1 1 1 1 1 1 1
Stop & Rho	of commercial stry mall. p to but not incl. McD's.
he had a state	Bockside u. dirty. See
muon imperiore	sound h. may roa
1 - 1	xcellen outreach target.
norsper form. C	scerien anxioca in go.
2 / //	
Men la tal.	1, Ithe mailable love
moghe remoju	, but little orailable lavel
<i>U</i>	
orea.	
	4



						_	×=
SURVEY REACH	ID: <u>CSB-0</u> \ w	TRSHD/SUBSHD: Col	d Spring Bk	DATE: 8 / 24	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ESSED BY:	MB
START TIM	IE: 9 :38 AM/PI	M LMK: 52-01	END TIME:	: AM/PM	LMK:	K	GPS ID:
The state of the state of the state of		13 0 27 1482"			3027 150	2.6"	GB
DESCRIPTION: 5							Maple
DESCRIPTION: 3	pill way from s	st John's Pound	DESCRIPTION. (c	ld Spring t	larbor		mapoo
RAIN IN LAST 24 HO		이 그 전쟁으로 가루 하셔요?	PRESENT CONDITIONS	☐ Heavy rain	☐ Steady rain	□ Interm	nittent
None None	☐ Intermitten		Clear Clear	☐ Trace	☐ Overcast	☐ Partly	cloudy
SURROUNDING LAN		al □ Commercial urse □ Park	☐ Urban/Residential / ☐ Crop	Suburban/Res ☐ Pasture	☐ Forested ☐ Other:	□ Institu	tional
AVERAGE	E CONDITIONS (cho	eck applicable)	REACH S	SKETCH AND SI	TE IMPACT TI	RACKING	
BASE FLOW AS % CHANNEL WIDTH	□ 0-25% □25-50 %	№ 50%-75% □ 75-100%	Simple planar sketch of within the survey rea	f survey reach. Tra ich (OT, ER, IB,SC, deemed appropriate.	UT, TR, MI) as w	ell as any a	ite impacts dditional
DOMINANT SUBSTR ☐ Silt/clay (fine or ☐ Sand (gritty) ☑ Gravel (0.1-2.5	slick) ဩC □ B	cobble (2.5 –10") coulder (>10") ed rock	START II	557 55		Pond	- A
WATER CLARITY △ Stained (clear, n □ Other (chemicals,	dyes) in S	Opaque (milky)		1	SC-02		K
AQUATIC PLANTS IN STREAM		ne ⊠ some □ lots e □ some □ lots	4		-01	T	1
WILDLIFE IN OR AROUND STREAM	(Evidence of) ☐ Fish ☐ Beav ☐ Snails ☐ Othe	100 mm m 1.74			A.	6 OT-03	6
STREAM SHADING (water surface)	☐ Mostly shaded☐ Halfway (≥50% ☑ Partially shade☐ Unshaded (< 2.	%) d (≥25%)			-	IB-01	
CHANNEL	☐ Downcutting	Bed scour		1		7	
DYNAMICS	Widening	Bank failure				/	
	Headcutting	Bank scour		/	5 /		
Unknown	☐ Aggrading ☐ Sed. depositio	□ Slope failure n □ Channelized)	61		
CHANNEL DIMENSIONS	Height: LT bank RT bank	6 (ft) 3 (ft)		/	/		05-04
(FACING DOWNSTREAM)	Width: Bottom	g(ft)		1	1	11	
DOWNSTREADY)	Тор	25 (ft)		1		4	
R	REACH ACCESSIBILI			1	1	0/	
Good: Open area in	Fair: Forested or	Difficult. Must cross	1	1	1		
public ownership,	developed area adjacent to stream.	wetland, steep slope, or sensitive areas to get to		1			
sufficient room to stockpile materials,	Access requires tree	stream. Few areas to		1	-		
easy stream channel	removal or impact to	stockpile available		14	57-LN		_
access for heavy	landscaped areas. Stockpile areas	and/or located a great distance from stream.		5c-03 H	1	11-	T-05
equipment using existing roads or trails.	small or distant from	Specialized heavy	TA.			To	1-03
	stream.	equipment required.	-	1 Spens)	1	0 0	2.20
5 Notes: (biggest prob	1 3	reach)	1 000	1/	- /) P	wag
- 10 the longgest prot	erem you see in survey	reach)	07-06 8480	10	Que 93		
			in in	DING	\ /		
			END co	LE SPLING	TED TO AUTHOR	RITIES	ES No
				Howbor			4

	Optimal	Suboptimal	Marginal	Poor		
IN-STREAM HABITAT (May modify criteria based on appropriate habitat regime)	Greater than 70% of substrate favorable for epifaunal colonization and fish cover; mix of snags, submerged logs, undercut banks, cobble or other stable habitat and at stage to allow full colonization potential (i.e., logs/snags that are not new fall and not transient).	40-70% mix of stable habitat; well- suited for full colonization potential; adequate habitat for maintenance of populations; presence of additional substrate in the form of newfall, but not yet prepared for colonization (may rate at high end of scale).	20-40% mix of stable habitat; habitat availability less than desirable; substrate frequently disturbed or removed.	Less than 20% stable habitat; lac of habitat is obvious; substrate unstable or lacking.		
	20 19 18 17 16	15 14 (13) 12 11	10 9 8 7 6			
VEGETATIVE PROTECTION (score each bank, determine sides by facing downstream)	More than 90% of the streambank surfaces and immediate riparian zone covered by native vegetation, including trees, understory shrubs, or nonwoody macrophytes; vegetative disruption through grazing or mowing minimal or not evident; almost all plants allowed to grow naturally.	70-90% of the streambank surfaces covered by native vegetation, but one class of plants is not well-represented; disruption evident but not affecting full plant growth potential to any great extent; more than one-half of the potential plant stubble height remaining.	50-70% of the streambank surfaces covered by vegetation; disruption obvious; patches of bare soil or closely cropped vegetation common; less than one-half of the potential plant stubble height remaining.	Less than 50% of the streambank surfaces covered by vegetation; disruption of streambank vegetation is very high; vegetation has been removed to 5 centimeters or less in average stubble height.		
	Left Bank 10 9	(8) 7 6	5 4 3	2 1 0		
	Right Bank 10 9	(8) 7 6	5 4 3	2 1 0		
BANK EROSION (facing downstream)	Banks stable; evidence of erosion or bank failure absent or minimal; little potential for future problems. <5% of bank affected.	Grade and width stable; isolated areas of bank failure/erosion; likely caused by a pipe outfall, local scour, impaired riparian vegetation or adjacent use.	Past downcutting evident, active stream widening, banks actively eroding at a moderate rate; no threat to property or infrastructure	Active downcutting; tall banks on both sides of the stream eroding a a fast rate; erosion contributing significant amount of sediment to stream; obvious threat to property or infrastructure.		
	Left Bank 10 9	8 7 6	5 4 3	2 1 0		
	Right Bank 10 9	8 7 6	5 4 3	2 1 0		
FLOODPLAIN CONNECTION	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.		
	20 19 18 17 16	15 14 13 12 (11)	10 9 8 7 6	5 4 3 2 1 0		
	OVER	ALL BUFFER AND FLOODPLAI	N CONDITION			
	Optimal	Suboptimal	Marginal	Poor		
VEGETATED BUFFER WIDTH Width of buffer zone >50 feet; human activities (i.e., parking lots, roadbeds, clear-cuts, lawns, crops) have not impacted zone.		Width of buffer zone 25-50 feet; human activities have impacted zone only minimally.	Width of buffer zone 10-25 feet; human activities have impacted zone a great deal.	Width of buffer zone <10 feet: little or no riparian vegetation due to hurnan activities.		
	Left Bank 10 9	8 7 6	(5) 4 3	2 1 0		
	Right Bank 10 9	8 (7) 6	5 4 3	2 1 0		
FLOODPLAIN Predominant floodplain vegetation is mature forest		Predominant floodplain vegetation type is young forest	Predominant floodplain vegetation type is shrub or old field	Predominant floodplain vegetation type is turf or crop land		
	20 19 18 17 16	15 14 13 12 11	(10) 9 8 7 6	5 4 3 2 1 0		
FLOODPLAIN HABITAT	Even mix of wetland and non-wetland habitats, evidence of standing/ponded water	Even mix of wetland and non-wetland habitats, no evidence of standing/ponded water	Either all wetland or all non- wetland habitat, evidence of standing/ponded water	Either all wetland or all non- wetland habitat, no evidence of standing/ponded water		
	20 19 18 17 16	15 14 13 12 11	10 (9) 8 7 6	5 4 3 2 1 0		
FLOODPLAIN ENCROACH- MENT No evidence of floodplain encroachment in the form of fill material, land development, or manmade structures		Minor floodplain encroachment in the form of fill material, land development, or manmade structures, but not effecting floodplain function	Moderate floodplain encroachment in the form of filling, land development, or manmade structures, some effect on floodplain function	Significant floodplain encroachment (i.e. fill material, land development, or man-made structures). Significant effect on floodplain function		
				4 3 2 1 0		

Stream Crossing SC

WATERSHE	DISUBSHED: Cold S	oring Brut	I	DATE: 8 124 109	Ass	ESSED BY: KMB	
URVEY RE.	ACH ID: LAB -01	TIME: Q : L	100	ното ID: (Сатега-Р			
SITE ID: (Co	ndition-#) SC-0/	LAT 400 51	" Long 73	22 0	MK	GPS (Unit ID)	
m	90-100 V		5.8	48,1			
TYPE: L Ro	Formation -	d Crossing Manmad		Dam Geological Fo	mation [Other:	
FOR ROAD/ RAILROAD CROSSINGS ONLY	SHAPE: #BARRELS: Arch Bottomless Single Box Elliptical Double Circular Triple Other: Other:		MATERIAL: Concrete Metal Other:	ALIGNMENT: Flow-aligned Not flow-aligned Do not know	DIMENS Barrel di	SIONS: (if variable, sketch) ameter:	
	CONDITION: (Evidence of) Cracking/chipping/corrosion Downstream scour hole Sediment deposition Failing embankment Other (describe):			CULVERT SLOPE: Flat Slight (2° - 5°) Obvious (>5°)	Culvert length: 10 (Width: 15 (Roadway elevation: 25)		
POTENTIAL I	RESTORATION CANDI	DATE Fish barrier Local stream		repair/replacement	Upstream s	torage retrofit	
	G AS GRADE CONTROL			wn.			
	EXTENT OF PHYSIC	AL BLOCKAGE:		BLOCKAGE SEVE	RITV: (circ	rle #)	
If yes for fish barrier	Drop too high Water Drop:		greater stream block upstream movement anadromous fish; no passage device presi	of or partial blockage fish interfere with the	of stream, ge that may migration of	beaver dam or a blockage at the very head of a stream wi very little viable fish habitat above it; natural barriers suc as waterfalls.	
NOTES/SKET			(5)	4 3		2 1	
		St John's	5 /				

Stream Crossing SC

WATERSHEI		y DE			5124100	73001	ESSED BY: KM	B
URVEY REA		TIME: 10: 1			D: (Camera-Pi		1# 00	
SHE ID: (Co	ndition-#) SC- 1 LAT	10.71.2	LONG_	3027	1981) L	MK	GPS (Unit I	D)
TYPE: Ro	oad Crossing Railroad Cross	ing Manmade	e Dam Beave	er Dam	Geological For	mation [Other:	
FOR ROAD/ RAILROAD CROSSINGS ONLY	SHAPE: #BARRELS: MATERIAL: ALIGNMENT: Arch Bottomless Single Double Metal Not flow-aligned Circular Other: Other: Do not know		GNMENT: low-aligned ot flow-aligned	DIMENSIONS: (if variable, s Barrel diameter:		(1		
	CONDITION: (Evidence of) Cracking/chipping/corrosion Sediment deposition This is a cour hole Failing embankment Other (describe):				CULVERT SLOPE: Flat Slight (2° - 5°) Obvious (>5°)		Culvert length: Width: Roadway elevation:	
POTENTIAL I	RESTORATION CANDIDATE	☐ Fish barrier r☐ Local stream	removal Culve		eplacement 🔲	Upstream s	torage retrofit	
IS SC ACTING	G AS GRADE CONTROL	□No □Y	es 🔲 Unkn	iown				
	EXTENT OF PHYSICAL BLO	OCKAGE:		BLO	OCKAGE SEVE	RITY: (circ	le #)	
If yes for fish barrier	☐ Temporary ☐ Unknown CAUSE: ☐ Drop too high Water Drop: 24 (in) ☐ Flow too shallow Water Depth: (in) ☐ Other: ☐ A structure road culvert greater stre upstream manadromous passage de			order or tributary that wou significant reach or partial blockag interfere with the		uld isolate a beaver dam or a blockage a of stream, ge that may very little viable fish habitat above it; natural barriers su		
			540	eps of D	AM		_)	
		Brono ces	STED WE	R		7		
					REPOR	TED TO AUT	HORITIES [] VES	Mai

Stream Crossing

SC

URVEY REA	D/SUBSHED: Cold JOVIN			DATE: 🖁			ESSED BY: KMB
WHAT IS NOT THE WAY TO SHAPE THE PARTY OF TH		TIME: (0 :7/				c#) 49	008 147017
SITE ID: (Co.	ndition#) SC-13 LAT	40051.2	Soft LONG T	5077	49.8" L	MK	GPS (Unit ID)
Type, Mr	10 .: При 10	H.					
TYPE: MRO	ad Crossing Railroad Cross				Geological For		Other:
FOR ROAD/ RAILROAD	SHAPE: Arch Bottomless Box Elliptical Circular Other:	# BARRELS: Single Double Triple Other:	ngle Concrete ouble Metal iple Other		ALIGNMENT: Flow-aligned Not flow-aligned Do not know		SIONS: (if variable, sketch lameter: 2 (Height: (
CROSSINGS ONLY	CONDITION: (Evidence of) Cracking/chipping/corrosion Sediment deposition Other (describe):	n Downstrea		☐ FI ⊠ SI	VERT SLOPE: at ight (2° – 5°) bvious (>5°)	Roadway	Width: 30 (
Mila	RESTORATION CANDIDATE	Fish barrier r	removal Culve		eplacement 1	Upstream s	storage retrofit
IS SC ACTIN	G AS GRADE CONTROL	□No □Y	es Unkn	own			
		CKAGE:		BLO	OCKAGE SEVER	RITY: (circ	cle #)
		rop:(in)	A structure such as road culvert on a 3r greater stream bloc upstream movemer anadromous fish; no passage device pre	A total fish blockage on a tributary that would isolate a significant reach of stream, or partial blockage that may interfere with the migration of anadromous fish.		A temporary barrier such as beaver dam or a blockage at the very head of a stream wi very little viable fish habitat above it; natural barriers suc as waterfalls.	
		PET 2	5A				
		1					
	×17	F+ Toff					
	Civilynt be	ft wift					

Impacted Buffer

IB

JRVEY REACH: /51		ong GF	To the	-	TE: 81 74 16	29 Ass	SESSED BY: KIB
V'	3-01		E: 10:17		ото ID: (Сатег	a-Pic#)	1# 004
SITE ID: (Condition-#)		AT 40°51 'U	LONG_	3027.7	LMK LMK		GPS: (Unit ID)
IMPACTED BANK:	REASON IN		ack of vegetation		row 🗌 Widesprea	d invasive p	plants
LAND USE: (Facing downstream) LT Bar RT Bar	1.0		If Course Pa		oblic : Fish hal	deng	
DOMINANT LAND COVER: LT Ba RT Ba	V L	Bare ground T	urf/lawn T	all grass Shr	ub/scrub Trees	Other	
INVASIVE PLANTS:	None None	Rare	Partial co	verage [Extensive coverage		znown
STREAM SHADE PROVI	DED? No	one 🛛 Partial	☐ Full	WETLAND	PRESENT? \(\sum \) N	o Kiy	es Unknown
LT BAN Length (ft):	K RT	REFORESTATIO: POTENTIAL: (Circle #)	where the not appe specific p	I area on public lar e riparian area doe ar to be used for a ourpose; plenty of ilable for planting	s public or private	land that is or a specific le area for	Impacted area on private land where road; building encroachment or other feature significantly limits available area for planting
"/idth (ft):/				5	(4) 3	2	1
POTENTIAL CONFLICTS Poor/unsafe access to si			Widespread	invasive plant	Potential co		Lack of sun
		EN!	habel				
NOTES:		01	DECK	70	o ((10P	VIEW)
NOTES:		2	DECK	70)	(70P	VIEW)
NOTES:		2		7/5 61)	TOP	VIEW
NOTES:		2		700)	(10 P	VIEW)
NOTES:		2		7/54		10 P	VIEW

Storm Water Outfalls **OT**

WATERSHED	/SUBSHEE	o: Cold s	pn	1 BE		DATE: _8	1/24	19	ASSES	SED BY:	FMB	
SURVEY REA	сн ID: (58-01	TIME	E: 10:04 AM/PM	1.	Рното II	D: (Camera-	Pic#)		/#	805	
SITE ID (Cond	ition-#): O	T01_	LAT	40.51.26.1	Lo	NG 73°	27.48	7	LMK_	5	GPS: (Unit	ID)
BANK: LT RT FLOW: None	Head Trickle	TYPE: Closed pipe	Sed Concrete M			SHAPE: Circula Elliptic	☐ Single r ☐ Doub al ☐ Triple	le	IMENSI	ons: 24 _{(in}	SUBMER No Partia	
☐ Moderate ☐ Substantial ☐ Open ☐ Other: channel			Concrete Earthen Other:		Trapezoid Depth: Parabolic Width (Top): Other: " (Bottom):			(Top):	(in) (in) (in)	NOT APPAS	CABLE	
CONDITION: None Chip/Cracke		ODOR: ☑ ☐ Gas ☐ Sewage	as None Oily			VEGGIE I None Normal			PE BENT Brown Other:		OWTH: N	one
☐ Peeling Paint ☐ Rancid/S ☐ Corrosion ☐ Sulfide ☐ Other: ☐ Other:]	☐ Flow Line ☐ Paint ☐ Other:		☐ Inhibited ☐ Excessive ☐ Other:		B	POOL QUALITY: No pool Good Odors Colors Oil Suds Algae Floatables Other:			□Oils	
For	Color:	×	Clear	☐ Brown ☐ Gre	у [Yellow	Green	☐ Orai	ige 🔲 l	Red 🔲 C	Other:	
FLOWING ONLY	TURBIDI			☐ Slight Cloudines ☐ Sewage (toilet pa		Cloudy	Opaque Petroleur			- 33	Other:	
no If yes for dayl	ESTORAT		DATE	☐ Discharge investi☐ Storm water retro	igation fit	Stream Other:		L	ocal strea			zation
If yes for storn Is stormwater compared No.	nwater: urrently co	ntrolled?	l:	ft Type of Land Us Area ava	se desc	eription:	on;			_ Slope;		0
OUTFALL SEVERITY: (circle #)	stron com strea	yy discharge with ng smell. The am pared to the amo nm; discharge ap ficant impact dov	ount of dis unt of nor pears to b	scharge is significant mal flow in receiving be having a	lischarge lischarge	e has a color a e is very small	nostly clear and nd/or odor, the compared to the pears to be min	amount o	f s base	discharge;	s not have dry we staining; or appea any erosion probl	arance
GV - All Province I	1		5	4			3)		2		1	
SKETCH/NOT	ь.		The same	nese but mount	10 8	(orl						

Storm Water Outfalls OT

WATERSHED	/SUBSHEI): (o	11 51	oring Brook	4	DATE: 8	12410	ASSE	SSED BY:	KMB
SURVEY REA	CH ID:	CSB-	O/ Tr	ME: <u>[0] : 0 84</u> M/P	M	Рното I	D: (Camera-P	ic#) 000	C /#	
SITE ID (Cond	lition-#): O	T- 01	3 LA	т 40. 51 . 76	2ºL	ong 13 °	27.48.9			GPS: (Unit ID)
BANK: LT RT FLOW: None	Head	☐ Concrete		☐ PVC/Plastic ☐	[]Metal]Brick		☐ Single ar ☐ Double cal ☐ Triple	DIMENS	SIONS: r:6_(in)	SUBMERGED: No Partially Substituting
Moderate Substantial □ Open □ Co		Concrete E	Sarthen	☐ Trapez ☐ Parabo ☐ Other:	lie v	epth: /idth (Top):_ " (Bottom):		NOT APPESCABLE		
CONDITION: None Chip/Cracked Peeling Paint Corrosion Other:		☐Gas ☐ None ☐ Oily			NS:	None Norma		☐ Brown ☐ Other:	Orang	OWTH: None
		ide	☐ Flow Line ☐ Paint ☐ Other:		☐ Inhibited ☐ Excessive ☐ Other:		POOL QUALITY: No pool Sood Odors Colors O Suds Algae Floatables Other:			
For	COLOR:		Clear	☐ Brown ☐ C	Grey	☐ Yellow	Green [Orange [Red 🗆 O	ther:
FLOWING	TURBID		None	Slight Cloudin		Cloudy	☐ Opaque			
ONLY	FLOATA		None None				Petroleum	(oil sheen)		ther:
OTHER CONCERNS:	The second secon		(paper/pla r Mainten		Dumping Bank Ero	g (bulk) osion	☐ Excessive ☐ Other:	Sedimentation	on	
POTENTIAL F	RESTORAT	TION CA	NDIDATE	☐ Discharge invo		on Stream		Local stre	eam repair/o	outfall stabilization
If yes for dayl	iohtino:			Storm water rea	uont	U Other:				
Length of vege		r from o	utfall:	ft Type	of exis	ting vegetation	on:		Slope;	o o
If yes for storm	urrently co			Land	Use de	scription:				
☐ Yes ☐ No					availab	e:				
OUTFALL SEVERITY: (circle #)	stror com strea	ng smell. The pared to the am; discharg	e amount of	nct color and/or a discharge is significant normal flow in receiving to be having a m.	dischar dischar	ge has a color a ge is very small	mostly clear and o and/or odor, the an I compared to the s opears to be minor	nount of stream's base	discharge; s	not have dry weather staining; or appearance any erosion problems.
			5		4		3	(2)	.1
SKETCH/NOT	ES:		1 07	J .02 07	103	BANK				
			~~		_	6	STILEAM	REPORTED TO	O AUTHORI	IIES: ☐ YES ☐ NO

Storm Water Outfalls

WATERSHED	/SUBSHEI): (olds	pring BK		DATE: 8	12410	7 ASSE	SSED BY:	KMB
SURVEY REA	CH ID: (5B-0	TI	ME: 10 : 77 AM/PI	М	Рното П	D: (Camera-F	Pic#)	1# 6	007
SITE ID (Cona	lition-#): O	T-04	LA	T40.21 23	do" Lo					GPS: (Unit ID)
The second secon	Head	TYPE:	sed	MATERIAL: Concrete PVC/Plastic Other:]Metal]Brick	SHAPE: Circula Elliptic Other:	Single or Double cal Triple	DIMENS Diameter	111	SUBMERGED: No Partially Fully
Moderate Substantial Other:			arthen	rthen						
CONDITION: None Chip/Crack		☐Gas ☐ Sev	vage	DEPOSITS/STAIN None Oily	S:	VEGGIE I None Normal			THIC GRO	WTH: None
☐ Corrosion ☐ Sulfide ☐ P		☐ Flow Line ☐ Paint ☐ Other:	Paint		☐ Inhibited ☐ Excessive ☐ Other:		POOL QUALITY: No pool Good Odors Colors O Suds Algae Floatables Other:			
FOR	COLOR:		Clean	r Brown C	irev	Yellow	Green [Orange	Red DO	ner -
FLOWING	TURBIDI		None			Cloudy	Opaque	_ Crange _	I Ked 🔲 Ot	ici,
ONLY	FLOATA	BLES:	☐ None	The second secon			Petroleum	(oil sheen)	Ot	her:
OTHER CONCERNS:			(paper/pla r Mainten		Oumping ank Ero		☐ Excessive	e Sedimentati	on	
POTENTIAL F	RESTORAT	TION CA	NDIDATE	☐ Discharge inve		n Stream Other:	daylighting	Local str	eam repair/o	utfall stabilization
If yes for dayl	ighting:			_ Storm water ret	TOIL	U Omer.				
Length of vege		r from o	utfall:	ft Type	of exist	ing vegetation	on:		Slope: _	0
If yes for stori	nwater:									
Is stormwater c		ntrolled?	10	Land	Use des	scription:				
☐ Yes ☐ No	the second secon				availabl					
OUTFALL SEVERITY: (circle #)	stror com strea	ng smell. The pared to the am; dischar	ne amount of e amount of	inct color and/or a f discharge is significant normal flow in receiving to be having a am.	dischar	ge has a color a ge is very small	mostly clear and and/or odor, the a compared to the pears to be mino	mount of stream's base	discharge; st	not have dry weather aining; or appearance y erosion problems.
			5		4		3	(2)	- 1
SKETCH/NOT	ES:		my 5 cd good &	he now for	Drove	1	> BANK	ξ.		
				Tratay				REPORTED T	O AUTHORIT	ES: YES NO

Storm Water Outfalls

-		_		
1	J		П	
и.	. 19		п	
W			8	

co: Cold S	my Brook	DATE: 8/24/0	ASSESSED BY:	EMB		
C9B-01	TIME: 10:32 AM/PM	РНОТО ID: (Camera-	Pic#) /# (012		
OT-05	LAT 10 . 51 . 254 "I	LONG 13.27 509	" LMK	GPS: (Unit ID)		
TYPE: Closed pipe		ck Elliptical Triple Diameter: (in) Par				
☐ Open channel	☐ Concrete ☐ Earther☐ Other:	Trapezoid		Fully NOT APDESCABLE		
☐Gas ☐ Sewage	□None □Oily	VEGGIE DENSITY: None Normal	PIPE BENTHIC GRO			
Sulfide Other:	Paint Other:	Excessive Other:	POOL QUALITY: No pool Good Godors Colors Goil Suds Algae Floatables Other:			
		Yellow Green Cloudy Opaque	☐ Orange ☐ Red ☐ C	Other;		
eess Trash (paper eds Regular Mair	r/plastic bags)	ng (bulk)	e Sedimentation			
	Storm water retrofit	Other;				
			Slope:	0		
ong smell. The amou mpared to the amour eam; discharge appe	unt of discharge is significant and of normal flow in receiving ears to be having a	arge has a color and/or odor, the a arge is very small compared to the	amount of discharge;	s not have dry weather staining; or appearance any erosion problems.		
	5 (4)	3	2	12		
	Control Ro	MALU AN STRUCK	possil A	ofely		
	TYPE: Closed pipe Open channel Open channel Open channel Open channel Open channel Other: Closed pipe Open channel Open	TIME: D: J AM/PM OT- 05 LAT	TYPE: MATERIAL: SHAPE: Single Circular Double PVC/Plastic Brick Elliptical Triple Other: Other: Open	TIME:		

BOLLVERTS

WATERSHED	/SUBSHEI	o: Cali	1 50	ning Brk		DATE: \$ 124 /	og Asser	SSED BY:	KUB .
SURVEY REA		2		ME: 0:42AM/P	M	РНОТО ID: (Camera-			217
SITE ID (Cond		0.7	_			ONG 73 . 27. 48,	1		GPS: (Unit ID)
BANK: □LT X RT [FLOW; □ None □	Head Trickle	TYPE: Close pipe	ed	MATERIAL: Concrete PVC/Plastic Other:]Metal]Brick	SHAPE: Single Circular Doub Elliptical Triple Other:	le	sions:	SUBMERGED: No Partially Fully
Moderate X Substantial Other:		Open chanr		Concrete E	Earthen	☐ Trapezoid ☐ Parabolic ☐ Other:	Depth: Width (Top):_ " (Bottom):_		NOT APPEICABLE
CONDITION: None Chip/Crack Peeling Pail Corrosion Other:		ODOR: Gas Sewa Rancie Sulfic	ge d/Sour de	DEPOSITS/STAIN None Oily Flow Line Paint Other:	NS:	VEGGIE DENSITY: None Normal Inhibited Excessive Other:	PIPE BEI Brown Other: POOL Qu Good	NTHIC GRO Orang UALITY: Odors Algae	Colors Oil
FOR FLOWING ONLY OTHER CONCERNS:	The second second second	TY:		Slight Clouding Sewage (toiler stic bags)	ness	☐ Cloudy ☐ Opaque etc.) ☐ Petroleur ☐ (bulk) ☐ Excessive	Orange m (oil sheen) ve Sedimentati	Ot	***
POTENTIAL F no f yes for dayl Length of vege	ighting:			Storm water ret	trofit	n Stream daylighting Other:	☐ Local str	eam repair/o	utfall stabilization
f yes for storn s stormwater c ☐ Yes ☐ No	urrently co		d		Use des	scription:e:			
OUTFALL SEVERITY: (circle #)	stror com strea	ng smell. The pared to the a	amount of amount of a appears t	nct color and/or a discharge is significant normal flow in receiving to be having a m.	dischar dischar	ischarge; flow mostly clear and ge has a color and/or odor, the ge is very small compared to the d any impact appears to be min	amount of e stream's base	discharge; sta	not have dry weather aining; or appearance y erosion problems.
SKETCH/NOT	ES:		5	wet la	4.))	at 3		2	1
				0705 PD:	AD AD		Sovrce ~5	unkna	nn ad discha
					Juns	pmd			ies: □ yes ፟፟ no

SURVEY REACH ID: C5B-02 WTRSHD/SUBSHD: Co	d Spring Bk DATE: 8/24/09 ASSESSED BY: JHW/KMB
START TIME: 12:40 AM/RM LMK: 5C-01	END TIME: 12:00 AM/M LMK: GPS ID:
LAT40 .51 '08.1" LONG 73. 27 '383"	LAT 40° 57 '11.8" LONG 73° 27 '38.7" GPS
A (1) A = (1) A (1	
DESCRIPTION: Spillway of Franklin Pond	DESCRIPTION: Confluence of CSB of St Jana Mapbo
RAIN IN LAST 24 HOURS Heavy rain Steady rain	PRESENT CONDITIONS
None ☐ Intermittent ☐ Trace	Clear
SURROUNDING LAND USE: ☐ Industrial ☐ Commercial ☐ Golf course ☐ Park	☐ Urban/Residential ☐ Suburban/Res ☐ Forested ☐ Institutional ☐ Crop ☐ Pasture ☐ Other:
AVERAGE CONDITIONS (check applicable)	REACH SKETCH AND SITE IMPACT TRACKING
BASE FLOW AS % □ 0-25% □ 50%-75% CHANNEL WIDTH ■ 25-50 % □ 75-100%	Simple planar sketch of survey reach. Track locations and IDs for all site impacts within the survey reach (OT, ER, IB,SC, UT, TR, MI) as well as any additional features deemed appropriate in library direction of flow
DOMINANT SUBSTRATE	features deemed appropriate of fluit cate direction of flow
Silt/clay (fine or slick) (Cobble (2.5 –10")	
☐ Sand (gritty) ☐ Boulder (>10") ☐ Gravel (0.1-2.5") ☐ Bed rock	START SC-01
WATER CLARITY Clear Turbid (suspended matter)	
Stained (clear, naturally colored) Opaque (milky)	
Other (chemicals, dyes) Iron floc	
AOUATIC PLANTS Attached: ☑ none ☐ some ☐ lots	
IN STREAM Floating: □ none ☒ some □ lots	
(Evidence of)	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
APOUND STREAM Fish Beaver Deer	Wetland seeps
Snails Other:	
STREAM SHADING ☐ Halfway (≥50%)	
(water surface) ☐ Partially shaded (≥25%)	3
☐ Unshaded (< 25%)	
CHANNEL Downcutting Bed scour	
DYNAMICS Widening Bank failure	
Headcutting Bank scour	
Unknown Aggrading Slope failure	
Sed. deposition Channelized	
CHANNEL Height: LT bank 5(ft)	
DIMENSIONS RT bank 3 (ft)	MoHand
(FACING Width: Bottom 10-12 (ff)	Wetland Seeps
DOWNSTREAM) Top 15-20 (ft)	
REACH ACCESSIBILITY	2 ///
Good: Open area in Fair: Forested or Difficult. Must cross	
public ownership developed area wetland, steep slope, or	[3] 1
sufficient room to adjacent to stream. sensitive areas to get to stream. Access requires tree stream. Few areas to	25
easy stream channel removal or impact to stockpile available	
access for heavy Stockpile areas. and/or located a great	
equipment using existing roads or trails. Specialized heavy	win .
equipment required.	END ST John's Poud
5 4 (2) 1 NOTES: (biggest problem you see in survey reach)	
(v.88est providen you see in survey reach)	
	.=.
	REPORTED TO AUTHORITIES YES NO

	Optimal	Suboptimal	Marginal	Poor		
IN-STREAM HABITAT (May modify criteria based on appropriate habitat regime)	Greater than 70% of substrate favorable for epifaunal colonization and fish cover; mix of snags, submerged logs, undercut banks, cobble or other stable habitat and at stage to allow full colonization potential (i.e., logs/snags that are not new fall and not transient).	40-70% mix of stable habitat; well- suited for full colonization potential; adequate habitat for maintenance of populations; presence of additional substrate in the form of newfall, but not yet prepared for colonization (may rate at high end of scale).	20-40% mix of stable habitat; habitat availability less than desirable; substrate frequently disturbed or removed.	Less than 20% stable habitat; lack of habitat is obvious; substrate unstable or lacking.		
	20 19 18 (17) 16	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0		
PROTECTION surfaces and immediate riparian zone covered by native vegetation, including trees, understory shrubs, or nonwoody macrophytes; vegetative disruption through grazing or mowing minimal or covered by native vegetation, class of plants is not well-represented; disruption eviden not affecting full plant growth processing full		represented; disruption evident but not affecting full plant growth potential to any great extent; more than one- half of the potential plant stubble	e 50-70% of the streambank surfaces covered by vegetation; disruption obvious; patches of disruption of streamb			
	Left Bank 10 (9)	8 7 6	5 4 3	2 1 0		
	Right Bank 10 9	8 7 6	5 4 3	2 1 0		
BANK EROSION (facing downstream)	Banks stable; evidence of erosion or bank failure absent or minimal; little potential for future problems. <5% of bank affected.	Grade and width stable; isolated areas of bank failure/erosion; likely caused by a pipe outfall, local scour, impaired riparian vegetation or adjacent use.	Past downcutting evident, active stream widening, banks actively eroding at a moderate rate; no threat to property or infrastructure	Active downcutting; tall banks on both sides of the stream eroding at a fast rate; erosion contributing significant amount of sediment to stream; obvious threat to property or infrastructure.		
	Left Bank 10 9	(8) 7 6	5 4 3	2 1 0		
	Right Bank 10 (9)	8 7 6	5 4 3	2 1 0		
FLOODPLAIN CONNECTION	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain, Stream deeply entrenched.		
	20 19 18 17 (16)	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0		
	OVER	ALL BUFFER AND FLOODPLAN	IN CONDITION			
	Optimal	Suboptimal	Marginal	Poor		
VEGETATED Buffer Width	Width of buffer zone >50 feet; human activities (i.e., parking lots, roadbeds, clear-cuts, lawns, crops) have not impacted zone.	Width of buffer zone 25-50 feet; human activities have impacted zone only minimally.	Width of buffer zone 10-25 feet; human activities have impacted zone a great deal.	Width of buffer zone <10 feet: little or no riparian vegetation due to human activities.		
	Left Bank 10 (9)	2 6	5 4 3	2 1 0		
	Right Bank 10 9	8 (7) 6	5 4 3	2 1 0		
FLOODPLAIN VEGETATION	Predominant floodplain vegetation type is mature forest	Predominant floodplain vegetation type is young forest	Predominant floodplain vegetation type is shrub or old field	Predominant floodplain vegetation type is turf or crop land		
	20 19 18 17 16	(15) 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0		
FLOODPLAIN HABITAT	Even mix of wetland and non-wetland habitats, evidence of standing/ponded water	Even mix of welland and non-wetland habitats, no evidence of standing/ponded water	Either all wetland or all non- wetland habitat, evidence of standing/ponded water	Either all wetland or all non- wetland habitat, no evidence of standing/ponded water		
	20 19 (18) 17 16	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0		
FLOODPLAIN ENCROACH- MENT	No evidence of floodplain encroachment in the form of fill material, land development, or manmade structures	Minor floodplain encroachment in the form of fill material, land development, or manmade structures, but not effecting floodplain function	Moderate floodplain encroachment in the form of filling, land development, or manmade structures, some effect on floodplain function	Significant floodplain encroachment (i.e. fill material, land development, or man-made structures). Significant effect on floodplain function		
	20 19 (18/17 16	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0		

Stream Crossing SC

WATERSHED	SUBSHED: (OU S	pring Brow	K		DATE: 9	5124109	ASSE	SSED BY: KMB
THE ALC: NO THE RESERVE	ACH ID: (9B-62					D; (Camera-Pi	ic #)	1#021
SITE ID: (Con	ndition#) SC-07	LAT UDOS	51.8	13" LONG 7	3027	<u>'38.5"</u> L	MK	GPS (Unit ID)
TYPE; Ros	ad Crossing Railroa	d Crossing 🔯 1	Manmade	Dam Beave	er Dam	Geological For	mation \square	Other:
FOR ROAD/ RAILROAD	SHAPE: Arch Botto Box Ellipt Circular Other:	#BAR	RELS: gle uble ple	MATERIAL: Concrete Metal Other:	ALIG	ALIGNMENT: Flow-aligned Not flow-aligned Do not know		IONS: (if variable, sketch) _ imeter:
CROSSINGS ONLY	CONDITION: (Evidence □Cracking/chipping/c □ Sediment depositio □ Other (describe):	corrosion D		m scour hole bankment	□ FI	VERT SLOPE: at ight (2° – 5°) bvious (>5°)		ength: $\frac{25}{15}$ (ft) Width: $\frac{15}{15}$ (ft) elevation: $\frac{N}{15}$ (ft)
POTENTIAL I	RESTORATION CANDI	T. Commercial Control of the Control	n barrier r al stream			eplacement 🔲	Upstream st	orage retrofit
IS SC ACTING	G AS GRADE CONTROL EXTENT OF PHYSIC.		X Y	es Unkn		OCKAGE SEVE		
If yes for fish barrier	☐ Temporary ☐ CAUSE:	Vater Drop:	(in)	A structure such as road culvert on a 3 greater stream blo upstream moveme anadromous fish; r passage device pro	ard order or cking the ent of no fish	A total fish block: tributary that wou significant reach or partial blockag interfere with the anadromous fish	uld isolate a of stream, ge that may migration of	A temporary barrier such as a beaver dam or a blockage at the very head of a stream with very little viable fish habitat above it; natural barriers such as waterfalls.
	Loordingles— taken HERE	FLAT POND	N STATE OF THE STA	HANNEK P		1 661 661	NEW	cement
	(1-1-	MARSH	133			Pepon	TED TO AUG	THORITIES ☐ YES 🗖 NO

Reach Level Assessment RCH

	IE: 39 : 50 AM/PM LMK:	END TIME: 3: / SAM(PM) LMK: GPS ID:
	40.5" LONG 73 ° 27 1234"	0/12
DESCRIPTION: F	ootholde	DESCRIPTION: Frankfin Fond Inlet Maple
	DURS ☐ Heavy rain ☐ Steady rain	PRESENT CONDITIONS
None	☐ Intermittent ☐ Trace	A Clear
SURROUNDING LAN	D USE: ☐ Industrial ☐ Commercial ☐ Golf course ☐ Park	☐ Urban/Residential
AVERAGE	E CONDITIONS (check applicable)	REACH SKETCH AND SITE IMPACT TRACKING
BASE FLOW AS % CHANNEL WIDTH	□ 0-25% □ 50%-75% □ 25-50 % □ 75-100%	Simple planar sketch of survey reach. Track locations and IDs for all site impacts within the survey reach (OT, ER, IB,SC, UT, TR, MI) as well as any additional features deemed appropriate. Indicate direction of flow
DOMINANT SUBSTR Silt/clay (fine or Sand (gritty) Gravel (0.1-2.5	slick) ☐ Cobble (2.5 –10") ☐ Boulder (>10")	N
	Clear Turbid (suspended matter) aturally colored) Dopaque (milky) dyes)	START
AQUATIC PLANTS IN STREAM	Attached: ☐ none ☒ some ☐ lots Floating: ☒ none ☐ some ☐ lots	7 Trai
WILDLIFE IN OR AROUND STREAM	(Evidence of) ☐ Fish ☐ Beaver ☑ Deer ☐ Snails ② Other: € € € € €	Scroz (fostlandge
STREAM SHADING (water surface)	M Mostly shaded (≥75% coverage) ☐ Halfway (≥50%) ☐ Partially shaded (≥25%) ☐ Unshaded (< 25%)	//:((
CHANNEL DYNAMICS Unknown	□ Downcutting □ Bed scour ⋈ Widening □ Bank failure □ Headcutting □ Bank scour □ Aggrading □ Slope failure ⋈ Sed. deposition □ Channelized	
CHANNEL DIMENSIONS (FACING DOWNSTREAM)	Height: LT bank 3-4 (ft) RT bank 3-7 (ft) Width: Bottom 4-70 (ft) Top 75-20 (ft)	#428
R	REACH ACCESSIBILITY	
Good: Open area in public ownership, sufficient room to stockpile materials, easy stream channel access for heavy equipment using existing roads or trails.	Fair: Forested or developed area adjacent to stream. Access requires tree removal or impact to landscaped areas. Stockpile areas small or distant from stream. Difficult. Must cross wetland, steep slope, or sensitive areas to get to stream. Few areas to stockpile available and/or located a great distance from stream. Specialized heavy equipment required.	END Franklin Amen
	1 (3) 2 1	1000
	olem you see in survey reach)	

	Optimal	Suboptimal	Marginal	Poor	
iN-STREAM HABITAT (May modify criteria based on appropriate habitat regime)	Greater than 70% of substrate favorable for epifaunal colonization and fish cover; mix of snags, submerged logs, undercut banks, cobble or other stable habitat and at stage to allow full colonization potential (i.e., logs/snags that are not new fall and not transient).	40-70% mix of stable habitat; well- suited for full colonization potential; adequate habitat for maintenance of populations; presence of additional substrate in the form of newfall, but not yet prepared for colonization (may rate at high end of scale).	20-40% mix of stable habitat; habitat availability less than desirable; substrate frequently disturbed or removed.	Less than 20% stable habitat, lact of habitat is obvious; substrate unstable or lacking.	
	20 19 18 17 16	15 (4) 13 12 11	10 9 8 7 6	5 4 3 2 1 0	
VEGETATIVE PROTECTION (score each bank, determine sides by facing downstream)	More than 90% of the streambank surfaces and immediate riparian zone covered by native vegetation, including trees, understory shrubs, or nonwoody macrophytes; vegetative disruption through grazing or mowing minimal or not evident; almost all plants allowed to grow naturally.	70-90% of the streambank surfaces covered by native vegetation, but one class of plants is not well-represented; disruption evident but not affecting full plant growth potential to any great extent; more than one-half of the potential plant stubble height remaining.	50-70% of the streambank surfaces covered by vegetation; disruption obvious; patches of bare soil or closely cropped vegetation common; less than one-half of the potential plant stubble height remaining.	Less than 50% of the streambank surfaces covered by vegetation; disruption of streambank vegetation is very high; vegetation has been removed to 5 centimeters or less in average stubble height.	
	Left Bank (10) 9	8 7 6	5 4 3	2 1 0	
	Right Bank (0) 9	8 7 6	5 4 3	2 1 0	
BANK EROSION (facing downstream)	Banks stable; evidence of erosion or bank failure absent or minimal; little potential for future problems.	Grade and width stable; isolated areas of bank failure/erosion; likely caused by a pipe outfall, local scour, impaired riparian vegetation or adjacent use.	Past downcutting evident, active stream widening, banks actively eroding at a moderate rate; no threat to property or infrastructure	Active downcutting; tall banks on both sides of the stream eroding a a fast rate; erosion contributing significant amount of sediment to stream; obvious threat to property or infrastructure.	
	Left Bank 10 (9)	8 7 6	5 4 3	2 1 0	
	Right Bank 10 (9)	8 7 6	5 4 3	2 1 0	
FLOODPLAIN CONNECTION	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.	
	20 19 (18) 17 16	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0	
	OVER	ALL BUFFER AND FLOODPLAI	N CONDITION		
	Optimal	Suboptimal	Marginal	Poor	
VEGETATED Buffer Width	Width of buffer zone >50 feet; human activities (i.e., parking lots, roadbeds, clear-cuts, lawns, crops) have not impacted zone.	Width of buffer zone 25-50 feet; human activities have impacted zone only minimally.	Width of buffer zone 10-25 feet; human activities have impacted zone a great deal.	Width of buffer zone <10 feet: little or no riparian vegetation due to human activities.	
	Left Bank (10) 9	8 7 6	5 4 3	2 1 0	
	Right Bank (10) 9	8 7 6	5 4 3	2 1 0	
FLOODPLAIN VEGETATION	Predominant floodplain vegetation type is mature forest	Predominant floodplain vegetation type is young forest	Predominant floodplain vegetation type is shrub or old field	Predominant floodplain vegetation type is turf or crop land	
	20 19 18 17 (16)	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0	
FLOODPLAIN HABITAT	habitate audenna of atomaline/newded habitate as a different		Either all wetland or all non- wetland habitat, evidence of standing/ponded water Either all wetland or all no wetland habitat, no eviden standing/ponded water		
	20 19 (18) 17 16	15 14 13 12 11	10 9 8 7 6	5 4 3 2 1 0	
FLOODPLAIN ENCROACH- MENT	No evidence of floodplain encroachment in the form of fill material, land development, or manmade structures	Minor floodplain encroachment in the form of fill material, land development, or manmade structures, but not effecting floodplain function	Moderate floodplain encroachment in the form of filling, land development, or manmade structures, some effect on floodplain function	Significant floodplain encroachment (i.e. fill material, land development, or man-made structures). Significant effect on floodplain function	
	20 19 (18) 17 16				

Stream Crossing SC

FOR ROAD Circular		DISUBSHED: COLD SO						5/24/09		ESSED BY: KMB
TYPE: Road Crossing Railroad Crossing Manmade Dam Geological Formation Other:	A CONTRACTOR OF THE CONTRACTOR	hjeldy access				PHO	ото П	D: (Camera-Pi		
SHAPE:	SITE ID: (Co.	ndition-#) SC- 2/	LAT 40	050 14	LONG_	150	C7	127.7" L	MK	GPS (Unit ID)
SHAPE:	TYPE: KRO	ad Crossing Railroa	d Crossing	Manmade	Dam Beau	er Da	m [Geological For	mation [Other
ONLY Caracking/chipping/corrosion Downstream scour hole Gulvert spain/replacement Width: 25	FOR ROAD/ RAILROAD	SHAPE: Arch Bottomless Box Elliptical Circular		BARRELS: Single Double Triple	MATERIAL: Concrete Metal		ALIG	ONMENT: ow-aligned of flow-aligned	DIMENS	SIONS: (if variable, sketch, ameter:
Local stream repair Other:	ONLY	☐ Cracking/chipping/c	corrosion [☐ SI	at ight (2° – 5°)		Width: 25 (1
EXTENT OF PHYSICAL BLOCKAGE: Total	Dino Priva	ale direction		Local stream	repair Othe		pair/re	placement 🔲 l	Jpstream s	torage retrofit
Total Temporary Unknown North Temporary Unknown radial discharge at thibutary that would isolate a significant reach of stream, or partial blockage that may interfere with the migration of anadromous fish, no fish passage device present. NOTES/SKETCH: A structure such as a dam or road culvert on a 3rd order or greater stream blocking the usery head of a stream or a partial blockage that may interfere with the migration of anadromous fish. as waterfalls. NOTES/SKETCH: 5 4 3 2 11 NOTES/SETCH:	IS SC ACTIN				es Unk	nown				
Other: NOTES/SKETCH: S 4 3 2 1) DON'T CONCRETE SEAN		☐ Total ☐ ☐ Temporary ☐ ☐ ☐ Temporary ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	Partial Unknown Sc Vater Drop:	Nove and bottom (in)	road culvert on a greater stream bl upstream movem anadromous fish;	3rd ord ocking ent of no fish	m or der or the	A total fish blocka tributary that wou significant reach o or partial blockag interfere with the	ge on a ld isolate a of stream, e that may	A temporary barrier such as beaver dam or a blockage a the very head of a stream w very little viable fish habitat above it; natural barriers such
NOTES/SKETCH: NOTES/SKETCH: NOW A CONCRETE BEAN			rater Depart	()	7-12			100000000000000000000000000000000000000		
40tan	The state of the s	7			Card	1	BEA	nete An		- Spare
					Yollan	^				

Stream Crossing SC

WATERSHEI	D/SUBSHED: (old	sorry Brack		DATE: 8	124 109	Ass	ESSED BY: CAB
URVEY REA	ACHID: (SB-03"	TIME: 3:	38 AM/EM)	Рното I	D: (Camera-P		/# 31
SITE ID: (Co.	ndition-#) SC-02	LAT 40 . 50 "	10,5" LONG]	3027	13.4" I	MK	GPS (Unit ID)
TYPE: Ro	and Crossing D Pailron	Crossina D.Manan	1.D. □D	ь г	1800000	. 4	- W 6
FOR ROAD/ RAILROAD	SHAPE: #BARRELS: Single Double Triple Other:		MATERIAL: Concrete Metal Other:	ALIC	J Geological For GNMENT: low-aligned ot flow-aligned o not know		Other: Footbondgs SIONS: (if variable, sketch) ameter:(fi Height:(fi
CROSSINGS ONLY	CONDITION: (Evidence Cracking/chipping/c Sediment deposition Other (describe):	e of)	eam scour hole mbankment	⊠ FI	VERT SLOPE: lat light (2° – 5°) bvious (>5°)	Culvert l	ength:
POTENTIAL I	RESTORATION CANDII	DATE Fish barrier Local stream	removal Culver		eplacement [Upstream s	torage retrofit
IS SC ACTING	G AS GRADE CONTROI		Yes Unkno	own			
	EXTENT OF PHYSICA	TO THE TOTAL PROPERTY OF THE PARTY OF THE PA		BLO	OCKAGE SEVE	RITY: (circ	:le #)
If yes for fish barrier	☐ Temporary ☐ CAUSE:	Partial Unknown Vater Drop: (in) Vater Depth: (in)	A structure such as road culvert on a 3rd greater stream block upstream movemen anadromous fish; no passage device present a structure of the	d order or king the it of o fish	A total fish blocka tributary that wou significant reach or partial blockag interfere with the anadromous fish.	of stream, that may migration of	A temporary barrier such as beaver dam or a blockage at the very head of a stream wit very little viable fish habitat above it; natural barriers such as waterfalls.
NOTES/SKET	4 2 2 4 4 4 4 4		5		4 3		2 1
		Wood And And And And And And And And And An	Tream railroad t		abutine	ent s	upport
		Forte 1	08		REPOR	TED TO AIM	rhorities □ Yes 屋 N



WATERSHED/SU	BSHED: Cold Spring Br	ook	DATE: 4 1 2	1109	ASSESSED BY: FMB	
JURVEY REACH	ID: CB-03 TI	ME: 3: 27 AM/PM	Рното ID: (Can	nera-Pic #)	# 30	
SITE ID: (Condition	n#) TR- <u>D </u> LAT°	The second secon		_" LMK	GPS; (Unit ID)	
TYPE: Industrial Commercial Residential	MATERIAL: Plastic Paper Tires Construction Appliances Yard V Automotive Other:		SOURCE: Unknown Flooding Ullegal dump Local outfall	LOCATION: Stream Riparian Area Lt bank Rt bank	LAND OWNERSHIP: Public Unknown Private AMOUNT (# Pickup truck loads):	
POTENTIAL RES	TORATION CANDIDATE S	tream cleanup Strea	m adoption segment	Removal/pre		
If yes for trash or	EQUIPMENT NEEDED:	vn	DUMPSTER WITHIN 100 FT:			
debris removal	WHO CAN DO IT:	☑ Volunteers ☐ Local Gov ☐ Hazmat Team ☐ Other ☐ Yes ☐ No ☑ Unkn				
CLEAN-UP POTENTIAL: (Circle #)	A small amount of trash (i.e., less than two pickup truck loads) located inside a park with easy access	A large amount of trash, or with easy access. Trash m a long period of time but few days, possibly with a sr	nay have been dumped ove it could be cleaned up in	area, where acc	of trash or debris scattered over a large ess is very difficult. Or presence of drums hazardous materials	
(Circle #)	(5)	4	3	2	1	
NOTES: Pative	reach has bottle	15, [m/5, £1	various ofh	er smal	d traish	
				REPORTED	TO AUTHORITIES YES NO	

Reach Level Assessment RCH

SURVEY REACH		TRSHD/SUBSHD: Col	d Spring Bh	DATE: 8/2	109 ASSE	SSED BY: HW/KMB
	1E: 4 : 08 AM/PM	D LMK: SC-01	The second secon	3 :50 AM/PM	LMK:	GPS ID:
LAT40 .50 .	31.1 " LONG 3	13027 197"	LAT 40 0 50 1	9015 " LONG 7	13027 123	4" GPS
DESCRIPTION: 8	ginning of Ch	LAVI noidap-N	DESCRIPTION:			Map60
3,	Jun 1 Co	dregion have		our milde		
	ours Heavy rain	☐ Steady rain	PRESENT CONDITIONS	S ☐ Heavy rain	☐ Steady rain	☐ Intermittent
None	☐ Intermitten		Ø Clear	☐ Trace	☐ Overcast	☐ Partly cloudy
SURROUNDING LAN		al ☐ Commercial urse ☐ Park	☐ Urban/Residential ☐ Crop	Suburban/Res Pasture	Forested Other:	☐ Institutional
AVERAG	E CONDITIONS (che	eck applicable)	REACH	SKETCH AND SI	FE IMPACT TR	ACKING
BASE FLOW AS % CHANNEL WIDTH	Ø0-25% □25-50 %	□ 50%-75% □ 75-100%	within the survey re	of survey reach. Tra each (OT, ER, IB,SC, deemed appropriate	UT, TR, MI) as we	Ds for all site impacts ell as any additional
DOMINANT SUBSTI ☐ Silt/clay (fine or ☐ Sand (gritty) ☐ Gravel (0.1-2.	slick) \square C \square B	obble (2.5 –10") oulder (>10") ed rock	jeaures	a deemed appropriate.	STAPT	n of flow
	☑Clear □Turbi naturally colored) □ dyes)			K.	TROZ	-
AQUATIC PLANTS IN STREAM	Floating: Inon	ne M som e □ lots e Some □ lots		/		
WILDLIFE IN OR AROUND STREAM	(Evidence of) ☐ Fish ☐ Beav ☐ Snails ☐ Othe			-XX	CXX T	R-01
STREAM SHADING (water surface)	Mostly shaded	(≥75% coverage) %) d (≥25%)	Harbor Li			J
CHANNEL	■ Downcutting	Bed scour) /	
DYNAMICS	Widening	Bank failure			//	
2.771111111		Bank scour	00	/		
Unknown	☐ Aggrading ☐ Sed. depositio	☐ Slope failure Channelized	(0)	11	(
Law and	Height: LT bank	3 (ft)	12	((
CHANNEL DIMENSIONS	RT bank	3 (ft)		1		
(FACING	Width: Bottom	(11)		1.1		
DOWNSTREAM)	10.12.1	2 -	2	1.7		
	Top					
de la Section Committee	REACH ACCESSIBILI Fair: Forested or	Difficult. Must cross	1 1 1	1 1		
Good: Open area in public ownership,	developed area	wetland, steep slope, or			\	
sufficient room to	adjacent to stream.	sensitive areas to get to			1	
stockpile materials,	Access requires tree removal or impact to	stream. Few areas to stockpile available	11	1	1	
easy stream channel access for heavy	landscaped areas.	and/or located a great	11		1	
equipment using	Stockpile areas	distance from stream.				
existing roads or trails.	small or distant from stream.	Specialized heavy equipment required.	1 1 1 -			FOOTBEIDGE
	4 3 (2) 1	111	1.		10-106
NOTES: (biggest pro	blem you see in survey	reach)		EN	D	
				REPOR	TED TO AUTHOR	ITIES YES No

	Optimal	Suboptimal	Marginal	Poor
N-STREAM HABITAT (May modify criteria based on appropriate habitat regime)	Greater than 70% of substrate favorable for epifaunal colonization and fish cover; mix of snags, submerged logs, undercut banks, cobble or other stable habitat and at stage to allow full colonization potential (i.e., logs/snags that are not new fall and not transient).	40-70% mix of stable habitat; well- suited for full colonization potential; adequate habitat for maintenance of populations; presence of additional substrate in the form of newfall, but not yet prepared for colonization (may rate at high end of scale).	20-40% mix of stable habitat; habitat availability less than desirable; substrate frequently disturbed or removed.	Less than 20% stable habitat; lact of habitat is obvious; substrate unstable or lacking.
	20 19 18 17 16	15 14 (13) 12 11	10 9 8 7 6	5 4 3 2 1 0
VEGETATIVE PROTECTION (score each bank, determine sides by facing downstream)	More than 90% of the streambank surfaces and immediate riparian zone covered by native vegetation, including trees, understory shrubs, or nonwoody macrophytes; vegetative disruption through grazing or mowing minimal or not evident; almost all plants allowed to grow naturally.	70-90% of the streambank surfaces covered by native vegetation, but one class of plants is not well-represented; disruption evident but not affecting full plant growth potential to any great extent; more than one-half of the potential plant stubble height remaining.	50-70% of the streambank surfaces covered by vegetation; disruption obvious; patches of bare soil or closely cropped vegetation common; less than one-half of the potential plant stubble height remaining.	Less than 50% of the streambank surfaces covered by vegetation; disruption of streambank vegetation is very high; vegetation has been removed to 5 centimeters or less in average stubble height.
	Left Bank 10 9	8 7 6	5 4 3	2 1 0
	Right Bank 10 9	8 7 (6)	5 4 3	2 1 0
BANK EROSION (facing downstream)	Banks stable; evidence of erosion or bank failure absent or minimal; little potential for future problems. <5% of bank affected.	Grade and width stable; isolated areas of bank failure/erosion; likely caused by a pipe outfall, local scour, impaired riparian vegetation or adjacent use.	Past downcutting evident, active stream widening, banks actively eroding at a moderate rate; no threat to property or infrastructure	Active downcutting; tall banks on both sides of the stream eroding a a fast rate; erosion contributing significant amount of sediment to stream; obvious threat to property or infrastructure.
	Left Bank 10 9	8 7 6	(5) 4 3	2 1 0
	Right Bank 10 9	8 7 6	(s) 4 3	2 1 0
FLOODPLAIN CONNECTION	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.
	20 19 18 17 16	15 14 13 12 (11)	10 9 8 7 6	5 4 3 2 1 0
	OVER	ALL BUFFER AND FLOODPLA	IN CONDITION	
	Optimal	Suboptimal	Marginal	Poor
VEGETATED Buffer Width	Width of buffer zone >50 feet; human activities (i.e., parking lots, roadbeds, clear-cuts, lawns, crops) have not impacted zone.	Width of buffer zone 25-50 feet; human activities have impacted zone only minimally.	Width of buffer zone 10-25 feet; human activities have impacted zone a great deal.	Width of buffer zone <10 feet; little or no riparian vegetation due to human activities.
	Left Bank (10) 9	7 6	5 4 3	2 1 0
	Right Bank 10 9	8 7 6	(5) 4 3	2 1 0
FLOODPLAIN VEGETATION	Predominant floodplain vegetation type is mature forest	Predominant floodplain vegetation type is young forest	Predominant floodplain vegetation type is shrub or old field	Predominant floodplain vegetation type is turf or crop land
	20 19 18 17 16	15 14 13 (12) 11	10 9 8 7 6	5 4 3 2 1 0
FLOODPLAIN HABITAT	Even mix of wetland and non-wetland habitats, evidence of standing/ponded water	Even mix of wetland and non-wetland habitats, no evidence of standing/ponded water	Either all wetland or all non- wetland habitat, evidence of standing/ponded water	Either all wetland or all non- wetland habitat, no evidence of standing/ponded water
	20 19 18 17 16	15 14 13 12 11	(10) 9 8 7 6	5 4 3 2 1 0
FLOODPLAIN ENCROACH- MENT	No evidence of floodplain encroachment in the form of fill material, land development, or manmade structures	Minor floodplain encroachment in the form of fill material, land development, or manmade structures, but not effecting floodplain function	Moderate floodplain encroachment in the form of filling, land development, or manmade structures, some effect on floodplain function	Significant floodplain encroachment (i.e. fill material, land development, or man-made structures). Significant effect on floodplain function
	20 19 18 17 16	15 14 13 12 (11)	10 9 8 7 6	5 4 3 2 1 0

Stream Crossing

SC


WATERSHEI		pring [irle		DATE: 9	124109	Assi	ESSED BY: FMB
URVEY REA	ACH ID: (98-04	1 1	TIME: 01			D : (Camera-Pi	ic #)	1# 34
SITE ID: (Con	ndition-#) SC-01	LAT	40.50 .3	LONG	3027	· 19.7" L	MK	GPS (Unit ID)
TYPE: \square Ro	ad Crossing Railroa	d Cross	ing Manmade	Dam Reav	er Dam	Geological For	motion [7 Othor
FOR ROAD/ RAILROAD	SHAPE: #BAI Arch Bottomless Sin Box Elliptical Do Circular Tr		#BARRELS:	MATERIAL: Concrete Metal Other:	ALIC	GNMENT: low-aligned ot flow-aligned to not know	DIMENS Barrel di	SIONS: (if variable, sketc ameter: Height: 24
CROSSINGS ONLY	CONDITION: (Evidence Cracking/chipping/c Sediment depositio Other (describe):	corrosio	n Downstread	m scour hole	CUL F	VERT SLOPE: lat light (2° – 5°) bytious (>5°)	Culvert le	ength: 28 Width: 6
POTENTIAL I	RESTORATION CANDI	DATE	Fish barrier r			eplacement	Upstream s	storage retrofit
IS SC ACTIN	G AS GRADE CONTRO		□No □Y	es Unk	nown			
	EXTENT OF PHYSIC. ☐ Total	AL BLO Partial	CKAGE:		BL	OCKAGE SEVE	RITY: (circ	cle #)
If yes for fish barrier	☐ Temporary ☐ CAUSE:	Unkno Vater D	rop: <u>24</u> (in)	A structure such a road culvert on a greater stream blupstream movem anadromous fish; passage device p	3rd order or ocking the ent of no fish	A total fish block tributary that wot significant reach or partial blockag interfere with the anadromous fish	of stream, that may migration of	A temporary barrier such beaver dam or a blockage the very head of a stream very little viable fish habit above it; natural barriers s as waterfalls.
NOTES/SKET				5	1	4 3		(2) 1
	Crest Barrey of St.		Gabron W	all Jest vo	To have	ead cuttin		
		b	ļ			Repor	RTED TO AU	THORITIES YES




WATERSHED/SUI	BSHED: COLD SPYING	Bk	DATE: 8/7	14109 A	ASSESSED BY: CMB		
SURVEY REACH	D: CSB-04 G	IME: 3:54 AM/PM	Рното ID: (Са	mera-Pic #)	I# 32		
SITE ID: (Condition	1-#) TR-0 LAT 40	. 50 . 346" LONG	: 13-27.20.	3" LMK	GPS: (Unit ID)		
TYPE: Industrial Commercial	MATERIAL: Plastic Paper Tires Const	A CONTRACTOR OF THE PARTY OF TH	SOURCE: Unknown Flooding	LOCATION: Stream Riparian Area	LAND OWNERSHIP: Public Unknown Private		
Residential	Appliances Yard Automotive Other	1 2027	☐ Illegal dump ☐ Local outfall	Lt bank	AMOUNT (# Pickup truck loads):		
POTENTIAL REST		Stream cleanup Strea	nm adoption segment	Removal/prev	rention of dumping		
If yes for trash or	EQUIPMENT NEEDED:	DUMPSTER WITHIN 100 FT:					
debris removal	WHO CAN DO IT:	Volunteers Local C	ocal Gov Hazmat Team Other Yes No Unknown				
CLEAN-UP POTENTIAL: (Circle #)	A small amount of trash (i.e., less than two pickup truck loads) located inside a park with easy access		nay have been dumped o it could be cleaned up in	ver area, where acces	of trash or debris scattered over a large ss is very difficult. Or presence of drums azardous materials		
(Circle II)	(5)	4	3	2	1		
NOTES:	wire fence acro	road through	hough	ong; 45 f	t tall Probably previo		
		1			TO AUTHORITIES YES NO		



WATERSHED/SUI	BSHED: Cold Sprin	BL	DATE: 8/2	4109	ASSESSED BY: KAR	
JURVEY REACH	ID: (4B-04 T	IME: 4:02 AMPM	Рното ID: (Са	amera-Pic #)	/# 33	
SITE ID: (Condition	n#) TR-02 LAT 40	50, 33,5" LONG	373.27.19.	g LMK	GPS: (Unit ID)	
TYPE: Industrial Commercial Residential	MATERIAL: Plastic Paper Tires Const Appliances Yard Automotive Other	ruction	SOURCE: Unknown Flooding Ullegal dump Local outfall	LOCATION: Stream Riparian Are Lt bank	LAND OWNERSHIP: Public Unknown Private AMOUNT (# Pickup truck loads):	
POTENTIAL REST	TORATION CANDIDATE (am adoption segmen		vention of dumping	
If yes for trash or	EQUIPMENT NEEDED:	own	DUMPSTER WITHIN 100 FT:			
debris removal	WHO CAN DO IT: Volunteers Local Gov Hazmat Team Other Yes No Unknow					
CLEAN-UP POTENTIAL: (Circle #)	A small amount of trash (i.e., less than two pickup truck loads) located inside a park with easy access	A large amount of trash, o with easy access. Trash n a long period of time but few days, possibly with a s	nay have been dumped of it could be cleaned up it	over area, where acc	of trash or debris scattered over a large sess is very difficult. Or presence of drums hazardous materials	
(Circle II)	(5)	4	3	2	1	
NOTES: Traf	fic cone, planter,	plastic bags,	plastic co	ps/bottles	, alun (aus	
				REPORTED	TO AUTHORITIES YES NO	



SURVEY REACH START TIM	ID: CS6 OS WTRSHD/SUBSHD: Coll	END TIME:	DATE: 8/24/0	11010	MB
	I my me in the same and a second			LMK:	GPS ID:
LAT 10 50	Long 770 27 23 1		1.1" LONG 73°		
DESCRIPTION: 4	50 21 13 27 10,0	DESCRIPTION:	ABION WALE		Major
E CONTRACTOR A	Cup like				
	OURS Heavy rain Steady rain	PRESENT CONDITIONS		Steady rain Inter	mittent
None	☐ Intermittent ☐ Trace	Clear			ly cloudy
SURROUNDING LAN	DUSE: ☐ Industrial ☐ Commercial ☐ Golf course ☐ Park	☐ Urban/Residential 1 ☐ Crop			tutional
AVERAGI	E CONDITIONS (check applicable)	REACH S	SKETCH AND SITE IN	MPACT TRACKING	G
BASE FLOW AS % CHANNEL WIDTH	□ 0-25% □ 50%-75% □ 75-100%	within the survey rea	of survey reach. Track loo sch (OT, ER, IB,SC, UT, I deemed appropriate. Indi	TR, MI) as well as any	site impacts additional
DOMINANT SUBSTR ☐ Silt/clay (fine or ☐ Sand (gritty) ☑ Gravel (0.1-2	slick)	jediures d	ecemea appropriate. Inal	M 1	
	DClear Turbid (suspended matter) naturally colored) Dpaque (milky) dyes)	15	60	A h	ox Augus
AQUATIC PLANTS IN STREAM	Attached: ⊠none ☐ some ☐ lots Floating: ☑ none ☐ some ☐ lots	7 10			Visible
WILDLIFE IN OR AROUND STREAM	(Evidence of) ☐ Fish ☐ Beaver ☐ Deer ☐ Snails ☐ Other: (Accord		9		C 14
STREAM SHADING (water surface)	☐ Mostly shaded (≥75% coverage) ☐ Halfway (≥50%) ☐ Partially shaded (≥25%) ☐ Unshaded (< 25%)		3	mod	Lanel
CHANNEL DYNAMICS Unknown	Downcutting Widening Headcutting Aggrading Sed. deposition Bed scour Bank failure Slope failure Channelized		e ig	8	}
CHANNEL DIMENSIONS (FACING DOWNSTREAM)	Height: LT bank	2	5		
	REACH ACCESSIBILITY	15/			
The second of	Fair: Forested or Difficult. Must cross			1	
Good: Open area in public ownership, sufficient room to stockpile materials, easy stream channel access for heavy equipment using existing roads or trails.	developed area adjacent to stream. Access requires tree removal or impact to landscaped areas. Stockpile areas small or distant from stream. Wetland, steep slope, or sensitive areas to get to stockpile available and/or located a great distance from stream. Specialized heavy equipment required.	1	A COLUMN	50-01	
S S	4 (3) 2 1		(CSH-04)	30-01	
NOTES: (biggest pro	blem you seelin survey reach)				
			REPORTED	TO AUTHORITIES [YES NO



B

	Optimal	Suboptimal	Marginal	Poor
N-STREAM HABITAT (May modify criteria based on appropriate habitat regime)	Greater than 70% of substrate favorable for epifaunal colonization and fish cover; mix of snags, submerged logs, undercut banks, cobble or other stable habitat and at stage to allow full colonization potential (i.e., logs/snags that are not new fall and not transient).	40-70% mix of stable habitat; well- suited for full colonization potential; adequate habitat for maintenance of populations; presence of additional substrate in the form of newfall, but not yet prepared for colonization (may rate at high end of scale).	20-40% mix of stable habitat; habitat availability less than desirable; substrate frequently disturbed or removed.	Less than 20% stable habitat; lack of habitat is obvious; substrate unstable or lacking.
	20 19 18 17 16	15 14 13 12 11	10 9 (8) 7 6	5 4 3 2 1 0
VEGETATIVE PROTECTION (score each bank, determine sides by facing downstream)	More than 90% of the streambank surfaces and immediate riparian zone covered by native vegetation, including trees, understory shrubs, or nonwoody macrophytes; vegetative disruption through grazing or mowing minimal or not evident; almost all plants allowed to grow naturally.	70-90% of the streambank surfaces covered by native vegetation, but one class of plants is not well-represented; disruption evident but not affecting full plant growth potential to any great extent; more than one-half of the potential plant stubble height remaining.	50-70% of the streambank surfaces covered by vegetation; disruption obvious; patches of bare soil or closely cropped vegetation common; less than one-half of the potential plant stubble height remaining.	Less than 50% of the streambank surfaces covered by vegetation; disruption of streambank vegetation is very high; vegetation has been removed to 5 centimeters or less in average stubble height.
	Left Bank 10 9	8 7 6	5 (4) 3	2 1 0
	Right Bank 10 9	8 7 6	5 (4) 3	2 1 0
BANK EROSION (facing downstream)	Banks stable; evidence of erosion or bank failure absent or minimal; little potential for future problems. <5% of bank affected.	Grade and width stable; isolated areas of bank failure/erosion; likely caused by a pipe outfall, local scour, impaired riparian vegetation or adjacent use.	Past downcutting evident, active stream widening, banks actively eroding at a moderate rate; no threat to property or infrastructure	Active downcutting; tall banks on both sides of the stream eroding a a fast rate; erosion contributing significant amount of sediment to stream; obvious threat to property or infrastructure.
	Left Bank 10 9	8 6 6	5 4 3	2 1 0
	Right Bank 10 9	8 (7) 6	5 4 3	2 1 0
FLOODPLAIN CONNECTION	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.
	20 19 18 17 16	15 14 13 12 11	10 9 (8) 7 6	5 4 3 2 1 0
	OVER	ALL BUFFER AND FLOODPLAI	IN CONDITION	
	Optimal	Suboptimal	Marginal	Poor
VEGETATED BUFFER WIDTH	Width of buffer zone >50 feet; human activities (i.e., parking lots, roadbeds, clear-cuts, lawns, crops) have not impacted zone.	Width of buffer zone 25-50 feet; human activities have impacted zone only minimally.	Width of buffer zone 10-25 feet; human activities have impacted zone a great deal.	Width of buffer zone <10 feet; little or no riparian vegetation due to human activities.
	Left Bank 10 9	8 7 6	(B) 4 (3)	2 1 0
	Right Bank 10 9	8 7 6	3 4 3	1 0
FLOODPLAIN VEGETATION	Predominant floodplain vegetation type is mature forest	Predominant floodplain vegetation type is young forest	Predominant floodplain vegetation type is shrub or old field	Predominant floodplain vegetation type is turf or crop land
	20 19 18 17 16	15 14 13 12 11	10 9 8 (1) (6)	5 4 3 2 1 0
FLOODPLAIN HABITAT	habitate avidance of standing/sended bakitete		Either all wetland or all non- wetland habitat, evidence of standing/ponded water	Either all wetland or all non- wetland habitat, no evidence of standing/ponded water
	20 19 18 17 16	15 14 13 12 11	10 9 8 7 (6)	5 4 3 2 1 0
FLOODPLAIN ENCROACH- MENT	No evidence of floodplain encroachment in the form of fill material, land development, or manmade structures	Minor floodplain encroachment in the form of fill material, land development, or manmade structures, but not effecting floodplain function	Moderate floodplain encroachment in the form of filling, land development, or manmade structures, some effect on floodplain function	Significant floodplain encroachment (i.e. fill material, land development, or man-made structures). Significant effect on floodplain function
	20 19 18 17 16			TO THE TOTAL PROPERTY OF THE PARTY OF THE PA

Channel Modification

CM

		4117	*			
WATERSHEI		Cold Spr		DATE: 8/2		ASSESSED BY: KMB
SURVEY REA		33-05	TIME: 4:22 AM/PM		: (Camera-Pic #)	# 3.6
SITE ID: (Co.	ndition-#)			3.27.19.7	LMK	GPS: (Unit ID)
CM0 /		END LAT 9	0 . 10 . 242 Long 7	30 27:19.2	LMK	
TYPE: C	annelization	Bank armoring Ban	ng concrete channel 1	Floodplain encroach	nent X Other:	hannel armoring
MATERIAL:		Does channel	have perennial flow?	X Yes □ No	DIMENSIONS:	and a seled
Concrete		Is there evider	ace of sediment deposition?	☑ Yes ☐ No	Height	(ft)
☐ Rip Rap Metal	☐ Earthen		growing in channel?	☐ Yes ☒ No	Bottom Width Top Width:	(ft)
Other:			nected to floodplain?	☑ Yes ☐ No	Length:	(ft)
	7					
BASE FLOW Depth of flow		(in)		ADJACENT STR	EAM CORRIDOR	
are for a state of a				Available width	LT	(ft) RT(ft)
	Defined low flow channel? ✓ Yes No			Utilities Present	?	Fill in floodplain?
% of channel bottom <u>90</u> %		☐ Yes ☐ No		□Yes □ No		
	RESTORATI	ON CANDIDATE	Structural repair Ba	ase flow channel crea		nannel design
no no			☐ De-channelization ☐ Fi	sh barrier removal	☑ Bioengine	eering
CHANNEL- IZATION SEVERITY:	channel whe	on of concrete stream (re water is very shallow o natural sediments pre	v (<1" A moderate length (> 200')	natural stream channel.	depth, a natural	nel less than 100 ft with good water sediment bottom, and size and the unchannelized stream reaches y impacted area.
(Circle #)		5	4 3		(2)	1
8	M-02 otherste	7 (- CM-01 -		Grillion	
			Wire Grain		Sunsteam	

Channel Modification

CM

				4		
WATERSHED	/SUBSHED;	Cold Spring	nook		4109	ASSESSED BY: KMB
SURVEY REA	CH ID: C		IME: 4:23 AM/PM	Рното І	D: (Camera-Pic#)	/# 3 5
SITE ID: (Cor	idition-#)	START LAT 40 .5	0:29,2 LONG 7	302719.7	LMK	GPS: (Unit ID)
CM-O		END LAT 40 ° \$	6 17 'D LONG T	3.027.18.11	LMK	
TYPE: Ch	annelization	☐ Bank armoring 🔯	concrete channel	loodplain encroach	ment Other:	
MATERIAL:		Does channel have p	erennial flow?	☑ Yes ☐ No	DIMENSIONS:	
☐ Concrete ☐ Gabion ☐ Rip Rap ☐ Earthen ☐ Metal		Is there evidence of	sediment deposition?	Yes No	Height Bottom Width	(ft)
		Is vegetation growin	g in channel?	☐ Yes ☑ No	Top Width:	12 (ft) 12 (ft)
Other:		Is channel connected	l to floodplain?	☐ Yes 🛛 No	Length:	unk-veryb
% of channel	bottom	ON CANDIDATE S	Structural repair		eation Natural c	Hill in Hoodplain? ☐Yes ☐ No Channel design ☐ Can't tell
CHANNEL-	channel whe	n of concrete stream (>500') re water is very shallow (<1"	A moderate length (> 200') beginning to function as a n	,but channel stabilized a	depth, a natura	annel less than 100 ft with good wate al sediment bottom, and size and
SEVERITY: (Circle #)	the channel.	natural sediments present in	Vegetated bars may have for			o the unchannelized stream reaches ow impacted area.
NOTES:		(5)	4 3		2	1
/	Æ					

Channel Modification

CM

FILE A COLUMN		~				
WATERSHED	-			DATE: 8/	24109	ASSESSED BY: LAG
BURVEY REA	CH ID:	13-05	TIME: 4: 45 AM/RM	Рното I	D: (Camera-Pic #)	/# 40
SITE ID: (Con	dition-#)	START LAT 40°		3027 1910	LMK	GPS: (Unit ID)
TYPE: Ch	annelization	☑ Bank armoring	☐ concrete channel ☐ F	loodplain encroach	nment Other:	
MATERIAL:	2	Does channel hav	e perennial flow?	Yes No	DIMENSIONS:	
☐ Concrete ¶☐ Rip Rap [☑ Gabion ☐ Earthen	Is there evidence	of sediment deposition?	☐ Yes 🖾 No	Height Bottom Width	
☐ Metal	_ carmen	Is vegetation grov	ving in channel?	¥Yes □ No	Top Width:	(ft)
Other: Cha	innel wire	Is channel connec	ted to floodplain?	Yes No	Length:	> 500 (ft)
% of channel	low channe		☐ Structural repair ☐ Ba☐ De-channelization ☐ Fis	Available widt Utilities Preser Yes No	nt?	(ft) RT(ft) Fill in floodplain? □Yes □ No channel design □ Can't tell
CHANNEL- IZATION SEVERITY: (Circle #)	channel when	n of concrete stream (>500 re water is very shallow (<1 natural sediments present	A moderate length (> 200'), beginning to function as a n Vegetated bars may have fo	but channel stabilized a	An earthen cha depth, a natura shape similar t	annel less than 100 ft with good water al sediment bottom, and size and to the unchannelized stream reaches ow impacted area.
NOTES:		(5)	Front View 3		2	P
V. 33 HW			2 Fra	fr Jabia	n walls	


Storm Water Outfalls **OT**

Closed pipe Cype: Closed pipe Closed pipe Channel Channel Companies of the pipe Compa	PVC/Plastic Other: Other: Concrete E Other:	SHAPE Metal	Single cular Double ptical Triple er: pezoid Dep abolic Wide er: IE DENSITY: ne mal bited essive er:	DIMENSIONS: Diameter:	Fully NOT APPLICABLE ROWTH: None nge Green No pool Colors Goil Floatables
Closed pipe Closed pipe Open channel ODOR: No Gas Sewage Rancid/Sou Sulfide Other:	MATERIAL: Concrete PVC/Plastic Other: Other: Concrete E Other: Other: DEPOSITS/STAIN None Oily Flow Line Paint Other: Other: Slight Clouding Sewage (toilet plastic bags) D	SHAPE Metal	C: Single cular Double ptical Triple er: Dezoid Department Wide er: DEDENSITY: Desoid Department Wide er: Desoid Department Wide er: Desoid Department Wide er: Desoid Department Wide er:	DIMENSIONS: Diameter: (in) Oth: (in) Oth (Top): (in) (Bottom): (in) PIPE BENTHIC GR Dother: POOL QUALITY: Good Dodors Suds Algae Other:	SUBMERGED: No Partially Fully NOT APPLICABLE ROWTH: None nge Green No pool Colors Oil Floatables
Closed pipe Open channel ODOR: No Gas Sewage Rancid/Sou Sulfide Other: Cl : No Grash (paper/	Concrete PVC/Plastic Other: Concrete E Other: Concrete E Other: DEPOSITS/STAIN None Oily Flow Line Paint Other: Clear Brown Cone Slight Clouding One Sewage (toilet /plastic bags)	Metal	cular Double ptical Triple er: pezoid Dep abolic Wic er: " IE DENSITY: ne mal bited essive er:	Diameter: (in) oth: (in) oth (Top): (in) (Bottom): (in) PIPE BENTHIC GR Brown Oran Other: POOL QUALITY: Good Odors Suds Algae Other:	No Partially Fully NOT APPACABLE SOWTH: None nge Green No pool Colors Gil Floatables
Channel DOOR: NO Gas Sewage Rancid/Sou Sulfide Other: Cl : No Grash (paper/	Other: DEPOSITS/STAIN None Oily Flow Line Paint Other: Clear Brown Clone Slight Cloudin Ione Sewage (toilet //plastic bags)	□ Para □ Oth IS: VEGG □ Nor □ Nor □ Inhi □ Exc □ Oth Grey □ Yello ness □ Cloud	abolic Wider: BE DENSITY: Be mal bited essive er:	Ith (Top):(in) (Bottom):(in) PIPE BENTHIC GR Brown	ROWTH: None Inge Green No pool Colors Oil Floatables
Gas Sewage Rancid/Sou Sulfide Other:	None Oily Flow Line Paint Other: Clear Brown Clear Slight Clouding Sewage (toilet Plastic bags) Discontinuous Discon	Nor Nor Inhi Exc Oth	mal bited essive er:	☐ Brown ☐ Oran ☐ Other: POOL QUALITY: ☐ Good ☐ Odors ☐ Suds ☐ Algae ☐ Other:	nge ☐ Green ☑ No pool ☐ Colors ☐ Oi ☐ Floatables
Sulfide Other:	Paint Other: Clear Brown Cone Slight Clouding Cone Sewage (toilet /plastic bags)	Grey Yello	essive er: w Green C	☐ Good ☐ Odors ☐ Suds ☐ Algae ☐ Other:	□Colors □Oi □ Floatables
: No	one Slight Cloudin	iess 🔲 Cloud		Drange ☐ Red ☐ (
egular Maint	itenance B	Dumping (bulk) Sank Erosion	Petroleum (o Excessive So Other:		Other:
rom outfall: _	Land	rofit Oth of existing veget Use description:		Local stream repair	outfall stabilization
mell. The amount	distinct color and/or a nt of discharge is significant t of normal flow in receiving ars to be having a	discharge has a co discharge is very si	ow mostly clear and odor lor and/or odor, the amou mall compared to the stre t appears to be minor / lo	int of am's base discharge;	es not have dry weather staining; or appearance any erosion problems.
, 5		4	3	2	(D)
Charmon Charmon	British Cylind	C.A.	VICET OPEN C	PORTED TO AUTHORI	TIES; 🗌 YES 🔲 N
(Clarkon Clarkon	Chrospant Brite	Brit.	Brite (overt RE)	Brut DRY and

WATERSHEI		my Brook		DATE:	124 109	Assi	ESSED BY:	
URVEY REA		TIME: 4	: 54AM/PM)		D: (Camera-Pi	c #)	/#	39
SITE ID: (Co	ndition-#) SCD	LAT 40° 50	173.8" LONG	73° L7	175" L	MK	GPS	(Unit ID)
TVPE MP	ad Crossing Railroad	Crossing Manual	and Danie II Bar	D [10 1 1 10		101	
FOR ROAD/	AILROAD Other: CROSSINGS CONDITION: (Evidence of)		S: MATERIAI Concrete Metal Other:	ALIC	Dam Geological Form ALIGNMENT: Flow-aligned Not flow-aligned Do not know		DIMENSIONS: (if variable, ski Barrel diameter: 12 Height: 3	
CROSSINGS ONLY Cracking/chipping/corrosion Sediment deposition Other (describe):		orrosion Downs	Other: Downstream scour hole Failing embankment		CULVERT SLOPE: Flat Slight (2° - 5°) Obvious (>5°)		Culvert length: 25 Width: Roadway elevation: 8	
no	RESTORATION CANDID	Local stre	ier removal 🔲 Cu eam repair 🔲 Ot		eplacement 🔲 t	Jpstream s	torage retro	fit
IS SC ACTIN	G AS GRADE CONTROL		Yes Un	known				
	EXTENT OF PHYSICA			BLO	OCKAGE SEVER	RITY: (circ	:le #)	
Temporary Unknown If yes for fish barrier CAUSE: Drop too high Water Drop: Flow too shallow Water Depth:		Unknown (ater Drop:(i	7	a 3rd order or blocking the ment of h; no fish	A total fish blockage on a tributary that would isolate a significant reach of stream, or partial blockage that may interfere with the migration of anadromous fish.		the very head of a stream with very little viable fish habitat f above it; natural barriers such as waterfalls.	
NOTES/SKET	Other:			5	4 3		2	1
		of Stav	115	ASION				
					1	1 21	>	
					REPOR	TED TO AU	THORITIES	YES N

	ACH TD. / 98-	old Sprin	g brook		DATE: 8	124109	ASS	ESSED BY:	KMB
		051	TIME: 5:1		Рното I	D: (Camera-Pi			41-42
-	ondition-#) SC-0	LAT	40.50 1	LONG	3027	16.6" L	MK	GPS	(Unit ID)
VPE: IM R	oad Crossing D	Pailroad Cros	sing [] Mananada	D	ъ г	I a		124	
FOR ROAD/	SHAPE:		# BARRELS: Single Double Triple	Dam		ONMENT: ow-aligned ot flow-aligned		SIONS: (if ve	ariable, sketch) [7(f
CROSSINGS ONLY					☐ FI	vert slope: at ight (2° – 5°) ovious (>5°)	Culvert length: 25 (f Width: (f		
∮no	RESTORATION C	12. 1X.	☐ Fish barrier r	repair Othe		placement 🔲 I	Jpstream s	torage retro	fit
SC ACTIN	G AS GRADE COL EXTENT OF PE		No □Y	es Unk	10 200	OCKAGE SEVER			
yes for sh barrier	☐ Total ☐ Temporary CAUSE: ☐ Drop too high ☐ Flow too shall	Partial Unkno		A structure such a road culvert on a s greater stream blo upstream moveme anadromous fish; passage device pr	s a dam or Brd order or ocking the ent of no fish	A total fish blocka tributary that wou significant reach o or partial blockage interfere with the anadromous fish.	ge on a ld isolate a of stream, e that may	A temporary beaver dam the very hea very little via	or a blockage at or a blockage at ad of a stream wit able fish habitat tural barriers such
OTES/SKET	Other:			-5		4 3		2	-1
	ame as drivelyay Address: t	0004511V4 \$ 523	y upstream Harbor Rd	co€ 5C-0	(

	DISUBSHED: COL Spr	ny Brook	4		DATE: S	124 109	ASSI	ESSED BY: YMR	
URVEY REA	ACH ID: (3B-05)		IME: 5:4			D: (Camera-Pi		I# NONE	
SITE ID: (Con	ndition-#) SC-03	LAT 4	· 50 · [18" LONG	13027		MK	GPS (Unit ID)	
Tripp, 🗆 -	10 1 -		-OP-C	The state of the s	roodhun	-		ain side	
TYPE: Ro						Geological For		Other:	
FOR ROAD/ RAILROAD	SHAPE: Arch Botton Box Ellipt Circular Other:	ottomless Single Cor Illiptical Double Me Triple Other:		MATERIAL: Concrete Metal Other:	Ď FI □ N	ALIGNMENT: Flow-aligned Not flow-aligned Do not know		SIONS: (if variable, sketch) ameter: 36 (fi Height: (fi	
CROSSINGS ONLY					☐ FI	VERT SLOPE: at ight (2° – 5°) bytious (>5°)	Culvert length: 300 (ft) Width: (ft) Roadway elevation: (ft)		
no no	RESTORATION CANDII		Fish barrier re Local stream			eplacement 🔲 I	Upstream s	storage retrofit	
IS SC ACTING	G AS GRADE CONTROI		No XY	es Unk	nown				
	EXTENT OF PHYSICA		AGE:		BLC	CKAGE SEVER	UTY: (circ	cle #)	
☐ Total ☐ Partial ☐ Temporary ☐ Unknow If yes for fish barrier ☐ CAUSE: ☐ Drop too high Water Dr ☐ Flow too shallow Water De ☐ Other:					3rd order or ocking the ent of no fish	order or tributary that would isolate a significant reach of stream, or partial blockage that may interfere with the migration of		A temporary barrier such as a beaver dam or a blockage at the very head of a stream with very little viable fish habitat above it, natural barriers such as waterfalls.	
NOTES/SKET	сн:				Orobably	no arrad	workers f	stish low)	
	Road avorsing	g from	N 0 W	toulpe	Wood	ovry/Pul			
	woodbury	PARKLI	No H	+ /	ref.	ted not	lo-d	vp of SB-06	
						REPORT	TED TO AUT	THORITIES YES NO	



SURVEY REACH	ID:	WTRSHD/SUBSHD:	d Spring 8h	DATE:8 /2"	109 ASSESSED BY: JHW/KMB
START TIM	1E: 4 : 08 AN	1/PM LMK:	END TIME: 5	:45 AM(PM)	LMK: 5C-03CSR GPS ID:
LAT TO SU	31 LON	16 13 0 27 197 19	LAT 40 0 50 12	L " Long 7	3° 27 1/00 " 05 GPS
DESCRIPTION: 610		a (heid waters)	DESCRIPTION: Di	ON CHAP #	MayGo
400 50 13	21/ 73	27 3 J	10	LE CALL &	
RAIN IN LAST 24 HO	OURS Heavy	rain	PRESENT CONDITIONS	☐ Heavy rain	☐ Steady rain ☐ Intermittent
None	☐ Intermi		Clear	☐ Trace	☐ Overcast ☐ Partly cloudy
SURROUNDING LAN		strial Commercial Course Park	*Urban/Residential		☐ Forested ☐ Institutional ☐ Other:
AVERAGI	E CONDITIONS	(check applicable)	REACH S	KETCH AND SIT	TE IMPACT TRACKING
BASE FLOW AS % CHANNEL WIDTH	□25-50 %	□ 50%-75% □ 75-100%	within the survey read	ch (OT, ER, IB,SC,	ck locations and IDs for all site impacts UT, TR, MI) as well as any additional Indicate direction of flow
DOMINANT SUBSTR ☐ Silt/clay (fine or ☑ Sand (gritty) ☐ Gravel (0.1-2.5	slick)	□ Cobble (2.5 −10") □ Boulder (>10") □ Bed rock		еетей арргоргане.	START
	naturally colored)	urbid (suspended matter) Opaque (milky)			
AQUATIC PLANTS IN STREAM	6	none □ some □ lots		/ we	Hand
WILDLIFE IN OR AROUND STREAM	(Evidence of) □ Fish □ E □ Snails □ C	Beaver □ Deer			
STREAM SHADING (water surface)	☐ Mostly shad ☐ Halfway (≥ ☐ Partially shaded (aded (≥25%)	/		
CHANNEL	Downcutti	ng Bed scour		(
DYNAMICS Unknown	Widening Headcuttin Aggrading	Bank failure Bank scour Slope failure	\		
	Sed. depos				
CHANNEL	Height: LT ba	ink3(ft)		/ /	
DIMENSIONS	RT ba	ank 4 (ft)		1 1	2
(FACING	Width: Botto	m 7 (ft)	1		-03 (CSB 05) dual squark pipe cmp
DOWNSTREAM)	Тор	18 (ft)	100	1 50	-03(
Ī	REACH ACCESSII		1 201	K	dual squash
Good: Open area in	Fair: Forested or	Difficult. Must cross	12/12/6	TENIN	Pint IMP
public ownership,	developed area adjacent to stream	wetland, steep slope, or	16	CHO	The Court
sufficient room to stockpile materials,	Access requires to			/	7
easy stream channel	removal or impact			1	136-1
access for heavy	landscaped areas. Stockpile areas	and/or located a great distance from stream.	\	1	12/
equipment using existing roads or trails.	small or distant fro	m Specialized heavy		1 1	
	stream.	equipment required,		1 1	
NOTES: (biggest prob		vev reach)			
1-00	and the second				
				REPOR	TED TO AUTHORITIES YES NO

CSB-06

	Optimal	Suboptimal	Marginal	Poor		
N-STREAM HABITAT (May modify criteria based on appropriate habitat regime)	Greater than 70% of substrate favorable for epifaunal colonization and fish cover; mix of snags, submerged logs, undercut banks, cobble or other stable habitat and at stage to allow full colonization potential (i.e., logs/snags that are not new fall and not transient).	40-70% mix of stable habitat; well- suited for full colonization potential; adequate habitat for maintenance of populations; presence of additional substrate in the form of newfall, but not yet prepared for colonization (may rate at high end of scale).	20-40% mix of stable habitat; habitat availability less than desirable; substrate frequently disturbed or removed.	Less than 20% stable habitat; lack of habitat is obvious; substrate unstable or lacking.		
	20 19 18 17 16	15 14 13 12 11	(10) 9 8 7 6	5 4 3 2 1 0		
VEGETATIVE PROTECTION (score each bank, determine sides by facing downstream)	More than 90% of the streambank surfaces and immediate riparian zone covered by native vegetation, including trees, understory shrubs, or nonwoody macrophytes; vegetative disruption through grazing or mowing minimal or not evident; almost all plants allowed to grow naturally.	70-90% of the streambank surfaces covered by native vegetation, but one class of plants is not well-represented; disruption evident but not affecting full plant growth potential to any great extent; more than one-half of the potential plant stubble height remaining.	50-70% of the streambank surfaces covered by vegetation; disruption obvious; patches of bare soil or closely cropped vegetation common; less than one-half of the potential plant stubble height remaining.	Less than 50% of the streambank surfaces covered by vegetation; disruption of streambank vegetation is very high; vegetation has been removed to 5 centimeters or less in average stubble height.		
	Left Bank 10 9	8 7 (6)	5 4 3	2 1 0		
	Right Bank 10 9	8 7 (6)	5 4 3	2 1 0		
BANK EROSION (facing downstream) Banks stable; evidence of erosion or bank failure absent or minimal; little potential for future problems.		Banks stable; evidence of erosion or bank failure absent or minimal; little potential for future problems.		Active downcutting; tall banks on both sides of the stream eroding a a fast rate; erosion contributing significant amount of sediment to stream; obvious threat to property or infrastructure.		
	Left Bank 10 9	8 7 (6)	5 4 3	2 1 0		
	Right Bank 10 9	8 7 6	5 4 3	2 1 0		
FLOODPLAIN CONNECTION High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.		High flows (greater than bankfull) able to enter floodplain. Stream not deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.	High flows (greater than bankfull) not able to enter floodplain. Stream deeply entrenched.		
	20 19 18 17 16	15 14 13 12 11 ALL BUFFER AND FLOODPLAI	10 9 (8) 7 6	5 4 3 2 1 0		
	Optimal	Suboptimal	Marginal	Poor		
VEGETATED BUFFER WIDTH	Width of buffer zone >50 feet; human activities (i.e., parking lots, roadbeds, clear-cuts, lawns, crops) have not impacted zone.	Width of buffer zone 25-50 feet; human activities have impacted zone only minimally.	Width of buffer zone 10-25 feet; human activities have impacted zone a great deal.	Width of buffer zone <10 feet: little or no riparian vegetation due to human activities.		
	Left Bank 10 9	8 7 (6)	5 4 3	2 1 0		
	Right Bank 10 9	8 7 6	5 (4) 3	2 1 0		
FLOODPLAIN VEGETATION	Predominant floodplain vegetation type is mature forest	Predominant floodplain vegetation type is young forest	Predominant floodplain vegetation type is shrub or old field	Predominant floodplain vegetation type is turf or crop land		
	20 19 18 17 16	15 14 (13)12 11	10 9 8 7 6	5 4 3 2 1 0		
FLOODPLAIN HABITAT	Even mix of wetland and non-wetland habitats, evidence of standing/ponded water	Even mix of wetland and non-wetland habitats, no evidence of standing/ponded water	Either all wetland or all non- wetland habitat, evidence of standing/ponded water	Either all wetland or all non- wetland habitat, no evidence of standing/ponded water		
	20 19 18 17 16	15 14 13 12 11	(10) 9 8 7 6	5 4 3 2 1 0		
FLOODPLAIN ENCROACH- MENT	No evidence of floodplain encroachment in the form of fill material, land development, or manmade structures	Minor floodplain encroachment in the form of fill material, land development, or manmade structures, but not effecting floodplain function	Moderate floodplain encroachment in the form of filling, land development, or manmade structures, some effect on floodplain function	Significant floodplain encroachment (i.e. fill material, land development, or man-made structures). Significant effect on floodplain function		
	20 19 18 17 16	15 14 13 12 11	(10) 9 8 7 6	5 4 3 2 1 0		

Sub Total In-stream: 47 /80

+ Buffer/Floodplain:

4 / /80

Total Survey Reach 85 /160



(By Camera)

STREAM ASSESSMENTS

Project: OB CSH

Group: JHW KMB

Camera: Carrion A580

This field sheet is to be completed AS photos are taken in the field. The intent is to force us to organize pictures taken on a camera basis. Fill out one sheet per camera (add sheets as needed). Only fill in Date/Reach/Location ID when you start in a new spatial or temporal location.

Date	Stream/ Reach	Location ID	Photo #	Description
8/24/09	CSB-01	SC-01	100-	spillmay (W/s)
		SC-01	100-	scor lale (DIS)
		SC-02	003	2° spillway (uls) + 1° spillway (back)
		I3-01	004	Stream reach (D/S) + IB-01
		OT-01	005	0T-01
		0T-02/03	006	0t - 02/03 = Z × 6" drain pipes
		07-04	7007	OT-04 = 12" day pipe from hatchery
		SC-03	008	DIS Left I dual box culvert under
		Sc-03	009	DIS Left 7 dual box culvert under DIS Right SWY-ZSA Bridge # 0183-0
		Sc-03	0(0	uls Right 7 Ibid
		52-03	Ou	uss Left)
		67-05	012	us look @ 0T-05
		OT-05	013	DIS From OT-US Iroha CSH
		M	014 to	Panoramic of CSH
7	1	07-06	017	US (00 L @ 0T-06

OT-06 018 DIS 10012 From UT-06 (BACK)

(By Camera)

Project: CSH OBH

Group: JHW/KMB

Camera: Canon A580

This field sheet is to be completed AS photos are taken in the field. The intent is to force us to organize pictures taken on a camera basis. Fill out one sheet per camera (add sheets as needed). Only fill in Date/Reach/Location ID when you start in a new spatial or temporal location.

Date	Stream/ Reach	Location ID	Photo #	Description
8/24/09	CSB-02		100-	U/S and & reach
			020	Dts end of reach toward St John's Pond
		50-01	021	U/S start of reach @ Sc-01
			022	Dls from start of reach
			023	uls mid-reach
			024	DIS mid-reach
	4		025	Typical iron staining no source other the
	C5B-63	50-01	026	US facing 428 Harbor Ln x-ing
		SC-01	027	U/S Right
			028	U/s From end of reach
			629	DIS from end of reach
		TR-01	030	Typ. trash in stream reach
	V	Sc-02	031	Footbridge AMU timber abutments
	CSB-04	TK-01	032	O wire fonce
A	1	TR-02	033	misc. debris

(By Camera)

Project: CSH/OBH

Group: THW/KMB

Camera: Causson A580

This field sheet is to be completed AS photos are taken in the field. The intent is to force us to organize pictures taken on a camera basis. Fill out one sheet per camera (add sheets as needed). Only fill in Date/Reach/Location ID when you start in a new spatial or temporal location.

Date	Stream/ Reach	Location ID	Photo #	Description
8/24/0	CSB-04	SC-01	100-	gasion wall presenting headout
	CSB-05	CM 86-02	035	Us Facing SC-01
	CSBOS	CM-01	036	DIS facing modified stream channel
		0F-01	037	faung OFOI
			038	facing rentran smale connected to
		SC-01	034	U/s facing SC-01 (511 Harbor Ln)
		CM-03	040	Cabion lined channel (CM-03) Facing D/S Q
				V/S of SCOZ
			42	DIS & SCOZ
		SC-02	43	U/s facing SCOZ
	CS8-06		44	U/s from CSB-05 "SC-03"
	KBJE-RICH			
V				

(By Camera)

UPLAND ASSESSMENT

Project: AUENDROETHE DAY
Group: KNS/DIZIS

Camera: Com

This field sheet is to be completed AS photos are taken in the field. The intent is to force us to organize pictures taken on a camera basis. Fill out one sheet per camera (add sheets as needed). Only fill in Date/Reach/Location ID when you start in a new spatial or temporal location.

Date	Stream/ Reach	Location ID	Photo #	Description
6 15	Mathst		100 -	Tooking east on Frain St
			1041	Storefront or Nain St.
			0046	Gorden & adjacus stom chair
	V		-0052	Storm drow in hour of fire station
	Storter	CSH-NGI-01	-005g	Storm draw in front of fire station cold Spring Howler Fire Dept.
		CSH-NS1-01	2061	State park parking area - sandy apportuning
			006Z -006Y	for rehafite the reighborhood
		CSH-450-01	-0064 -0059	terrace place oromotion & poved died
	\downarrow		-0010	Port & dan St/ Horbor Rd Rhoto behird Doutour Huntington
	Main St Huntington	HSF- 01 (LSH)	-0076	Huntuglan Dountour Muni Lorking Lot (post fice)
	Florence/ Shlo's Pt Neighborhad	08H-N5A-	-0019	Horeva Rood
		WASI-OI	0083	Commonder Oal Fenrial
		0BHNSA-01 6BH+-01	008%	Dog work sign Melbonne St Storm chain w/ masher CB-/
		The state of the s	0086	Shipe part Orifall
		OBHSSDOI		Ships Paint fore along levoth

Photo Inventory

(By Camera)

Project: FRIENDS OF THE BLY

Group: LUIS/pizis

Camera: Conor

This field sheet is to be completed AS photos are taken in the field. The intent is to force us to organize pictures taken on a camera basis. Fill out one sheet per camera (add sheets as needed). Only fill in Date/Reach/Location ID when you start in a new spatial or temporal location.

Date	Stream/ Reach	Location ID	Photo	Description
8/25	-02 }	-7	100-2094	ayeter Bry Thefr School
			0104-	Town Africes
		OBH-HSI-	0109	L.I. Roubery Yered
			0125	Jocobsen
			0134	Dechorge Boxu
		MNC-NSA-01 MNR-SSDG		CB-1
8/26/09			0147	Oak Hill Dive Basin
		MEK-NEX-DI	0148	Singworth ST Neighborhood
			0149	0150 STORM BASIN 600
	Bailey Arbovetum	BA1-NSA-	151-	Martine cock Lane
	Mill Neck Creek	MNC-NSA-	154	Hervan Ave dead end outfall to DAK NOCK Creek (Milheck XI)
	Mill Noch Creek	MNC -55D-	155	Hemon are C15-01
	Ø.	1	156	Hermon Ohie CB-02
	V	1	120	ortlet to wetland area - Hernan Ave
	CTR	CTR-NSA- 01	160	House on Centre Island Rd
		CTP2-451-	161-	Seawahanah Yasht Club

Photo Inventory

(By Camera)

Project:	01	Ster	Ba	7
Group:	CN	B/1	326	0

Camera:

This field sheet is to be completed AS photos are taken in the field. The intent is to force us to organize pictures taken on a camera basis. Fill out one sheet per camera (add sheets as needed). Only fill in Date/Reach/Location ID when you start in a new spatial or temporal location.

Date	Stream Reach	ID	#	Description
8/26/09	MCR	1 WCA-55	D 163-	Catch loasing in Stp & shop lot (163); plaza; 166-1622
			168	Pine Hellow possible siderale retoft
		- WCR-HSI	-02 (69-170 171-183	Stop shop-behind
			176	Construction - DeBRINS & Sons Contractors
	NCE	WCP- PFI	- 177	NYS Recharge Basin 115
			178	Bogs & Civis Crows Back Front
	BAI	13A1-HS1-	01 (82-	Locust Valley lut, School Bug Maintenana
		18A1-451	-01/185	facting - and ans
		BA1-RR1-	01 187-192	Petrofit at Int. School - Locust Vallay
		BA1-841-6		Ann M. MarArthur Primary school
	MNE	MNCTO	196	FUD OF WALTON AUE - MUK polential restoration spec
	WCR	WCR-RFI	199- 204	restoration spot white's Creek on white st for retrofit -> daylighting stream
	OBH	0BH-N5A -02	210	Moxwell St NSM
	CSB	CSB-PRI	- 2/1-2/2 2/3-2/4	evidence of exosion -> 40'50' 84" 120 2+ 10.7"
			217-218	evidence of erosion -> 40'50'84" 73°27' 10.7" save loc 1 possible brovet/garden -5 manholes front grossisland

Photo Inventory

your francis Agus	(By Camera)	
the truncis bons	d = "Smittes" & Nassav (2

Project: _	
Group:	

Camera:

This field sheet is to be completed AS photos are taken in the field. The intent is to force us to organize pictures taken on a camera basis. Fill out one sheet per camera (add sheets as needed). Only fill in Date/Reach/Location ID when you start in a new spatial or temporal location.

8/27/09 OBH OBH-PRI- 219 - High school admin Bldg - Eximist. 220 lower lot brainage - no covol gotter 221 Beakman's Creek drainage at let to stream conveys sediment 222 - Le Birder - Melenny & surrounding shreets - Druis, etc. 224 - Pond draining to Beakman Creek 1050 Shore Rd. 8/27 NillBlue MEV-NSA 229- So Clean East Road - CT3 Housey OI 233 Generale Cufardin MEV-HST 234 OT3 Form Highway General MEV-HST 234 OT3 Form Highway General 244 Ziffeng Erecs Succommodation 245 Come Rd & Spetter Love 246 Johns Road Caphin 247 Demons Road Caphin 249 Demons & Dogwood Fore evoir 240 Shalley Application fore evoir 241 Alm Amons & Dogwood Fore evoir 252 Mul Atur Road - Coolin religiot 253 Mul Atur Road - Coolin religiot 254 Locust Ave Mill River headwaters 51 Hry Standing water in outlet stream
ON 200 lower lot brainage - no corb gather 221 Beatman's Creek drainage at let to stream conveys sediment 222- 226 The Bircher-Meleny of strongling Shreets - Davis, etc. 224- Pond draining to Beakman Creek 228 1050 Shore Rd. 6/27 WillBur MRV-NSA 229- 50 Chen Row Rood - CB Hoosey OI 233 aportunate Cinfernia MRV-HSI 234 OT3 Form Highing Gampe - OI 243 244 Ziffong Creek Duccommodation 245 Cone Rd & Affecter Lone 246- Foctory Road Road Cathin 249 Recommendation 240 Alm Among & Togunard Porce movine 250251 Yaley Alad Aft being with intelligent 251 Mill Rain Rood - Coolin relight 258- Locust Ave Mill River beadwaters
Beakman's Creek drainage atlet to Stream conveys sediment 222- 226 122- 226 122- 226 122- 226 122- 226 122- 226 122- 226 122- 226 122- 226 122- 226 122- 226 122- 226 122- 227 122- 228 122- 228 122- 228 122- 228 122- 228 122- 228 122- 228 122- 228 122- 228 122- 228 224- 222- 223 224- 224- 224- 224- 224
to stream conveys sediment 222- 226 The Birches-Melenay of Surrounding Shorets - Davis, etc. 214- Pend draining to Benkman Creek 218 1050 Shore Rd. 1050
212- The Birches- Meleray & surrounding Streets - Davis, etc. 214- Pond draining to Benkman Creek 218 1050 Shore Rd. 8/21 NillBlux MRV-NSA 229- So Chen Ear Road - CTS Thousay COI 233 apostoriale Cinformia MRV-HSI 234 OTS Form Highway Bourge - OI 243 244 Ziffong Ereck Duccommodates Che Rd & Spritter Fone 246- Fortony Road Road Caphin 249 Alm Among & Toguerd Force evoir 240 Alm Among & Toguerd Force evoir 250751 Yally Alab Mit bongs surbinded from 250751 Mally Alab Mit bongs surbinded from 251- Mill River beadwaters
1050 Shore Rd. 1050 Shore Rd.
1050 Shore Rd. MEV-NSA 229 Dalen Ear Rood - CTS Housey CH 233 apartmente Chefurni MEV-HSI 234 OTS Fam Highway Bourge - OI 243 244 Ziffong Eleck Delicomenolation 245 Cone Rd & Sputter Lone 146 John Pord Road Olphin 249 Recommendation 241 Alm Among & Doquered fore evoirs 250-251 Yally Alad Alt borge with intels & conere 151 Mill River Rood - Coolin retrofit 158- Locust Ave Mill River beadwaters
1050 Shore Pd. NEV-NSA-229- Dalen Ear Rood-CTS Housey. OI 233 aportarine Chifurni. MEV-HSI 234 OTS Form Highway Bourge - OI 243 244 Ziffong Elect Duccomerolation 745 Cone Rd & Spritter Lone 746- Johny Rood Road Caphin 749 Recommendation 241 Alm Among & Doquerol Lore evoir 250751 Maley Aladd Mit borgs curb inless & concre 157 Mill River Rood-Coolin relight 158- Locust Ave Mill River beadwaters
101 100 MEV-NSA 229- 50 Chen Ear Road - CTS Housey MEV-NSA 239 CTS Form Highway Garage -01 243 CTS Form Highway Source 244 Ziffong Erech Duccommodates 245 Eare Ed & Spritter Lone 246- Forrory Road Poad Caphin 249 Alm Among & Togueral Love movin 250751 Yally Hadd All barge curb intel & conere 250 Mill River beachers
101 753 aportarente Claferia. MEV-HSI 234 OTS Form Highway Garage -01 244 Ziffong Erech Decommendation 245 Eone Rd & Sputter Love 746 Forrory Road Road Ediphin 244 Recommendation 241 Alm Among & Loguered force erosin 250751 Yally Road All borgo curb intellet concept 252 Mill River Road Coopin religit 258- Locust Ave Mill River beadwaters
MEV HST 234 OTS Form Highway Garage 244 Ziffang Ereck Decommendation 245 Eone Rd & Sputter Lone 246 Forrow Road Road Caphin 249 Recommendation 241 Alm Among & Dogwood Fore erosin 250751 Yarley Alad Alt borge earlinks & concre 252 Mul Dear Road Caphin relight 258 Locvet Ave Mill River beadwaters
244 Ziffong Ereck Succommodation 245 Cone Rd & Sputter Lone 246 Forrory Road Poad Elephin 244 Recommendation 241 Ahm Amomp & Dogwood Love movin 250751 Yalley Madd Afte berge surbinkly Connected 252 Mail Dan Road Cookin religion 258 Locust Ave Mill River headwaters
246 - Forrow Pord Road Ediphin 244 Recommendation 241 Ahm Among & Dogwood Fore evoirs 250751 Yarley Made Alt berge earlinkles & conerge 252 - Mill Rever Road - Coolin relight
246 Forrory Pord Poad Ediphin 244 Recommendation 241 Ahm Among & Dogwood fore evoirs 250-751 Walley Ald AME being with inless & concre 252 Mill Dun Rood - Coolin relight 257 Locust Ave Mill River beadwaters
246 Forrow Pord Road Edifin 249 Recommendation 241 Ahm Among & Dogwood Fore evoirs 250-751 Yarley Mad Alt berge with intellet concre 252 Mill Bur Road - Coolin relight 257 Locust Ave Mill River beadwaters
249 Shu swamp & Dogwood fore evain 250751 Walley Abod ASE berge with intellet concre 252 Mill Steen Rood - Coolin religion 257 Locust Ave Mill River headwaters
250-751 Walley Abod Alt berge wit intellet concrete 252- Mill Dun Rood-Coolin relight 257 Locust Ave Mill River beadwaters
250-751 Walley Ald Alt berge curb intels & cone of 252 Mill Deur Rood - Coalin relight 257 Locust Ave MII River beadwaters
257 9MM Been Rood - Cooper religion 257 Locust Ave Mill River beadwaters
258- Locust Ave Mill River beadwaters
filthy standing nater in orther stream

